



Week 8.2

Recap Everything, Build PayTM Backend

In this lecture, Harkirat guides us through an [end-to-end tutorial](#) on building a comprehensive [full-stack application](#) resembling [Paytm](#). While there are no specific notes provided for this section, a mini guide is outlined below to assist you in navigating through each step of the tutorial. Therefore, it is strongly advised to actively follow along during the lecture for a hands-on learning experience.

It's important to note that this session primarily focuses on the backend section of the application. For the frontend portion, be sure to check out the content covered in the subsequent 8.4 lecture.

Recap Everything, Build PayTM Backend

Step 1 - What are we building, Clone the starter repo

Things to do

Explore the repository

Backend

Frontend

Step 2 - User Mongoose schemas

Solution

Step 3 - Create routing file structure

Step 1

Solution

Step 2

Solution

Step 4 - Route user requests

1. Create a new user router

Solution

2. Create a new user router

Solution

Step 5 - Add cors, body parser and jsonwebtoken

1. Add cors

Hint

Solution

2. Add body-parser

Hint

Solution

3. Add jsonwebtoken

4. Export JWT_SECRET

Solution

5. Listen on port 3000

Solution

Step 6 - Add backend auth routes

1. Signup

Solution

2. Route to sign in

Solution

Solution

Step 7 - Middleware

Solution

Step 8 - User routes

1. Route to update user information

Solution

2. Route to get users from the backend, filterable via firstName/lastName

Hints

Solution

Step 9 - Create Bank related Schema

Accounts table

Solution

By the end of it, db.js should look like this

Step 10 - Transactions in databases

Solution

Step 11 - Initialize balances on signup

Solution

Step 12 - Create a new router for accounts

1. Create a new router

Solution

2. Route requests to it

Solution

Step 13 - Balance and transfer Endpoints

1. An endpoint for user to get their balance.

Solution

2. An endpoint for user to transfer money to another account

Bad Solution (doesn't use transactions)

Good solution (uses txns in db)

Problems you might run into

Final Solution

Finally, the account.js file should look like this

Experiment to ensure transactions are working as expected

Code

Error

Step 14 - Checkpoint your solution

Get balance

Make transfer

Get balance again (notice it went down)

Mongo should look something like this

Step 1 - What are we building, Clone the starter repo

We're building a PayTM like application that let's users send money to each other given an initial dummy balance

The screenshot shows a web-based application titled "Payments App". At the top right, there is a "Hello, User" greeting and a user icon. Below the title, the text "Your Balance \$5000" is displayed. Under the heading "Users", there is a search bar with the placeholder "Search users...". A list of three users is shown: "User 1" (U1), "User 2" (U2), and "User 3" (U3). To the right of each user name is a "Send Money" button.

Things to do

Clone the 8.2 repository from <https://github.com/100xdevs-cohort-2/paytm>

```
git clone https://github.com/100xdevs-cohort-2/paytm
```



Please keep a MongoDB URL handy before you proceed. This will be your primary database for this assignment

1. Create a free one here - <https://www.mongodb.com/>
2. There is a Dockerfile in the codebase, you can run mongo locally using it.

Explore the repository

The repo is a basic express + react + tailwind boilerplate

Backend

1. Express - HTTP Server
2. mongoose - ODM to connect to MongoDB
3. zod - Input validation

```
// index.js
const express = require("express");
const app = express();
```

Frontend

1. React - Frontend framework
2. Tailwind - Styling framework

```
// App.jsx
function App() {

  return (
    <div>
      Hello world
    </div>
  )
}

export default App
```

Step 2 - User Mongoose schemas

We need to support 3 routes for user authentication

1. Allow user to sign up.
2. Allow user to sign in.
3. Allow user to update their information (firstName, lastName, password).

To start off, create the mongo schema for the users table

1. Create a new file (db.js) in the root folder
2. Import mongoose and connect to a database of your choice
3. Create the mongoose schema for the users table
4. Export the mongoose model from the file (call it User)

▼ Solution

Simple solution

```
// backend/db.js
const mongoose = require('mongoose');

// Create a Schema for Users
const userSchema = new mongoose.Schema({
    username: String,
    password: String,
    firstName: String,
    lastName: String
});

// Create a model from the schema
const User = mongoose.model('User', userSchema);

module.exports = {
    User
};
```

Elegant Solution

```
// backend/db.js
const mongoose = require('mongoose');

// Create a Schema for Users
const userSchema = new mongoose.Schema({
    username: {
        type: String,
        required: true,
        unique: true,
        trim: true,
        lowercase: true,
        minLength: 3,
        maxLength: 30
    },
});
```

```

password: {
    type: String,
    required: true,
    minLength: 6
},
firstName: {
    type: String,
    required: true,
    trim: true,
    maxLength: 50
},
lastName: {
    type: String,
    required: true,
    trim: true,
    maxLength: 50
}
});

// Create a model from the schema
const User = mongoose.model('User', userSchema);

module.exports = {
    User
};

```

Step 3 - Create routing file structure

In the index.js file, route all the requests to `/api/v1` to a apiRouter defined in `backend/routes/index.js`

Step 1

Create a new file `backend/routes/index.js` that exports a new express router.

(How to create a router - <https://www.geeksforgeeks.org/express-js-express-router-function/>)

▼ Solution

```

// backend/api/index.js
const express = require('express');

const router = express.Router();

```

```
module.exports = router;
```

Step 2

Import the router in index.js and route all requests from `/api/v1` to it

▼ Solution

```
// backend/index.js
const express = require("express");
const rootRouter = require("./routes/index");

const app = express();

app.use("/api/v1", rootRouter);
```

Step 4 - Route user requests

1. Create a new user router

Define a new router in `backend/routes/user.js` and import it in the index router.

Route all requests that go to `/api/v1/user` to the user router.

▼ Solution

```
// backend/routes/user.js
const express = require('express');

const router = express.Router();

module.exports = router;
```

2. Create a new user router

Import the userRouter in `backend/routes/index.js` so all requests to `/api/v1/user` get routed to the userRouter.

► Solution

```
// backend/routes/index.js
const express = require('express');
const userRouter = require("./user");

const router = express.Router();

router.use("/user", userRouter)

module.exports = router;
```

Step 5 - Add cors, body parser and jsonwebtoken

1. Add cors

Since our frontend and backend will be hosted on separate routes, add the `cors` middleware to `backend/index.js`

▼ Hint

Look at <https://www.npmjs.com/package/cors>

▼ Solution

```
// backend/index.js
const express = require('express');
const cors = require("cors");

app.use(cors());

const app = express();

module.exports = router;
```

2. Add body-parser

Since we have to support the JSON body in post requests, add the express body parser middleware to `backend/index.js`

You can use the `body-parser` npm library, or use `express.json`

▼ Hint

<https://medium.com/@mmajdanski/express-body-parser-and-why-may-not-need-it-335803cd048c>

▼ Solution

```
// backend/index.js
const express = require('express');
const cors = require("cors");
const rootRouter = require("./routes/index");

const app = express();

app.use(cors());
app.use(express.json());

app.use("/api/v1", rootRouter);
```

3. Add jsonwebtoken

We will be adding authentication soon to our application, so install jsonwebtoken library. It'll be useful in the next slide

```
npm install jsonwebtoken
```

4. Export JWT_SECRET

Export a `JWT_SECRET` from a new file `backend/config.js`

▼ Solution

```
//backend/config.js
module.exports = {
  JWT_SECRET: "your-jwt-secret"
}
```

5. Listen on port 3000

Make the express app listen on PORT 3000 of your machine

▼ Solution

```
// backend/index.js
... Existing code

app.listen(3000);
```

Step 6 - Add backend auth routes

In the user router (`backend/routes/user`), add 3 new routes.

1. Signup

This route needs to get user information, do input validation using zod and store the information in the database provided

1. Inputs are correct (validated via zod)
2. Database doesn't already contain another user

If all goes well, we need to return the user a jwt which has their user id encoded as follows -

```
{
  userId: "userId of newly added user"
}
```



Note - We are not hashing passwords before putting them in the database. This is standard practise that should be done, you can find more details here -

<https://mojoauth.com/blog/hashing-passwords-in-nodejs/>

Method: POST

Route: /api/v1/user/signup

Body:

```
{  
  username: "name@gmail.com",  
  firstName: "name",  
  lastName: "name",  
  password: "123456"  
}
```

Response:

Status code - 200

```
{  
  message: "User created successfully",  
  token: "jwt"  
}
```

Status code - 411

```
{  
  message: "Email already taken / Incorrect inputs"  
}
```

▼ Solution

```
const zod = require("zod");
const { User } = require("../db");
const jwt = require("jsonwebtoken");
const { JWT_SECRET } = require("../config");

const signupBody = zod.object({
  username: zod.string().email(),
  firstName: zod.string(),
  lastName: zod.string(),
  password: zod.string()
})

router.post("/signup", async (req, res) => {
  const { success } = signupBody.safeParse(req.body)
  if (!success) {
    return res.status(411).json({
```

```

        message: "Email already taken / Incorrect inputs"
    })
}

const existingUser = await User.findOne({
    username: req.body.username
})

if (existingUser) {
    return res.status(411).json({
        message: "Email already taken/Incorrect inputs"
    })
}

const user = await User.create({
    username: req.body.username,
    password: req.body.password,
    firstName: req.body.firstName,
    lastName: req.body.lastName,
})
const userId = user._id;

const token = jwt.sign({
    userId
}, JWT_SECRET);

res.json({
    message: "User created successfully",
    token: token
})
}

```

2. Route to sign in

Let's an existing user sign in to get back a token.

Method: POST

Route: /api/v1/user/signin

Body:

```
{
    username: "name@gmail.com",
    password: "123456"
}
```

Response:

Status code - 200

```
{  
  token: "jwt"  
}
```

Status code - 411

```
{  
  message: "Error while logging in"  
}
```

▼ Solution

```
const signinBody = zod.object({  
  username: zod.string().email(),  
  password: zod.string()  
})  
  
router.post("/signin", async (req, res) => {  
  const { success } = signinBody.safeParse(req.body)  
  if (!success) {  
    return res.status(411).json({  
      message: "Incorrect inputs"  
    })  
  }  
  
  const user = await User.findOne({  
    username: req.body.username,  
    password: req.body.password  
});  
  
  if (user) {  
    const token = jwt.sign({  
      userId: user._id  
    }, JWT_SECRET);  
  
    res.json({  
      token: token  
    })  
  }  
  return;  
}
```

```

        res.status(411).json({
            message: "Error while logging in"
        })
    })
}

```

By the end, `routes/user.js` should look like follows

▼ Solution

```

// backend/routes/user.js
const express = require('express');

const router = express.Router();
const zod = require("zod");
const { User } = require("../db");
const jwt = require("jsonwebtoken");
const { JWT_SECRET } = require("../config");

const signupBody = zod.object({
    username: zod.string().email(),
    firstName: zod.string(),
    lastName: zod.string(),
    password: zod.string()
})

router.post("/signup", async (req, res) => {
    const { success } = signupBody.safeParse(req.body)
    if (!success) {
        return res.status(411).json({
            message: "Email already taken / Incorrect inputs"
        })
    }

    const existingUser = await User.findOne({
        username: req.body.username
    })

    if (existingUser) {
        return res.status(411).json({
            message: "Email already taken/Incorrect inputs"
        })
    }

    const user = await User.create({

```

```
        username: req.body.username,
        password: req.body.password,
        firstName: req.body.firstName,
        lastName: req.body.lastName,
    })
const userId = user._id;

const token = jwt.sign({
    userId
}, JWT_SECRET);

res.json({
    message: "User created successfully",
    token
})
})

const signinBody = zod.object({
    username: zod.string().email(),
    password: zod.string()
})

router.post("/signin", async (req, res) => {
    const { success } = signinBody.safeParse(req.body)
    if (!success) {
        return res.status(411).json({
            message: "Email already taken / Incorrect inputs"
        })
    }

    const user = await User.findOne({
        username: req.body.username,
        password: req.body.password
    });

    if (user) {
        const token = jwt.sign({
            userId: user._id
        }, JWT_SECRET);

        res.json({
            token
        })
        return;
    }

    res.status(411).json({
        message: "Error while logging in"
    })
})
```

```
module.exports = router;
```

Step 7 - Middleware

Now that we have a user account, we need to `gate` routes which authenticated users can hit.

For this, we need to introduce an auth middleware

Create a `middleware.js` file that exports an `authMiddleware` function

1. Checks the headers for an Authorization header `Bearer <token>`
2. Verifies that the token is valid
3. Puts the `userId` in the request object if the token checks out.
4. If not, return a 403 status back to the user

Header -

`Authorization: Bearer <actual token>`

▼ Solution

```
const { JWT_SECRET } = require("./config");
const jwt = require("jsonwebtoken");

const authMiddleware = (req, res, next) => {
  const authHeader = req.headers.authorization;

  if (!authHeader || !authHeader.startsWith('Bearer ')) {
    return res.status(403).json({});
  }

  const token = authHeader.split(' ')[1];

  try {
    const decoded = jwt.verify(token, JWT_SECRET);

    req.userId = decoded.userId;

    next();
  } catch (err) {
    return res.status(403).json({});
  }
}
```

```
};

module.exports = {
  authMiddleware
}
```

Step 8 - User routes

1. Route to update user information

User should be allowed to **optionally** send either or all of

1. password
2. firstName
3. lastName

Whatever they send, we need to update it in the database for the user.

Use the **middleware** we defined in the last section to authenticate the user

Method: PUT

Route: /api/v1/user

Body:

```
{
  password: "new_password",
  firstName: "updated_first_name",
  lastName: "updated_first_name",
}
```

Response:

Status code - 200

```
{
  message: "Updated successfully"
}
```

Status code - 411 (Password is too small...)

```
{
  message: "Error while updating information"
}
```

▼ Solution

```
const { authMiddleware } = require("../middleware");

// other auth routes

const updateBody = zod.object({
  password: zod.string().optional(),
  firstName: zod.string().optional(),
  lastName: zod.string().optional(),
})

router.put("/", authMiddleware, async (req, res) => {
  const { success } = updateBody.safeParse(req.body)
  if (!success) {
    res.status(411).json({
      message: "Error while updating information"
    })
  }

  await User.updateOne(req.body, {
    _id: req.userId
  })

  res.json({
    message: "Updated successfully"
  })
})
```

2. Route to get users from the backend, filterable via firstName/lastName

This is needed so users can search for their friends and send them money

Method: GET

Route: /api/v1/user/bulk

Query Parameter: ?filter=harkirat

Response:

Status code - 200

```
{
  users: [{
```

```

    firstName: "",
    lastName: "",
    _id: "id of the user"
  ]
}

```

▼ Hints

<https://stackoverflow.com/questions/7382207/mongooses-find-method-with-or-condition-does-not-work-properly>

<https://stackoverflow.com/questions/3305561/how-to-query-mongodb-with-like>

▼ Solution

```

router.get("/bulk", async (req, res) => {
  const filter = req.query.filter || "";

  const users = await User.find({
    $or: [
      {
        firstName: {
          "$regex": filter
        }
      },
      {
        lastName: {
          "$regex": filter
        }
      }
    ]
  })

  res.json({
    user: users.map(user => ({
      username: user.username,
      firstName: user.firstName,
      lastName: user.lastName,
      _id: user._id
    }))
  })
})

```

Step 9 - Create Bank related Schema

Update the `db.js` file to add one new schemas and export the respective models

Accounts table

The `Accounts` table will store the INR balances of a user.

The schema should look something like this -

```
{  
  userId: ObjectId (or string),  
  balance: float/number  
}
```

In the real world, you shouldn't store `floats` for balances in the database. You usually store an integer which represents the INR value with decimal places (for eg, if someone has 33.33 rs in their account, you store 3333 in the database).

There is a certain precision that you need to support (which for india is 2/4 decimal places) and this allows you to get rid of precision errors by storing integers in your DB

You should reference the users table in the schema (Hint -

<https://medium.com/@mendes.develop/joining-tables-in-mongodb-with-mongoose-489d72c84b60>)

▼ Solution

```
const accountSchema = new mongoose.Schema({  
  userId: {  
    type: mongoose.Schema.Types.ObjectId, // Reference to User model  
    ref: 'User',  
    required: true  
  },  
  balance: {  
    type: Number,  
    required: true  
  }  
});  
  
const Account = mongoose.model('Account', accountSchema);  
  
module.exports = {  
  Account  
}
```

- ▶ By the end of it, `db.js` should look like this

Step 10 - Transactions in databases

A lot of times, you want multiple database transactions to be `atomic`

Either all of them should update, or none should

This is super important in the case of a `bank`

Can you guess what's wrong with the following code -

```
const mongoose = require('mongoose');
const Account = require('./path-to-your-account-model');

const transferFunds = async (fromAccountId, toAccountId, amount) => {
    // Decrement the balance of the fromAccount
    await Account.findByIdAndUpdate(fromAccountId, { $inc: { balance: -amount } });

    // Increment the balance of the toAccount
    await Account.findByIdAndUpdate(toAccountId, { $inc: { balance: amount } });
}

// Example usage
transferFunds('fromAccountID', 'toAccountID', 100);
```

▼ Solution

1. What if the database crashes right after the first request (only the balance is decreased for one user, and not for the second user)
2. What if the Node.js crashes after the first update?

It would lead to a `database inconsistency`. Amount would get debited from the first user, and not credited into the other user's account.

If a failure ever happens, the first txn should rollback.

This is what is called a `transaction` in a database. We need to implement a `transaction` on the next set of endpoints that allow users to transfer INR

Step 11 - Initialize balances on signup

Update the `signup` endpoint to give the user a random balance between 1 and 10000.

This is so we don't have to integrate with banks and give them random balances to start with.

▼ Solution

```
router.post("/signup", async (req, res) => {
  const { success } = signupBody.safeParse(req.body)
  if (!success) {
    return res.status(411).json({
      message: "Email already taken / Incorrect inputs"
    })
  }

  const existingUser = await User.findOne({
    username: req.body.username
  })

  if (existingUser) {
    return res.status(411).json({
      message: "Email already taken/Incorrect inputs"
    })
  }

  const user = await User.create({
    username: req.body.username,
    password: req.body.password,
    firstName: req.body.firstName,
    lastName: req.body.lastName,
  })
  const userId = user._id;

  // ----- Create new account -----

  await Account.create({
    userId,
    balance: 1 + Math.random() * 10000
  })

  // ----- 

  const token = jwt.sign({
    userId
  }, JWT_SECRET);

  res.json({
    message: "User created successfully",
```

```
    token: token
  })
})
```

Step 12 - Create a new router for accounts

1. Create a new router

All user balances should go to a different express router (that handles all requests on `/api/v1/account`).

Create a new router in `routes/account.js` and add export it

▼ Solution

```
// backend/routes/account.js
const express = require('express');

const router = express.Router();

module.exports = router;
```

2. Route requests to it

Send all requests from `/api/v1/account/*` in `routes/index.js` to the router created in step 1.

▼ Solution

```
// backend/user/index.js
const express = require('express');
const userRouter = require("./user");
const accountRouter = require("./account");

const router = express.Router();

router.use("/user", userRouter);
router.use("/account", accountRouter);

module.exports = router;
```

Step 13 - Balance and transfer Endpoints

Here, you'll be writing a bunch of APIs for the core user balances. There are 2 endpoints that we need to implement

1. An endpoint for user to get their balance.

Method: GET

Route: /api/v1/account/balance

Response:

Status code - 200

```
{  
  balance: 100  
}
```

▼ Solution

```
router.get("/balance", authMiddleware, async (req, res) => {  
  const account = await Account.findOne({  
    userId: req.userId  
  });  
  
  res.json({  
    balance: account.balance  
  })  
});
```

2. An endpoint for user to transfer money to another account

Method: POST

Route: /api/v1/account/transfer

Body

```
{  
  to: string,  
}
```

```
    amount: number  
}
```

Response:

Status code - 200

```
{  
  message: "Transfer successful"  
}
```

Status code - 400

```
{  
  message: "Insufficient balance"  
}
```

Status code - 400

```
{  
  message: "Invalid account"  
}
```

▼ Bad Solution (doesn't use transactions)

```
router.post("/transfer", authMiddleware, async (req, res) => {  
  const { amount, to } = req.body;  
  
  const account = await Account.findOne({  
    userId: req.userId  
  });  
  
  if (account.balance < amount) {  
    return res.status(400).json({  
      message: "Insufficient balance"  
    })  
  }  
  
  const toAccount = await Account.findOne({  
    userId: to  
  });  
  
  if (!toAccount) {  
    return res.status(400).json({  
      message: "Invalid account"  
    })  
  }
```

```

await Account.updateOne({
  userId: req.userId
}, {
  $inc: {
    balance: -amount
  }
})

await Account.updateOne({
  userId: to
}, {
  $inc: {
    balance: amount
  }
})

res.json({
  message: "Transfer successful"
})
});

```

▼ Good solution (uses txns in db)

```

router.post("/transfer", authMiddleware, async (req, res) => {
  const session = await mongoose.startSession();

  session.startTransaction();
  const { amount, to } = req.body;

  // Fetch the accounts within the transaction
  const account = await Account.findOne({ userId: req.userId }).session(session);

  if (!account || account.balance < amount) {
    await session.abortTransaction();
    return res.status(400).json({
      message: "Insufficient balance"
    });
  }

  const toAccount = await Account.findOne({ userId: to }).session(session);

  if (!toAccount) {
    await session.abortTransaction();
    return res.status(400).json({

```

```
        message: "Invalid account"
    });
}

// Perform the transfer
await Account.updateOne({ userId: req.userId }, { $inc: { balance: -amount } }).s
await Account.updateOne({ userId: to }, { $inc: { balance: amount } }).session(se

// Commit the transaction
await session.commitTransaction();
res.json({
    message: "Transfer successful"
});
});
```

▼ Problems you might run into

Problems you might run into If you run into the problem mentioned above, feel free to proceed with the bad solution

<https://stackoverflow.com/questions/51461952/mongodb-v4-0-transaction-mongoerror-transaction-numbers-are-only-allowed-on-a>

Final Solution

▼ Finally, the account.js file should look like this ▶

Experiment to ensure transactions are working as expected

Try running this code locally. It calls transfer twice on the same account ~almost concurrently

▼ Code

```
// backend/routes/account.js
const express = require('express');
const { authMiddleware } = require('../middleware');
const { Account } = require('../db');
const { default: mongoose } = require('mongoose');

const router = express.Router();

router.get("/balance", authMiddleware, async (req, res) => {
  const account = await Account.findOne({
    userId: req.userId
  });

  res.json({
    balance: account.balance
  })
});

async function transfer(req) {
  const session = await mongoose.startSession();

  session.startTransaction();
  const { amount, to } = req.body;

  // Fetch the accounts within the transaction
  const account = await Account.findOne({ userId: req.userId }).session(session);

  if (!account || account.balance < amount) {
    await session.abortTransaction();
    console.log("Insufficient balance")
    return;
  }

  const toAccount = await Account.findOne({ userId: to }).session(session);

  if (!toAccount) {
    await session.abortTransaction();
    console.log("Invalid account")
    return;
  }

  // Perform the transfer
  await Account.updateOne({ userId: req.userId }, { $inc: { balance: -amount } }).s
  await Account.updateOne({ userId: to }, { $inc: { balance: amount } }).session(se

  // Commit the transaction
  await session.commitTransaction();
```

```

        console.log("done")
    }

transfer({
    userId: "65ac44e10ab2ec750ca666a5",
    body: {
        to: "65ac44e40ab2ec750ca666aa",
        amount: 100
    }
})

transfer({
    userId: "65ac44e10ab2ec750ca666a5",
    body: {
        to: "65ac44e40ab2ec750ca666aa",
        amount: 100
    }
})
module.exports = router;

```

▼ Error

```

balance: 2099.5399690668773,
__v: 0
}
/Users/harkiratsingh/Projects/100x/week-8.2/backend/node_modules/mongodb/lib/cmap/connection.js:205
    callback(new error_1.MongoServerError(document));
^

MongoServerError: WriteConflict error: this operation conflicted with another operation. Please retry your operation or multi-document transaction.
    at Connection.onMessage (/Users/harkiratsingh/Projects/100x/week-8.2/backend/node_modules/mongodb/lib/cmap/connection.js:205:26)
    at MessageStream.<anonymous> (/Users/harkiratsingh/Projects/100x/week-8.2/backend/node_modules/mongodb/lib/cmap/connection.js:64:60)
    at MessageStream.emit (node:events:519:28)
    at processIncomingData (/Users/harkiratsingh/Projects/100x/week-8.2/backend/node_modules/mongodb/lib/cmap/message_stream.js:117:16)
    at MessageStream._write (/Users/harkiratsingh/Projects/100x/week-8.2/backend/node_modules/mongodb/lib/cmap/message_stream.js:33:9)
    at writeOrBuffer (node:internalstreams/writable:564:12)
    at _write (node:internalstreams/writable:493:10)
    at Writable.write (node:internalstreams/writable:502:10)
    at Socket.ondata (node:internalstreams/readable:1007:22)
    at Socket.emit (node:events:519:28)
    at operationTime: Timestamp { low: 1, high: 1705839061, unsigned: true },
    ok: 0,
    code: 112,

```

Step 14 - Checkpoint your solution

A completely working backend can be found here - <https://github.com/100xdevs-cohort-2/paytm/tree/backend-solution>

Try to send a few calls via postman to ensure you are able to sign up/sign in/get balance

Get balance

The screenshot shows the Postman interface. In the left sidebar, there's a history of requests. In the main area, a specific GET request to `http://localhost:3000/api/v1/account/balance` is selected. The Headers tab shows an `Authorization` header with the value `Bearer eyJhbGciOiJUzI1NiIsInR5cCI6IkpxVCJ9eyJ1c2VySW...`. The response body is displayed in JSON format:

```
1 "balance": 2099.5399690668773
```

Make transfer

The screenshot shows the Postman interface with a successful API call. The URL is `http://localhost:3000/api/v1/account/transfer`. The request method is `POST`. The Body tab shows the following JSON payload:

```
1 "to": "65ac44e10ab2ec750ca666a5",
2 "amount": "100"
```

The response status is `200 OK` with a `message`: "Transfer successful".

Get balance again (notice it went down)

The screenshot shows the Postman interface with a successful API call. The URL is `http://localhost:3000/api/v1/account/balance`. The request method is `GET`. The Headers tab shows `(9)` headers. The Query Params section has one entry: Key. The response status is `200 OK` with a `balance`: 1999.5399690668773.

Mongo should look something like this

MongoDB Compass - localhost:27017/paytm.accounts

localhost:27017 ... Documents paytm.accounts +

My Queries Databases Search +

paytm.accounts

Documents Aggregations Schema Indexes Validation

Filter Type a query: { field: 'value' } or [Generate query](#)

ADD DATA EXPORT DATA Explain Reset Find Options

1 - 3 of 3 ⌂ ⌄ ⌅ ⌆ ⌇ ⌈ ⌉ ⌊ ⌋

3 DOCUMENTS 1 INDEXES

`_id: ObjectId('65ac44df0ab2ec750ca666a2')`
`userId: ObjectId('65ac44df0ab2ec750ca666a0')`
`balance: 1736.510310286142`
`__v: 0`

`_id: ObjectId('65ac44e10ab2ec750ca666a7')`
`userId: ObjectId('65ac44e10ab2ec750ca666a5')`
`balance: 513.810707628458`
`__v: 0`

`_id: ObjectId('65ac44e40ab2ec750ca666ac')`
`userId: ObjectId('65ac44e40ab2ec750ca666aa')`
`balance: 1999.5399690668773`
`__v: 0`

MongoDB Compass - localhost:27017/paytm.users

localhost:27017 ... Documents paytm.users +

My Queries Databases Search +

paytm.users

Documents Aggregations Schema Indexes Validation

Filter Type a query: { field: 'value' } or [Generate query](#)

ADD DATA EXPORT DATA Explain Reset Find Options

1 - 3 of 3 ⌂ ⌄ ⌅ ⌆ ⌇ ⌈ ⌉ ⌊ ⌋

3 DOCUMENTS 2 INDEXES

`_id: ObjectId('65ac44df0ab2ec750ca666a0')`
`username: "harkirat1111@gmail.com"`
`password: "123456"`
`firstName: "harkirat"`
`lastName: "Singh"`
`__v: 0`

`_id: ObjectId('65ac44e10ab2ec750ca666a5')`
`username: "harkirat1111@gmail.com"`
`password: "123456"`
`firstName: "harkirat"`
`lastName: "Singh"`
`__v: 0`

`_id: ObjectId('65ac44e40ab2ec750ca666aa')`
`username: "harkirat11@gmail.com"`
`password: "123456"`
`firstName: "harkirat"`
`lastName: "Singh"`
`__v: 0`