

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8" />
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
<title>Document</title>
<style>
body {
background-color: pink;
font-family: Arial, sans-serif;
}

h1 {
margin-left: 20px;
color: #333;
}
button {
padding: 10px 20px;
background-color: aqua;
font-size: 18px;
font-weight: bold;
border: none;
border-radius: 8px;
margin-left: 20px;
cursor: pointer;
transition: background-color 0.3s ease;
}

button:hover {
background-color: #00ced1;
}
</style>
</head>
<body>
<!-- Inline Events -->
<h1>Inline Events</h1>
<button onclick="alert('Welcome to js Workshop')">Welcome</button>
<button onmouseover="alert('Welcome to js Workshop')">Welcome</button>
<button ondblclick="alert('Welcome to js Workshop')">Welcome Again</button>

<!-- DOM Events Handler -->
<h1>DOM event handler</h1>
<button id="mybtn1">Welcome</button>
<button id="mybtn2">Welcome</button>
<button id="mybtn3">Welcome Again</button>

<!-- addEventListener Events Handler -->
<h1>ADDEventsListener Events Handler</h1>
<button id="mybtn4">Welcome</button>
<button id="mybtn5">Welcome</button>
<button id="mybtn6">Welcome Again</button>

<script>
// DOM Events Handler
document.getElementById("mybtn1").onclick = function () {
alert("Welcome to js workshop");
};
document.getElementById("mybtn2").onmouseover = function () {
alert("Welcome to js workshop");
};

```

```
};
document.getElementById("mybtn3").ondblclick = function () {
alert("Welcome to js workshop");
};

// addEventListener Events Handler
document.getElementById("mybtn4").addEventListener("click", function () {
alert("Welcome to js workshop");
});
document
.getElementById("mybtn5")
.addEventListener("mouseover", function () {
alert("Welcome to js workshop");
});
document
.getElementById("mybtn6")
.addEventListener("dblclick", function () {
alert("Welcome to js workshop");
});
</script>
</body>
</html>
```