

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8" />
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
<title>Document</title>
</head>
<style>
body {
font-family: Arial, sans-serif;
padding: 20px;
background-color: black;
}

.output {
background-color: gray;
width: 325px;
height: 230px;
border-radius: 5px;
border-left: 5px solid white;
margin: auto;
margin-top: 50px;
}
.output p {
margin: 5px 0;
font-size: 18px;
color: goldenrod;
/* line-height: 30px; */
padding-top: 25px;
margin-left: 20px;
}

input {
padding: 8px;
width: 300px;
font-size: 16px;
border: 5px double goldenrod;
border-radius: 10px;
text-align: center;
}
section {
display: flex;
flex-direction: column;
align-items: center;
justify-content: center;
margin-top: 170px;
}
</style>
<body>
<section>
<input type="text" id="myInput" placeholder="Type something..." name="username"/>
<div class="output">
<p id="keyPressed">Input Value :</p>
<p id="keyCode">Input Name :</p>
<p id="charCode">Input Type :</p>
<p id="eventType">Event Type :</p>
</div>
</section>

```

```
<script>
// Function to handle keypress events
const handleinput = (event) => {
  console.log(event);
  console.log("Input Value :", event.target.value);
  console.log("Input Name :", event.target.name);
  console.log("Input Type :", event.inputType);
  console.log("Event Type :", event.type);

  document.getElementById(
    "keyPressed"
  ).textContent = `Input Value : ${event.target.value}`;
  document.getElementById(
    "keyCode"
  ).textContent = `Input Name : ${event.target.name}`;
  document.getElementById(
    "charCode"
  ).textContent = `Input Type : ${event.inputType}`;
  document.getElementById(
    "eventType"
  ).textContent = `Event Type : ${event.type}`;
};

// Get input element
let myInput = document.getElementById("myInput");

// Add event listener
myInput.addEventListener("input", handleinput);
// myInput.addEventListener("change", handleinput);
</script>
</body>
</html>
```