

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8" />
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
<title>Document</title>
</head>
<style>
body {
font-family: Arial, sans-serif;
padding: 20px;
background-color: black;
}

.output {
background-color: gray;
width: 325px;
height: 230px;
border-radius: 5px;
border-left: 5px solid white;
margin: auto;
margin-top: 50px;
}
.output p {
margin: 5px 0;
font-size: 18px;
color: goldenrod;
/* line-height: 30px; */
padding-top: 25px;
margin-left: 20px;
}

input {
padding: 8px;
width: 300px;
font-size: 16px;
border: 5px double goldenrod;
border-radius: 10px;
text-align: center;
}
section {
display: flex;
flex-direction: column;
align-items: center;
justify-content: center;
margin-top: 170px;
}
</style>
<body>
<section>
<input type="text" id="myInput" placeholder="Type something..." />
<div class="output">
<p id="keyPressed">Key Pressed :</p>
<p id="keyCode">Key Code :</p>
<p id="charCode">Char codeAt :</p>
<p id="eventType">Event Type :</p>
</div>
</section>

```

```
<script>
// Function to handle keypress events
const handleKeyPress = (event) => {
  console.log(event);
  console.log("keyPressed :", event.key);
  console.log("keyCode :", event.code);
  console.log("charCode :", event.key.charCodeAt(0));
  console.log("charType :", event.type);

  document.getElementById(
    "keyPressed"
  ).textContent = `Key Pressed : ${event.key}`;
  document.getElementById(
    "keyCode"
  ).textContent = `Key Code : ${event.code}`;
  document.getElementById(
    "charCode"
  ).textContent = `Key CodeAt : ${event.key.charCodeAt(0)}`;
  document.getElementById(
    "eventType"
  ).textContent = `Key Type : ${event.type}`;
};

// Get input element
let myInput = document.getElementById("myInput");

// Add event listener
myInput.addEventListener("keydown", handleKeyPress);
myInput.addEventListener("keyup", handleKeyPress);
</script>
</body>
</html>
```