

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8" />
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
<title>Document</title>
<style>
body{
background-color: black;
}
#rectangle {
width: 300px;
height: 300px;
background-color: goldenrod;
border-radius: 10px;
box-shadow: 0 4px 10px rgba(0, 0, 0, 0.3);
margin: auto;
margin-top: 170px;
}
#myBtn {
display: block;
margin: 20px auto;
padding: 12px 24px;
font-size: 18px;
font-weight: bold;
background-color: teal;
color: white;
border: none;
border-radius: 8px;
cursor: pointer;
transition: background-color 0.3s ease;
}
#myBtn1 {
display: block;
margin: 20px auto;
padding: 12px 24px;
font-size: 18px;
font-weight: bold;
background-color: teal;
color: white;
border: none;
border-radius: 8px;
cursor: pointer;
transition: background-color 0.3s ease;
}
#rectangle.transition {
border-radius: 50%;
transition: 1.5s ease;
}
#rectangle.transition1 {
transition: 1.5s ease;
translate: -30rem 0;
border-radius: 50%;
background-color: cadetblue;
}
#rectangle.transition2 {
transition: 1.5s ease;
translate: 0 0;
border-radius: 0%;
}
```

```

background-color: goldenrod;
}
#rectangle.transition3 {
transition: 1.5s ease;
translate: 30rem 0;
border-radius: 50%;
background-color: chocolate;
}
#rectangle.transition4 {
transition: 1.5s ease;
translate: 0 0;
background-color: goldenrod;
border-radius: 0%;
}
</style>
</head>
<body>
<section>
<div id="rectangle"></div>
<button id="myBtn">Click Me</button>
<button id="myBtn1">Click Me</button>
</section>

<script>
let rect = document.getElementById("rectangle");
let Btn = document.getElementById("myBtn");
let Btn1 = document.getElementById("myBtn1");

Btn.addEventListener("click", function () {
console.log("click");
rect.style.backgroundColor = "red";
});

Btn.addEventListener("dblclick", function () {
console.log("dblclick");
rect.classList.add("transition");
});

rect.addEventListener("mouseover", function () {
console.log("mouseover");
rect.classList.add("transition1");
});

rect.addEventListener("mouseout", function () {
console.log("mouseout");
rect.classList.add("transition2");
});

Btn1.addEventListener("mousedown", function () {
console.log("mousedown");
rect.classList.add("transition3");
});

Btn1.addEventListener("mouseup", function () {
console.log("mouseup");
rect.classList.add("transition4");
});
</script>
</body>

```

</html>