



# Const keyword in C++

Difficulty Level : Medium • Last Updated : 10 Oct, 2022



In this article, the various functions of the [const keyword](#) which is found in **C++** are discussed. Whenever **const keyword** is attached with any method(), variable, [pointer variable](#), and with the object of a class it prevents that specific **object/method()/variable** to modify its data items value.


## Constant Variables:

There are a certain set of rules for the declaration and initialization of the constant variables:

- The [const variable](#) cannot be left un-initialized at the time of the assignment.
- It cannot be assigned value anywhere in the program.
- Explicit value needed to be provided to the constant variable at the time of declaration of the constant variable.

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**



Below is the C++ program to demonstrate the above concept:

## C++

```
// C++ program to demonstrate the
// the above concept
#include <iostream>
using namespace std;

// Driver Code
int main()
{
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
cout << y;
```

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

## Output:

```
10
```

**The error faced for faulty declaration:** If you try to initialize the const variable without assigning an explicit value then a compile-time error (CTE) is generated.

```
Binary.C++: In function 'int main()':
Binary.C++:6:15: error: uninitialized const 'x' [-fpermissive]
    const int x;
            ^
Binary.C++:7:7: error: assignment of read-only variable 'x'
    x=9;
    ^
PS E:\C++_prog>
```

## **Const Keyword With Pointer Variables:**

Pointers can be declared with a const keyword. So, there are three possible ways to use a const keyword with a pointer, which are as follows:

### **When the pointer variable point to a const value:**

#### **Syntax:**

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

Below is the C++ program to implement the above concept:

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

```
// C++ program to demonstrate the
// above concept
#include <iostream>
using namespace std;

// Driver Code
int main()
{
    int x{ 10 };
    char y{ 'M' };

    const int* i = &x;
    const char* j = &y;

    // Value of x and y can be altered,
    // they are not constant variables
    x = 9;
    y = 'A';

    // Change of constant values because,
    // i and j are pointing to const-int
    // & const-char type value
    // *i = 6;
    // *j = 7;

    cout << *i << " " << *j;
}
```

### Output:

9 A

**Explanation:** Here in the above case, i and j are two pointer variables that are pointing to a memory location const int-type and char-type,

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

**Otherwise, the following error will appear:** If we try to modify the

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

```
Binary.C++: In function 'int main()':
Binary.C++:62:8: error: assignment of read-only location '* i'
    *i=6;    // We aren't allowed to change constant values,because pointer variable pointing to
    ^
Binary.C++:63:8: error: assignment of read-only location '* j'
    *j=7;    // the Const type values i,j. Cte(Error)
```

### When the const pointer variable point to the value:

#### Syntax:

```
data_type* const var_name;
```

Below is the example to demonstrate the above concept:

#### C++

```
// C++ program to demonstrate the
// above concept
#include <iostream>
using namespace std;

// Driver Code
int main()
{
    // x and z non-const var
    int x = 5;
    int z = 6;

    // y and n non-const var
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
// to the var x's location
int* const i = &x;
```

[Read](#)[Discuss\(4\)](#)   [Courses](#)   [Practice](#)   [Video](#)

```
// to the var y's location
char* const j = &y;
```

```
// The values that is stored at the memory location can modified
// even if we modify it through the pointer itself
// No CTE error
*i = 10;
*j = 'D';
```

```
// CTE because pointer variable
// is const type so the address
// pointed by the pointer variables
// can't be changed
// i = &z;
// j = &p;
```

```
cout << *i << " and " << *j
      << endl;
cout << i << " and " << j;
```

```
return 0;
```

```
}
```

Output:

10 and D

0x7ffe7b2392a0 and DC

**Explanation:** The values that are stored in the corresponding pointer variable i and j are modifiable, but the locations that are pointed out by const-pointer variables where the corresponding values of x and y are stored aren't modifiable.

**Otherwise, the following error will appear:** The pointer variables are const and pointing to the locations where the x and y are stored if we

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

```
PS C:\Users\LENOVO Z50\Desktop\edureka\Contribute\infer> cd "e:\C++_prog\" ; if ($?) { g++ Binary.C++ -o Binary } ; if ($?) { .\Binary }
Binary.C++: In function 'int main()':
Binary.C++:66:9: error: invalid conversion from 'int*' to 'int' [-fpermissive]
    *i=&z; //Cte(error), because pointer variable is const type
    ^~
Binary.C++:67:9: error: invalid conversion from 'char*' to 'char' [-fpermissive]
    *j=&p; //Cte(error), because pointer variable is const type
    ^~
```

## When const pointer pointing to a const variable:

### Syntax:

```
const data_type* const var_name;
```

Below is the C++ program to demonstrate the above concept:

### C++

```
// C++ program to demonstrate
// the above concept
#include <iostream>
using namespace std;

// Driver code
int main()
{
    int x{ 9 };

    const int* const i = &x;

    // *i=10;
    // The above statement will give CTE
    // Once Ptr(*i) value is
    // assigned, later it can't
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

**Got It !**

```
const char* const j = &y;
```

[Read](#)
[Discuss\(4\)](#)
[Courses](#)
[Practice](#)
[Video](#)

```
// Once Ptr(*j) value is
// assigned, later it can't
// be modified(Error)
```

```
cout << *i << " and " << *j;
```

```
return 0;
```

```
}
```

## Output:

9 and A

**Explanation:** Here, the const pointer variable points to the const variable. So, you are neither allowed to change the const **pointer variable(\*P)** nor the value stored at the location pointed by that **pointer variable(\*P)**.

**Otherwise, the following error will appear:** Here both pointer variable and the locations pointed by the pointer variable are const so if any of them is modified, the following error will appear:

Try the new cross-platform PowerShell <https://aka.ms/pscore6>

```
PS C:\Users\LENOVO Z50\Desktop\edureka\Contribute\infer> cd "e:\C++_prog\" ; if ($?) { g++ Binary.C++ -o Binary } ; if ($?) { .\Binary }
Binary.C++: In function 'int main()':
Binary.C++:58:8: error: assignment of read-only location '*(const int*)i'
    *i=10; //Cte(error)
    ^~
Binary.C++:60:8: error: assignment of read-only location '*(const char*)j'
    *j='B'; //Once Ptr(*j) value is assigned later it can't be modified
    ^~~~
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

**Got It !**



## **cause error:** Passing const argument value to a non-const parameter

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

Below is the C++ program to demonstrate the above concept.

### C++

```
// C++ program to demonstrate
// the above concept
#include <iostream>
using namespace std;

int foo(int* y)
{
    return *y;
}

// Driver code
int main()
{
    int z = 8;
    const int* x = &z;
    cout << foo(x);
    return 0;
}
```

**Output:** The compile-time error that will appear as if const value is passed to any non-const argument of the function then the following compile-time error will appear:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

```

PS C:\Users\LENOVO Z50\Desktop\edureka\Contribute\infer> cd "e:\C++_prog\" ; if ($?) { g++ Binary.C++ -o Binary } ; if ($?) { .\Binary }
Binary.C++: In function 'int main()':
Binary.C++:63:16: error: invalid conversion from 'const int*' to 'int*' [-fpermissive]
    cout<<foo(x);
               ^
               ~
Binary.C++:54:5: note: initializing argument 1 of 'int foo(int*)'
    int foo(int* y)
    ~~~
PS E:\C++_prog>

```

**In nutshell, the above discussion can be concluded as follows:**

1. *int value = 5;      // non-const value*
2. *const int \*ptr\_1 = &value;    // ptr\_1 points to a "const int" value, so this is a pointer to a const value.*
3. *int \*const ptr\_2 = &value;    // ptr\_2 points to an "int", so this is a const pointer to a non-const value.*
4. *const int \*const ptr\_3 = &value; // ptr\_3 points to a "const int" value, so this is a const pointer to a const value.*

### **Constant Methods:**

Like member functions and member function arguments, the objects of a class can also be declared as **const**. An object declared as const cannot be modified and hence, can invoke only const member functions as these functions ensure not to modify the object.

### **Syntax:**

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

of object, const object as well as non-const objects.

.... . . . . .

[Read](#)

[Discuss\(4\)](#)

[Courses](#)

[Practice](#)

[Video](#)

declaring is possible only with the help of constructors.

There are two ways of a [constant function](#) declaration:

### **Ordinary const-function Declaration:**

```
const void foo()
{
    //void foo() const Not valid
}
int main()
{
    foo();
}
```

### **A const member function of the class:**

```
class
{
    void foo() const
    {
        //.....
    }
}
```

Below is the example of a constant function:

## **C++**

```
// C++ program to demonstrate the
// constant function
#include <iostream>
using namespace std;
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

**public:**

**Read**

Discuss(4)

Courses

Practice

Video

```
{
    value = v;
}

// We get compiler error if we
// add a line like "value = 100;"
// in this function.
int getValue() const
{
    return value;
}

// a nonconst function trying to modify value
void setValue(int val) {
    value = val;
}
};

// Driver Code
int main()
{
    // Object of the class T
    Test t(20);

    // non-const object invoking const function, no error
    cout << t.getValue() << endl;

    // const object
    const Test t_const(10);

    // const object invoking const function, no error
    cout << t_const.getValue() << endl;

    // const object invoking non-const function, CTE
    // t_const.setValue(15);

    // non-const object invoking non-const function, no error
    t.setValue(12);

    cout << t.getValue() << endl;
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

## Output:

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

**The Following error will if you try call the non-const function from a const object**

Compilation failed due to following error(s).

```
main.cpp: In function 'int main()':
main.cpp:42:28: error: passing 'const Test' as 'this' argument discards qualifiers [-fpermissive]
    t_const.setValue(15);
                   ^
main.cpp:25:18: note: in call to 'void Test::setValue(int)'
    void setValue(int val) {
        ^~~~~~
```

### Constant Function Parameters And Return Type:

A function() parameters and return type of function() can be declared as constant. Constant values cannot be changed as any such attempt will generate a compile-time error.

Below is the C++ program to implement the above approach:

### C++

```
// C++ program to demonstrate the
// above approach
#include <iostream>
using namespace std;
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
// y = 6; const value
// can't be change
```

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

```
// Function foo() with variable int
void foo1(int y)
{
    // Non-const value can be change
    y = 5;
    cout << '\n'
         << y;
}

// Driver Code
int main()
{
    int x = 9;
    const int z = 10;

    foo(z);
    foo1(x);

    return 0;
}
```

### Output:

```
10
5
```

**Explanation:** The following error will be displayed:

- // y = 6; a const value can't be changed or modified.

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

Try the new cross-platform PowerShell <https://aka.ms/pscore6>

```
PS C:\Users\LENOVO Z50\Desktop\edureka\Contribute\infer> cd "e:\C++_prog\" ; if ($?) { g++ Binary.C++ -o Binary } ; if ($?) { .\Binary }
Binary.C++: In function 'void foo(int)':
Binary.C++:56:5: error: assignment of read-only parameter 'y'
    y=6;
    ^
```

**For const return type:** The return type of the function() is const and so it returns a const integer value to us. Below is the C++ program to implement the above approach:

## C++

```
// C++ program for the above approach
#include <iostream>
using namespace std;

const int foo(int y)
{
    y--;
    return y;
}

int main()
{
    int x = 9;
    const int z = 10;
    cout << foo(x) << '\n'
         << foo(z);

    return 0;
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

Got It !

8

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

There is no substantial issue to pass const or non-const variable to the function because the value that will be returned by the function will be constant automatically. As the argument of the function is non-const.

**For const return type and const parameter:** Here, both return type and parameter of the function are of const types. Below is the C++ program to implement the above approach:

## C++

```
// C++ program for the above approach
#include <iostream>
using namespace std;

const int foo(const int y)
{
    // y = 9; it'll give CTE error as
    // y is const var its value can't
    // be change
    return y;
}

// Driver code
int main()
{
    int x = 9;
    const int z = 10;
    cout << foo(x) << '\n'
         << foo(z);

    return 0;
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !



10

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

**Explanation:** Here, both const and non-const values can be passed as the const parameter to the function, but we are not allowed to then change the value of a passed variable because the parameter is const. **Otherwise, we'll face the error as below:**

// y=9; it'll give the compile-time error as y is const var its value can't be changed.

```
Binary.C++: In function 'const int foo(int)':  
Binary.C++:6:5: error: assignment of read-only parameter 'y'  
    y=9; //it'll give CTE error as y is const var its value can't be change  
    ^  
PS E:\C++_prog>
```

**Hiring Challenge: Ticket to Your Dream Career!**



Like 71

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

## C++

## C++ to perform various

[Read](#)[Discuss\(4\)](#)[Courses](#)[Practice](#)[Video](#)

### Related Articles

1. Difference between `const char *p`, `char * const p` and `const char * const p`
2. C++ | const keyword | Question 1
3. C++ | const keyword | Question 2
4. C++ | const keyword | Question 3
5. C++ | const keyword | Question 5
6. C++ | const keyword | Question 5
7. Function overloading and const keyword
8. Why copy constructor argument should be const in C++?
9. How to modify a const variable in C?
10. "static const" vs "#define" vs "enum"

#### Company

[About Us](#)[Careers](#)[In Media](#)

#### Learn

[DSA](#)[Algorithms](#)[Data Structures](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[Got It !](#)

Advertise with us

Video Tutorials

Read

Discuss(4)

Courses

Practice

Video

## News



**madhav\_mohan**  
Top News  
@madhav\_mohan  
Technology

Work & Career

**Vote for difficulty**

Current difficulty : **Medium**

Business  
Finance  
Lifestyle

Easy Normal Medium Hard Expert

## Languages

Python

Java

CPP

Golang

C#

SQL

Kotlin

## Web Development

**Improved By:** [surendrapandey](#), [CoderSaty](#), [snaze01](#), [akashpatil3640](#),  
[gauravgupta050300](#)

Django Tutorial

**Article Tags :** [HTML](#) [C++-const keyword](#), [const keyword](#), [Articles](#), [C++ Programs](#), [Technical Scripter](#)

JavaScript

**Practice Tags :** [Bootstrap](#)

ReactJS

NodeJS

Improve Article

Report Issue

## Contribute

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships

Video Internship

@geeksforgeeks , Some rights reserved

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !