



Mega Job-a-thon

DSA

Data Structures

Algorithms

Interview Preparation

Data Science

**MEGA JOB-A-THON** FOR FRESHERSAPPLY FOR  
10+ COMPANIES!**MEGA JOB-A-THON** FOR PROFESSIONALSFIND BETTER  
OPPORTUNITIES!

# Program for nth Catalan Number

Difficulty Level : Medium • Last Updated : 23 Nov, 2022



**Catalan numbers** are defined as a mathematical sequence that consists of positive integers, which can be used to find the number of possibilities of various combinations.

The **nth** term in the sequence denoted **C<sub>n</sub>**, is found in the following formula:

$$\frac{(2n)!}{(n+1)!n!}$$

*The first few Catalan numbers for  $n = 0, 1, 2, 3, \dots$  are : 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, ...*

**Catalan numbers occur in many interesting counting problems like the following.**

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

parentheses that are correctly matched. For  $n = 3$ , possible expressions are  $((()))$ ,  $()(())$ ,  $(())()$ ,  $((())())$ ,  $((())())$ .

2. Count the number of possible Binary Search Trees with  $n$  keys (See [this](#))
3. Count the number of full binary trees (A rooted binary tree is full if every vertex has either two children or no children) with  $n+1$  leaves.
4. Given a number  $n$ , return the number of ways you can draw  $n$  chords in a circle with  $2 \times n$  points such that no 2 chords intersect.

See [this](#) for more applications.

**Examples:**

**Input:**  $n = 6$

**Output:** 132

**Input:**  $n = 8$

**Output:** 1430

Recommended: Please solve it on "[PRACTICE](#)" first, before moving on to the solution.

## Recursive Solution for Catalan number:

*Catalan numbers satisfy the following recursive formula:*

$$C_0 = 1 \text{ and } C_{n+1} = \sum_{i=0}^n C_i C_{n-i} \text{ for } n \geq 0$$

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

- Base condition for the recursive approach, when **n <= 1**, return **1**

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

adding the product of both into **res**.

- Return the **res**.

Following is the implementation of the above recursive formula.

## C++

```
#include <iostream>
using namespace std;

// A recursive function to find nth catalan number
unsigned long int catalan(unsigned int n)
{
    // Base case
    if (n <= 1)
        return 1;

    // catalan(n) is sum of
    // catalan(i)*catalan(n-i-1)
    unsigned long int res = 0;
    for (int i = 0; i < n; i++)
        res += catalan(i) * catalan(n - i - 1);

    return res;
}

// Driver code
int main()
{
    for (int i = 0; i < 10; i++)
        cout << catalan(i) << " ";
    return 0;
}
```

## Java

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

Got It !

```
// A recursive function to find nth catalan number
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
{
    int res = 0;

    // Base case
    if (n <= 1) {
        return 1;
    }
    for (int i = 0; i < n; i++) {
        res += catalan(i) * catalan(n - i - 1);
    }
    return res;
}

// Driver Code
public static void main(String[] args)
{
    CatalnNumber cn = new CatalnNumber();
    for (int i = 0; i < 10; i++) {
        System.out.print(cn.catalan(i) + " ");
    }
}
```

## Python3

```
# A recursive function to
# find nth catalan number
```

```
def catalan(n):
    # Base Case
    if n <= 1:
        return 1

    # Catalan(n) is the sum
    # of catalan(i)*catalan(n-i-1)
    res = 0
    for i in range(n):
        res += catalan(i) * catalan(n-i-1)
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
# Driver Code
for i in range(10):
```

[Read](#)   [Discuss](#)   [Courses](#)   [Practice](#)   [Video](#)

```
# Nikhil Kumar Singh (nickzuck_007)
```

## C#

```
// A recursive C# program to find
// nth catalan number
using System;

class GFG {

    // A recursive function to find
    // nth catalan number
    static int catalan(int n)
    {
        int res = 0;

        // Base case
        if (n <= 1) {
            return 1;
        }
        for (int i = 0; i < n; i++) {
            res += catalan(i) * catalan(n - i - 1);
        }
        return res;
    }

    // Driver Code
    public static void Main()
    {
        for (int i = 0; i < 10; i++)
            Console.Write(catalan(i) + " ");
    }
}

// This code is contributed by
// nitin mittal.
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
// Catalan Number
```

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

```
function catalan($n)
{
    // Base case
    if ($n <= 1)
        return 1;

    // catalan(n) is sum of
    // catalan(i)*catalan(n-i-1)
    $res = 0;
    for($i = 0; $i < $n; $i++)
        $res += catalan($i) *
            catalan($n - $i - 1);

    return $res;
}

// Driver Code
for ($i = 0; $i < 10; $i++)
    echo catalan($i), " ";

// This code is contributed aj_36
?>
```

## Javascript

```
// Javascript Program for nth
// Catalan Number

// A recursive function to
// find nth catalan number
function catalan(n)
{
    // Base case
    if (n <= 1)
        return 1;
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```

        res += catalan(i) *
               catalan(n - i - 1);

```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```

    }

```

```

// Driver Code

```

```

for (let i = 0; i < 10; i++)
    document.write(catalan(i) + " ");

```

```

// This code is contributed _saurabh_jaiswal

```

## Output

```

1 1 2 5 14 42 132 429 1430 4862

```

**Time Complexity:** The above implementation is equivalent to nth Catalan number.

$$T(n) = \sum_{i=0}^{n-1} T(i) * T(n-i-1) \text{ for } n \geq 1;$$

The value of **nth** Catalan number is exponential which makes the time complexity exponential.

**Auxiliary Space:**  $O(n)$

## Dynamic Programming Solution for Catalan number:

*We can observe that the above recursive implementation does a lot of repeated work. Since there are overlapping subproblems, we can use dynamic programming for this.*

**Below is the implementation of the above idea:**

- Create an array **catalan[]** for storing **ith** Catalan number.

• Initialize **catalan[0]** and **catalan[1] = 1**

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

- Finally, return **catalan[n]**.

[Read](#) [Discuss](#) [Courses](#) [Practice](#) [Video](#)

Follow the steps below to implement the above approach.

## C++

```
#include <iostream>
using namespace std;

// A dynamic programming based function to find nth
// Catalan number
unsigned long int catalanDP(unsigned int n)
{
    // Table to store results of subproblems
    unsigned long int catalan[n + 1];

    // Initialize first two values in table
    catalan[0] = catalan[1] = 1;

    // Fill entries in catalan[] using recursive formula
    for (int i = 2; i <= n; i++) {
        catalan[i] = 0;
        for (int j = 0; j < i; j++)
            catalan[i] += catalan[j] * catalan[i - j - 1];
    }

    // Return last entry
    return catalan[n];
}

// Driver code
int main()
{
    for (int i = 0; i < 10; i++)
        cout << catalanDP(i) << " ";
    return 0;
}
```

## Java

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !



```
// Catalan number
static int catalanDP(int n)
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
int catalan[] = new int[n + 2];

// Initialize first two values in table
catalan[0] = 1;
catalan[1] = 1;

// Fill entries in catalan[]
// using recursive formula
for (int i = 2; i <= n; i++) {
    catalan[i] = 0;
    for (int j = 0; j < i; j++) {
        catalan[i]
            += catalan[j] * catalan[i - j - 1];
    }
}

// Return last entry
return catalan[n];
}

// Driver code
public static void main(String[] args)
{
    for (int i = 0; i < 10; i++) {
        System.out.print(catalanDP(i) + " ");
    }
}

// This code contributed by Rajput-Ji
```

## Python3

```
# A dynamic programming based function to find nth
# Catalan number
```

```
def catalan(n):
    if (n == 0 or n == 1):
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
# Initialize first two values in table
```

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

```
# Fill entries in catalan[]
# using recursive formula
for i in range(2, n + 1):
    for j in range(i):
        catalan[i] += catalan[j] * catalan[i-j-1]

# Return last entry
return catalan[n]
```

```
# Driver code
```

```
for i in range(10):
    print(catalan(i), end=" ")
# This code is contributed by Ediga_manisha
```

## C#

```
using System;
```

```
class GFG {
```

```
// A dynamic programming based
// function to find nth
// Catalan number
static uint catalanDP(uint n)
{
    // Table to store results of subproblems
    uint[] catalan = new uint[n + 2];

    // Initialize first two values in table
    catalan[0] = catalan[1] = 1;

    // Fill entries in catalan[]
    // using recursive formula
    for (uint i = 2; i <= n; i++) {
        catalan[i] = 0;
        for (uint j = 0; j < i; j++)
            catalan[i]
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
    return catalan[n];
```

```
}
```

[Read](#)

[Discuss](#)

[Courses](#)

[Practice](#)

[Video](#)

```
static void Main()
```

```
{
```

```
    for (uint i = 0; i < 10; i++)
```

```
        Console.Write(catalanDP(i) + " ");
```

```
}
```

```
}
```

```
// This code is contributed by Chandan_jnu
```

## PHP

```
<?php
```

```
// PHP program for nth Catalan Number
```

```
// A dynamic programming based function
```

```
// to find nth Catalan number
```

```
function catalanDP( $n)
```

```
{
```

```
    // Table to store results
```

```
    // of subproblems
```

```
    $catalan= array();
```

```
    // Initialize first two
```

```
    // values in table
```

```
    $catalan[0] = $catalan[1] = 1;
```

```
    // Fill entries in catalan[]
```

```
    // using recursive formula
```

```
    for ($i = 2; $i <= $n; $i++)
```

```
    {
```

```
        $catalan[$i] = 0;
```

```
        for ( $j = 0; $j < $i; $j++)
```

```
            $catalan[$i] += $catalan[$j] *
```

```
                $catalan[$i - $j - 1];
```

```
    }
```

```
    // Return last entry
```

```
    return $catalan[$n];
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
echo catalanDP($i) , " ";
```

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

## Javascript

```
// Javascript program for nth Catalan Number

// A dynamic programming based function
// to find nth Catalan number
function catalanDP(n)
{
    // Table to store results
    // of subproblems
    let catalan= [];

    // Initialize first two
    // values in table
    catalan[0] = catalan[1] = 1;

    // Fill entries in catalan[]
    // using recursive formula
    for (let i = 2; i <= n; i++)
    {
        catalan[i] = 0;
        for (let j = 0; j < i; j++)
            catalan[i] += catalan[j] *
                        catalan[i - j - 1];
    }

    // Return last entry
    return catalan[n];
}

// Driver Code
for (let i = 0; i < 10; i++)
    document.write(catalanDP(i) + " ");

// This code is contributed _saurabh_jaiswal
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

1 1 2 5 14 42 132 429 1430 4862

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

**Auxiliary Space:**  $O(n)$

## Binomial Coefficient Solution for Catalan number:

We can also use the below formula to find **nth** Catalan number in  **$O(n)$**  time.

$$C_n = \frac{1}{n+1} \binom{2n}{n}$$

Below are the steps for calculating  $nC_r$ .

- Create a variable to store the answer and change **r** to **n - r** if **r** is greater than **n - r** because we know that  $C(n, r) = C(n, n-r)$  if  $r > n - r$
- Run a loop from **0** to **r-1**
  - In every iteration update ans as  $(ans * (n-i)) / (i+1)$ , where **i** is the loop counter.
- So the answer will be equal to  $((n/1) * ((n-1)/2) * ... * ((n-r+1)/r)$ , which is equal to  $nC_r$ .

Below are steps to calculate Catalan numbers using the formula:

$$2nC_n / (n+1)$$

- Calculate  $2nC_n$  using the similar steps that we use to calculate  $nC_r$
- Return the value  $2nC_n / (n+1)$

Below is the implementation of the above approach:

### C++

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
// Returns value of Binomial Coefficient C(n, k)
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
{
    unsigned long int res = 1;

    // Since C(n, k) = C(n, n-k)
    if (k > n - k)
        k = n - k;

    // Calculate value of [n*(n-1)*---*(n-k+1)] /
    // [k*(k-1)*---*1]
    for (int i = 0; i < k; ++i) {
        res *= (n - i);
        res /= (i + 1);
    }

    return res;
}

// A Binomial coefficient based function to find nth catalan
// number in O(n) time
unsigned long int catalan(unsigned int n)
{
    // Calculate value of 2nCn
    unsigned long int c = binomialCoeff(2 * n, n);

    // return 2nCn/(n+1)
    return c / (n + 1);
}

// Driver code
int main()
{
    for (int i = 0; i < 10; i++)
        cout << catalan(i) << " ";
    return 0;
}
```

## Java

```
// Returns value of Binomial Coefficient C(n, k)
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
static long binomialCoeff(int n, int k)
{
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```

    // Since C(n, k) = C(n, n-k)
    if (k > n - k) {
        k = n - k;
    }

    // Calculate value of [n*(n-1)*---*(n-k+1)] /
    // [k*(k-1)*---*1]
    for (int i = 0; i < k; ++i) {
        res *= (n - i);
        res /= (i + 1);
    }

    return res;
}

// A Binomial coefficient based function
// to find nth catalan number in O(n) time
static long catalan(int n)
{
    // Calculate value of 2nCn
    long c = binomialCoeff(2 * n, n);

    // return 2nCn/(n+1)
    return c / (n + 1);
}

// Driver code
public static void main(String[] args)
{
    for (int i = 0; i < 10; i++) {
        System.out.print(catalan(i) + " ");
    }
}
}
```

## Python3

# Python program for nth Catalan Number

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
# since  $C(n, k) = C(n, n - k)$ 
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
# initialize result
res = 1

# Calculate value of  $[n * (n-1) * \dots * (n-k + 1)]$ 
# /  $[k * (k-1) * \dots * 1]$ 
for i in range(k):
    res = res * (n - i)
    res = res / (i + 1)
return res
```

```
# A Binomial coefficient based function to
# find nth catalan number in  $O(n)$  time
```

```
def catalan(n):
    c = binomialCoefficient(2*n, n)
    return c/(n + 1)
```

```
# Driver Code
```

```
for i in range(10):
    print(catalan(i), end=" ")
```

```
# This code is contributed by Aditi Sharma
```

## C#

```
// C# program for nth Catalan Number
using System;
class GFG {

    // Returns value of Binomial Coefficient  $C(n, k)$ 
    static long binomialCoeff(int n, int k)
    {
        long res = 1;

        // Since  $C(n, k) = C(n, n-k)$ 
        if (k > n - k) {
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !



```
// [k*(k-1)*---*1]
for (int i = 0; i < k; ++i) {
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
}
```

```
return res;
```

```
}
```

```
// A Binomial coefficient based function to find nth
// catalan number in O(n) time
```

```
static long catalan(int n)
```

```
{
```

```
// Calculate value of  $2nC_n$ 
```

```
long c = binomialCoeff(2 * n, n);
```

```
// return  $2nC_n/(n+1)$ 
```

```
return c / (n + 1);
```

```
}
```

```
// Driver code
```

```
public static void Main()
```

```
{
```

```
for (int i = 0; i < 10; i++) {
```

```
Console.Write(catalan(i) + " ");
```

```
}
```

```
}
```

```
}
```

```
// This code is contributed
```

```
// by Akanksha Rai
```

## PHP

```
<?php
```

```
// PHP program for nth Catalan Number
```

```
// Returns value of Binomial
```

```
// Coefficient  $C(n, k)$ 
```

```
function binomialCoeff($n, $k)
```

```
{
```

```
$res = 1;
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
// Calculate value of [n*(n-1)*---*(n-k+1)] /
// [k*(k-1)*---*1]
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
$res *= ($n - $i);
$res = floor($res / ($i + 1));
}

return $res;
}

// A Binomial coefficient based function
// to find nth catalan number in O(n) time
function catalan($n)
{
    // Calculate value of 2nCn
    $c = binomialCoeff(2 * ($n), $n);

    // return 2nCn/(n+1)
    return floor($c / ($n + 1));
}

// Driver code
for ($i = 0; $i < 10; $i++)
echo catalan($i), " ";

// This code is contributed by Ryuga
?>
```

## Javascript

```
// Javascript program for nth Catalan Number

// Returns value of Binomial
// Coefficient C(n, k)
function binomialCoeff(n, k)
{
    let res = 1;

    // Since C(n, k) = C(n, n-k)
    if (k > n - k)
        k = n - k;

    // Calculate value of C(n, k) using
    // iterative formula
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

        res *= (n - i);
        res = Math.floor(res / (i + 1));

```

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

```

    return res;
}

// A Binomial coefficient based function
// to find nth catalan number in O(n) time
function catalan(n)
{
    // Calculate value of 2nCn
    c = binomialCoeff(2 * (n), n);

    // return 2nCn/(n+1)
    return Math.floor(c / (n + 1));
}

// Driver code
for (let i = 0; i < 10; i++)
    document.write(catalan(i) + " ");

// This code is contributed by _saurabh_jaiswal

```

## Output

```
1 1 2 5 14 42 132 429 1430 4862
```

**Time Complexity:**  $O(n)$ .

**Auxiliary Space:**  $O(1)$

We can also use the below formulas to find **nth** Catalan number in  $O(n)$  time.

$$C_n = \frac{(2n)!}{(n+1)!n!} = \prod_{k=2}^n \frac{n+k}{k} \text{ for } n \geq 0$$

$$C_n = \frac{2(2n-1)}{n+1} * C_{n-1} \quad | \quad n > 0$$

## Catalan number using the multi-Precision library:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

to calculate Catalan numbers.

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

- a) initially set `cat_=1` and print it
- b) run a for loop `i=1` to `i<=n`
  - `cat_ *= (4*i-2)`
  - `cat_ /= (i+1)`
  - `print cat_`
- c) end loop and exit

Below is the implementation using the multi-precision library:

## C++

```
#include <bits/stdc++.h>
#include <boost/multiprecision/cpp_int.hpp>
using boost::multiprecision::cpp_int;
using namespace std;

// Function to print the number
void catalan(int n)
{
    cpp_int cat_ = 1;

    // For the first number
    cout << cat_ << " "; // C(0)

    // Iterate till N
    for (cpp_int i = 1; i <= n; i++) {
        // Calculate the number
        // and print it
        cat_ *= (4 * i - 2);
        cat_ /= (i + 1);
        cout << cat_ << " ";
    }
}

// Driver code
int main()
{
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
    return 0;
}
```

[Read](#) [Discuss](#) [Courses](#) [Practice](#) [Video](#)

## Java

```
import java.util.*;
class GFG {

    // Function to print the number
    static void catalan(int n)
    {
        int cat_ = 1;

        // For the first number
        System.out.print(cat_ + " "); // C(0)

        // Iterate till N
        for (int i = 1; i < n; i++) {
            // Calculate the number
            // and print it
            cat_ *= (4 * i - 2);
            cat_ /= (i + 1);
            System.out.print(cat_ + " ");
        }
    }

    // Driver code
    public static void main(String args[])
    {
        int n = 5;

        // Function call
        catalan(n);
    }
}

// This code is contributed by Debojyoti Mandal
```

## Python3

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
# For the first number
print(cat_, " ", end='') # C(0)
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
for i in range(1, n):

    # Calculate the number
    # and print it
    cat_ *= (4 * i - 2)
    cat_ //= (i + 1)
    print(cat_, " ", end='')
```

```
# Driver code
```

```
n = 5
```

```
# Function call
```

```
catalan(n)
```

```
# This code is contributed by rohan07
```

## C#

```
using System;
```

```
public class GFG {
```

```
// Function to print the number
```

```
static void catalan(int n)
```

```
{
```

```
    int cat_ = 1;
```

```
    // For the first number
```

```
    Console.Write(cat_ + " "); // C(0)
```

```
    // Iterate till N
```

```
    for (int i = 1; i < n; i++) {
```

```
        // Calculate the number
```

```
        // and print it
```

```
        cat_ *= (4 * i - 2);
```

```
        cat_ /= (i + 1);
```

```
        Console.Write(cat_ + " ");
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```
public static void Main(String[] args)
{
```

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

```
    // Function call
    catalan(n);
}
}
```

// This code is contributed by Rajput-Ji

## Javascript

```
// Function to print the number
function catalan(n)
{
    let cat_ = 1;

    // For the first number
    document.write(cat_ + " "); // C(0)

    // Iterate till N
    for (let i = 1; i < n; i++)
    {
        // Calculate the number
        // and print it
        cat_ *= (4 * i - 2);
        cat_ /= (i + 1);
        document.write(cat_ + " ");
    }
}

// Driver code
let n = 5;

// Function call
catalan(n);

//This code is contributed by Mayank Tyagi
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

## Time Complexity: $O(n)$

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

### Catalan number using BigInteger in java:

Finding values of Catalan numbers for  $N > 80$  is not possible even by using **long** in java, so we use **BigInteger**.

Follow the steps below for the implementation:

- Create a BigInteger variable **b** and initialize it to **1**.
- Calculate **n!** and store it into **b**.
- Calculate **n! \* n!** and store into **b**.
- Create another BigInteger variable **d** and initialize it to **1**.
- Calculate **2n!** and store into **d**.
- Calculate **(2n)! / (n! \* n!)** into **ans**
- Calculate **ans / (n + 1)** and return **ans**.

Below is the implementation of the above approach:

### C++

```
#include <bits/stdc++.h>
using namespace std;

#define bigint long long int

bigint findCatalan(int n)
{
    bigint b = 1;

    // calculating n!
    for (int i = 1; i <= n; i++) {
        b = b * i;
    }

    // calculating n! * n!
    b = b * b;

    // calculating 2n!
    bigint d = 1;
    for (int i = 1; i <= 2*n; i++) {
        d = d * i;
    }

    return d / b;
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !



```

        d = d * i;
    }

```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```

    bigint ans = d / b;

    // calculating (2n)! / ((n! * n!) * (n+1))
    ans = ans / (n + 1);
    return ans;
}

// Driver Code
int main() {
    int n = 5;
    cout << findCatalan(n);
}

// This code is contributed by ajaymakvana.

```

## Java

```

import java.io.*;
import java.math.*;
import java.util.*;

class GFG {
    public static BigInteger findCatalan(int n)
    {
        // using BigInteger to calculate large factorials
        BigInteger b = new BigInteger("1");

        // calculating n!
        for (int i = 1; i <= n; i++) {
            b = b.multiply(BigInteger.valueOf(i));
        }

        // calculating n! * n!
        b = b.multiply(b);

        BigInteger d = new BigInteger("1");

        // calculating (2n)!
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
// calculating (2n)! / (n! * n!)
BigInteger ans = d.divide(b);
```

[Read](#)
[Discuss](#)
[Courses](#)
[Practice](#)
[Video](#)

```
ans = ans.divide(BigInteger.valueOf(n + 1));
return ans;
}

// Driver Code
public static void main(String[] args)
{
    int n = 5;
    System.out.println(findCatalan(n));
}
}
// Contributed by Rohit Oberoi
```

## Python3

```
def findCatalan(n):
    b = 1

    # calculating n!
    for i in range(1, n + 1, 1):
        b = b * i

    # calculating n! * n!
    b = b * b
    d = 1

    # calculating (2n)!
    for i in range(1, 2 * n + 1, 1):
        d = d * i

    # calculating (2n)! / (n! * n!)
    ans = d / b

    # calculating (2n)! / ((n! * n!) * (n+1))
    ans = ans / (n + 1)

    return ans
```

# Driver Code

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

**Got It !**

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

```
// C# code to implement the approach
using System;
using System.Numerics;

class GFG {
    public static BigInteger findCatalan(int n)
    {
        // using BigInteger to calculate large factorials
        BigInteger b = new BigInteger(1);

        // calculating n!
        for (int i = 1; i <= n; i++) {
            b = BigInteger.Multiply(b, new BigInteger(i));
        }

        // calculating n! * n!
        b = BigInteger.Multiply(b, b);

        BigInteger d = new BigInteger(1);

        // calculating (2n)!
        for (int i = 1; i <= 2 * n; i++) {
            d = BigInteger.Multiply(d, new BigInteger(i));
        }

        // calculating (2n)! / (n! * n!)
        BigInteger ans = BigInteger.Divide(d, b);

        // calculating (2n)! / ((n! * n!) * (n+1))
        ans = BigInteger.Divide(ans, new BigInteger(n + 1));
        return ans;
    }

    // Driver Code
    public static void Main(string[] args)
    {
        int n = 5;
        Console.WriteLine(findCatalan(n));
    }
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

# Javascript

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

```
function findCatalan(n){
    let b = 1

    // calculating n!
    for(let i = 1; i <= n; i++){
        b = b * i;
    }

    // calculating n! * n!
    b = b * b;
    let d = 1;

    // calculating (2n)!
    for(let i = 1; i <= 2 * n; i++){
        d = d * i
    }

    // calculating (2n)! / (n! * n!)
    let ans = d/b;

    // calculating (2n)! / ((n! * n!) * (n+1))
    ans = ans / (n + 1);

    return ans;
}

let n = 5;
console.log(findCatalan(n));

// This code is contributed by lokeshmvs21.
```

## Output

42

## Time Complexity: $O(n)$

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

# Start Your Codina journey Now!

[Login](#)[Register](#)[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)**Like** 202[Previous](#)[Next](#)[Pascal's Triangle](#)[Find x and y satisfying  \$ax + by = n\$](#) 

## Related Articles

1. Program for nth Fuss–Catalan Number
2. Total number of possible Binary Search Trees using Catalan Number
3. Minimum changes required to make a Catalan Sequence
4. Applications of Catalan Numbers
5. Program to find Nth odd Fibonacci Number
6. Program to find the Nth natural number with exactly two bits set | Set 2

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[Got It !](#)

## 9. Program to delete Nth digit of a Number

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

### Article Contributed By :

**GeeksforGeeks**

### Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert

**Improved By :** [icr0](#), [jit\\_t](#), [nitin mittal](#), [vt\\_m](#), [soumya7](#), [29AjayKumar](#), [Harshit Singhal 2](#), [ankthon](#), [Akanksha\\_Rai](#), [Chandan\\_Kumar](#), [Rajput-Ji](#), [anantiitrk](#), [ankit\\_deshmukh](#), [madhav\\_mohan](#), [RohitOberoi](#), [manishaediga23](#), [jyoti369](#), [\\_saurabh\\_jaiswal](#), [mayanktyagi1709](#), [rohan07](#), [bunnyram19](#), [manishku12j](#), [amartyaghoshgfg](#), [prasanna1995](#), [07prashantsgh](#), [phasing17](#), [rishav1329](#), [harendrakumar123](#), [kothavvsaakash](#), [ajaymakvana](#), [lokeshmvs21](#)

**Article Tags :** [Amazon](#), [catalan](#), [series](#), [Dynamic Programming](#), [Mathematical](#), [Misc](#)

**Practice Tags :** [Amazon](#), [Dynamic Programming](#), [Mathematical](#), [Misc](#), [series](#)

[Improve Article](#)[Report Issue](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

**Got It !**

[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

## Company

[About Us](#)  
[Careers](#)  
[In Media](#)  
[Contact Us](#)  
[Privacy Policy](#)  
[Copyright Policy](#)  
[Advertise with us](#)

## News

[Top News](#)  
[Technology](#)  
[Work & Career](#)  
[Business](#)  
[Finance](#)  
[Lifestyle](#)  
[Knowledge](#)

## Web Development

[Web Tutorials](#)  
[Django Tutorial](#)  
[HTML](#)  
[JavaScript](#)  
[Bootstrap](#)  
[ReactJS](#)  
[Models](#)

## Learn

[DSA](#)  
[Algorithms](#)  
[Data Structures](#)  
[SDE Cheat Sheet](#)  
[Machine learning](#)  
[CS Subjects](#)  
[Video Tutorials](#)  
[Courses](#)

## Languages

[Python](#)  
[Java](#)  
[CPP](#)  
[Golang](#)  
[C#](#)  
[SQL](#)  
[Kotlin](#)

## Contribute

[Write an Article](#)  
[Improve an Article](#)  
[Pick Topics to Write](#)  
[Write Interview Experience](#)  
[Internships](#)  
[Video Internship](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**