

Hands-on Lab: Querying the Data Warehouse (Cubes, Rollups, Grouping Sets and Materialized Views)

Estimated time needed: 30 minutes

Objectives

In this lab you will learn how to create:

- Grouping sets
- Rollup
- Cube
- Materialized Query Tables (MQT)

Exercise 1 - Login to your Cloud IBM DB2

This lab requires that you complete the previous lab [Populate a Data Warehouse](#).

If you have not finished the Populate a Data Warehouse Lab yet, please finish it before you continue.

GROUPING SETS, CUBE, and ROLLUP allow us to easily create subtotals and grand totals in a variety of ways. All these operators are used along with the GROUP BY operator.

GROUPING SETS operator allows us to group data in a number of different ways in a single SELECT statement.

The ROLLUP operator is used to create subtotals and grand totals for a set of columns. The summarized totals are created based on the columns passed to the ROLLUP operator.

The CUBE operator produces subtotals and grand totals. In addition it produces subtotals and grand totals for every permutation of the columns provided to the CUBE operator.

Exercise 2 - Write a query using grouping sets

After you login to the cloud instance of IBM DB2, go to the sql tab and run the query below.

To create a grouping set for three columns labeled year, category, and sum of billedamount, run the sql statement below.

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8

1. select year,category, sum(billedamount) as totalbilledamount
2. from factbilling
3. left join dimcustomer
4. on factbilling.customerid = dimcustomer.customerid
5. left join dimmonth
6. on factbilling.monthid=dimmonth.monthid
7. group by grouping sets(year,category)
8. order by year, category
```

Copied!

The output of the above command will contain 13 rows. The partial output can be seen in the image below.

To see the full output click on the open in the new tab icon.

Run SQL

* Untitled - 1 x

SQL

1 select year,category, sum(billedamount) as totalbilledamount
2 from factbilling
3 left join dimcustomer
4 on factbilling.customerid = dimcustomer.customerid
5 left join dimmonth
6 on factbilling.monthid=dimmonth.monthid
7 group by grouping sets(year,category)
8 order by year, category
9

Result - Oct 11, 2021 4:22:19 PM

select year,category, sum(billedamou

Result set 1

YEAR	CATEGORY
2009	
2010	
2011	
2012	
2013	

Result set is truncated, only the first 13 rows have been displayed. Click here to view all loaded rows.

Run SQL

*Untitled - 1 x

```

1 select year,category, sum(billedamount) as totalbilledamount
2 from factbilling
3 left join dimcustomer
4 on factbilling.customerid = dimcustomer.customerid
5 left join dimmonth
6 on factbilling.monthid=dimmonth.monthid
7 group by rollup(year,category)
8 order by year, category

```

Result - Oct 2019

Year	Category	Total billed amount
2009	Food	200
2009	Beverage	200
2009	Tobacco	200
2010	Food	201
2010	Beverage	201
2010	Tobacco	201

Run all Remember my selection

Exercise 4 - Write a query using cube

To create a cube using the three columns labeled year, category, and sum of billedamount, run the sql statement below.

1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8

- ```

1. select year,category, sum(billedamount) as totalbilledamount
2. from factbilling
3. left join dimcustomer
4. on factbilling.customerid = dimcustomer.customerid
5. left join dimmonth
6. on factbilling.monthid=dimmonth.monthid
7. group by cube(year,category)
8. order by year, category

```

Copied!

The output of the above command will contain 468 rows. The partial output can be seen in the image below.

To see the full output click on the open in the new tab icon.

Run SQL

SQL

Run all

Remember my selection

\* Untitled - 1

1

2

3

4

5

6

7

8

```

select year,category, sum(billedamount) as totalbilledamount
from factbilling
left join dimcustomer
on factbilling.customerid = dimcustomer.customerid
left join dimmonth
on factbilling.monthid=dimmonth.monthid
group by cube(year,category)
order by year, category

```

Result - Oct 2

Result

Y

200

200

200

201

201

## Exercise 5 - Create a Materialized Query Table(MQT)

In DB2 we can implement materialized views using Materialized Query Tables.

Step 1: Create the MQT.

Execute the sql statement below to create an MQT named countrystats.

```

1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
9. 9
10. 10
11. 11

1. CREATE TABLE countrystats (country, year, totalbilledamount) AS
2. (select country, year, sum(billedamount)
3. from factbilling
4. left join dimcustomer
5. on factbilling.customerid = dimcustomer.customerid
6. left join dimmonth
7. on factbilling.monthid=dimmonth.monthid
8. group by country,year)
9. DATA INITIALLY DEFERRED
10. REFRESH DEFERRED
11. MAINTAINED BY SYSTEM;

```

Copied!

You may get a warning in the output as below.

**The materialized query table may not be used to optimize the processing of queries.**

**You can safely ignore the warning and proceed to the next step.**

The above command creates an MQT named countrystats that has 3 columns.

- country
- year
- totalbilledamount

The MQT is essentially the result of the below query, which gives you the country, year and the sum of billed amount grouped by country and year.

```
1. 1
```

```
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
```

```
1. select country, year, sum(billedamount)
2. from factbilling
3. left join dimcustomer
4. on factbilling.customerid = dimcustomer.customerid
5. left join dimmonth
6. on factbilling.monthid=dimmonth.monthid
7. group by country,year
```

Copied!

The settings

- DATA INITIALLY DEFERRED
- REFRESH DEFERRED
- MAINTAINED BY SYSTEM

Simple mean that data is not initially populated into this MQT. Whenever the underlying data changes, the MQT does NOT automatically refresh. The MQT is system maintained and not user maintained.

Step 2: Populate/refresh data into the MQT.

Execute the sql statement below to populate the MQT countrystats

```
1. 1
1. refresh table countrystats;
```

Copied!

The command above populates the MQT with relevant data.

Step 3: Query the MQT.

Once an MQT is refreshed, you can query it.

Execute the sql statement below to query the MQT countrystats.

```
1. 1
1. select * from countrystats
```

Copied!

## Practice exercises

1. Problem:

*Create a grouping set for the columns year, quartername, sum(billedamount).*

▼ Click here for Hint

Select columns year, quartername, sum(billedamount), and use a group by query and join the dimcustomer and dimmonth tables to factbilling table.

▼ Click here for Solution

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7

1. select year, quartername, sum(billedamount) as totalbilledamount
2. from factbilling
3. left join dimcustomer
4. on factbilling.customerid = dimcustomer.customerid
5. left join dimmonth
6. on factbilling.monthid=dimmonth.monthid
7. group by grouping sets(year, quartername)
```

Copied!

2. Problem:

*Create a rollup for the columns country, category, sum(billedamount).*

▼ Click here for Hint

Select columns country, category, sum(billedamount), and use a group by query and join the dimcustomer and dimmonth tables to factbilling table.

▼ Click here for Solution

```
1. 1
2. 2
3. 3
4. 4
5. 5
```

```
6. 6
7. 7

1. select country, category, sum(billedamount) as totalbilledamount
2. from factbilling
3. left join dimcustomer
4. on factbilling.customerid = dimcustomer.customerid
5. left join dimmonth
6. on factbilling.monthid=dimmonth.monthid
7. group by rollup(country,category)
```

Copied!

3. Problem:

*Create a cube for the columns year, country, category, sum(billedamount).*

▼ Click here for Hint

Select columns year, country, category, sum(billedamount), and use a group by query and join the dimcustomer and dimmonth tables to factbilling table.

▼ Click here for Solution

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7

1. select year, country, category, sum(billedamount) as totalbilledamount
2. from factbilling
3. left join dimcustomer
4. on factbilling.customerid = dimcustomer.customerid
5. left join dimmonth
6. on factbilling.monthid=dimmonth.monthid
7. group by cube(year, country, category)
```

Copied!

4. Problem:

*Create an MQT named average\_billamount with columns year, quarter, category, country, average\_bill\_amount.*

You can safely ignore the warning and proceed

▼ Click here for Hint

Select columns year, quarter, category, country, avg(billedamount), and use a group by query and join the dimcustomer and dimmonth tables to factbilling table.

▼ Click here for Solution

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
9. 9
10. 10
11. 11
12. 12

1. CREATE TABLE average_billamount (year, quarter, category, country, average_bill_amount) AS
2. (select year, quarter, category, country, avg(billedamount) as average_bill_amount
3. from factbilling
4. left join dimcustomer
5. on factbilling.customerid = dimcustomer.customerid
6. left join dimmonth
7. on factbilling.monthid=dimmonth.monthid
8. group by year, quarter, category, country
9.)
10. DATA INITIALLY DEFERRED
11. REFRESH DEFERRED
12. MAINTAINED BY SYSTEM;
```

Copied!

```
1. 1

1. refresh table average_billamount;
```

Copied!

Congratulations! You have successfully finished this lab.

## Authors

Ramesh Sannareddy

## Other Contributors

Rav Ahuja

# Change Log

| Date (YYYY-MM-DD) | Version | Changed By        | Change Description                                                              |
|-------------------|---------|-------------------|---------------------------------------------------------------------------------|
| 2021-09-28        | 0.1     | Ramesh Sannareddy | Created initial version of the lab<br>IBM Corporation 2021. All rights reserved |