

Harmonisation Template for Cohort B

My Name

2025-03-10

Table of contents

File Structure	4
I Cohort B Cleaning	10
1 R Package And Environment	11
1.1 R Packages Used	11
1.2 R Platform Information	11
1.3 Data dictionary	12
2 Read Cohort B Data	13
2.1 Read Data	13
2.2 Write Preprocessed File	15
3 Extract Demographic	16
3.1 Read Preprocessed File	16
3.2 Demographics and Behavioral parameters	16
3.2.1 Age and Sex	16
3.2.2 Height, Weight, BMI and BSA	17
3.2.3 Smoking History	18
3.2.4 Chest Pain	20
3.2.4.1 Shortness of Breath	20
3.2.4.2 Have chest pain or not	21
3.2.4.3 Symptomatic or Asymptomatic	22
3.2.4.4 Chest Pain Type	23
3.2.4.5 Combined chest pain related tables	25
3.2.5 Combine Demographics	25
3.3 Write Preprocessed File	26
4 Export To Excel	28
4.1 Read all tabular data	28
4.2 Export Data as Excel	28

Preface

Here is the documentation of the data harmonisation step generated using [Quarto](https://quarto.org/docs/books). To learn more about Quarto books visit <https://quarto.org/docs/books>.

File Structure

Here is the file structure of the project used to generate the document.

```
harmonisation/                                # Root of the project template.
|
|   .quarto/ (not in repository)              # Folder to keep intermediate
files/folders                                # generated when Quarto renders
|                                              the files.
|
|   archive/                                  # Folder to keep previous books
and harmonised data.
|   |
|       reports/                             # Folder to keep previous versions
of
|   |   |
|   |   |   {some_date}_batch/               # Folder to keep {some_date}
documentation.                               # data harmonisation
|   |   |
|   |   |   {some_date}_batch/               # Folder to keep {some_date}
version of                                  # data harmonisation
|   |   |   documentation.
|   |   |   |
|   |   |   |   Flowchart.xlsx               # Flowchart sheet to record
version control.
|   |   |
|   |   |   harmonised/                      # Folder to keep previous version
of harmonised data.
|   |   |
|   |   |   {some_date}_batch/               # Folder to keep {some_date}
version of
|   |   |
|   |   |   # harmonised data.
```

	Flowchart.xlsx	# Flowchart sheet to record
version control.		
codes/		# Folder to keep R/Quarto scripts
		# to run data harmonisation.
{cohort name}/		# Folder to keep Quarto scripts to
run		
		# data cleaning, harmonisation
		# and output them for each
cohort.		
	preprocessed_data/	# Folder to keep preprocessed
data.		
harmonisation_summary/		# Folder to keep Quarto scripts to
create		
		# data harmonisation summary
report.		
output/		# Folder to keep harmonised data.
cohort_harmonisation_script.R		# R script to render each {cohort
name}/ folder.		
		# folder into html, pdf and word
document.		
harmonisation_summary_script.R		# R script to render the
{harmonisation_summary}/		
		# folder into word document.
data-raw/		# Folder to keep cohort raw data
(.csv, .xlsx, etc.)		
{cohort name}/		# Folder to keep cohort raw data.
{data_dictionary}		# Data dictionary file that
correspond to the		
		# cohort raw data. Can be one
from the		
		# collaborator provide or
provided by us.		
Flowchart.xlsx		# Flowchart sheet to record
version control.		

	data-dictionary/	# Folder to keep data dictionary
		# used for harmonising data.
	Flowchart.xlsx	# Flowchart sheet to record
	version control.	
	data-input/	# Folder to keep data input file
		# for collaborators to fill in.
	Flowchart.xlsx	# Flowchart sheet to record
	version control.	
	docs/	# Folder to keep R functions
	documentation	
		# generated using
	pkgdown::build_site_external().	
	inst/	# Folder to keep arbitrary
	additional files	
		# to include in the project.
	WORDLIST	# File generated by
	spelling::update_wordlist()	
	man/	# Folder to keep R functions
	documentation	
		# generated using
	devtools::document().	
	{fun-demo}.Rd	# Documentation of the demo R
	function.	
	harmonisation-template.Rd	# High-level documentation.
	R/	# Folder to keep R functions.
	{fun-demo}.R	# Script with R functions.
	harmonisation-package.R	# Dummy R file for high-level
	documentation.	
	renv/ (not in repository)	# Folder to keep all packages
		# installed in the renv
	environment.	

reports/	# Folder to keep the most recent
data harmonisation	
	# documentation.
templates/	# Folder to keep template files
needed to generate	
	# data harmonisation
documentation efficiently.	
quarto-yaml/	# Folder to keep template files to
generate	
	# data harmonisation
documentation structure	
	# in Quarto.
quarto{cohort name}.yaml	# Quarto book template data
harmonisation documentation	
	# for {cohort name}.
_quarto_summary.yaml	# Quarto book template data
harmonisation summary.	
index-qmd/	# Folder to keep template files to
generate	
	# the preface page of the data
harmonisation	
	# documentation.
_index_report.qmd	# Preface template for each cohort
data harmonisation	
	# report.
_index_summary.qmd	# Preface template for data
harmonisation	
	# summary report.
tests/	# Folder to keep test unit files.
	# Files will be used by R package
testthat.	
.Rbuildignore	# List of files/folders to be
ignored while	
	# checking/installing the package.
.Renvron (not in repository)	
variables.	# File to set environment

.Rprofile (not in repository)		# R code to be run when R starts
up.		
		# It is run after the .Renvi
file is sourced.		
.Rhistory (not in repository)		# File containing R command
history.		
.gitignore		# List of files/folders to be
ignored while		
		# using the git workflow.
.lintr		# Configuration for linting
		# R projects and packages using
linter.		
.renvignore		# List of files/folders to be
ignored when		
		# renv is doing its snapshot.
DESCRIPTION[*]		# Overall metadata of the project.
LICENSE		# Content of the MIT license
generated via		
		# usethis::use_mit_license().
LICENSE.md		# Content of the MIT license
generated via		
		# usethis::use_mit_license().
NAMESPACE		# List of functions users can use
or imported		
		# from other R packages. It is
generated		
		# by devtools::document().
README.md		# GitHub README markdown file
generated by Quarto.		
README.qmd		# GitHub README quarto file used
to generate README.md.		
_pkgdown.yml		# Configuration for R package
documentation		


```

|                                     # using
pkgdown:::build_site_external().
|
|   _quarto.yml                       # Configuration for Quarto book
generation.
|                                     # It is also the project
configuration file.
|
|   csl_file.csl                     # Citation Style Language (CSL)
file to ensure
|                                     # citations follows the Lancet
journal.
|
|   custom-reference.docx            # Microsoft word template for data
harmonisation
|                                     # documentation to Word.
|
|   harmonisation_template.Rproj      # RStudio project file.
|
|   index.qmd                        # Preface page of Quarto book
content.
|
|   references.bib                   # Bibtex file for Quarto book.
|
|   renv.lock                         # Metadata of R packages installed
generated
|                                     # using renv::snapshot().

```

[*] These files are automatically created but user needs to manually add some information.

Part I

Cohort B Cleaning

1 R Package And Environment

1.1 R Packages Used

Here are the R packages used in this analysis.

```
harmonisation::get_r_package_info() |>  
  knitr::kable()
```

package	version	date	source
dplyr	1.1.4	2023-11-17	RSPM (R 4.5.0)
fontawesome	0.5.3	2024-11-16	RSPM (R 4.5.0)
forcats	1.0.0	2023-01-29	RSPM (R 4.5.0)
glue	1.8.0	2024-09-30	RSPM (R 4.5.0)
harmonisation	1.0.0.0	2025-05-20	local
here	1.0.1	2020-12-13	RSPM (R 4.5.0)
htmltools	0.5.8.1	2024-04-04	RSPM (R 4.5.0)
lubridate	1.9.4	2024-12-08	RSPM (R 4.5.0)
magrittr	2.0.3	2022-03-30	RSPM (R 4.5.0)
openxlsx	4.2.8	2025-01-25	RSPM (R 4.5.0)
pointblank	0.12.2	2024-10-23	RSPM (R 4.5.0)
purrr	1.0.4	2025-02-05	RSPM (R 4.5.0)
quarto	1.4.4	2024-07-20	RSPM (R 4.5.0)
reactable	0.4.4	2023-03-12	RSPM (R 4.5.0)
sessioninfo	1.2.2	2021-12-06	CRAN (R 4.5.0)
stringr	1.5.1	2023-11-14	RSPM (R 4.5.0)
testthat	3.2.3	2025-01-13	RSPM (R 4.5.0)
tibble	3.2.1	2023-03-20	RSPM (R 4.5.0)
tidyr	1.3.1	2024-01-24	RSPM (R 4.5.0)
vroom	1.6.5	2023-12-05	RSPM (R 4.5.0)

1.2 R Platform Information

Here are the R platform environment used in this analysis.

```
harmonisation::get_r_platform_info() |>
  knitr::kable()
```

setting	value
version	R version 4.5.0 (2025-04-11 ucrt)
os	Windows 11 x64 (build 26100)
system	x86_64, mingw32
ui	RTerm
language	(EN)
collate	English_Singapore.utf8
ctype	English_Singapore.utf8
tz	Asia/Singapore
date	2025-05-31
pandoc	3.4 @ C:/Program Files/RStudio/resources/app/bin/quarto/bin/tools/ (via rmarkdown)
quarto	1.7.30 @ C:/Program Files/Quarto/bin/quarto.exe/ (via quarto)
knitr	1.49 from RSPM (R 4.5.0)

1.3 Data dictionary

Check to see if the data dictionary 20250310_data_dictionary.xlsx exists.

```
dict_relative_path <- fs::path(
  "data-raw",
  "data_dictionary",
  params$data_dictionary
)

dict_path <- here::here(dict_relative_path)

if (!file.exists(dict_path)) {
  stop(glue::glue("Input data dictionary {dict_path} cannot be found"))
}
```

2 Read Cohort B Data

2.1 Read Data

We read the file `data_to_harmonise_age_issue.csv` using `vroom::vroom`

```
cohort_B_data <- vroom::vroom(  
  file = here::here("data-raw",  
                    "Cohort_B",  
                    "data_to_harmonise_age_issue.csv"),  
  delim = ",",  
  col_select = 1:2,  
  show_col_types = FALSE,  
  col_types = list(  
    ID = vroom::col_character(),  
    Age = vroom::col_integer()  
  )  
) |>  
dplyr::rename(cohort_unique_id = "ID") |>  
# Remove rows when the ID value is NA  
dplyr::filter(!is.na(.data[["cohort_unique_id"]])) |>  
# Remove white spaces in column names  
dplyr::rename_all(stringr::str_trim) |>  
# Check if cohort id is unique  
pointblank::rows_distinct(  
  columns = "cohort_unique_id",  
)
```

To safeguard a csv file with issues, we can use the function `vroom::problems`

If there are issues with the data, the output of `vroom::problems` will be a `tibble`.

```
cohort_B_data |>  
  vroom::problems()
```

```
# A tibble: 3 x 5  
  row    col expected    actual  file  
  <int> <int> <chr>      <chr>  <chr>
```

```

1      4      2 an integer missing
D:/Jeremy/PortableR/RPortableWorkDirectory/har~
2     10      2 an integer missing
D:/Jeremy/PortableR/RPortableWorkDirectory/har~
3     17      2 an integer missing
D:/Jeremy/PortableR/RPortableWorkDirectory/har~

```

To check for this in an automatically, we can use `pointblank::expect_row_count_match`

```

cohort_B_data |>
  vroom::problems() |>
  pointblank::expect_row_count_match(count = 0)

```

Error: Row counts for the two tables did not match.
 The `expect_row_count_match()` validation failed beyond the absolute threshold level (1).
 * failure level (1) >= failure threshold (1)

Suppose we have a csv file with no issues, we can safeguard it with the following code.

```

cohort_B_data <- vroom::vroom(
  file = here::here("data-raw",
                    "Cohort_B",
                    "data_to_harmonise.csv"),
  delim = ",",
  col_select = 1:8,
  show_col_types = FALSE,
  col_types = list(
    ID = vroom::col_character(),
    Age = vroom::col_integer(),
    Sex = vroom::col_character(),
    Height = vroom::col_double(),
    Weight = vroom::col_double(),
    `Smoke History` = vroom::col_character(),
    `Chest Pain Character` = vroom::col_character(),
    Dyspnea = vroom::col_character()
  )
) |>
dplyr::rename(cohort_unique_id = "ID") |>
# Remove rows when the ID value is NA
dplyr::filter(!is.na(.data[["cohort_unique_id"]])) |>
# Remove white spaces in column names
dplyr::rename_all(stringr::str_trim) |>
# Check if cohort id is unique
pointblank::rows_distinct(
  columns = "cohort_unique_id",

```

```
)  
  
cohort_B_data |>  
  vroom::problems() |>  
  pointblank::expect_row_count_match(count = 0)
```

2.2 Write Preprocessed File

We output data to be used for the next session.

```
cohort_B_data |>  
  fst::write_fst(  
    path = here::here(params$analysis_folder,  
                      params$harmonisation_folder,  
                      params$preprocessing_folder,  
                      "01_Cohort_B_cleaned.fst")  
  )
```

3 Extract Demographic

3.1 Read Preprocessed File

We read output data from the previous section.

3.2 Demographics and Behavioral parameters

3.2.1 Age and Sex

`age_years` will be mapped from the column `Age`.

`sex` is grouped as follows:

Sex	sex
Female	0
Male	1

```
age_gender_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id",
                  "Age",
                  "Sex")) |>
  pointblank::col_vals_expr(
    expr = ~ harmonisation::is_integer_vector(
      cohort_A_data[["age"]],
      allow_na = TRUE)
  ) |>
  dplyr::mutate(
    # Convert age to type integer
    age_years = as.integer(.data[["Age"]]),
    # Convert categorical columns to factors
    sex = dplyr::case_when(
      .data[["Sex"]] == "Female" ~ "0",
      .data[["Sex"]] == "Male" ~ "1",
      .default = NA_character_
    ),
    `Sex` = forcats::fct_relevel(
```



```

    .data[["Sex"]],
    c("Female", "Male")
  ),
  sex = forcats::fct_relevel(
    .data[["sex"]],
    c("0", "1")),
) |>
dplyr::relocate(
  "sex",
  .before = "Sex"
) |>
dplyr::relocate(
  "age_years",
  .after = "Age"
) |>
pointblank::col_vals_in_set(
  columns = "sex",
  set = c("0", "1")
) |>
pointblank::col_vals_between(
  columns = "age_years",
  left = 0,
  right = 100,
  inclusive = c(FALSE, TRUE),
  na_pass = TRUE
)

```

Remove unnecessary columns so that we can merge with the other fields.

```

age_gender_data <- age_gender_data |>
  dplyr::select(-c("Age", "Sex"))

```

3.2.2 Height, Weight, BMI and BSA

`height_cm` will be mapped from the column `Height`. `weight_kg` will be mapped from the column `Weight`.

`bsa_m2` in m^2 will be calculated as $\sqrt{[Height(cm) \times Weight(kg)]/3600}$ `bmi` will be calculated as $Weight(kg)/((Height(m))^2)$

All values are then converted to two decimal places.

```
body_measurement_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id",
                  "Height", "Weight")) |>
  dplyr::mutate(
    height_cm = .data[["Height"]],
    weight_kg = .data[["Weight"]],
    bsa_m2 = sqrt((.data[["height_cm"]] * .data[["weight_kg"]]) / 3600),
    bsa_m2 = harmonisation::round_to_nearest_digit(.data[["bsa_m2"]],
    ↪ digits = 2),
    bmi = .data[["weight_kg"]] / ((.data[["height_cm"]] / 100)^2),
    bmi = harmonisation::round_to_nearest_digit(.data[["bmi"]], digits =
    ↪ 2),
    height_cm = harmonisation::round_to_nearest_digit(.data[["height_cm"]],
    ↪ digits = 2),
    weight_kg = harmonisation::round_to_nearest_digit(.data[["weight_kg"]],
    ↪ digits = 2)
  ) |>
  pointblank::col_vals_between(
    columns = "bmi",
    left = 10,
    right = 50,
    inclusive = c(TRUE, TRUE),
    na_pass = TRUE
  )
```

Remove unnecessary columns so that we can merge with the other fields.

```
body_measurement_data <- body_measurement_data |>
  dplyr::select(-c("Height", "Weight"))
```

3.2.3 Smoking History

smoke_current is grouped as follows:

Smoke History	smoke_current
non-smoker	0
past smoker	0
current smoker	1
NA	-1

smoke_past is grouped as follows:

Smoke History	smoke_past
non-smoker	0
past smoker	1
current smoker	0
NA	-1

We do a check to ensure that we can only have these scenarios

- smoke_current as 1 and smoke_past as 0 for current smokers
- smoke_current as 0 and smoke_past as 1 for past smokers
- smoke_current as 0 and smoke_past as 0 for non-smokers
- smoke_current as -1 and smoke_past as -1 for unknown

```
smoking_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id",
                  "Smoke History")) |>
  dplyr::mutate(
    smoke_current = dplyr::case_when(
      is.na(.data[["Smoke History"]]) ~ "-1",
      .data[["Smoke History"]] == "non-smoker" ~ "0",
      .data[["Smoke History"]] == "past smoker" ~ "0",
      .data[["Smoke History"]] == "current smoker" ~ "1",
      .default = NA_character_
    ),
    smoke_current = forcats::fct_relevel(
      .data[["smoke_current"]],
      c("0", "1")),
    smoke_past = dplyr::case_when(
      is.na(.data[["Smoke History"]]) ~ "-1",
      .data[["Smoke History"]] == "non-smoker" ~ "0",
      .data[["Smoke History"]] == "past smoker" ~ "1",
      .data[["Smoke History"]] == "current smoker" ~ "0",
      .default = NA_character_
    ),
    smoke_past = forcats::fct_relevel(
      .data[["smoke_past"]],
      c("0", "1")),
    `Smoke History` = forcats::fct(
      .data[["Smoke History"]]
    )
  ) |>
  pointblank::col_vals_in_set(
    columns = c("smoke_current", "smoke_past"),
    set = c("0", "1", "-1")
  ) |>
```

```
pointblank::col_vals_expr(
  expr = pointblank::expr(
    (.data[["smoke_current"]] == "1" & .data[["smoke_past"]] == "0") |
    (.data[["smoke_current"]] == "-1" & .data[["smoke_past"]] == "-1") |
    (.data[["smoke_current"]] == "0" & .data[["smoke_past"]] %in% c("0",
↪  "1"))
  )
)
```

```
if (params$show_table) {
  smoking_data |>
    dplyr::distinct(.data[["Smoke History"]],
                    .keep_all = TRUE) |>
    knitr::kable()
}
```

cohort_unique_id	Smoke History	smoke_current	smoke_past
B001	non-smoker	0	0
B002	current smoker	1	0
B004	past smoker	0	1
B017	NA	-1	-1

Remove unnecessary columns so that we can merge with the other fields.

```
smoking_data <- smoking_data |>
  dplyr::select(-c("Smoke History"))
```

3.2.4 Chest Pain

3.2.4.1 Shortness of Breath

have_sob is grouped as follows:

Dyspnea	have_sob
no	0
yes	1

```

shortness_of_breath_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id", "Dyspnea")) |>
  dplyr::mutate(
    have_sob = dplyr::case_when(
      .data[["Dyspnea"]] == "no" ~ "0",
      .data[["Dyspnea"]] == "yes" ~ "1",
      .default = NA_character_
    ),
    have_sob = forcats::fct_relevel(
      as.character(.data[["have_sob"]]),
      c("0", "1")),
    Dyspnea = forcats::fct_relevel(
      as.character(.data[["Dyspnea"]]),
      c("no", "yes")),
  ) |>
  pointblank::col_vals_in_set(
    columns = c("have_sob"),
    set = c("0", "1", "-1")
  )

```

Remove unnecessary columns so that we can merge with the other fields.

```

shortness_of_breath_data <- shortness_of_breath_data |>
  dplyr::select(-c("Dyspnea"))

```

3.2.4.2 Have chest pain or not

have_chest_pain is grouped as follows:

Chest Pain Character	have_chest_pain
no chest pain	0
typical, atypical or nonanginal	1

```

have_chest_pain_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id", "Chest Pain Character")) |>
  dplyr::mutate(
    have_chest_pain = dplyr::case_when(
      .data[["Chest Pain Character"]] %in% c("no chest pain") ~ "0",
      .data[["Chest Pain Character"]] %in% c("typical", "atypical",
↵ "nonanginal") ~ "1",
      .default = NA_character_
    )
  )

```

```

),
have_chest_pain = forcats::fct_relevel(
  .data[["have_chest_pain"]],
  c("0", "1")
),
`Chest Pain Character` = forcats::fct_relevel(
  as.character(.data[["Chest Pain Character"]]),
  c("no chest pain", "typical", "atypical", "nonanginal")
)
) |>
pointblank::col_vals_in_set(
  columns = c("have_chest_pain"),
  set = c("0", "1")
)

```

Remove unnecessary columns so that we can merge with the other fields.

```

have_chest_pain_data <- have_chest_pain_data |>
  dplyr::select(-c("Chest Pain Character"))

```

3.2.4.3 Symptomatic or Asymptomatic

symptoms is grouped as follows:

have_sob	have_chest_pain	symptoms
-1	-1	-1
0	0	0
0 or 1	1	1
1	0	2

```

symptoms_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id")) |>
  dplyr::inner_join(shortness_of_breath_data,
    by = dplyr::join_by("cohort_unique_id"),
    unmatched = "error",
    relationship = "one-to-one") |>
  dplyr::inner_join(have_chest_pain_data,
    by = dplyr::join_by("cohort_unique_id"),
    unmatched = "error",
    relationship = "one-to-one") |>
  dplyr::mutate(
    symptoms = dplyr::case_when(

```

```

    (.data[["have_chest_pain"]] == "-1" &
      .data[["have_sob"]] == "-1"
    ) ~ "-1",
    (.data[["have_chest_pain"]] == "0" &
      .data[["have_sob"]] == "0"
    ) ~ "0",
    (.data[["have_chest_pain"]] == "1" &
      .data[["have_sob"]] %in% c("0", "1")
    ) ~ "1",
    (.data[["have_chest_pain"]] == "0" &
      .data[["have_sob"]] == "1"
    ) ~ "2",
    .default = NA_character_
  ),
  symptoms = forcats::fct_relevel(
    .data[["symptoms"]],
    c("0", "1", "2"))
) |>
pointblank::col_vals_in_set(
  columns = c("symptoms"),
  set = c("0", "1", "2")
)

```

Remove unnecessary columns so that we can merge with the other fields.

```

symptoms_data <- symptoms_data |>
  dplyr::select(-c("have_chest_pain", "have_sob"))

```

3.2.4.4 Chest Pain Type

chest_pain_type is grouped as follows:

Dyspnea	Chest Pain Character	chest_pain_type
no	no chest pain	0
no or yes	typical	1
no or yes	atypical	2
no or yes	nonanginal	3
yes	no chest pain	4

```

chest_pain_type_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id", "Chest Pain Character", "Dyspnea"))
  ↪ |>

```

```

dplyr::mutate(
  chest_pain_type = dplyr::case_when(
    (.data[["Chest Pain Character"]] == "no chest pain" &
     .data[["Dyspnea"]] == "no"
    ) ~ "0",
    (.data[["Chest Pain Character"]] == "typical" &
     .data[["Dyspnea"]] %in% c("no", "yes")
    ) ~ "1",
    (.data[["Chest Pain Character"]] == "atypical" &
     .data[["Dyspnea"]] %in% c("no", "yes")
    ) ~ "2",
    (.data[["Chest Pain Character"]] == "nonanginal" &
     .data[["Dyspnea"]] %in% c("no", "yes")
    ) ~ "3",
    (.data[["Chest Pain Character"]] == "no chest pain" &
     .data[["Dyspnea"]] == "yes"
    ) ~ "4",
    .default = NA_character_
  ),
  `Chest Pain Character` = forcats::fct_relevel(
    as.character(.data[["Chest Pain Character"]]),
    c("no chest pain", "typical", "atypical", "nonanginal")
  ),
  `Dyspnea` = forcats::fct_relevel(
    as.character(.data[["Dyspnea"]]),
    c("no", "yes")
  ),
  chest_pain_type = forcats::fct_relevel(
    .data[["chest_pain_type"]],
    c("0", "1", "2", "3"))
) |>
dplyr::relocate(
  "Chest Pain Character",
  .after = "cohort_unique_id"
) |>
pointblank::col_vals_in_set(
  columns = c("chest_pain_type"),
  set = c("0", "1", "2", "3", "4")
)

```

Remove unnecessary columns so that we can merge with the other fields.

```

chest_pain_type_data <- chest_pain_type_data |>
dplyr::select(-c("Dyspnea", "Chest Pain Character"))

```


3.2.4.5 Combined chest pain related tables

We combine all chest related tables together

```
join_specification <- dplyr::join_by("cohort_unique_id")

chest_pain_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id")) |>
  dplyr::inner_join(have_chest_pain_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one") |>
  dplyr::inner_join(chest_pain_type_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one") |>
  dplyr::inner_join(shortness_of_breath_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one") |>
  dplyr::inner_join(symptoms_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one")

testthat::expect_true(
  pointblank::has_columns(
    chest_pain_data,
    columns = c("have_sob", "have_chest_pain", "symptoms",
               ↪ "chest_pain_type")
  )
)

testthat::expect_equal(
  ncol(chest_pain_data), 5
)
```

3.2.5 Combine Demographics

We combine all the data to give the demo_behave_data.

```
join_specification <- dplyr::join_by("cohort_unique_id")

demo_behave_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id")) |>
```

```

dplyr::inner_join(age_gender_data,
  by = join_specification,
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::inner_join(body_measurement_data,
  by = join_specification,
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::inner_join(smoking_data,
  by = join_specification,
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::inner_join(chest_pain_data,
  by = join_specification,
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::relocate(c("bsa_m2", "bmi"),
  .after = "sex")

testthat::expect_true(
  pointblank::has_columns(
    demo_behave_data,
    columns = c(
      "age_years", "sex",
      "height_cm", "weight_kg", "bsa_m2", "bmi",
      "smoke_current", "smoke_past",
      "have_sob", "have_chest_pain",
      "symptoms", "chest_pain_type"
    )
  )
)

testthat::expect_equal(
  ncol(demo_behave_data), 13
)

```

3.3 Write Preprocessed File

We output data to be used for the next session.

```

demo_behave_data |>
  fst::write_fst(
    path = here::here(

```

```
params$analysis_folder,  
params$harmonisation_folder,  
params$preprocessing_folder,  
"02_demographic_data.fst"),  
)
```

4 Export To Excel

```
out_type <- knitr::opts_chunk$get("rmarkdown.pandoc.to")
```

4.1 Read all tabular data

We read all tabular data from the previous section.

4.2 Export Data as Excel

We export the standardised data to an excel file called harmonised__Cohort__B.xlsx

```
# Create a new workbook
my_workbook <- openxlsx::createWorkbook()

sheet_name = c("demographics")

output_data = list(demo_behave_data) |>
  purrr::map(
    .f = harmonisation::add_cohort_name,
    cohort_name = params$cohort_name,
    cohort_name_column = "cohort_name"
  )

purrr::walk2(
  .x = sheet_name,
  .y = output_data,
  .f = harmonisation::write_to_sheet,
  workbook = my_workbook
)

# Save workbook
openxlsx::saveWorkbook(
  wb = my_workbook,
  file = here::here(params$analysis_folder,
    params$output_folder,
```

```
        params$cleaned_folder,  
        params$output_excel_file),  
  overwrite = TRUE  
)
```