

Harmonisation Template for Cohort B

My Name

2025-03-10

Table of contents

File Structure	4
I Cohort B Cleaning	10
1 R Package And Environment	11
1.1 R Packages Used	11
1.2 R Platform Information	11
1.3 Data dictionary	12
2 Read Cohort B Data	13
2.1 Read Data	13
2.2 Write Preprocessed File	15
3 Extract Demographic	16
3.1 Read Preprocessed File	16
3.2 Demographics and Behavioral parameters	16
3.2.1 Age and Sex	16
3.2.2 Height, Weight, BMI and BSA	18
3.2.3 Smoking History	19
3.2.4 Chest Pain	21
3.2.4.1 Shortness of Breath	21
3.2.4.2 Have chest pain or not	22
3.2.4.3 Symptomatic or Asymptomatic	23
3.2.4.4 Chest Pain Type	25
3.2.4.5 Combined chest pain related tables	26
3.2.5 Combine Demographics	27
3.3 Write Preprocessed File	28
4 Export To Excel	30
4.1 Read all tabular data	30
4.2 Export Data as Excel	30

Preface

Here is the documentation of the data harmonisation step generated using [Quarto](https://quarto.org/docs/books). To learn more about Quarto books visit <https://quarto.org/docs/books>.

File Structure

Here is the file structure of the project used to generate the document.

```
harmonisation/                                # Root of the project template.
|
|   .quarto/ (not in repository)             # Folder to keep intermediate
files/folders                                # generated when Quarto renders
|                                              the files.
|
|   archive/                                # Folder to keep previous books
and harmonised data.
|   |
|       reports/                            # Folder to keep previous versions
of
|   |   |
|   |   |   {some_date}_batch/              # Folder to keep {some_date}
documentation.                               # data harmonisation
|   |   |
|   |   |   {some_date}_batch/              # Folder to keep {some_date}
version of                                  # data harmonisation
|   |   |   documentation.
|   |   |   |
|   |   |   |   Flowchart.xlsx              # Flowchart sheet to record
version control.
|   |   |
|   |       harmonised/                     # Folder to keep previous version
of harmonised data.
|   |   |
|   |       {some_date}_batch/              # Folder to keep {some_date}
version of
|   |   |
|   |   |   # harmonised data.
```

	Flowchart.xlsx	# Flowchart sheet to record
version control.		
codes/		# Folder to keep R/Quarto scripts
		# to run data harmonisation.
{cohort name}/		# Folder to keep Quarto scripts to
run		
		# data cleaning, harmonisation
		# and output them for each
cohort.		
	preprocessed_data/	# Folder to keep preprocessed
data.		
harmonisation_summary/		# Folder to keep Quarto scripts to
create		
		# data harmonisation summary
report.		
output/		# Folder to keep harmonised data.
cohort_harmonisation_script.R		# R script to render each {cohort
name}/ folder.		
		# folder into html, pdf and word
document.		
harmonisation_summary_script.R		# R script to render the
{harmonisation_summary}/		
		# folder into word document.
data-raw/		# Folder to keep cohort raw data
(.csv, .xlsx, etc.)		
{cohort name}/		# Folder to keep cohort raw data.
{data_dictionary}		# Data dictionary file that
correspond to the		
		# cohort raw data. Can be one
from the		
		# collaborator provide or
provided by us.		
Flowchart.xlsx		# Flowchart sheet to record
version control.		

	data-dictionary/	# Folder to keep data dictionary
		# used for harmonising data.
	Flowchart.xlsx	# Flowchart sheet to record
	version control.	
	data-input/	# Folder to keep data input file
		# for collaborators to fill in.
	Flowchart.xlsx	# Flowchart sheet to record
	version control.	
	docs/	# Folder to keep R functions
	documentation	
		# generated using
	pkgdown::build_site_external().	
	inst/	# Folder to keep arbitrary
	additional files	
		# to include in the project.
	WORDLIST	# File generated by
	spelling::update_wordlist()	
	man/	# Folder to keep R functions
	documentation	
		# generated using
	devtools::document().	
	{fun-demo}.Rd	# Documentation of the demo R
	function.	
	harmonisation-template.Rd	# High-level documentation.
	R/	# Folder to keep R functions.
	{fun-demo}.R	# Script with R functions.
	harmonisation-package.R	# Dummy R file for high-level
	documentation.	
	renv/ (not in repository)	# Folder to keep all packages
		# installed in the renv
	environment.	

```

reports/
data harmonisation
|
|
|   templates/
needed to generate
|   |
documentation efficiently.
|   |
|       quarto-yaml/
generate
|   |   |
documentation structure
|   |   |
|   |   |
|       |       _quarto_{cohort name}.yaml
harmonisation documentation
|   |   |
|   |   |
|   |       _quarto_summary.yaml
harmonisation summary.
|   |
|       index-qmd/
generate
|       |
harmonisation
|       |
|       |       _index_report.qmd
data harmonisation
|       |
|       |
|       |       _index_summary.qmd
harmonisation
|
|
|   tests/
|
testthat.
|
|   .Rbuildignore
ignored while
|
|   .Renvron (not in repository)
variables.

```

```

# Folder to keep the most recent
# documentation.
# Folder to keep template files
# data harmonisation
# Folder to keep template files to
# data harmonisation
# in Quarto.
# Quarto book template data
# for {cohort name}.
# Quarto book template data
# Folder to keep template files to
# the preface page of the data
# documentation.
# Preface template for each cohort
# report.
# Preface template for data
# summary report.
# Folder to keep test unit files.
# Files will be used by R package
# List of files/folders to be
# checking/installing the package.
# File to set environment

```

.Rprofile (not in repository)	# R code to be run when R starts	
up.		
	# It is run after the .Renvi	
file is sourced.		
.Rhistory (not in repository)	# File containing R command	
history.		
.gitignore	# List of files/folders to be	
ignored while	# using the git workflow.	
.lintr	# Configuration for linting	
	# R projects and packages using	
linter.		
.renvignore	# List of files/folders to be	
ignored when	# renv is doing its snapshot.	
DESCRIPTION[*]	# Overall metadata of the project.	
LICENSE	# Content of the MIT license	
generated via	# usethis::use_mit_license().	
LICENSE.md	# Content of the MIT license	
generated via	# usethis::use_mit_license().	
NAMESPACE	# List of functions users can use	
or imported	# from other R packages. It is	
	# by devtools::document().	
generated		
README.md	# GitHub README markdown file	
generated by Quarto.		
README.qmd	# GitHub README quarto file used	
to generate README.md.		
_pkgdown.yml	# Configuration for R package	
documentation		


```

|                                     # using
pkgdown:::build_site_external().
|
|   _quarto.yml                       # Configuration for Quarto book
generation.
|                                     # It is also the project
configuration file.
|
|   csl_file.csl                     # Citation Style Language (CSL)
file to ensure
|                                     # citations follows the Lancet
journal.
|
|   custom-reference.docx            # Microsoft word template for data
harmonisation
|                                     # documentation to Word.
|
|   harmonisation_template.Rproj      # RStudio project file.
|
|   index.qmd                        # Preface page of Quarto book
content.
|
|   references.bib                   # Bibtex file for Quarto book.
|
|   renv.lock                         # Metadata of R packages installed
generated
|                                     # using renv::snapshot().

```

[*] These files are automatically created but user needs to manually add some information.

Part I

Cohort B Cleaning

1 R Package And Environment

1.1 R Packages Used

Here are the R packages used in this analysis.

```
harmonisation::get_r_package_info() |>  
  knitr::kable()
```

package	version	date	source
dplyr	1.1.4	2023-11-17	RSPM
fontawesome	0.5.3	2024-11-16	RSPM
forcats	1.0.1	2025-09-25	RSPM
glue	1.8.0	2024-09-30	RSPM
harmonisation	1.0.0.0	2025-11-12	local
here	1.0.2	2025-09-15	RSPM
htmltools	0.5.8.9000	2024-06-07	https://j~
magrittr	2.0.4	2025-09-12	RSPM
openxlsx	4.2.8.1	2025-10-31	RSPM
pointblank	0.12.2	2024-10-23	RSPM
purrr	1.2.0	2025-11-04	RSPM
quarto	1.5.1	2025-09-04	RSPM
reactable	0.4.4	2023-03-12	RSPM
sessioninfo	1.2.3	2025-02-05	RSPM
stringr	1.6.0	2025-11-04	RSPM
testthat	3.2.3	2025-01-13	RSPM
tibble	3.3.0	2025-06-08	RSPM
tidyr	1.3.1	2024-01-24	RSPM
vroom	1.6.6	2025-09-19	RSPM

1.2 R Platform Information

Here are the R platform environment used in this analysis.

```
harmonisation::get_r_platform_info() |>
  knitr::kable()
```

setting	value
version	R version 4.5.1 (2025-06-13 ucrt)
os	Windows 11 x64 (build 26200)
system	x86_64, mingw32
ui	RTerm
language	(EN)
collate	English_Singapore.utf8
ctype	English_Singapore.utf8
tz	Asia/Singapore
date	2025-11-12
pandoc	3.6.3 @ C:/Program Files/RStudio/resources/app/bin/quarto/bin/tools/ (via rmarkdown)
quarto	1.8.21 @ C:/Program Files/Quarto/bin/quarto.exe/ (via quarto)
knitr	1.50 from RSPM

1.3 Data dictionary

Check to see if the data dictionary 20250310_data_dictionary.xlsx exists.

```
dict_relative_path <- fs::path(
  "data-raw",
  "data_dictionary",
  params$data_dictionary
)

dict_path <- here::here(dict_relative_path)

if (!file.exists(dict_path)) {
  stop(glue::glue("Input data dictionary {dict_path} cannot be found"))
}
```

2 Read Cohort B Data

2.1 Read Data

We read the file `data_to_harmonise_age_issue.csv` using `vroom::vroom`

```
cohort_B_data <- vroom::vroom(  
  file = here::here("data-raw",  
                    "Cohort_B",  
                    "data_to_harmonise_age_issue.csv"),  
  delim = ",",  
  col_select = 1:2,  
  show_col_types = FALSE,  
  col_types = list(  
    ID = vroom::col_character(),  
    Age = vroom::col_integer()  
  )  
) |>  
dplyr::rename(cohort_unique_id = "ID") |>  
# Remove rows when the ID value is NA  
dplyr::filter(!is.na(.data[["cohort_unique_id"]])) |>  
# Remove white spaces in column names  
dplyr::rename_all(stringr::str_trim) |>  
# Check if cohort id is unique  
pointblank::rows_distinct(  
  columns = "cohort_unique_id",  
)
```

To safeguard a csv file with issues, we can use the function `vroom::problems`

If there are issues with the data, the output of `vroom::problems` will be a `tibble`.

```
cohort_B_data |>  
  vroom::problems()
```

```
# A tibble: 3 x 5  
  row   col expected actual file  
  <int> <int> <chr>    <chr> <chr>
```

```

1      4      2 an integer missing
D:/Jeremy/PortableR/RPortableWorkDirectory/har~
2     10      2 an integer missing
D:/Jeremy/PortableR/RPortableWorkDirectory/har~
3     17      2 an integer missing
D:/Jeremy/PortableR/RPortableWorkDirectory/har~

```

To check for this in an automatically, we can use `pointblank::expect_row_count_match`

```

cohort_B_data |>
  vroom::problems() |>
  pointblank::expect_row_count_match(count = 0)

```

Error: Row counts for the two tables did not match.
 The `expect\_row\_count\_match()` validation failed beyond the absolute threshold level (1).
 * failure level (1) >= failure threshold (1)

Suppose we have a csv file with no issues, we can safeguard it with the following code.

```

cohort_B_data <- vroom::vroom(
  file = here::here("data-raw",
                    "Cohort_B",
                    "data_to_harmonise.csv"),
  delim = ",",
  col_select = 1:8,
  show_col_types = FALSE,
  col_types = list(
    ID = vroom::col_character(),
    Age = vroom::col_integer(),
    Sex = vroom::col_character(),
    Height = vroom::col_double(),
    Weight = vroom::col_double(),
    `Smoke History` = vroom::col_character(),
    `Chest Pain Character` = vroom::col_character(),
    Dyspnea = vroom::col_character()
  )
) |>
dplyr::rename(cohort_unique_id = "ID") |>
# Remove rows when the ID value is NA
dplyr::filter(!is.na(.data[["cohort_unique_id"]])) |>
# Remove white spaces in column names
dplyr::rename_all(stringr::str_trim) |>
# Check if cohort id is unique
pointblank::rows_distinct(
  columns = "cohort_unique_id",

```

```
)  
  
cohort_B_data |>  
  vroom::problems() |>  
  pointblank::expect_row_count_match(count = 0)
```

2.2 Write Preprocessed File

We output data to be used for the next session.

```
cohort_B_data |>  
  nanoparquet::write_parquet(  
    file = here::here(  
      params$analysis_folder,  
      params$harmonisation_folder,  
      params$preprocessing_folder,  
      "01_Cohort_B_cleaned.parquet"  
    )  
  )
```

3 Extract Demographic

3.1 Read Preprocessed File

We read output data from the previous section.

3.2 Demographics and Behavioral parameters

3.2.1 Age and Sex

`age_years` will be mapped from the column `Age`.

`sex` is grouped as follows:

Sex	sex
Female	0
Male	1

```
age_gender_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id",
                  "Age",
                  "Sex")) |>
  pointblank::col_vals_expr(
    expr = ~ harmonisation::is_integer_vector(
      cohort_A_data[["age"]],
      allow_na = TRUE)
  ) |>
  dplyr::mutate(
    # Convert age to type integer
    age_years = as.integer(.data[["Age"]]),
    # Convert categorical columns to factors
    sex = dplyr::case_when(
      .data[["Sex"]] == "Female" ~ "0",
      .data[["Sex"]] == "Male" ~ "1",
      .default = NA_character_
    ),
    `Sex` = forcats::fct_relevel(
```



```

    .data[["Sex"]],
    c("Female", "Male")
  ),
  sex = forcats::fct_relevel(
    .data[["sex"]],
    c("0", "1")),
) |>
dplyr::relocate(
  "sex",
  .after = "Sex"
) |>
dplyr::relocate(
  "age_years",
  .after = "Age"
) |>
pointblank::col_vals_in_set(
  columns = "sex",
  set = c("0", "1")
) |>
pointblank::col_vals_between(
  columns = "age_years",
  left = 0,
  right = 100,
  inclusive = c(FALSE, TRUE),
  na_pass = TRUE
)

```

```

if (params$show_table) {
  age_gender_data |>
    dplyr::distinct(.data[["Sex"]],
                    .keep_all = TRUE) |>
    knitr::kable()
}

```

cohort_unique_id	Age	age_years	Sex	sex
B001	32	32	Female	0
B003	80	80	Male	1

Remove unnecessary columns so that we can merge with the other fields.

```

age_gender_data <- age_gender_data |>
  dplyr::select(-c("Age", "Sex"))

```

3.2.2 Height, Weight, BMI and BSA

height_cm will be mapped from the column Height. weight_kg will be mapped from the column Weight.

bsa_m2 in m^2 will be calculated as $\sqrt{(\text{Height}(\text{cm}) \times \text{Weight}(\text{kg}))/3600}$ bmi will be calculated as $\text{Weight}(\text{kg})/((\text{Height}(\text{m}))^2)$

All values are then converted to two decimal places.

```
body_measurement_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id",
                  "Height", "Weight")) |>
  dplyr::mutate(
    height_cm = .data[["Height"]],
    weight_kg = .data[["Weight"]],
    bsa_m2 = sqrt((.data[["height_cm"]] * .data[["weight_kg"]]) / 3600),
    bsa_m2 = harmonisation::round_to_nearest_digit(.data[["bsa_m2"]],
    ↪ digits = 2),
    bmi = .data[["weight_kg"]] / ((.data[["height_cm"]] / 100)^2),
    bmi = harmonisation::round_to_nearest_digit(.data[["bmi"]], digits =
    ↪ 2),
    height_cm = harmonisation::round_to_nearest_digit(.data[["height_cm"]],
    ↪ digits = 2),
    weight_kg = harmonisation::round_to_nearest_digit(.data[["weight_kg"]],
    ↪ digits = 2)
  ) |>
  pointblank::col_vals_between(
    columns = "bmi",
    left = 10,
    right = 50,
    inclusive = c(TRUE, TRUE),
    na_pass = TRUE
  )
```

```
if (params$show_table) {
  body_measurement_data |>
    head(n = 5) |>
    knitr::kable()
}
```

cohort_unique_id	Height	Weight	height_cm	weight_kg	bsa_m2	bmi
B001	170	63	170	63	1.72	21.80
B002	167	71	167	71	1.81	25.46
B003	184	77	184	77	1.98	22.74

cohort_unique_id	Height	Weight	height_cm	weight_kg	bsa_m2	bmi
B004	160	83	160	83	1.92	32.42
B005	155	61	155	61	1.62	25.39

Remove unnecessary columns so that we can merge with the other fields.

```
body_measurement_data <- body_measurement_data |>
  dplyr::select(-c("Height", "Weight"))
```

3.2.3 Smoking History

`smoke_current` is grouped as follows:

Smoke History	smoke_current
non-smoker	0
past smoker	0
current smoker	1
NA	-1

`smoke_past` is grouped as follows:

Smoke History	smoke_past
non-smoker	0
past smoker	1
current smoker	0
NA	-1

We do a check to ensure that we can only have these scenarios

- `smoke_current` as 1 and `smoke_past` as 0 for current smokers
- `smoke_current` as 0 and `smoke_past` as 1 for past smokers
- `smoke_current` as 0 and `smoke_past` as 0 for non-smokers
- `smoke_current` as -1 and `smoke_past` as -1 for unknown

```
smoking_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id",
                  "Smoke History")) |>
  dplyr::mutate(
    smoke_current = dplyr::case_when(
      is.na(.data[["Smoke History"]]) ~ "-1",
```

```

      .data[["Smoke History"]] == "non-smoker" ~ "0",
      .data[["Smoke History"]] == "past smoker" ~ "0",
      .data[["Smoke History"]] == "current smoker" ~ "1",
      .default = NA_character_
    ),
    smoke_current = forcats::fct_relevel(
      .data[["smoke_current"]],
      c("0", "1")),
    smoke_past = dplyr::case_when(
      is.na(.data[["Smoke History"]]) ~ "-1",
      .data[["Smoke History"]] == "non-smoker" ~ "0",
      .data[["Smoke History"]] == "past smoker" ~ "1",
      .data[["Smoke History"]] == "current smoker" ~ "0",
      .default = NA_character_
    ),
    smoke_past = forcats::fct_relevel(
      .data[["smoke_past"]],
      c("0", "1")),
    `Smoke History` = forcats::fct(
      .data[["Smoke History"]]
    )
  ) |>
pointblank::col_vals_in_set(
  columns = c("smoke_current", "smoke_past"),
  set = c("0", "1", "-1")
) |>
pointblank::col_vals_expr(
  expr = pointblank::expr(
    (.data[["smoke_current"]] == "1" & .data[["smoke_past"]] == "0") |
    (.data[["smoke_current"]] == "-1" & .data[["smoke_past"]] == "-1") |
    (.data[["smoke_current"]] == "0" & .data[["smoke_past"]] %in% c("0",
↵ "1"))
  )
)

```

```

if (params$show_table) {
  smoking_data |>
    dplyr::distinct(.data[["Smoke History"]],
                     .keep_all = TRUE) |>
    knitr::kable()
}

```

cohort_unique_id	Smoke History	smoke_current	smoke_past
B001	non-smoker	0	0
B002	current smoker	1	0
B004	past smoker	0	1
B017	NA	-1	-1

Remove unnecessary columns so that we can merge with the other fields.

```
smoking_data <- smoking_data |>
  dplyr::select(-c("Smoke History"))
```

3.2.4 Chest Pain

3.2.4.1 Shortness of Breath

have_sob is grouped as follows:

Dyspnea	have_sob
no	0
yes	1

```
shortness_of_breath_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id", "Dyspnea")) |>
  dplyr::mutate(
    have_sob = dplyr::case_when(
      .data[["Dyspnea"]] == "no" ~ "0",
      .data[["Dyspnea"]] == "yes" ~ "1",
      .default = NA_character_
    ),
    have_sob = forcats::fct_relevel(
      as.character(.data[["have_sob"]]),
      c("0", "1")),
    Dyspnea = forcats::fct_relevel(
      as.character(.data[["Dyspnea"]]),
      c("no", "yes")),
  ) |>
  pointblank::col_vals_in_set(
    columns = c("have_sob"),
    set = c("0", "1", "-1")
  )
```

```

if (params$show_table) {
  shortness_of_breath_data |>
    dplyr::distinct(.data[["Dyspnea"]],
                    .keep_all = TRUE) |>
    knitr::kable()
}

```

cohort_unique_id	Dyspnea	have_sob
B001	no	0
B002	yes	1

Remove unnecessary columns so that we can merge with the other fields.

```

shortness_of_breath_data <- shortness_of_breath_data |>
  dplyr::select(-c("Dyspnea"))

```

3.2.4.2 Have chest pain or not

have_chest_pain is grouped as follows:

Chest Pain Character	have_chest_pain
no chest pain	0
typical, atypical or nonanginal	1

```

have_chest_pain_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id", "Chest Pain Character")) |>
  dplyr::mutate(
    have_chest_pain = dplyr::case_when(
      .data[["Chest Pain Character"]] %in% c("no chest pain") ~ "0",
      .data[["Chest Pain Character"]] %in% c("typical", "atypical",
↪ "nonanginal") ~ "1",
      .default = NA_character_
    ),
    have_chest_pain = forcats::fct_relevel(
      .data[["have_chest_pain"]],
      c("0", "1")
    ),
    `Chest Pain Character` = forcats::fct_relevel(
      as.character(.data[["Chest Pain Character"]]),
      c("no chest pain", "typical", "atypical", "nonanginal")
    )
  )

```

```

)
) |>
pointblank::col_vals_in_set(
  columns = c("have_chest_pain"),
  set = c("0", "1")
)

```

```

if (params$show_table) {
  have_chest_pain_data |>
    dplyr::distinct(.data[["Chest Pain Character"]],
                    .keep_all = TRUE) |>
    knitr::kable()
}

```

cohort_unique_id	Chest Pain Character	have_chest_pain
B001	atypical	1
B002	no chest pain	0
B005	typical	1
B006	nonanginal	1

Remove unnecessary columns so that we can merge with the other fields.

```

have_chest_pain_data <- have_chest_pain_data |>
  dplyr::select(-c("Chest Pain Character"))

```

3.2.4.3 Symptomatic or Asymptomatic

symptoms is grouped as follows:

have_sob	have_chest_pain	symptoms
-1	-1	-1
0	0	0
0 or 1	1	1
1	0	2

```

symptoms_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id")) |>
  dplyr::inner_join(shortness_of_breath_data,
                    by = dplyr::join_by("cohort_unique_id"),
                    unmatched = "error",

```

```

        relationship = "one-to-one") |>
dplyr::inner_join(have_chest_pain_data,
  by = dplyr::join_by("cohort_unique_id"),
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::mutate(
  symptoms = dplyr::case_when(
    (.data[["have_chest_pain"]] == "-1" &
     .data[["have_sob"]] == "-1"
    ) ~ "-1",
    (.data[["have_chest_pain"]] == "0" &
     .data[["have_sob"]] == "0"
    ) ~ "0",
    (.data[["have_chest_pain"]] == "1" &
     .data[["have_sob"]] %in% c("0", "1")
    ) ~ "1",
    (.data[["have_chest_pain"]] == "0" &
     .data[["have_sob"]] == "1"
    ) ~ "2",
    .default = NA_character_
  ),
  symptoms = forcats::fct_relevel(
    .data[["symptoms"]],
    c("0", "1", "2"))
) |>
pointblank::col_vals_in_set(
  columns = c("symptoms"),
  set = c("0", "1", "2")
)

```

```

if (params$show_table) {
  symptoms_data |>
    dplyr::distinct(.data[["have_chest_pain"]], .data[["have_sob"]],
      .keep_all = TRUE) |>
    knitr::kable()
}

```

cohort_unique_id	have_sob	have_chest_pain	symptoms
B001	0	1	1
B002	1	0	2
B003	1	1	1
B007	0	0	0

Remove unnecessary columns so that we can merge with the other fields.


```
symptoms_data <- symptoms_data |>
  dplyr::select(-c("have_chest_pain", "have_sob"))
```

3.2.4.4 Chest Pain Type

chest_pain_type is grouped as follows:

Dyspnea	Chest Pain Character	chest_pain_type
no	no chest pain	0
no or yes	typical	1
no or yes	atypical	2
no or yes	nonanginal	3
yes	no chest pain	4

```
chest_pain_type_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id", "Chest Pain Character", "Dyspnea"))
  |>
  dplyr::mutate(
    chest_pain_type = dplyr::case_when(
      (.data[["Chest Pain Character"]] == "no chest pain" &
        .data[["Dyspnea"]] == "no"
      ) ~ "0",
      (.data[["Chest Pain Character"]] == "typical" &
        .data[["Dyspnea"]] %in% c("no", "yes")
      ) ~ "1",
      (.data[["Chest Pain Character"]] == "atypical" &
        .data[["Dyspnea"]] %in% c("no", "yes")
      ) ~ "2",
      (.data[["Chest Pain Character"]] == "nonanginal" &
        .data[["Dyspnea"]] %in% c("no", "yes")
      ) ~ "3",
      (.data[["Chest Pain Character"]] == "no chest pain" &
        .data[["Dyspnea"]] == "yes"
      ) ~ "4",
      .default = NA_character_
    ),
    `Chest Pain Character` = forcats::fct_relevel(
      as.character(.data[["Chest Pain Character"]]),
      c("no chest pain", "typical", "atypical", "nonanginal")
    ),
    `Dyspnea` = forcats::fct_relevel(
      as.character(.data[["Dyspnea"]]),
      c("no", "yes")
    )
  )
```

```

),
chest_pain_type = forcats::fct_relevel(
  .data[["chest_pain_type"]],
  c("0", "1", "2", "3"))
) |>
dplyr::relocate(
  "Chest Pain Character",
  .after = "cohort_unique_id"
) |>
pointblank::col_vals_in_set(
  columns = c("chest_pain_type"),
  set = c("0", "1", "2", "3", "4")
)

```

```

if (params$show_table) {
  chest_pain_type_data |>
    dplyr::distinct(.data[["Dyspnea"]], .data[["Chest Pain Character"]],
      .keep_all = TRUE) |>
    knitr::kable()
}

```

cohort_unique_id	Chest Pain Character	Dyspnea	chest_pain_type
B001	atypical	no	2
B002	no chest pain	yes	4
B003	atypical	yes	2
B005	typical	no	1
B006	nonanginal	yes	3
B007	no chest pain	no	0
B013	nonanginal	no	3
B015	typical	yes	1

Remove unnecessary columns so that we can merge with the other fields.

```

chest_pain_type_data <- chest_pain_type_data |>
  dplyr::select(-c("Dyspnea", "Chest Pain Character"))

```

3.2.4.5 Combined chest pain related tables

We combine all chest related tables together

```

join_specification <- dplyr::join_by("cohort_unique_id")

chest_pain_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id")) |>
  dplyr::inner_join(have_chest_pain_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one") |>
  dplyr::inner_join(chest_pain_type_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one") |>
  dplyr::inner_join(shortness_of_breath_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one") |>
  dplyr::inner_join(symptoms_data,
                    by = join_specification,
                    unmatched = "error",
                    relationship = "one-to-one")

testthat::expect_true(
  pointblank::has_columns(
    chest_pain_data,
    columns = c("have_sob", "have_chest_pain", "symptoms",
               ↵ "chest_pain_type")
  )
)

testthat::expect_equal(
  ncol(chest_pain_data), 5
)

```

3.2.5 Combine Demographics

We combine all the data to give the `demo_behave_data`.

```

join_specification <- dplyr::join_by("cohort_unique_id")

demo_behave_data <- cohort_B_data |>
  dplyr::select(c("cohort_unique_id")) |>
  dplyr::inner_join(age_gender_data,
                    by = join_specification,
                    unmatched = "error",

```

```

        relationship = "one-to-one") |>
dplyr::inner_join(body_measurement_data,
  by = join_specification,
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::inner_join(smoking_data,
  by = join_specification,
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::inner_join(chest_pain_data,
  by = join_specification,
  unmatched = "error",
  relationship = "one-to-one") |>
dplyr::relocate(c("bsa_m2", "bmi"),
  .after = "sex")

testthat::expect_true(
  pointblank::has_columns(
    demo_behave_data,
    columns = c(
      "age_years", "sex",
      "height_cm", "weight_kg", "bsa_m2", "bmi",
      "smoke_current", "smoke_past",
      "have_sob", "have_chest_pain",
      "symptoms", "chest_pain_type"
    )
  )
)

testthat::expect_equal(
  ncol(demo_behave_data), 13
)

```

3.3 Write Preprocessed File

We output data to be used for the next session.

```

demo_behave_data |>
  nanoparquet::write_parquet(
    file = here::here(
      params$analysis_folder,
      params$harmonisation_folder,
      params$preprocessing_folder,

```

```
    "02_demographic_data.parquet"  
  )  
)
```

4 Export To Excel

```
out_type <- knitr::opts_chunk$get("rmarkdown.pandoc.to")
```

4.1 Read all tabular data

We read all tabular data from the previous section.

4.2 Export Data as Excel

We export the standardised data to an excel file called harmonised__Cohort__B.xlsx

```
# Create a new workbook
my_workbook <- openxlsx::createWorkbook()

sheet_name = c("demographics")

output_data = list(demo_behave_data) |>
  purrr::map(
    .f = harmonisation::add_cohort_name,
    cohort_name = params$cohort_name,
    cohort_name_column = "cohort_name"
  )

purrr::walk2(
  .x = sheet_name,
  .y = output_data,
  .f = harmonisation::write_to_sheet,
  workbook = my_workbook
)

# Save workbook
openxlsx::saveWorkbook(
  wb = my_workbook,
  file = here::here(params$analysis_folder,
    params$output_folder,
```

```
        params$cleaned_folder,  
        params$output_excel_file),  
  overwrite = TRUE  
)
```