
What are Comparison Operators?

Comparison operators **compare two values** and return a **true** or **false** result. They are mostly used in **if statements** and **loops**.

1. === (Strict Equality)

🔑 Checks if **both value and type** are the same.

✓ **No type conversion** happens.

Example:

```
console.log(5 === 5); // true (same value, same type)
console.log(5 === "5"); // false (same value, different type)
console.log(true === 1); // false (boolean vs number)
```

2. == (Loose Equality)

🔑 Checks if values are the same, but **allows type conversion**.

✗ **Not recommended** because it can give unexpected results.

Example:

```
console.log(5 == "5"); // true (string "5" is converted to number)
console.log(0 == false); // true (0 is treated as false)
console.log(null == undefined); // true (special case)
```

● **Avoid using == because it can cause confusion.** Use === instead.

3. !== (Strict Inequality)

🔑 Checks if **either value or type is different**.

✓ **No type conversion** happens.

Example:

```
console.log(10 !== "10"); // true (different types)
console.log(10 !== 10); // false (same value, same type)
```

4. != (Loose Inequality)

☞ Checks if values are **not the same**, but **allows type conversion**.
✗ **Not recommended** because of unexpected type conversion.

Example:

```
console.log(5 != "5"); // false (converted, so considered equal)
console.log(false != 0); // false (converted, so considered equal)
console.log(null != undefined); // false (special case)
```

● **Use !== instead to avoid confusion.**

5. > (Greater Than)

☞ Checks if the **left value is greater** than the right value.

Example:

```
console.log(10 > 5); // true
console.log(5 > 10); // false
console.log("b" > "a"); // true (based on Unicode values)
```

★ **Strings are compared based on their Unicode values.**
For example, "b" has a **higher Unicode value** than "a".

6. < (Less Than)

☞ Checks if the **left value is smaller** than the right value.

Example:

```
console.log(5 < 10); // true
console.log(10 < 5); // false
console.log("apple" < "banana"); // true (compares first letter)
```

7. >= (Greater Than or Equal To)

☞ Checks if the **left value is greater than or equal** to the right value.

Example:

```
console.log(10 >= 10); // true (equal)
console.log(11 >= 10); // true (greater)
console.log(5 >= 10); // false
```

8. <= (Less Than or Equal To)

🔗 Checks if the **left value is less than or equal** to the right value.

Example:

```
console.log(5 <= 10); // true (less)
console.log(10 <= 10); // true (equal)
console.log(15 <= 10); // false
```

Comparison Operators Summary

Operator	Meaning	Example	Result
===	Strict equality (checks type & value)	5 === "5"	false
==	Loose equality (allows type conversion)	5 == "5"	true
!==	Strict inequality (checks type & value)	10 !== "10"	true
!=	Loose inequality (allows type conversion)	10 != "10"	false
>	Greater than	10 > 5	true
<	Less than	5 < 10	true
>=	Greater than or equal to	10 >= 10	true
<=	Less than or equal to	5 <= 10	true

Key Takeaways

- ✓ **Use === and !== instead of == and !=** to avoid type conversion issues.
- ✓ **String comparisons are case-sensitive** ("Apple" !== "apple").
- ✓ **Avoid == and != unless you know how type conversion works.**
- ✓ **Use > and < for number comparisons.**

Would you like some coding exercises to practice these? 🚀