

JSXGraph Reference Card

Include JSXGraph in HTML

Three parts are needed: Include files containing the software, an HTML element, and JavaScript code.

Include files:

Two files have to be included: `jsxgraph.css`, and `jsxgraph-core.js`.

```
- <link rel="stylesheet" type="text/css"
      href="domain/jsxgraph.css"/>
- <script type="text/javascript"
      src="domain/jsxgraphcore.js"></script>
```

`domain` is the location of the files. This can be a local directory or `http://jsxgraph.uni-bayreuth.de/distrib/`

HTML element containing the construction:

```
<div id="box" class="jxgbox"
      style="width:600px; height:600px;"></div>
```

JavaScript code:

```
<script type="text/javascript">
  var brd = JXG.JSXGraph.initBoard('box',{axis:true});
</script>
```

Initializing the board

```
var brd = JXG.JSXGraph.initBoard('box',{attributes});
```

– *Attributes of the board*

```
boundingbox:      [x1,y1,x2,y2] user coordinates of the
                    upper left and bottom right corner
keepaspectratio:true/false      default: false
zoomX,zoomY:      zoom factor in x/y-axis direction
zoomfactor:      overall zoom factor in both directions
axis,grid,showNavigation,showCopyright:      true/false
                    show axis, grid, zoom/navigation buttons, display copyright
```

Properties and methods of the board:

```
brd.snapToGrid:true/false:      grid mode
brd.suspendUpdate()      stop updating (if speed is needed)
brd.unsuspendUpdate()      restart updating
brd.addChild(brd2)      Connect board brd2 to board brd
```

Basic commands

```
var el = brd.create('type',[parents],[attributes]);
el.setProperty({key1:value1,key2:value2,...});
```

Point

```
brd.create('point',[parents],[attributes]);
```

Parent elements:

```
[x,y]      Euclidean coordinates
[z,x,y]      Homogeneous coordinates (z in first place)
[function(){return p1.X();},
 function(){return p2.Y();}]      Functions for x, y, (and z)
[function(){return [a,b];}]      Function returning array
[function(){return new JXG.Coords(...);}]      Function returning Coords object
```

Methods

```
p.X(),p.Y()      x-coordinate, y-coordinate
p.Z()      (Homogeneous) z-coordinate
p.Distance(q)      Distance from p to point q
```

Glider

Point on circle, line, curve, or turtle.

```
brd.create('glider',[parents],[attributes]);
```

Parent elements:

```
[x,y,c]      Initial coordinates and object to glide on
[c]      Object to glide on (initially at origin)
```

Coordinates may also be defined by functions, see [Point](#).

Line

```
brd.create('line',[parents],[attributes]);
```

Parent elements:

```
[p1,p2]      line through 2 points
[c,a,b]      line defined by 3 coordinates (can also be functions)
[[x1,y1],[x2,y2]]      line by 2 coordinate pairs
```

In case of coordinates as parents, the line is the set of solutions of the equation $a \cdot x + b \cdot y + c \cdot z = 0$.

Circle

```
brd.create('circle',[parents],[attributes]);
```

Parent elements:

```
[p1,p2]      2 points: center and point on circle line
[p,r]      center, radius (constant or function)
[p,c],[c,p]      center, circle from which the radius is taken
[p,l],[l,p]      center, line segment for the radius
[p1,p2,p3]      circle through 3 points
Points may also be specified as array of coordinates.
```

Polygon

```
brd.create('polygon',[p1,p2,...],[attributes]);
[p1,p2,...]      The array of points
is connected by line segments and the inner area is filled.
brd.create('regularpolygon',[p1,p2,n],[attributes]);
```

Slider

```
var s = brd.create('slider',[[a,b],[c,d],[e,f,g]],{atts});
[a,b],[c,d]:      visual start and end position of the slider
[e,f,g]:      the slider returns values between e and g,
                    the initial position is at value f
snapWidth:num      minimum distance between 2 values
s.Value():      returns the position of the slider  $\in [e,g]$ 
```

Group

```
brd.create('group',[p1,p2,...],[attributes]);
[p1,p2,...]      array of points
Invisible grouping of points. If one point is moved, the others
are transformed accordingly.
```

Curve

```
- brd.create('functiongraph',[parents],[atts]);
                    Function graph,  $x \mapsto f(x)$ 
```

```
[function(x){return x*x;},-1,1]      function term
                    optional: start, end
```

```
- brd.create('curve',[parents],[attributes]);
· Parameter curve,  $t \mapsto (f(t),g(t))$ :
```

```
[function(t){return 5*t;},function(t){return t*t;},0,2]
                    x function, y function, optional: start, end
```

```
· Polar curve: Defined by the equation  $r = f(\phi)$ .
```

```
[function(phi){return 5*phi;},[1,2],0,Math.PI]
                    Defining function, optional: center, start, end
```

```
· Data plot:
```

```
[[1,2,3],[4,-2,3]]      array of x- and y-coordinates, or
[[1,2,3],function(x){return x*x;}]
                    array of x-coordinates, function term
```

```
- brd.create('spline',[p1,p2,...],[attributes]);
[p1,p2,...]      Cubic spline: array of points
```

```
- brd.create('riemannsum',[f,n,type],[atts]);
Riemann sum of type 'left', 'right', 'middle', 'trapezodial', 'upper', or 'lower'
```

Tangent, normal

```
var el = brd.create('tangent',[g],[attributes]);
var el = brd.create('normal',[g],[attributes]);
g      glider on circle, line, polygon, curve, or turtle
```

Turtle

```
var t = brd.create('turtle',[parents],[atts]);
t.X(), t.Y(), t.dir      position, direction (degrees).
```

Parent elements:

```
[x,y,angle]      Optional start values for x, y, and direction
```

Methods:

```
t.back(len); or t.bk(len);
t.clean();      erase the turtle lines without resetting the turtle
t.clearScreen(); or t.cs();      call t.home() and t.clean()
t.forward(len); t.fd(len);
t.hideTurtle(); or t.ht();
t.home();      Set the turtle to [0,0] and direction to 90.
t.left(angle); or t.lt(angle);
t.lookTo(t2.pos);      Turtle looks to the turtle t2
t.lookTo([x,y]);      Turtle looks to a coordinate pair
t.moveTo([x,y]);      Move the turtle with drawing
t.penDown(); or t.pd();
t.penUp(); or t.pu();
t.popTurtle();      pop turtle status from stack
t.pushTurtle();      push turtle status on stack
t.right(angle); or t.rt(angle);
t.setPos(x,y);      Move the turtle without drawing
t.setPenColor(col); col: colorString, e.g. 'red' or '#ff0000'
t.setPenSize(size);      size: number
t.showTurtle(); or t.st();
```

Other geometric elements

– *angle*: filled area defined by 3 points
`el = brd.create('angle', [A,B,C], {attributes});`

– *arc*: circular arc defined by 3 points
`el = brd.create('arc', [A,B,C], {attributes});`

– *arrow*: line through 2 points with arrow head
`el = brd.create('arrow', [A,B], {attributes});`

– *arrowparallel*: arrow parallel to arrow *a* starting at point *P*
`el = brd.create('arrowparallel', [a,P], {atts});` or `[P,a]`

– *bisector*: angular bisector defined by 3 points, returns line
`el = brd.create('bisector', [A,B,C], {atts});`

angular bisector defined by 2 lines, returns 2 lines
`el = brd.create('bisectorlines', [l1,l2], {atts});`

– *circumcircle*: circle through 3 points (deprecated)
`el = brd.create('circumcircle', [A,B,C], {atts});`

– *circumcirclemidpoint*: center of circle through 3 points
`el = brd.create('circumcirclemidpoint', [A,B,C]);`

– *midpoint*: midpoint between 2 points or the 2 points defined by a line
`el = brd.create('midpoint', [A,B], {atts});` or `[line]`

– *mirrorpoint*: rotate point *B* around point *A* by 180°
`el = brd.create('mirrorpoint', [A,B], {atts});`

– *parallel*: line parallel to line *l* through point *P*
`el = brd.create('parallel', [l,P], {atts});` or `[P,l]`

– *parallelpont*: point D such that *ABCD* from a parallelogram
`el = brd.create('parallelpont', [A,B,C], {atts});`

– *perpendicular*: line perpendicular to line *l* through point *P*
`el = brd.create('perpendicular', [l,P], {atts});` or `[P,l]`

– *perpendicularpoint*: point defining a perpendicular line to line *l* through point *P*
`el = brd.create('perpendicularpoint', [l,P], {});` or `[P,l]`

– *reflection*: reflection of point *P* over the line *l*. Superseded by transformations
`el = brd.create('reflection', [l,P], {atts});` or `[P,l]`

– *sector*: circle sector defined by 3 points ???
`el = brd.create('sector', [A,B,C], {atts});`

– *semi circle*: defined by 2 points *p*₁ and *p*₂.
`brd.create('semicircle', [p1,p2], {atts});`

– *intersection*: of 2 objects (lines or circles).

Returns array of length 2 with first and second intersection point (also for line/line intersection).

`brd.create('intersection', [o1,o2,n], {atts});`

Text

Display static or dynamic texts.

`el = brd.create('text', [x,y,"Hello"]);`
`el = brd.create('text', [x,y,f]);` where
`f = function(){ return p.X(); }`
Example for a dynamic text: *f* returns the *x* coordinate of the point *p*.

Image

Display bitmap image (also as data uri).

`el = brd.create('image', [uri-string, [x,y], [w,h]]);`
`[x,y]`: position of lower left corner, `[w,h]`: width, height

Attributes of geometric elements

Generic attributes:

strokeWidth: number
strokeColor, fillColor, highlightFillColor, highlightStrokeColor, labelColor: color string
strokeOpacity, fillOpacity, highlightFillOpacity, highlightStrokeOpacity: value between 0 and 1
visible, trace, draft: true, false
dash: dash style for lines: 0, 1, ..., 6

Attributes for point elements:

face: possible point faces: '□', '○', 'x', '+', '<', '>', 'A', 'v'
size: number
fixed: true, false

Attributes for line elements:

straightFirst, straightLast, withTicks: true, false

Attributes for line, arc and curve elements:

firstArrow, lastArrow: true, false

Attributes for polygon elements:

withLines: true, false

Attributes for text elements:

display: 'html', 'internal'

Color string:
HTML color definition or HSV color scheme:
`JXG.hsv2rgb(h,s,v)` $0 \leq h \leq 360, 0 \leq s, v \leq 1$
returns RGB color string.

Transform

Affine transformation of objects.

`t = brd.create('transform', [data,base], {type:'type'});`
base: the transformation is applied to the coordinates of this object.

Possible types:

- translate: `data=[x,y]`
- scale: `data=[x,y]`
- reflect: `data=[line]` or `[x1,y1,x2,y2]`
- rotate: `data=[angle,point]` or `[angle,x,y]`
- shear: `data=[angle]`
- generic: `data=[v11,v12,v13,v21,...,v33]` 3×3 matrix

Methods:

`t.bindTo(p)` the coordinates of *p* are defined by *t*
`t.applyOnce(p)` apply the transformation once
`t.melt(s)` combine two transformations to one: $t := t \cdot s$
`p2 = brd.create('point', [p1,t], {fixed:true});`
Point *p*₂: apply *t* on point *p*₁

Mathematical functions

Functions of the intrinsic JavaScript object *Math*:

`Math.abs, Math.acos, Math.asin, Math.atan, Math.ceil,`
`Math.cos, Math.exp, Math.floor, Math.log, Math.max,`
`Math.min, Math.random, Math.sin, Math.sqrt, Math.tan`

`(number).toFixed(3)`: Rounding a number to fixed precision

Additional mathematical functions are methods of `JXG.Board`.

`brd.angle(A,B,C)` angle *ABC*
`brd.cosh(x), board.sinh(x)`
`brd.pow(a,b)` a^b
`brd.D(f,x)` compute $\frac{d}{dx}f$ numerically
`brd.I([a,b],f)` compute $\int_a^b f(x)dx$ numerically
`brd.root(f,x)` root of the function *f*.
Uses Newton method with start value *x*
`brd.factorial(n)` computes $n! = 1 \cdot 2 \cdot 3 \cdots n$
`brd.binomial(n,k)` computes $\binom{n}{k}$
`brd.distance(arr1,arr2)` Euclidean distance
`brd.lagrangePolynomial([p1,p2,...])` returns a polynomial through the given points
`brd.neville([p1,p2,...])` polynomial curve interpolation
`c = JXG.Math.Numerics.bezier([p1,p2,...])` Bezier curve
*p*₂, *p*₃, *p*₅, *p*₆, ... are control points. `brd.create('curve',c);`
`f = JXG.Math.Numerics.regressionPolynomial(n,xArr,yArr)` Regression pol. of deg. *n*: `brd.create('functiongraph',f);`
`brd.riemannsum(f,n,type,start,end)` Volume of Riemann sum, see *Curves*

– Intersection of objects:
`brd.intersection(el1,el2,i,j)` intersection of the elements
*el*₁ and *el*₂ which can be lines, circles or curves

In case of circle and line intersection, $i \in \{0,1\}$ denotes the first or second intersection. In case of an intersection with a curve, *i* and *j* are floats which are the start values for the path positions in the Newton method for *el*₁ and *el*₂, resp.

Todo list

'axis', 'integral', 'ticks'.

Chart

To do ...

Links

Help pages are available at <http://jsxgraph.org>