

JSXGraph Reference Card

Include JSXGraph in HTML

Three parts are needed: Include files containing the software, an HTML element, and JavaScript code.

Include files:

Three files have to be included: `jsxgraph.css`, `jsxgraphcore.js` and either `prototype.js` or `jquery.js`.

```
-- <script type="text/javascript"
    src="domain/prototype.js"></script>
or -- <script type="text/javascript"
    src="domain/jquery.min.js"></script>
-- <link rel="stylesheet" type="text/css"
    href="domain/jsxgraph.css"/>
-- <script type="text/javascript"
    src="domain/jsxgraphcore.js"></script>
```

domain is the location of the files. This can be a local directory or `http://jsxgraph.uni-bayreuth.de/distrib/`

HTML element containing the construction:

```
<div id="box" class="jxgbox"
    style="width:600px; height:600px;"></div>
```

JavaScript code:

```
<script type="text/javascript">
    var brd = JXG.JSXGraph.initBoard('box',{axis:true});
</script>
```

Initializing the board

```
var brd = JXG.JSXGraph.initBoard('box',{attributes});
```

– *Attributes of the board*

<code>unitX, unitY:</code>	number of pixels of one unit in x/y -axis direction
<code>originX, originY:</code>	the coordinates of the origin in pixel coordinates
<code>zoomX, zoomY:</code>	zoom factor in x/y -axis direction
<code>zoomfactor:</code>	overall zoom factor in both directions
<code>axis:true/false:</code>	show axes
<code>grid:true/false:</code>	show grid

Basic commands

```
var el = brd.createElement('type',[parents],[attributes]);
el.setProperty({key1:value1,key2:value2,...});
```

Point

```
brd.createElement('point',[parents],[attributes]);
```

Parent elements:

<code>[x,y]</code>	Euclidean coordinates
<code>[z,x,y]</code>	Homogeneous coordinates (z in first place)
<code>[function(){return p1.X();},</code> <code>function(){return p2.Y();}]</code>	Functions for x, y , (and z)

Methods

<code>p.X()</code> , <code>p.Y()</code>	x -coordinate, y -coordinate
<code>p.Z()</code>	(Homogeneous) z -coordinate
<code>p.Distance(q)</code>	Distance from p to point q

Glider

Point on circle, line or curve.

```
brd.createElement('glider',[parents],[attributes]);
```

Parent elements:

<code>[x,y,c]</code>	Initial coordinates and object to glide on
<code>[c]</code>	Object to glide on (initially at origin)

Coordinates may also be defined by functions, see Point.

Line

```
brd.createElement('line',[parents],[attributes]);
```

Parent elements:

<code>[p1,p2]</code>	line through 2 points
<code>[c,a,b]</code>	line defined by 3 coordinates (can also be functions)

In case of coordinates as parents, the line is the set of solutions of the equation $a \cdot x + b \cdot y + c \cdot z = 0$.

Circle

```
brd.createElement('circle',[parents],[attributes]);
```

Parent elements:

<code>[p1,p2]</code>	2 points: center and point on circle line
<code>[p,r]</code>	center, radius (constant or function)
<code>[p,c],[c,p]</code>	center, circle from which the radius is taken
<code>[p,l],[l,p]</code>	center, line segment for the radius
<code>[p1,p2,p3]</code>	circle through 3 points

Polygon

```
brd.createElement('polygon',[p1,p2,...],[attributes]);
[p1,p2,...] array of points
```

The points array connected by line segments and the inner area is filled.

Group

```
brd.createElement('group',[p1,p2,...],[attributes]);
[p1,p2,...] array of points
Invisible grouping of points. If one point is moved, the others
are transformed accordingly.
```

Slider

```
var s = brd.createElement('slider',
    [[a,b],[c,d],[e,f,g]],{atts});
[a,b],[c,d]: visual start and end position of the slider
[e,f,g]: the slider returns values between  $e$  and  $g$ ,
the initial position is at value  $f$ 
s.Value(): returns the position of the slider  $\in [e,g]$ 
```

Curve

– *Function graph*, $x \mapsto f(x)$:

```
brd.createElement('functiongraph',[parents],[atts]);
```

Parent elements:

<code>[function(x){return x*x;},-1,1]</code>	function term optional: start, end
--	---------------------------------------

The other types of curves are defined through:

```
brd.createElement('curve',[parents],[attributes]);
```

Parent elements:

– *Parameter curve*, $t \mapsto (f(t), g(t))$:

```
[function(t){return 5*t;},function(t){return t*t;},0,2]
x function, y function, optional: start, end
```

– *Polar curve*:

Defined by the equation $r = f(\phi)$.

```
[function(phi){return 5*phi;},[1,2],0,Math.PI]
Defining function, optional: center, start, end
```

– *Data plot*:

```
[[1,2,3],[4,-2,3]]
array of  $x$ -coordinates, array of  $y$ -coordinates, or
[[1,2,3],function(x){return x*x;}]
array of  $x$ -coordinates, function term
```

– *Cubic spline*:

```
brd.createElement('spline',[p1,p2,...],[attributes]);
[p1,p2,...] array of points
```

Tangent, normal

```
var el = brd.createElement('tangent',[g],[attributes]);
var el = brd.createElement('normal',[g],[attributes]);
g circle, line, polygon, or curve to glide on
```

Turtle

```
var t = brd.createElement('turtle');
var t = brd.createElement('turtle',[],[attributes]);
var t = brd.createElement('turtle',[parents],[atts]);
The turtle has a position and a direction (in degrees). All
angles have to be supplied in degrees.
```

Parent elements:

<code>[x,y,angle]</code>	Optional start values for x, y , and direction
--------------------------	--

Methods:

Most of the methods have an abbreviated alternative version.

```
t.back(len); or t.bk(len);
t.clean(); erase the turtle lines without resetting the turtle
t.clearScreen(); or t.cs(); call t.home() and t.clean()
t.forward(len); t.fd(len);
t.hideTurtle(); or t.ht();
t.home(); Set the turtle to [0,0] and direction to 90.
t.left(angle); or t.lt(angle);
t.lookTo(t2.pos); Turtle looks to the turtle t2
t.lookTo([x,y]); Turtle looks to a coordinate pair
t.moveTo([x,y]); Move the turtle with drawing
t.penDown(); or t.pd();
t.penUp(); or t.pu();
t.popTurtle(); pop turtle status from stack
t.pushTurtle(); push turtle status on stack
```

```
t.right(angle); or t.rt(angle);
t.setPos(x,y);           Move the turtle without drawing
t.setPenColor(col); col: colorString, e.g. 'red' or '#ff0000'
t.setPenSize(size);      size: number
t.showTurtle(); or t.st();
```

Other geometric elements

```
- angle:                filled area defined by 3 points
el = brd.createElement('angle', [A,B,C], {attributes});

- arc:                  circular arc defined by 3 points
el = brd.createElement('arc', [A,B,C], {attributes});

- arrow:                line through 2 points with arrow head
el = brd.createElement('arrow', [A,B], {attributes});

- arrowparallel:        arrow parallel to arrow a starting at point P
el = brd.createElement('arrowparallel', [a,P], {atts});
el = brd.createElement('arrowparallel', [P,a], {atts});

- bisector:             angular bisector defined by 3 points, returns line
el = brd.createElement('bisector', [A,B,C], {atts});

- circumcircle:         circle through 3 points (deprecated)
el = brd.createElement('circumcircle', [A,B,C], {atts});

- circumcirclemidpoint: center of circle through 3 points
el = brd.createElement('circumcirclemidpoint', [A,B,C]);

- midpoint:             midpoint between 2 points or the 2 points defined
by a line
el = brd.createElement('midpoint', [A,B], {atts});
el = brd.createElement('midpoint', [line], {atts});

- mirrorpoint:          rotate point B around point A by 180°
el = brd.createElement('mirrorpoint', [A,B], {atts});

- parallel:             line parallel to line l through point P
el = brd.createElement('parallel', [l,P], {atts});
el = brd.createElement('parallel', [P,l], {atts});

- parallelpoint:        point D such that ABCD from a parallelogram
el = brd.createElement('parallelpoint', [A,B,C], {atts});

- perpendicular:        line perpendicular to line l through point P
el = brd.createElement('perpendicular', [l,P], {atts});
el = brd.createElement('perpendicular', [P,l], {atts});

- perpendicularpoint:   point defining a perpendicular line to
line l through point P
el = brd.createElement('perpendicularpoint', [l,P], {});
el = brd.createElement('perpendicularpoint', [P,l], {});

- reflection:           reflection of point P over the line l. Superseded
by transformations
el = brd.createElement('reflection', [l,P], {atts});
el = brd.createElement('reflection', [P,l], {atts});

- sector:               circle sector defined by 3 points      ???
el = brd.createElement('sector', [A,B,C], {atts});
```

Attributes of geometric elements

```
Generic attributes:
strokeWidth:                number
strokeColor,fillColor,highlightFillColor,
highlightStrokeColor,labelColor:    color string
strokeOpacity,fillOpacity,highlightFillOpacity,
highlightStrokeOpacity:    value between 0 and 1
visible,trace,draft:        true, false
dash:                       dash style for lines: 0, 1, ..., 6

Attributes for point elements:
style:                      point style: 0, 1, ..., 12
fixed:                      true, false

Attributes for line elements:
straightFirst,straightLast,withTicks:true, false

Attributes for line and arc elements:
firstArrow,lastArrow:       true, false
```

Text

```
Display static or dynamic texts.
el = brd.createElement('text', [x,y,"Hello"]);
el = brd.createElement('text', [x,y,f]);
Example for a dynamic text: return the x coordinate of the
point p.
f = function(){ return p.X(); }
```

Transform

```
Affine transformation of objects.
t = brd.createElement('transform', [data,base], {type:'type'});
base: the transformation is applied to the coordinates of this
object.
Possible types:
- translate: data=[x,y]
- scale: data=[x,y]
- reflect: data=[line] or [x1,y1,x2,y2]
- rotate: data=[angle,point] or [angle,x,y]
- shear: data=[angle]
- generic: data=[v11,v12,v13,v21,...,v33] 3 × 3 matrix
```

```
Methods:
t.bindTo(p)                the coordinates of p are defined by t
t.applyOnce(p)             apply the transformation once
t.melt(s)                  combine two transformations to one: t := t · s
```

Mathematical functions

```
Functions of the intrinsic JavaScript object Math:
Math.abs,Math.acos,Math.asin,Math.atan,Math.ceil,
Math.cos,Math.exp,Math.floor,Math.log,Math.max,
Math.min,Math.random,Math.sin,Math.sqrt,Math.tan

(number).toFixed(3): Rounding a number to fixed precision
Additional mathematical functions are methods of JXG.Board.
brd.angle(A,B,C)          angle ABC
brd.cosh(x), board.sinh(x)
brd.pow(a,b)              ab
brd.D(f,x)                compute  $\frac{d}{dx}f$  numerically
brd.I([a,b],f)            compute  $\int_a^b f(x)dx$  numerically
brd.root(f,x)             root of the function f.
                          Uses Newton method with start value x
brd.factorial(n)          computes n! = 1 · 2 · 3 · ... · n
brd.binomial(n,k)         computes  $\binom{n}{k}$ 
brd.distance(arr1,arr2)    Euclidean distance
brd.lagrangePolynomial([p1,p2,...])
                          returns a polynomial through the given points
brd.neville([p1,p2,...])  polynomial curve interpolation
```

```
- Intersection of objects:
brd.intersection(el1,el2,i,j) intersection of the elements
el1 and el2 which can be lines, circles or curves
In case of circle and line intersection, i ∈ {0,1} denotes the
first or second intersection. In case of an intersection with a
curve, i and j are floats which are the start values for the path
positions in the Newton method for el1 and el2, resp.
```

Todo list

```
'axis','image','integral','ticks',
```

Chart

```
To do ...
```

Links

```
Help pages are available at http://jsxgraph.org
```