

Parsing Natural Language

Parsing Without Grammar: Shift-Reduce Dependency Parsing

Parsing: Schematics

- So far, we considered algorithms that used a grammar to only produce „valid“ trees
- In this lecture, we are using machine-learning to directly produce a parse-tree, without relying on a grammar
 - This means our output can be super unintuitive, since it is not guide by a grammar, but we are able to incorporate strong features into the process!
- Two famous approaches:
 1. Shift-Reduce-Parsing
 2. Graph-based parsing


Shift-Reduce-Parsing

- Origins in parsing computer languages
- Makes use of a very clever data structure to deal with this problem
- Only difference to a classical parser for computer language is the addition of an „oracle“
- Usually used for Dependency Parsing problems!

Shift-Reduce-Parsing

- Makes use of a very clever data structure to deal with this problem
- The clever idea, is that we can convert the problem of producing a tree into a classification problem with just 3 classes!
- This works by the introduction of a Buffer and a Stack! (see next slide)

Dependency-Parsing: Data structure




Shift Reduce Parsing

Stack




Buffer




Shift Reduce Parsing

Stack




Buffer




- Operation:SHIFT

Shift Reduce Parsing

Stack




Buffer




- Operation:SHIFT

Shift Reduce Parsing

Stack




Buffer





- Operation:SHIFT

Shift Reduce Parsing

Stack



Buffer




- Operation:LEFTARC

Er kauft


- Result:

Shift Reduce Parsing

Stack



Buffer



- Operation:SHIFT


Er kauft

The words "Er kauft" are shown with a curved arrow pointing from "kauft" back to "Er", indicating the shift operation.


- Result:

Shift Reduce Parsing

Stack



Buffer




- Operation:RIGHTARC




- Result:

Shift Reduce Parsing

Stack



Buffer




- Operation:SHIFT




- Result:

Shift Reduce Parsing

Stack



Buffer




- Operation:SHIFT

Er kauft sich


- Result:

Shift Reduce Parsing

Stack



Buffer




- Operation:LEFTARC

- Result:




Shift Reduce Parsing

Stack



Buffer




- Operation:RIGHTARC



- Result:


Shift Reduce Parsing

Stack



• Result:

Buffer




• Operation:SHIFT



Shift Reduce Parsing

Stack



• Result:

Buffer




• Operation:SHIFT




Shift Reduce Parsing

Stack



Buffer




- Operation:SHIFT




- Result:

Shift Reduce Parsing

Stack



Buffer




- Operation:LEFTARC




- Result:

Shift Reduce Parsing

Stack



Buffer




- Operation:RIGHTARC




- Result:

Shift Reduce Parsing


Stack



Buffer




- Operation:RIGHTARC




- Result:

Shift Reduce Parsing


Stack



Buffer




- Operation:RIGHTARC




- Result:

Shift Reduce Parsing

Stack




Buffer



• DONE

• Result:



Shift Reduce Parsing: Arc Standard

- How to use this for Dependency Parsing?

→ Use an adjusted set of operations!

→ Arc-Standard

1. **LEFTARC**: Add an edge between the first token of the stack and the second token of the stack. Delete the second token from the stack
2. **RIGHTARC**: Add an edge between the second token of the stack and the first token of the stack. Delete the first token from the stack.
3. **SHIFT**: Move the first token from the buffer onto the stack



ein Eis



kauft sich

Dependency Parsing – Greedy Parse

function DEPENDENCYPARSE(*words*) **returns** dependency tree

state \leftarrow { [root], [*words*], [] } ; initial configuration

while *state* not final

t \leftarrow ORACLE(*state*) ; choose a transition operator to apply

 state \leftarrow APPLY(*t*, *state*) ; apply it, creating a new state

return *state*

Dependency Parsing – Oracle

- Features:
 - Use arbitrary features from the stack, the buffer, or the edges we produced already
 - Usually features are of the sort:
 - text of Stack[0] and operation $\langle s_0.text, op \rangle$
 - Text Stack[1] und operation $\langle s_1.text, op \rangle$
 - POS-Tag of Stack[0] and operation $\langle s_0.pos, op \rangle$
 - POS-Tag Stack[1] and operation $\langle s_1.pos, op \rangle$
 - text of Buffer[0] and operation $\langle b_0.text, op \rangle$
 - Text Buffer[1] and operation $\langle b_1.text, op \rangle$
 - POS-Tag of Buffer[0] and operation $\langle b_0.pos, op \rangle$
 - POS-Tag Buffer[1] und operation $\langle b_1.pos, op \rangle$
 - ...

Recap: Shift Reduce Parsing

- Grammarless way of parsing, but it relies on the quality of its oracle
 - Any classifier can be used as an oracle (e.g. SVM, MaxEnt)
 - Makes use of a clever data structure consisting of a stack and a buffer
 - Input is the sentence, split into tokens
 - Output is the set of operations:
 - Which is also the main way of adapting this kind of parser, you could add more operations (e.g. a SWAP)
 - If you want to train such a classifier, you have to convert the tree bank into a suitable sequence of operations beforehand.
 - If you want to predict Dependency-Relations, you just add them to the Operations: LEFTARC and RIGHTARC
- ➔ Greedy parsing has a linear runtime $O(n)$, with n tokens in the sentence