


QA Consulting.

Hadoop Command Reference Guide

BIG DATA COURSE



Prepared by
Thomas Knowles

 +447858368323

 Thomas.Knowles@qa.com

Contents

Overview.....	1
Unix Commands.....	1
Access the Manual Page for a Command.....	1
Listing Files in Directory. No filepath = current directory	1
Printing the Contents of a File.....	1
Moving a File	1
Removing a File. r = with sub-directories; f = ignore warnings.....	1
Copying a File.....	1
Moving a File	2
Creating a new directory	2
Adding Permissions (r – read, w – write, x – execute) to a File.....	2
Changing the Ownership of a File	2
Create a new Directory. Add ‘-p’ to create parent directories too	2
Delete a Directory	2
Download and Install Package. [pm] will be ‘apt-get’ or ‘yum’.....	2
Create a new Text File. [editor] can be ‘vi’, or any other installed editor	2
Change Ownership of a File	2
Run the previous Command with Sudo permissions	2
Vi Commands	3
Enter INSERT (text entry) mode	3
Save and Exit	3
Exit without Saving.....	3
Copy Selection	3
Paste Selection.....	3
Find String after cursor	3
Find String before cursor	3
Next/Previous Match.....	3
Write to a New File	3
Write to a Pre-existing File	3
Hadoop Commands.....	4
Using Unix commands in Hadoop - Example	4
Moving a File from Host to Hadoop	4
Alternative for Host to Hadoop File Transfer (if ‘put’ doesn’t work).....	4
Moving a File from Hadoop to Host	4
Alternative for Hadoop to Host File Transfer (if ‘get’ doesn’t work).....	4
Set Replication Number	4

Hive Commands.....5

 Creating a Table with Primitives, Array and Map5

 Optional Lines for Complex Types.....5

 Loading Data into Table5

 Accessing Complex Data Types.....5

Overview

This guide describes the most common commands needing during the Hadoop Admin, Hive and Impala Exercises. Basic SQL is assumed for interacting with Hive and Impala, but intricate tasks like creating tables from datasets are explained.

Anything not provided here will be found in the lecture slides or exercise guide.

Unix Commands

All commands must be conducted from the Terminal Prompt (not the Hive prompt). Prefacing with 'sudo' will be necessary to access certain filepaths. Square brackets indicate optional arguments – they are NOT part of the syntax.

Most of these commands can be used for HDFS administration too, but must be prefaced with 'hdfs dfs' OR 'hadoop fs' and a '-' before the command (turning it into a flag). All filepaths for the HDFS must be absolute.

Access the Manual Page for a Command

`man [command]`

Listing Files in Directory. No filepath = current directory

`ls [filepath]`

Printing the Contents of a File

`cat [filepath]`

Moving a File

`mv [source filepath] [destination filepath]`

Removing a File. r = with sub-directories; f = ignore warnings

`rm [-r] [-f]`

Copying a File

`cp [source filepath] [destination filepath]`

Moving a File

`mv [source filepath] [destination filepath]`

Creating a new directory

`mkdir [filepath]`

Adding Permissions (r – read, w – write, x – execute) to a File

`chmod +u[permissions] [filename]`

Changing the Ownership of a File

`chown [user][:usergroup]`

Create a new Directory. Add '-p' to create parent directories too

`mkdir [-p] [filepath]`

Delete a Directory

`rmdir [filepath]`

Download and Install Package. [pm] will be 'apt-get' or 'yum'

`sudo [pm] update`

`sudo [pm] install [package name]`

Create a new Text File. [editor] can be 'vi', or any other installed editor

`sudo [editor] [filepath].txt`

Change Ownership of a File

`chown [filename]`

Run the previous Command with Sudo permissions

`sudo !!`

Vi Commands

To access commands, you will need to 'esc' from INSERT mode.

Enter INSERT (text entry) mode

i

Save and Exit

:wq

Exit without Saving

:q!

Copy Selection

yy

Paste Selection

p

Find String after cursor

/string

Find String before cursor

?string

Next/Previous Match

n/N

Write to a New File

:w [filename]

Write to a Pre-existing File

:w! [filename]

Hadoop Commands

All commands must be conducted from the Terminal prompt (not the Hive prompt). Square brackets indicate optional arguments – they are NOT part of the syntax. All filepaths for the HDFS must be absolute.

Most of the Unix Commands can also be used here. To convert a Unix command to a Hadoop command, preface it with 'hadoop fs' or 'hdfs dfs' and convert the command to a flag with '-'.

Using Unix commands in Hadoop - Example

```
hadoop fs -mv [source_filepath] [destination_filepath]
```

Moving a File from Host to Hadoop

```
hadoop fs -put [host_filepath] [hdfs_filepath]
```

Alternative for Host to Hadoop File Transfer (if 'put' doesn't work)

```
hadoop fs -copyFromLocal [host_filepath] [hdfs_filepath]
```

Moving a File from Hadoop to Host

```
hadoop fs -get [hdfs_filepath] [host_filepath]
```

Alternative for Hadoop to Host File Transfer (if 'get' doesn't work)

```
hadoop fs -copyToLocal [hdfs_filepath] [host_filepath]
```

Set Replication Number

```
hadoop fs -setrep [replication_number] [filepath]
```


Hive Commands

Hive is mostly just a subset of standard SQL (HiveQL). Basics are covered in the PowerPoint slides, which Hive shares with SQL. The more verbose commands are repeated below for ease of reference.

Creating a Table with Primitives, Array and Map

```
CREATE TABLE jobs
```

```
    (id INT,  
     title STRING,  
     salary INT,  
     posted TIMESTAMP,  
     headquarters_address ARRAY <STRING>,  
     reviews STRUCT <review1 : STRING, review2 : STRING, review3 : STRING>
```

```
ROW FORMAT DELIMITED
```

```
FIELDS TERMINATED BY ';;'
```

Optional Lines for Complex Types

```
COLLECTION ITEMS TERMINATED BY ','
```

```
MAP KEYS TERMINATED BY ':'
```

Loading Data into Table

```
LOAD DATA [LOCAL] INPATH 'filepath' [OVERWRITE] INTO TABLE 'table_name';
```

Accessing Complex Data Types

```
array[index]
```

```
map[key]
```

```
struct.element
```