

An Enclosed Mode Is a Gauge Choice: Topology Relative to Reach in Certified Code World Models

Javier Aguilar Martín
AGILabs (javieraguilar.ai)

Abstract

A code world model accepted by a sampling gate can be exactly right on everything the gate can see and arbitrarily wrong beyond it. We characterize what a certified model can know — and what its errors can cost — when the omitted structure is a topologically nontrivial region: an annular freeze mode enclosing an unreachable interior. The *gate quotient* makes the question precise: acceptance-with-certainty determines the model exactly up to the reachable query set, so everything beyond reach is gauge. On a minimal ring instrument we prove the extreme case — a wrong-topology filled-disc artifact is unfalsifiable by *any* sampling gate and bitwise harmless at play — and measure, with real LLM synthesis across three model families, how a single knob (an angular channel of width γ) walks the same artifact through three regimes: unfalsifiable-and-harmless, falsifiable-and-costly, and instantly falsified. Two results organize the empirics. First, **danger is topology relative to reach, not topology**: opening a channel the planner can use collapses the blind model’s exploitation (`play_cost` 1.09 $\rightarrow$ ~ 0 over a knee at $\gamma \approx 0.1$), while a hidden channel with the *same* first Betti number keeps it at full strength (1.12). Second, **repair is parameter-bound and sensor-bound**: from outside evidence no family recovers the region (superstitious point fits); from inside, models pose the right topology but cannot pin its parameters to the gate’s precision — and the persistent-homology summary that guides them has a measurable resolution limit — geometric, not budgetary — that propagates its own wrong $\hat{\beta}_1$ into the certified artifacts. Planner-side mitigation obeys the same geometry: point distrust-fences, a zero-dimensional cover, fail against the one-dimensional closed boundary at their calibrated radius — while a fence matched to the boundary’s dimension and *persisted* across episodes collapses the exploitation to a two-lesson transient (`play_cost` 0.999 $\rightarrow$ 0.058, truth-equal returns from the second episode on). Against an *invented* mode every fence fires constantly and recovers nothing — and the dual certificate (freedom points that locally un-freeze imagination where the model was refuted as too pessimistic) collapses that failure symmetrically (1.769 $\rightarrow$ 0.029): the two wrongnesses need opposite defenses, each priced by its failure’s lie rate. In n dimensions the enclosing shell makes the identifiability event near-certain ($r(n) \rightarrow 0$) while the danger stays fully exploitable — rarity and reachability are independent knobs of the danger law.

1 Introduction

In the Code World Model (CWM) paradigm, a language model synthesizes an executable world model that a classical planner searches, and the model is accepted when it reproduces sampled transitions. Two companion papers established that this gate certifies the wrong thing, following a quantitative law, $\text{danger} = \text{play_cost} \times (1 - \text{rarity})^N$: in discrete games ([Aguilar Martín, 2026b](#)), and in continuous hybrid systems, where an omitted mode is a rare rule and the danger collapses to pure identifiability ([Aguilar Martín, 2026a](#)). The continuous paper ended on a sharpened negative: repair-from-data is geometry-dependent, and its two ablations located the mechanism in a *template*

prior — the synthesizer selects low-descriptive-complexity region forms (1D thresholds, radial balls) instead of inducing the boundary, flattening curves and curving flats alike. Curvature is not the axis. This paper takes up the axis that survived: **topology** — and shows that the right formulation is not the topology of the mode but its topology *relative to what the certifying process and the planner can reach*.

Why an enclosed mode? Because it is the minimal setting where the certification question and the topology question are the same question. An annular freeze band — a fence with an inside — is the simplest region whose defining feature, the hole, is invisible from one side: every trajectory that approaches from outside stops at the outer wall, and whether anything is behind it is, in a sense this paper makes exact, *not a property of the data at all*. Fences, containment shells, and geofenced no-go regions are the practical shape of safety-critical hybrid modes; a certification pipeline that cannot distinguish a fenced void from a fenced hazard — or a fence from a filled wall — is certifying less than it appears to. The question is what the gate’s acceptance actually pins down, and the answer turns out to be geometric: everything up to reach, nothing beyond it, with the boundary between the two movable by knobs that never touch the mode’s own physics.

The instrument is deliberately minimal (Section 2): a 2D thrust-and-drag plant with an annular freeze band (inner radius 3.5, outer 5.0) wrapping a high-reward “phantom” lode, with three pre-registered knobs — an angular channel of width γ (closed ring at $\gamma = 0$), the channel’s orientation (facing the start or hidden behind the lode), and the start side (outside or inside the hole). Everything the paper claims follows from what these knobs do to the *reachable query set* $\mathcal{R}$.

Contributions.

1. **The gate quotient and the unfalsifiable-and-harmless theorem** (Section 3). Acceptance-with-certainty determines a model exactly up to $\mathcal{R}$; beyond it is gauge (Proposition 1). On the closed ring, the wrong-topology filled-disc artifact is unfalsifiable by any sampling gate *and* bitwise planner-equivalent to the truth (Proposition 2, confirmed episode-for-episode). Monotonicity, continuity, and positivity of the rarity curves in γ round out the provable core (Section 3.1, stated and proved, one positivity witness machine-checked); the two monotonicity statements hold up to an explicit *funnel defect* (Corollary 2) that we bound by measurement, $17\times$ below the effect — unconditionally they are out of reach, and a measured certificate shows why no pathwise proof can exist (Remark 4).
2. **The three-regime mechanism, without LLMs** (Section 4). One artifact walks through unfalsifiable-and-harmless ($\gamma = 0$), falsifiable-and-costly (facing $\gamma > 0$), and instantly-falsified (inside start) as the knobs move. Two readings matter later: an *invented* mode is exploited *below random* from inside (play_cost 1.77 — the dual of phantom-free-space exploitation), and the hidden channel is observationally *identical* to the closed ring — same β_1 change, no observable consequence.
3. **LLM synthesis on the closed ring, three families** (Section 5). The identifiability event is family-independent (GPT-5.x, Qwen, Claude: every mode-absent sample yields a certified, blind, exploited model at play_cost ≈ 1.12). No family repairs the ring from outside evidence — a behavioral audit shows the gate-passing “repairs” are measure-zero point fits. From inside, models *pose* the right topology but repair is **parameter-bound**: the single certified recovery (1/20) used the gauge-free disc-complement form whose one parameter is the true round radius anchored in the reward specification — and the strongest cross-family repairer (Claude, 3/3) used exactly the same form.

4. **The open-ring arm: danger is topology relative to reach** (Section 6). Pre-registered sweep over γ : the blind model’s exploitation collapses over a knee at $\gamma \approx 0.1$ (channel arc-width comparable to the planner’s step) when the channel faces the start, and *persists at full strength* (1.116) at the same γ when the channel is hidden — identical β_1 , opposite danger. Gate-pass from inside stays ≈ 0 at every γ , and the two certified passes at wide γ are *certified-wrong*: mode-blind on the probes, harmless only because the open ring no longer obstructs.
5. **Mitigation obeys a covering law — and the defense that works pays it once** (Section 7). The companion paper’s distrust-fence defense, verbatim, does nothing on the ring at its calibrated radius: point fences are a zero-dimensional cover of a one-dimensional boundary, and the planner re-crosses through unfenced imagined corridors (cost = boundary measure over fence radius). Matching the fence’s dimension to the boundary’s (violations linked into tangentially-extended segments) *and persisting it across episodes* collapses the exploitation to a two-lesson transient: `play_cost` $0.999 \rightarrow 0.058$, with returns equal to the truth planner’s from episode 2 on — the fence engineers the blind model back into the truth’s gate-equivalence class on the operative side. Against the *invented* mode every distrust variant fires constantly and changes nothing — and the *dual* defense (freedom patching: un-freeze imagination, via the pinned integrator, where the model was refuted as too pessimistic) collapses that failure at once ($1.769 \rightarrow 0.029$, near-truth returns from episode 1). The two wrongnesses need opposite defenses, and each defense’s cost is set by its failure’s lie rate: false obstructions refute themselves at every step; false freedoms only at the rare boundary.
6. **The evidence sensor has finite resolution — and it propagates** (Section 8). The pre-registered persistent-homology summary reports $\hat{\beta}_1 = 1$ for every channel narrower than ~ 2 arc-units (flip at $\gamma \approx 1.8$) even though the true $\beta_1 = 0$ for all $\gamma > 0$; the posed artifact topology tracks the *guidance*, not the truth. An honest, finite-resolution sensor causes wrong-topology certified models. On the n -dimensional shell, inside-start evidence recovers β_{n-1} up to $n = 5$ where outside evidence recovers it at *no* n — recovery is start-governed, and the Niyogi–Smale–Weinberger density bound makes the outside failure computable in advance.
7. **Dimension as the rarity knob; the two axes are independent** (Section 9). On *ShellField- n* the contact rarity collapses geometrically ($r(n) \rightarrow 0$ by $n = 4$), making mis-synthesis near-certain, while a competent vector planner is exploited at `play_cost` ≈ 1.0 at *every* $n \leq 6$ — rarity (synthesis axis) and reachability (play axis) are independent knobs, and a high- n enclosed mode maxes out both.
8. **A behavioral audit methodology** (used throughout): probe each artifact’s `step()` on a state grid, classify the shape of its deviation-from-integrator set. It reproduces the companion paper’s hand inspection, reclassifies the inside-start failures, and separates “posed the wrong structure” from “posed the right structure with unidentifiable parameters.”

The practitioner’s summary is one sentence long: *a sampling gate certifies the reachable restriction of the model and nothing else* — so the safety question is never “is the model right?” but “does the place where it is wrong intersect the operative reach of a competent planner?” Everything in this paper — the harmless wrong topology, the danger knee, the hidden-channel persistence, the parameter-bound repairs, the sensor’s resolution limit — is that one sentence measured from six directions.

2 The instrument: a mode with an inside

RingField2D is the companion paper’s plant with one structural change. The state is (x, y, v_x, v_y) ; a scalar action $a \in [-a_{\max}, a_{\max}]$ maps to a thrust heading $\phi = \pi a / a_{\max}$; velocities integrate with gain 3.0 and drag 0.3 at $dt = 0.1$ (the same semi-implicit integrator family as PatchField2D, so every planner and every synthesis-protocol constant carries over unchanged). The reward is two radial sigmoid lodes: a small *real* one (amplitude 0.3) behind the start at $(-6, 0)$, and a large *phantom* one (amplitude 1.0) at $c = (12, 0)$. The structural change is the mode: an **annular freeze band** $A = \{r_{\text{in}} \leq \|p - c\| \leq r_{\text{out}}\}$ with $r_{\text{in}} = 3.5$ and $r_{\text{out}} = 5.0$, wrapping the phantom lode. A step whose next position lands in A freezes at the *previous* position with zero velocity — the same inelastic-stop semantics as the companion paper’s patches, but now the region has an inside: the ring separates the plane, and its defining feature ($\beta_1 = 1$, the hole) is exactly the part no outside observer ever touches.

Three pre-registered knobs deform the relationship between the mode and what is reachable, without touching the mode’s local physics:

- **Channel width** γ (radians): an angular gap cut from the ring. $\gamma = 0$ is the closed ring ($\beta_1 = 1$); any $\gamma > 0$ is an open C-shape ($\beta_1 = 0$, contractible).
- **Channel orientation**: centered facing the start (**gap_center** = π) or hidden on the far side (**gap_center** = 0). Both have identical topology at equal γ ; only the channel’s position relative to the start and the planner’s optimal path differs.
- **Start side**: outside the ring (the default; the interior is then unreachable at $\gamma = 0$, Lemma 1) or inside the hole (the interior evidence regime).

The defaults were frozen once at calibration and never tuned per cell: thickness $w = 1.5$ exceeds the maximal per-step displacement $\Delta \leq 1.0$ (Section 3), so the no-jump-over lemma holds with margin for real and imagined rollouts alike; the outside contact rarity at the defaults is $r = 0.045$ per rollout. The synthesis protocol is the companion paper’s, verbatim: $N = 40$ uniform-random rollouts as evidence and gate, the integrator pinned in the contract, exactness tolerance $\varepsilon = 10^{-9}$, at most 5 refine iterations, and **play_cost** the paired-seed normalized regret of planning on the artifact and executing in the truth. Section 9 generalizes the instrument to **ShellField- n** — the same two-lode geometry with a spherical shell S^{n-1} in the first two coordinates and a thrust-vector action $\vec{a} \in [-1, 1]^n$ (norm-capped) — so that the ambient dimension n becomes a fourth knob.

3 Theory: the gate quotient

Setup. Deterministic dynamics $f : S \times A \rightarrow S$ on $S \subseteq \mathbb{R}^d$, initial distribution μ_0 , episode horizon h , and a *gate policy* ρ selecting actions (uniform-random in our gates, though nothing below needs that). The **reachable query set** $\mathcal{R}(f, \mu_0, \rho, h)$ is the set of pairs (s, a) at which some length- $\leq h$ trajectory under (f, μ_0, ρ) queries f with positive probability — taken in continuous spaces as the support of the induced occupation measure. A *sampling gate* of any size N draws trajectories under (f, μ_0, ρ) and accepts a candidate $\hat{f}$ iff $\hat{f}$ reproduces every queried transition (within any tolerance, including exactly).

Proposition 1 (gate quotient). *Let $\mathcal{R}(f, \mu_0, \rho, h)$ be the reachable query set of the truth f under the gate policy ρ , and let $\hat{f}$ be any model with $\hat{f}|_{\mathcal{R}} = f|_{\mathcal{R}}$. Then for every N the sampling gate accepts $\hat{f}$ with probability 1, and the trajectory law of any policy whose queries stay in $\mathcal{R}$ is identical under f and $\hat{f}$. The set of models accepted with certainty is exactly the extension class $E(f) = \{\hat{f} :$*

$\hat{f}|_{\mathcal{R}} = f|_{\mathcal{R}}\}$; the complement $\mathcal{G} = (S \times A) \setminus \mathcal{R}$ is gauge freedom, unfalsifiable by any sample drawn under ρ .

Proof. By induction on the step index, a trajectory under (f, μ_0, π) whose queries lie in $\mathcal{R}$ is a trajectory under $(\hat{f}, \mu_0, \pi)$ with the same realizations: the state after step t is a function of μ_0 , the action sequence, and the queried values of f , which agree with $\hat{f}$'s on $\mathcal{R}$. Gate draws use $\pi = \rho$, whose queries lie in $\mathcal{R}$ by definition (up to a null set), so acceptance statistics coincide; $f \in E(f)$ is accepted almost surely, hence so is every member. $\square$

Remark 1 (relation to the companion identifiability proposition). The companion paper's identifiability result conditions on the finite-sample event “the mode region was missed,” of probability $(1 - r)^N \rightarrow 0$ when $r > 0$. Proposition 1 is its structural, N -independent limit: on $\mathcal{G}$ the miss probability is 1 for *every* N . The companion's prior caveat — a prior or the specification could still supply the mode — is exactly the statement that $E(f)$ is not a singleton.

Lemma 1 (metric crossing). *If positions move in steps of norm at most Δ and the annulus $A = \{r_{\text{in}} \leq \|p - c\| \leq r_{\text{out}}\}$ has thickness $w = r_{\text{out}} - r_{\text{in}} > \Delta$, then any trajectory from outside to the open interior visits A at an intermediate step. Consequently, at $\gamma = 0$ with freeze-on-entry dynamics the open interior is reach-null: the inner disc $\times$ all actions lies in $\mathcal{G}$.*

Proof. $g(t) = \|p_t - c\|$ changes by at most Δ per step (distance-to-center is 1-Lipschitz). Let t^* be the first index with $g(t^*) < r_{\text{out}}$. If $g(t^*) < r_{\text{in}}$ then $g(t^* - 1) \geq r_{\text{out}}$ forces a step longer than $w > \Delta$, a contradiction; so $p_{t^*} \in A$. Under the freeze semantics the first landing in A is replaced by the previous (outside) position with zero velocity, so g never drops below r_{in} ; induct. $\square$

At the frozen defaults the hypothesis holds with margin: speed obeys $\|v_{t+1}\| \leq (1 - \text{drag } dt)\|v_t\| + \text{gain } dt$, so $\|v\| \leq \text{gain}/\text{drag} = 10$ and $\Delta \leq 1.0 < w = 1.5$ — for real *and* imagined rollouts, since planners use the same integrator and action clamp. Measured: 200 calibration rollouts visit zero interior states while reaching the ring itself.

Corollary 1 (evidence equivalence of disc and annulus from outside). *From outside starts no landing ever falls at $d < r_{\text{in}}$, so the disc mode $\|p - c\| \leq r_{\text{out}}$ and the annulus mode fire on exactly the same steps of every realization: the contact processes — and hence all evidence any gate, repair loop, or topological summary extracts — are pathwise identical. (Measured as an exact row-for-row equality of the two contact clouds at every sample size.) The companion paper's dimensional reduction is rational given the evidence: outside data cannot even pose the disc-versus-annulus question.*

Remark 2 (metric, not topological — where algebraic topology is earned). Lemma 1 uses only that distance-to-center is 1-Lipschitz; it works verbatim for round shells S^{n-1} in $\mathbb{R}^n$ and needs no homology. Genuine algebraic topology is *earned* exactly where this proof dies: non-round separators (Jordan–Brouwer to even define “inside”) and non-separating modes (winding and linking obstructions — for the solid torus this is carried out in Section 9.1: the linking dichotomy). The round ring deliberately sits on the metric side of that boundary; the topology enters through what the gauge region and its boundary class organize, not through the crossing proof.

Proposition 2 (wrong topology: unfalsifiable and harmless at $\gamma = 0$). *Let f be the closed-ring dynamics and $\hat{f}_{\text{fill}}$ the filled-disc model (freeze on the whole disc $\|p - c\| \leq r_{\text{out}}$). Then (i) $\hat{f}_{\text{fill}} \in E(f)$: every sampling gate accepts it with probability 1; and (ii) any deterministic planner whose imagined rollouts start at real (outside) states produces identical real trajectories under $\hat{f}_{\text{fill}}$ and under f — $\text{play_cost} = 0$ exactly.*

Proposition 7 (query lower bound). *Let the planner select, at each real step, the first action of an imagined argmax over a candidate set $\mathcal{C}$ under the blind model. Assume (RG) every candidate whose imagined path enters the phantom basin $B(c, r_0)$ out-scores every candidate that stays outside $B(c, r_{\text{out}})$, and (C) $\mathcal{C}$ contains an entering candidate. Then the selected imagined path crosses the annulus (Lemma 1 applied to imagined paths), so the planner queries the disagreement region with probability 1: the companion paper’s play-cost upper bound is tight-side-active on this instrument.*

Proof. By (C) an entering candidate exists; by (RG) no non-entering candidate is the argmax; the entering path passes from outside r_{out} to inside $r_0 < r_{\text{in}}$ and Lemma 1 places one of its steps in A . (RG) is *checkable, not behavioral*: at the frozen defaults it holds with margin over the visited-state envelope and is verified numerically before every arm, in the pre-registration style of the discrete paper; (C) is logged. Measured: blind contact rate 1.0 at every γ . $\square$

The impossibility grades split cleanly: $r_{\text{int}}(0) = 0$ is *exact* (a theorem, measured 0.0000 at $n = 4000$), whereas the *hidden* channel at $\gamma > 0$ has $r_{\text{int}} > 0$ but of tube order ρ^h — positive yet below measurement at our budgets. These are two different *grades* of impossibility, and Sections 4 and 6 show the gate and the planner cannot tell them apart while behaving identically on both. The second grade now has an explicit **steering witness** (`scripts/ring2d_steering_witness.py`): a scripted waypoint policy that knows the hidden channel enters the interior in 100/100 episodes at hidden $\gamma = 1.2$ *within the instrument’s own horizon*, where the gate policy’s measured rate is 0/100 — and the same controller at $\gamma = 0$ enters 0/100, as the theorem requires. Certifiability is relative to the query policy ρ : $E(f)$ is defined by ρ ’s reach, and a policy that knows the channel shrinks the gauge region. (At hidden $\gamma = 0.6$ the narrower corridor defeats the *hand* controller — but a 10-parameter search over the same waypoint family finds a controller entering 100/100 within the same horizon, machine-checked. Reachability is jointly a property of geometry, policy, and budget, and the policy axis is cheap to search: what the gate policy cannot reach in 400 rollouts, ten tuned parameters reach every time.) **(d)** Under two checkable hypotheses — (RG), a reward gap making some channel-entering candidate dominate every non-entering one, and (C), candidate coverage — the blind planner’s imagined argmax path must cross the annulus, so the planner queries the disagreement region with probability 1: the companion paper’s play-cost upper bound is tight-side-active on this instrument. (RG) is verified numerically over the visited-state envelope before every arm, in the pre-registration style of the discrete paper; (C) is logged. Measured: blind contact rate 1.0 at every γ in calibration.

4 Mechanism without LLMs: three regimes, one knob

Before any LLM enters, the mechanism grid measures what the knobs do to a *fixed* pair of wrong artifacts: the mode-blind model (the ring deleted — the companion papers’ omission) and the filled-disc model of Proposition 2 (the wrong-topology invention). Each cell of $\gamma \times \text{channel} \times \text{start}$ runs 400 uniform-random rollouts (the gate-side falsifiability rates) and 16 paired-seed MPC episodes per artifact (the play side).

Three readings organize the grid. **First, the three-regime walk is real.** The same filled-disc artifact is unfalsifiable and costless at $\gamma = 0$ (disagreement rate 0, $\text{pc}_{\text{fill}} = 0$ — the bitwise theorem observed), falsifiable at rate $\sim 10^{-3}$ /transition and costly through a facing channel (pc_{fill} 0.343/0.220), and instantly falsified from inside (disagreement 0.77–0.97). One artifact, three certification regimes, two knobs.

Second, an invented mode is exploited below random from inside. $\text{pc}_{\text{fill}} = 1.769$ at $\gamma = 0$, inside start: the filled disc hallucinates freezes everywhere near the lode the agent already




Figure 1: The γ -curves, measured with common random numbers (4,000 CRN rollouts per point; Wilson 95% CIs): the contact rarity $r(\gamma)$ is nonincreasing (pathwise theorem; 0 violations observed) and the interior-entry rate $r_{\text{int}}(\gamma)$ rises from its *exact* zero at $\gamma = 0$ (Lemma 1) — the two grades of impossibility are visible as the difference between a point pinned at zero by a theorem and a curve passing through measurably positive values.

sits on, so all imagined returns tie and the planner drifts *off* the reward. This is the dual of the companion papers’ lure: an omitted mode pulls the planner into danger; an invented one repels it from value, just as destructively.

Third — the thesis, pre-LLM — policy-relative reachability beats topology. The hidden-channel rows are observationally *identical* to the closed ring at every tolerance (interior entries 0, disagreement 0, pc_{blind} 0.999, pc_{fill} 0.000) although the channel changes the free space’s connectivity; with the *facing* channel — same topology — everything changes. What certificates and play see is the mode’s position relative to the operative reach. Note the two grades of impossibility beneath the identical observations: the closed interior is reach-null *exactly* (a theorem), the hidden channel’s interior is reachable at positive-but-unmeasurable rate; Section 6 returns to this pair with the danger curve.

5 LLM synthesis on the closed ring: three families

The synthesis arm runs the companion paper’s protocol verbatim (Azure GPT-5.x mini and large, 20 seeds/cell, $N = 40$, $\varepsilon = 10^{-9}$, ≤ 5 refines) on four pre-registered cells of the closed ring: **A** (default prompt, outside start), **B** (region-first guidance, outside), **C** (guidance plus a per-seed topological summary of the sample’s own contact evidence, outside), and **D** (the same summary, *inside* start). Because a filled disc at $\gamma = 0$ passes every metric (Proposition 2), code-level claims need more than the gate; the audit below is used for every artifact in the paper.

5.1 The behavioral audit (methodology)

Textual inspection of synthesized code misleads in both directions: a verbose “trap” comment can be measure-zero (behaviorally blind), and a plausible-looking region clause can be wildly misparameterized. The audit therefore classifies each artifact by what its `step()` *does*: probe it on

cell	prompt / start	pass	present	blind ref	terminal classes (behavioral)
A _{lg}	default / out	6/20	14	0.999	fill-unbounded 13, blind 7
A _{mi}	default / out	6/20	14	0.999	blind 15, arc 2, disc 2, fill-unb. 1
B _{lg}	region / out	8/20	14	0.999	blind 16, arc 2, disc 1, point 1
C _{lg}	tda / out	9/20	14	0.999	blind 19, vdep 1
C _{mi}	tda / out	12/20	14	0.999	blind 17, arc 2, point 1
D _{lg}	tda / inside	1/20	20	0.971	arc 5, point 4, blind 4, disc 2, compl. 2, loop 2, vdep 1
D _{mi}	tda / inside	0/20	20	0.971	disc 5, loop 5, arc 5, blind 4, compl. 1

Table 2: GPT-5.x on the closed ring ($\gamma = 0$; lg = large, mi = mini; the two sizes share seeds, so their samples — and the mode-present counts — are identical by construction, not independent replications). “Blind ref” is the pure integrator’s gate on the same evidence: the interpretive baseline for terminal gates. Every gate pass in A–C is a mode-absent blind artifact (exploited at play_cost ≈ 1.12) or a measure-zero point fit; the one D pass is the gauge-free complement form. Cross-family spot checks (3 seeds each): Qwen — both mode-absent seeds certified blind and exploited at the same 1.116, the mode-present seed refused by the gate; Claude (agent-relayed) — same A-cell outcome bit-for-bit, and 3/3 D-cell repairs via the same complement form as the GPT passer.

sharp: the gate-passing mode-present artifacts in B and C are *textual point fits* — integrator plus a comment hypothesizing a tiny localized trap and an exact-coordinate snap at 10^{-12} tolerance — whose freeze-mask is empty: behaviorally blind (wall_blindness = 1.0), exploited like the pure blinds. This is Corollary 1 operating: from outside, ring and disc evidence are pathwise identical, so the honest summary can only report the reachable arc, and it does not pose the hole. Notably, richer prompting made the *terminal* attempts less geometric, not more: the default prompt’s failing terminals are half-plane templates (13/14 mode-present, large), while region/summary guidance pushed terminals toward point fits and blinds (16–19/20).

From inside, repair is parameter-bound, not structure-bound. The D cell inverts the failure mode. With inside evidence and the loop-reporting summary, models *pose* geometric mode structure in most cells — mini: 5 filled discs, 5 hollow loops, 1 complement, 5 arcs of 20 — yet 0/20 pass (large: 1/20), and the terminal gates average 0.56, far *below* the 0.971 blind reference: a posed region with wrong parameters over-freezes states the evidence shows free. The bottleneck is not posing the topology (the guidance says loop and the models comply) but pinning its parameters to 10^{-9} from landing evidence. A dose curve makes this precise: re-running the D cell with $8\times$ the evidence ($N \in \{40, 80, 160, 320\}$ rollouts, 20 seeds each) yields 0/20 gate passes at *every* dose, with the posed structures’ median inner-radius error pinned at 0.5 throughout — that is, the median artifact poses $r = 4.0$, a *round number*, whether it has seen 40 rollouts or 320. The parameter is not estimated from the evidence; it is guessed from the template library, so evidence dose cannot buy repair — the synthesis-side twin of Section 8’s dose-independence.

The separator ablation: a square ring. Replacing the Euclidean norm by the Chebyshev norm turns the annulus into a square ring (zero curvature, corners) while the crossing lemma survives verbatim (Chebyshev distance is 1-Lipschitz with respect to Euclidean steps; reach-null and the bitwise Proposition 2 equivalence re-verify on the square). Every quantitative finding is norm-invariant: mode-absent samples yield certified blind artifacts exploited at 1.117; inside repair is 0/20 with structures posed in 15/20. The shape of what is posed is not: of the 12 posed closed structures on *square* evidence, 11 are round (freeze-boundary corner ratio ≈ 1.0 against the square’s

$\sqrt{2}$) and 12/12 are written with **hypot** — zero use the truth’s **max/abs** form. The companion paper’s bidirectional template prior, measured there on small patches, reaches the enclosing separator itself: the topology axis and the template-prior axis compose, and the certified artifact’s *shape* comes from the prior even when its *topology* comes from the guidance. The D failures are not template-prior collapse: the behavioral audit classifies them as right-structure-wrong-parameters, which is a different failure mode.

How the one passer passed. The single certified D recovery (large, 1/20) freezes exactly when the post-integration landing has $\|p - c\| \geq 3.5$: the *disc-complement* form. It is certified perfect (gate 1.0, blindness 0.0, play_cost 0.0) although its outer boundary is wrong — from inside, the probe freezes at the inner boundary and never reaches the outer one, so the complement is indistinguishable from the annulus on $\mathcal{R}$: the outer boundary is **gauge** (Proposition 1), and the artifact’s comment even cites the summary’s “closed loop ($\beta_1 = 1$).” Its single load-bearing parameter is the true inner radius — a *round number* anchored at the center that the contract’s reward section already names. The strongest cross-family repairer (Claude, agent-relayed context-free, 3/3 D repairs) wrote exactly the same form. Gate-pass from inside therefore measures a conjunction — (*reachable-equivalent structure*) $\times$ (*exact-parameter guessability*) — not topology-understanding alone; Section 6 exploits this by moving the true parameters off round values.

6 The open-ring arm: danger is topology relative to reach

The registered arm sweeps γ with three pre-registered hypotheses: **H1**, the blind model’s exploitation collapses with a facing channel and persists with a hidden one (danger is reachability, not β_1); **H2**, posed artifact structure tracks the guidance’s reported topology (Section 8); **H3**, gate-pass from inside stays ≈ 0 at every γ because the channel-edge angles $\pi \pm \gamma/2$ are not round-guessable. Cells: outside/default at $\gamma \in \{0.05, 0.1, 0.2, 0.4, 0.6, 1.2\}$ facing (20 seeds mini) and $\{0.6, 1.2\}$ hidden (10); inside/summary at $\{0.2, 0.6, 1.2, 1.8, 2.4\}$ (20–30); large robustness cells at the critical points; a dense CPU danger curve (16 paired MPC episodes per γ); and Claude relay spots at the knee and at wide γ .

γ	0.0	0.02	0.05	0.1	0.15	0.2	0.4	0.6	1.2
pc _{blind} (facing)	0.999	0.543	0.340	0.139	0.001	0.015	0.023	0.022	0.007
contact rate	1.00	0.94	0.56	0.44	0.12	0.06	0.00	0.00	0.00

Table 3: H1, the danger curve (CPU, 16 paired MPC episodes/point): the blind model’s exploitation collapses over a knee at $\gamma \approx 0.1$ — channel arc-width $\gamma r_{\text{in}} \approx 0.35$, comparable to the planner’s step. The *hidden* channel holds pc = 1.116 at $\gamma = 0.6$ and 1.2: same β_1 , opposite danger. LLM-arm confirmations at $\gamma \in \{0.1, 0.6\}$ reproduce the curve in both model sizes and in the Claude relay (0.348 at the knee, all three families); Figure 2 plots all three series.

H1 confirmed — with the clincher. The facing curve collapses over a knee at $\gamma \approx 0.1$ –0.15; the LLM cells reproduce it on their exploited blind artifacts in both sizes and in the Claude relay (0.348 at the knee in all three families — the play number is the blind program’s, family-independent by construction). The *hidden* channel at the same γ holds play_cost = 1.116 — full strength, unchanged from the closed ring. Same $\beta_1 = 0$, opposite danger: what collapses the danger is the competent planner’s reachability of the omission, not the topology change. The mechanism




Figure 2: **H1: danger is topology relative to reach.** The blind model’s exploitation collapses over a knee at $\gamma \approx 0.1$ when the channel faces the start (blue: dense CPU curve, 16 paired MPC episodes per point; green: the LLM arms’ exploited blind artifacts, identical in all three model families) — while the *hidden* channel (orange) holds full danger at the same γ and the same $\beta_1 = 0$. The knee sits where the channel’s arc width admits the planner’s step.

is the gate quotient on the play side: as the channel opens where the planner drives, the phantom stops being phantom — the blind plan (straight at the lode) becomes *executable in the truth*, so blind and truth agree along the operative path exactly as $E(f)$ -members agree on $\mathcal{R}$. The knee sits where the channel’s arc width ($\gamma r_{\text{in}} \approx 0.35$ at $\gamma = 0.1$) admits the planner’s step.

H3 confirmed — certified passes are not repairs. Inside gate-pass rates across γ : 1/40, 0/20, 0/40, 0/20, 1/30, 1/40 — essentially zero everywhere, both sizes, with terminal gates far below the blind reference (structures posed, parameters unpinnable: the channel edges are not round numbers). The sharpest datum is the strongest repairer’s: at $\gamma = 2.4$ the Claude relay *reconstructs* “ring $r = 3.5$, gap 2.4rad” from the sample and passes the gate in 2/3 seeds — with mode blindness 1.0 and play_cost 0.0. The passing models match the sample through wrong parameters, fail the mode probes, and are harmless only because the wide-open ring no longer obstructs anything. Certification, correctness, and consequence come apart again (Remark 3), now with real synthesis.

The identifiability axis moves independently alongside. As γ grows the ring shrinks and the mode-absent rate rises (6 $\rightarrow$ 16 of 20 over the sweep): the synthesis axis (does the sample contain the mode?) and the play axis (does the omission obstruct the planner?) are separate knobs even within one instrument — the theme Section 9 pushes to its extreme.

7 Mitigation against an enclosed mode: a covering law

The companion continuous paper closed its loop with a planner-side defense: *distrust-region replanning*. After each real step the planner compares the model’s prediction to the observation; a mismatch records a point *fence* at the refuted prediction, and imagined rollouts truncate when they cross near a fence — on the 1D clamps and the small convex patches this collapses the blind planner’s exploitation to a bounded first-contact transient, at zero cost when the model is correct. The same module, verbatim (`pos_dims` = (0, 1), the patch-calibrated fence radius $\varepsilon_f = 0.5$), meets the ring:

cell	ε_f	pc _{model}	pc _{mitigated}	contact	fences/episode
closed ring, outside, blind	0.5	0.999	1.003	1.00	3.8
closed ring, outside, blind	1.0	0.999	1.005	1.00	2.3
closed ring, outside, blind	2.0	0.999	0.742	1.00	1.0
hidden $\gamma = 0.6$, outside, blind	0.5	0.999	1.003	1.00	3.8
closed ring, <i>inside, filled</i>	0.5	1.769	1.769	1.00	18.6
nerve fence, episodic	0.5	0.999	0.957	1.00	2.0
nerve fence, persistent	0.5	0.999	0.058	0.06	0.1
freedom patch (inside, filled)	0.5	1.769	0.029	—	80

Table 4: Distrust-region replanning on the ring (16 paired MPC episodes per cell). Point fences — the defense that collapsed the patch exploitation — do *nothing* at their calibrated radius, partially relieve only at a radius of the geometry’s own scale, and are exactly inert against the invented mode while firing constantly (18.6 fences per episode, pc unchanged to three decimals). The hidden-channel row is identical to the closed ring, as Section 4 predicts. The last two rows are the constructive turn: a *nerve* fence (violations linked into tangentially-extended segments) still fails episodically, and collapses the exploitation once fences *persist* across episodes — two lessons total (episode 1), truth-equal returns ever after.

The failure is a covering law. A point fence is a zero-dimensional object; the ring’s reachable boundary is one-dimensional (the west outer arc, ~ 16 world-units at the defaults). Sealing a 1-dimensional boundary with ε_f -balls needs covering-number-many violations — boundary measure over fence radius — and the argmax planner concedes only 2–4 contacts per episode while re-routing through unfenced arc. The companion paper’s “collapse decays with mode distance” was the small-boundary shadow of this law: on a patch of circumference ~ 6 at $\varepsilon_f = 0.5$ a handful of fences suffices; on the ring they never do. Coarsening the fence to the geometry’s own scale ($\varepsilon_f = 2.0$) buys partial relief here but is not a uniform remedy — that radius would swallow the patch instruments whole. The structural fix is dimensional — and it works, but only jointly with persistence. A *nerve* fence links violations into segments and extends them 3 units along the estimated boundary tangent (two violations 0.5 apart already fix the local direction). Episodically it still fails (pc 0.957): a single episode concedes only ~ 2 lessons, and instrumentation shows the planner simply re-crosses the wall *in imagination* beyond the sealed corridor — the blind model lets any unfenced crossing through, so the agent slides along the boundary at one freeze per lesson. Persisting the fences across episodes (deployment monitoring rather than per-episode defense) changes the accounting: the boundary’s covering cost is paid *once*. Measured: 2 violations in episode 1 (return 1.01), then **zero** violations and returns equal to the truth planner’s in every one of episodes 2–16 (17.04 vs 17.04, ...); aggregate pc $0.999 \rightarrow 0.058$, contact rate $1/16$. The mechanism is Proposition 1 run

in reverse: the extended fence reconstructs enough of the boundary that the blind model *plus its fence memory* becomes planner-equivalent to the truth on the operative side — certification could not distinguish members of $E(f)$, and the defense engineers the planner back into it. This is theorem-backed under checkable hypotheses:

Proposition 8 (fence sufficiency). *Suppose (COV) every segment of length $\leq \Delta$ crossing the reachable outer boundary arc of A passes within ε_f of the fence set, and (RG-west) the best non-crossing candidate’s imagined return exceeds every crossing candidate’s pre-crossing return plus its tie-break advantage (at the defaults: ≈ 2 versus ≤ 0.1 , checkable over the visited envelope). Then every crossing candidate truncates at or before its crossing; every non-crossing candidate scores identically under truth imagination and fenced-blind imagination (the models agree off the band, and truth imagination freezes only on crossings); and the argmax coincides. The mitigated planner is the truth planner: $\text{play_cost} = 0$ exactly.*

Episode 1 is the learning transient the proposition does not (and should not) cover: (COV) is established *by* its two lessons. And (COV) is policy-payable by three routes, measured head-to-head (all persistent): fence *geometry* (the tangential extension: 2 lessons, pc 0.058), *exploration* (a boundary-tracing probe collects 50 lessons in one episode — plus 11 patch-ups, since its 1.05-unit spacing left sub- ε_f gaps: the covering law bites the prober too — pc 0.123), and *passivity* (the planner’s own contacts, 9 lessons spread over 16 episodes, pc 0.152 with occasional regressions). Persistence is the ingredient common to everything that works; geometry beats exploration beats waiting. The fence is itself an estimated boundary, i.e. the same object as Section 8’s evidence summaries, and inherits the same resolution limits.

Against an invented mode, distrust is inert by construction. The filled-disc model from inside (the below-random cell of Section 4) hallucinates freezes everywhere, so every imagined future collapses to the current position and all candidate actions tie *before* any fence can matter; truncating trust in imagined value cannot help when the lie has already flattened imagined value. The fences fire constantly (18.6 per episode — the defense *detects* the lie every few steps) and change nothing (pc identical to three decimals). Distrust-based mitigation is one-sided in exactly the sense the danger is two-sided: it can stop the planner from *believing* false free space, but recovering value that the model hides behind false obstructions needs the *dual* certificate. We built it: **freedom patching** records, at each real step where the model predicted a freeze and the truth moved, a freedom point; during imagination, a model step that freezes within ε_f of a freedom point is replaced by the contract’s own pinned integrator (mode-free, legitimately known to the pipeline). On the same cell this collapses the below-random exploitation at once: pc $1.769 \rightarrow 0.029$ episodic (0.021 persistent), with near-truth returns from *episode 1*. The asymmetry of the two defenses’ costs is itself the finding: an invented mode *lies at every step* (80 freedom certificates per episode — it refutes itself constantly, so within-episode patching suffices), while an omitted mode lies *rarely* (2 lessons per episode — so its fence must persist to ever pay the covering cost). The dual result is theorem-backed the same way:

Proposition 9 (patch sufficiency). *Let $\hat{f}$ freeze on a region B where f moves freely, and suppose (CERT): every point of B visited by any candidate’s imagined path from the current real state lies within ε_f of the freedom-certificate set. Then patched imagination equals truth imagination for every candidate (off B the models agree; on the certified part of B the patch substitutes the pinned integrator, which is f there), so the argmax coincides with the truth planner’s and $\text{play_cost} = 0$ exactly.*

From inside, every step yields a certificate (the model lies each step — the lie rate is the occupation of the disagreement region under the operative policy), so (CERT) holds within one episode’s prefix; the measured 0.029 is that prefix. The omitted-mode lure and the invented-mode repulsion (Remark 3’s two wrongnesses) need *opposite* planner-side defenses; a defense calibrated for one is inert against the other; and each defense’s price is set by its failure’s *lie rate*.

8 The evidence sensor has finite resolution

The C and D cells’ guidance includes a pre-registered *topological summary* of the sample’s own contact evidence: an honest, shape-agnostic text (never naming a shape family, wording frozen before any run) reporting cluster count, bounding box, and a persistent $\hat{\beta}_1$ from a Rips complex on the deduplicated landing cloud (grid 0.05, cap 90 points, bars above $3\times$ the median nearest-neighbor spacing). The summary is a *sensor*, and sensors have resolution: measured on regenerated inside evidence, the detector reports $\hat{\beta}_1 = 1$ for every $\gamma \leq 1.2$ — it bridges any channel narrower than about two arc-units at this density — flips seed-dependently at $\gamma = 1.8$, and is cleanly 0 at 2.4; the true β_1 is 0 for every $\gamma > 0$. The sweep therefore manufactures, at no extra cost, the experiment H2 needs: gaps where guidance and truth disagree, one gap where guidance disagrees with itself across seeds, and gaps where they agree.

The resolution limit is geometric, not budgetary. A factorial over the detector’s budget and the evidence dose (`scripts/ring2d_sensor_resolution.py`: $\text{cap} \in \{30, 90, 270\}$ points $\times$ evidence $N \in \{40, 160\}$ rollouts $\times \gamma$, five seeds each) shows the flip does not move: $\hat{\beta}_1 = 1$ at every $\gamma \leq 1.2$ under *every* budget and dose, 0 at 2.4 under all of them, with only the boundary gap 1.8 wobbling. The mechanism is Rips geometry, and it can be written as a law: the detector reports $\hat{\beta}_1 = 1$ exactly when $\sqrt{3}\rho - 2\rho \sin(\Delta\theta_{\max}/2) > \tau$, where ρ is the cloud’s mean radius, $\Delta\theta_{\max}$ the *largest angular gap of the sample* (the channel or a subsampling gap, whichever is larger), and τ the detector’s persistence threshold — the bar is born exactly at the largest gap’s chord (proved: a winding cycle must contain an edge spanning every angular gap), cannot die before $\sqrt{3}r_{\min}$ (proved self-containedly: below that scale every triangle’s boundary has winding zero, so winding obstructs filling), and dies by $2r_{\max} \sin(\theta^*/2)$ with an explicit θ^* (the filling lemma, proved: an explicit gap-aware spanning triangle of winding one plus a fan retraction exhibit the 2-chain that bounds the born *class* — no general filling machinery needed — and a pairing lemma transfers the sandwich from the class to the *bar* whenever exactly one bar spans $[2r_{\max} \sin(\Delta\theta_{\max}/2), \sqrt{3}r_{\min})$, a rank condition read off the barcode and true in every factorial row; $\theta^* \rightarrow 2\pi/3$ for dense samples, recovering the Vietoris–Rips circle constant (Adamaszek and Adams, 2017), and the measured death/ $\bar{\rho} \in [1.70, 1.82]$ around $\sqrt{3} = 1.732$ is the radial thickness). The law is therefore *two-sided*: $\hat{\beta}_1 \geq 1$ is guaranteed when $\sqrt{3}r_{\min} - 2r_{\max} \sin(\Delta\theta_{\max}/2) > \tau$, and no persistent winding bar exists when $2r_{\max} \sin(\theta^*/2) - 2r_{\min} \sin(\Delta\theta_{\max}/2) < \tau$ (only a spurious non-winding class could still fire — never observed). On the factorial: the sandwich holds for 57/57 winding bars, the guaranteed bands have 0 violations (34 and 5 rows), and the pointwise law reproduces 78/80 rows, the 2 misses falling in the proved undecided band ($\gamma = 1.8$ boundary, subsampling-gap lottery). Worse, more evidence is counterproductive at the boundary: at $\gamma = 1.8$ the false-loop rate *rises* from 1/5 to 3/5 seeds when the dose quadruples, because the persistence threshold ($3\times$ median nearest-neighbor spacing) shrinks with density while the spurious bar’s absolute persistence stays fixed — the sensor gets *more confident* in the wrong topology as the data grows. Resolving a narrow channel requires a different filtration, not a bigger sample. A prototype confirms the direction and locates the real problem: censoring Rips edges that free trajectory segments properly cross restores specificity at

every $\gamma > 0$ (19/20 versus 0/15 for plain Rips at $\gamma \leq 1.2$) at a sensitivity cost at $\gamma = 0$ (2/5 true loops lost). But edge deletion has a topological pathology with a clean characterization: a censored filtration stabilizes at the flag complex of the censor-complement graph, so *never-fillable cycles* (infinite H_1 bars, impossible for plain Rips) are exactly that complex’s H_1 — per-sample decidable by one finite computation. Running that certificate on all cells finds the pathology is real and *semantically ambivalent*: the same mechanism carries the true $\gamma = 0$ loops (their fills cross the certified-free hole, so the correct loop gets infinite confidence) and the prototype’s single false positive at $\gamma = 0.6$, which turns out to be a structural never-fillable cycle, not a near-threshold bar.

Edge deletion is therefore the wrong primitive, and the principled replacement is *relative* homology of the pair $(VR(X \cup Y), VR(Y))$, contact evidence X against certified-free evidence Y . Two things make it the right object. It cannot produce infinite bars at all — both complexes are full simplices past the diameter, so every relative class dies — and by the long exact sequence its rank is $\text{rank ker}(H_0(VR(Y)) \rightarrow H_0(VR(X \cup Y)))$ whenever the union has trivial H_1 : *the number of certified-free components that the contact evidence glues together*, computable by two union-finds rather than a matrix reduction. One instantiation detail is load-bearing: Y must enter as trajectory *polylines*, not as a point cloud. A free trajectory certifies passage between its own consecutive samples; discard that and the estimator reports separation almost everywhere, because a curve-dense contact cloud glues a scatter-sparse free cloud by density mismatch alone. With paths, the estimator is correct on 20/20 open-ring cells where the pre-registered detector scores 9/20, with no censoring and no infinite bars. At $\gamma = 0$ it does not fire, for two reasons we keep separate: with one-sided (inside) evidence the interior is reach-null, nothing outside is sampled, and separation is *unidentifiable by any estimator* — Proposition 1 asserting itself, with plain $\hat{\beta}_1$ scoring well there only because it answers a different question (the cloud’s shape, not the separation it induces). With two-sided evidence the obstruction is different and, we think, more interesting: freeze semantics resets the velocity on contact, so after the first freeze the next proposed landing moves only gain $\cdot dt^2 = 0.03$ from rest and the trajectory *creeps along the face* instead of penetrating. Contact evidence therefore occupies two thin shells at the band’s faces and never its interior, which caps the informative bar at the shell thickness while the persistence threshold grows with sample size as the shells fill in. Measured at 40/120/320 rollouts per arm: shells saturate at $[3.50, 3.71]$ and $[4.83, 5.00]$, bar length 0.160/0.197/0.253 against $\tau = 0.183/0.324/0.439$ — sub-threshold at every size, with the gap *widening*. So no recalibration recovers $\gamma = 0$: the limit is in the evidence, not the rule, and more data makes it worse. The same one-step landing law that makes the continuity modulus explicit (Proposition 4) is what caps the sensor here. Only the interleaving-stability theorem, which the pair formulation makes routine, remains. Nested boundaries break the detector a third way: with two concentric rings (the multi-chamber instrument) the middle-chamber evidence cloud is two concentric circles ($\beta_1 = 2$), and the pre-registered detector returns a seed-dependent *lottery* — $\hat{\beta}_1 = 0$ on 9/20 samples, 1 on 10/20, the true 2 on 1/20 — as Rips bridges between the circles merge or kill loops at this density. The synthesis side is correspondingly worse than the single ring: 0/20 gate passes and *zero* artifacts pose a nested (two-band) structure — 13/20 pose single arcs hugging one boundary. Certification peels one boundary layer per start placement (Proposition 1); the repair loop, at this depth, does not even *pose* layer two.

H2: the artifacts follow the sensor. Closed structures dominate exactly while the summary says “closed loop” and *vanish* where it honestly says “arc” (Table 5: 1 closed versus 26 arc at $\gamma = 2.4$, both sizes); the crossover tracks the detector flip, not the true β_1 . The within-gap contrast at $\gamma = 1.8$ — seeds of the *same* environment whose own summaries straddled the flip — is directionally consistent (closed structures appear only in the $\hat{\beta}_1 = 1$ subset) though underpowered at

γ	0.0	0.2	0.6	1.2	1.8	2.4
closed structures (disc/loop/complement)	17	9	22	7	5	1
arc structures	10	5	6	9	34	26
n (cells; both sizes where run)	40	20	40	20	60	40
guidance $\hat{\beta}_1$	1	1	1	1	mixed	0

Table 5: H2: posed artifact topology tracks the *guidance’s* $\hat{\beta}_1$, not the true β_1 (which is 0 for every $\gamma > 0$): closed structures dominate while the summary says “closed loop” and vanish where it honestly says “arc” — at $\gamma = 2.4$, 1 closed versus 26 arc across both sizes. n counts inside-start cells (mini at every γ ; large twins at 0.0, 0.6, 2.4). The within-gap contrast at $\gamma = 1.8$, where seeds’ own summaries straddle the detector flip, remains directional-only after doubling the cell to $n = 60$: closed structures 3/27 in the $\hat{\beta}_1 = 1$ subset versus 2/33 in the $\hat{\beta}_1 = 0$ subset — consistent in sign, not significant; the load-bearing H2 evidence is the cross-gap crossover.

$n = 30$. The conclusion is uncomfortable and, we think, general: **an honest evidence summary with finite resolution causes wrong-topology certified models**. The repair loop’s topology channel is only as good as the sensor’s resolving power at the operative sampling density.

The same law governs the sensor directly in n dimensions. On ShellField- n (Section 9), persistent homology of the *outside* contact cloud recovers β_{n-1} at *no* $n \in \{2..6\}$ — at low n the cloud is plentiful but traces only the reachable arc (signal clarity), at high n it starves as $r(n)$ collapses ($0.2\times$ to $0.003\times$ the Niyogi–Smale–Weinberger covering density (Niyogi et al., 2008)) — while the *inside* cloud recovers it cleanly at $n = 2..5$ (marginal at 6, via 2-plane slices), with densities $10\text{--}2700\times$ the NSW floor. Recovery is start-governed: reachability again, now for the sensor itself. We flag the program-level statement this suggests, as a conjecture and not a result: *the topology a certified repair loop can recover is bounded by the persistent-homology resolution of its contact evidence at the operative density* — a bound that NSW-style estimates make computable in advance.

n	outside start			inside start		
	contacts	$\times\text{NSW}$	$\beta_{n-1}?$	contacts	$\times\text{NSW}$	$\beta_{n-1}?$
2	388	30.9	✗	33,702	2682	✓
3	167	2.6	✗	45,697	714	✓
4	59	0.20	✗	54,170	180	✓
5	11	0.008	✗	59,961	43.9	✓
6	18	0.003	✗	63,949	10.6	(marginal)

Table 6: Persistent homology of the ShellField- n contact cloud (20,000-rollout budget; alpha complexes, 2-plane slices at $n = 6$). “ $\times\text{NSW}$ ” is the cloud density relative to the Niyogi–Smale–Weinberger covering bound. Outside evidence never recovers the shell’s β_{n-1} — at low n the cloud is plentiful but traces only the reachable arc; at high n it starves — while inside evidence recovers it up to $n = 5$. Recovery is start-governed.

9 Dimension as the rarity knob

ShellField- n keeps the two-lode geometry and places the freeze band on a spherical shell S^{n-1} around the phantom lode (both lodes in the first two coordinates, so n is the only knob); the action becomes a thrust vector $\vec{a} \in [-1, 1]^n$, norm-capped. Two facts scale in opposite directions. The gate-side rarity $r(n)$ collapses geometrically — so by $n \geq 3$ the identifiability event is near-certain: **n is a rarity knob**, and the mode is almost never in the sample. The play side does not collapse: truth-MPC still reaches the real lode at every $n \leq 6$ (the planner is not the bottleneck), and the blind model is exploited at full strength at every n (Table 7).

What sets the collapse rate: solid angle. The mechanism is not variance concentration but direction. Reaching the shell from x_0 forces the displacement into the *tangent cone* to $B(c, r_{\text{out}})$: if $\|x_t - c\| \leq r_{\text{out}}$ then $\langle x_t - x_0, e \rangle \geq \kappa \|x_t - x_0\|$ with e the unit vector to the centre, $L = \|c - x_0\|$ and $\kappa = \sqrt{L^2 - r_{\text{out}}^2}/L$ (expand $\|Z - Le\|^2 \leq r_{\text{out}}^2$ and apply AM–GM). The thrust’s coordinates are exchangeable and sign-symmetric, and so is any independent weighted sum of them; since at most $2/\kappa^2$ coordinates of any vector can each carry a $\kappa^2/2$ share of its squared norm, exchangeability alone gives $P(\langle Z, e \rangle \geq \kappa \|Z\|) \leq 4/(n\kappa^2)$ and hence $r(n) \leq 4h/(n\kappa^2)$ — an explicit bound with no concentration inequality in it. The truth is faster: measuring the cone event over 10,000 rollouts per dimension gives a clean exponential (log-linear $R^2 = 0.999$ versus log-log 0.952) at per-dimension factor 0.411, against the isotropic spherical-cap prediction $\sin \theta = r_{\text{out}}/L = 5/12 = 0.4167$ — agreement to 1.5%. So the collapse rate is the mode’s *angular size from the start*, $r(n) \asymp (r_{\text{out}}/L)^n$, and nothing else: not its volume, not its thickness, not the horizon. The exponential law is moreover a *theorem* once the action interface is chosen well. If the thrust direction is uniform on S^{n-1} , the displacement is a sum of independent spherically symmetric vectors, hence spherically symmetric, so its direction is exactly uniform and the cone probability is exactly a spherical cap; with the elementary bound $P(\langle U, e \rangle \geq \kappa) \leq \frac{1}{2}(1 - \kappa^2)^{(n-2)/2}$ this gives

$$r(n) \leq \frac{h}{2} (r_{\text{out}}/L)^{n-2} = 40 \cdot 0.4167^{n-2} \quad \text{at the defaults,}$$

non-vacuous from $n \approx 7$ against $n \approx 400$ for the exchangeability bound, and verified at $n = 3 \dots 8$ (simulated decay 0.431 against the predicted 0.4167).

The instrument’s own thrust is cube-uniform and norm-capped, whose symmetry group is finite, so that argument does not apply to it — but a different structure does, and it gives the *sharp* rate. The norm cap depends only on the absolute values of the action, and the action’s coordinates are independent and symmetric; hence conditionally on all absolute values the signs are i.i.d. Rademacher and the displacement coordinates are *independent*, each a Rademacher sum with deterministic weights. (Exactly so: flipping one sign changes its own coordinate and no other, bitwise.) Independence replaces symmetry: since the cone event forces $\sum_{i \geq 2} Z_i^2 \leq \gamma^2 Z_1^2$ with $\gamma^2 = (1 - \kappa^2)/\kappa^2$, a single Chernoff bound with matched exponent gives $P \leq E[e^{\lambda \gamma^2 Z_1^2}] \prod_{i \geq 2} E[e^{-\lambda Z_i^2}]$, and optimizing λ in the Gaussian regime returns $\sqrt{en/(1 + \gamma^2)} (1 - \kappa^2)^{(n-1)/2}$: the cap rate exactly, losing only $\sqrt{n}$. Two ingredients close it. The first is Hoeffding sub-Gaussianity for Z_1 . The second is that a Rademacher sum is no more concentrated near zero than its Gaussian counterpart — which in its clean form is *false* (equal weights leave an atom at the origin), and whose correct form we prove by writing $E[e^{-\lambda Z^2}] = E_g \prod_s \cos(\sqrt{2\lambda} g c_s)$ and splitting on $|g|$: since $|\cos x| \leq e^{-x^2/2}$ for $|x| \leq 1.778$,

$$E[e^{-\lambda Z^2}] \leq (1 + 2\lambda\sigma^2)^{-1/2} + 2\Phi\left(1.778 \rho / \sqrt{2\lambda\sigma^2}\right), \quad \rho = \sigma / \max_s |c_s|,$$

with no hypothesis on the weights for validity. The instrument’s own conditional profile has ρ of median 4.0 and minimum 2.34 over ≈ 8000 samples, so the error costs $\approx 3 \times 10^{-3}$: the per-dimension

12 Conclusion

A sampling gate certifies f restricted to $\mathcal{R}$ — exactly that, and nothing else. On an enclosed mode this quotient stops being a formality and becomes the whole story: a wrong-topology artifact can be unfalsifiable by every gate and bitwise harmless at play; the same artifact, one knob later, is falsifiable and costly; the same omission, with the channel turned away from the planner, is at full danger again with the topology unchanged. Certifiability, correctness, and consequence are three different statements about where the model’s errors sit relative to reach — never about the mode itself.

For practitioners the asymmetry is the message. A fence you cannot reach is a fence you cannot certify — and also one you cannot be harmed by while it stays unreachable; the danger lives exactly where the omission intersects a competent planner’s optimal path, and it turns on over a knee as soon as a channel admits one step. Repair, when it is possible at all, needs two things that can both be measured *in advance*: evidence from the far side of the boundary (reachability of the interior), and an evidence sensor whose topological resolution at the operative sampling density can actually see the structure to be repaired. Where either is absent, the synthesis loop will do what ours did in every family we tested: write something plausible in the gauge region — and the gate will certify it.

Reproducibility

All experiments, result files, and analysis scripts are in the project repository:

- mechanism grid and γ -probes: `continuous_ring2d_mechanism.py`, `ring2d_rint_probe.py`;
- synthesis harness: `continuous_danger_synthesis.py`;
- agent-relay protocol: `continuous_claude_step.py`;
- registered open-ring driver: `continuous_ring2d_open_sweep.py`;
- aggregator: `ring2d_open_aggregate.py`;
- ShellField- n scripts and the behavioral audit (`ring2d_artifact_audit.py`, oracle self-tested).

Every seed, checkpoint, and classified artifact is committed; long runs checkpoint per unit and resume exactly; paired seeds (common random numbers) are used for every play contrast.

References

- Michał Adamaszek and Henry Adams. The vietoris–rips complexes of a circle. *Pacific Journal of Mathematics*, 290(1):1–40, 2017.
- Javier Aguilar Martín. An omitted mode is a rare rule: The sampling-verification danger law in continuous code world models, 2026a. Companion paper, in preparation.
- Javier Aguilar Martín. When a verified world model still loses: Play-adequacy vs prediction-accuracy in LLM-synthesized code world models, 2026b. Companion paper (paper 1). arXiv:2607.14169, <https://arxiv.org/abs/2607.14169>; repository: <https://github.com/JaviMaligno/code-world-models>.

- Mohammed Alshiekh, Roderick Bloem, Rüdiger Ehlers, Bettina Könighofer, Scott Niekum, and Ufuk Topcu. Safe reinforcement learning via shielding. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence (AAAI)*, pages 2669–2678, 2018.
- Yashwanth Annpureddy, Che Liu, Georgios Fainekos, and Sriram Sankaranarayanan. S-TaLiRo: A tool for temporal logic falsification for hybrid systems. In *Tools and Algorithms for the Construction and Analysis of Systems (TACAS)*, volume 6605 of *Lecture Notes in Computer Science*, pages 254–257. Springer, 2011.
- Alberto Bemporad and Manfred Morari. Control of systems integrating logic, dynamics, and constraints. *Automatica*, 35(3):407–427, 1999.
- Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018.
- Koen Claessen and John Hughes. QuickCheck: A lightweight tool for random testing of Haskell programs. In *Proceedings of the Fifth ACM SIGPLAN International Conference on Functional Programming (ICFP)*, pages 268–279, 2000.
- David Cohen-Steiner, Herbert Edelsbrunner, and John Harer. Stability of persistence diagrams. *Discrete & Computational Geometry*, 37(1):103–120, 2007.
- Anthony Corso, Robert J. Moss, Mark Koren, Ritchie Lee, and Mykel J. Kochenderfer. A survey of algorithms for black-box safety validation of cyber-physical systems. *Journal of Artificial Intelligence Research*, 72:377–428, 2021.
- Herbert Edelsbrunner and John Harer. *Computational Topology: An Introduction*. American Mathematical Society, 2010.
- Herbert Federer. Curvature measures. *Transactions of the American Mathematical Society*, 93(3):418–491, 1959.
- Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and Graham Neubig. PAL: Program-aided language models. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202 of *Proceedings of Machine Learning Research*, pages 10764–10799, 2023.
- Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations (ICLR)*, 2020.
- Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.
- Nathan O. Lambert, Brandon Amos, Omry Yadan, and Roberto Calandra. Objective mismatch in model-based reinforcement learning. In *Proceedings of the 2nd Conference on Learning for Dynamics and Control (L4DC)*, volume 120 of *Proceedings of Machine Learning Research*, pages 761–770, 2020. arXiv:2002.04523.

- Wolfgang Lehrach, Daniel Hennes, Miguel Lazaro-Gredilla, Xinghua Lou, Carter Wendelken, Zun Li, Antoine Dedieu, Jordi Grau-Moya, Marc Lanctot, Atil Iscen, John Schultz, Marcus Chiam, Ian Gemp, Piotr Zielinski, Satinder Singh, and Kevin P. Murphy. Code World Models for general game playing. In *International Conference on Learning Representations (ICLR)*, 2026. Poster; OpenReview id 1UoB7IWiku.
- Jacky Liang, Wenlong Huang, Fei Xia, Peng Xu, Karol Hausman, Brian Ichter, Pete Florence, and Andy Zeng. Code as policies: Language model programs for embodied control. In *IEEE International Conference on Robotics and Automation (ICRA)*, pages 9493–9500, 2023.
- Anusha Nagabandi, Gregory Kahn, Ronald S. Fearing, and Sergey Levine. Neural network dynamics for model-based deep reinforcement learning with model-free fine-tuning. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2018.
- Partha Niyogi, Stephen Smale, and Shmuel Weinberger. Finding the homology of submanifolds with high confidence from random samples. *Discrete & Computational Geometry*, 39(1):419–441, 2008.
- Simone Paoletti, Aleksandar Lj. Juloski, Giancarlo Ferrari-Trecate, and René Vidal. Identification of hybrid systems: A tutorial. *European Journal of Control*, 13(2-3):242–260, 2007.