

# Apply filters to SQL queries

## Project description

Security issues that involve login attempts and employee machines were discovered. As a security professional, I will examine the organization's data through the use of SQL filters to retrieve records from different datasets and investigate potential security issues.

## Retrieve after hours failed login attempts

The following screenshot demonstrates how I ran the SQL query to retrieve all failed login attempts entries after 18:00.

```
MariaDB [organization]> SELECT *  
->  
-> FROM log_in_attempts  
->  
-> WHERE login_time > '18:00' AND success = 0;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	aestrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

The first line of the screenshot shows the `SELECT *` keyword which returns all columns from the desired table. The next line shows the `FROM` keyword which indicates the table I'm querying,

which is 'log\_in\_attempts'. The third line shows the WHERE clause which filters the column 'login\_time' by filtering login times after 18:00, followed by the AND operator to also meet another condition which is the success of a log in, represented by the boolean value of 0 (FALSE).

## Retrieve login attempts on specific dates

The following partial screenshot shows how I queried to investigate all login attempts that occurred in 2022-05-09 or 2022-05-08. 75 results were returned.

```
MariaDB [organization]> SELECT *  
->  
-> FROM log_in_attempts  
->  
-> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0

Once again, SELECT \* will return all columns from the 'log\_in\_attempts' table in the FROM line. This time, the WHERE clause will filter the 'login\_date' column by setting it to 2022-05-09 and 2022-05-08 using the OR operator.

## Retrieve login attempts outside of Mexico

The following partial screenshot demonstrates how I filtered login attempts made outside of Mexico. 144 results were returned.

```
MariaDB [organization]> SELECT *  
->  
-> FROM log_in_attempts  
->  
-> WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrach	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
16	mcouliba	2022-05-11	06:44:22	CAN	192.168.172.189	1
17	pwashing	2022-05-11	02:33:02	USA	192.168.81.89	1

To filter logins made from countries outside of Mexico, I combined the NOT and LIKE operators. NOT will negate the condition of a country matching the string of LIKE. In this case, since there were entries with 'MEX' and 'MEXICO', the LIKE operator will have a wildcard next to the string ('MEX%').

## Retrieve employees in Marketing

The following screenshot shows all employees in the Marketing department who are located in all offices in the East building.

```
MariaDB [organization]> SELECT *  
->  
-> FROM employees  
-> WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

`SELECT*` will return all columns from the 'employees' table. The `WHERE` clause will return all entries that match 'Marketing' from the department column, and the `LIKE` operator will return all strings that start with East by using the wildcard %.

## Retrieve employees in Finance or Sales

The following partial screenshot shows how I queried for all employees in the Finance and Sales departments.

```
MariaDB [organization]> SELECT *  
->  
-> FROM employees  
-> WHERE department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduke	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156

*SELECT\** will return all columns from the 'employees' table. The *WHERE* clause will return all entries that match 'Finance' or 'Sales' in the department column.

## Retrieve all employees not in IT

The following partial screenshot shows all employees that don't belong in the Information Technology department.

```
MariaDB [organization]> SELECT*
->
-> FROM employees
->
-> WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1020	u899v381w363	arutley	Marketing	South-351
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1026	a998b568c863	apatel	Human Resources	West-320
1027	b806c503d354	mrh	Marketing	West-246
1028	c603d749e374	aestrada	Human Resources	West-121

`SELECT*` will return all columns from the 'employees' table. The `WHERE` clause includes the `NOT` operator to filter departments that match the string 'Information Technology'. This will display all employees not belonging to the IT department.

## Summary

I filtered multiple times through SQL to investigate login attempts. Using different filters helped me identify all employees that failed to login, including times and location.