

Cada `expect` del validador contra el test que aborta en él

Corrida: 2026-09-22T02:22:37.552Z · aiken aiken v1.1.21+42babe5 · 102 tests, 102 en verde

18 `expect` : 18 con test, 0 sin test.

Archivo:línea	<code>expect</code>	Tests que abortan ahí
validators/stage.ak:69	<code>expect Finite(lower) = range.lower_bound.bounds_type</code>	<code>spend_rejects_open_ended_validity_range</code> , <code>spend_rejects_missing_lower_bound</code>
validators/stage.ak:70	<code>expect Finite(upper) = range.upper_bound.bounds_type</code>	<code>spend_rejects_missing_upper_bound</code>
validators/stage.ak:84	<code>expect Some(old_datum) = datum</code>	<code>spend_rejects_missing_datum</code>
validators/stage.ak:85	<code>expect Some(own_input) = find_input(tx.inputs, own_ref)</code>	<code>spend_rejects_unknown_own_ref</code>
validators/stage.ak:87	<code>expect Script(own_policy) = own_address.payment_credential</code>	<code>spend_rejects_own_input_not_locked_by_a_script</code>
validators/stage.ak:91	<code>expect assets.quantity_of(own_input.output.value, own_policy, old_datum.stage_ref,) == 1</code>	<code>spend_rejects_utxo_without_thread_token</code> , <code>spend_rejects_thread_token_of_another_stage</code> , <code>spend_rejects_utxo_with_two_units_of_own_token</code> , <code>spend_rejects_own_input_with_two_units_when_a_decoy_absorbs_carrying_thread</code>
validators/stage.ak:100	<code>expect inputs_at_addresses(tx.inputs, own_addresses) == 1</code>	<code>spend_rejects_two_script_inputs</code>
validators/stage.ak:101	<code>expect [continuing_output] = at_address(tx.outputs, own_address)</code>	<code>spend_rejects_a_second_output_at_the_exact_script_address</code> , <code>spend_rejects_two_script_outputs</code> , <code>spend_rejects_no_continuing_output</code>
validators/stage.ak:104	<code>expect [_] = carrying_thread(tx.outputs, own_policy, old_datum.stage_ref)</code>	<code>spend_rejects_thread_split_across_a_staking_variant_of_the_script_address</code> , <code>spend_rejects_value_drain</code> , <code>spend_rejects_dropping_the_thread_token</code>
validators/stage.ak:107	<code>expect list.has(tx.extra_signatories, admin)</code>	<code>spend_rejects_missing_admin_signature</code> , <code>mint_rejects_missing_admin_signature</code>
validators/stage.ak:109	<code>expect InlineDatum(raw_new_datum) = continuing_output.datum</code>	<code>spend_rejects_non_inline_datum</code>
validators/stage.ak:110	<code>expect new_datum: StageDatum = raw_new_datum</code>	<code>spend_rejects_new_datum_of_the_wrong_type</code>
validators/stage.ak:125	<code>expect continuing_output.value == own_input.output.value</code>	<code>spend_rejects_ada_drain_while_keeping_the_token</code>

Archivo:línea	expect	Tests que abortan ahí
validators/stage.ak:144	expect list.has(tx.extra_signatories, admin)	spend_rejects_missing_admin_signature, mint_rejects_missing_admin_signature
validators/stage.ak:150	expect [Pair(asset_name, 1)] = dict.to_pairs(assets.tokens(tx.mint, policy_id))	mint_rejects_two_units_of_the_thread, mint_rejects_two_threads_in_one_tx, mint_rejects_two_asset_names_when_both_are_present_in_the_output, mint_rejects_a_burn
validators/stage.ak:153	expect [thread_output] = carrying_thread(tx.outputs, policy_id, asset_name)	mint_rejects_token_not_locked_in_the_script, mint_rejects_output_holding_extra_units_of_the_token, mint_rejects_two_outputs_each_carrying_one_unit
validators/stage.ak:154	expect InlineDatum(raw_datum) = thread_output.datum	mint_rejects_non_inline_datum
validators/stage.ak:155	expect initial_datum: StageDatum = raw_datum	mint_rejects_initial_datum_of_the_wrong_type