

Data Preparation:

Integration and Cleaning

Mining Massive Datasets

Prof. Carlos Castillo — <https://chato.cl/teach>




Universitat
Pompeu Fabra
Barcelona

Main Sources


- Data Mining, The Textbook (2015) by Charu Aggarwal (Chapter 2) + [slides by Lijun Zhang](#)
- Introduction to Data Mining 2nd edition (2019) by Tan et al. (Chapter 2)
- Data Mining Concepts and Techniques, 3rd edition (2011) by Han et al. (Chapter 3)

Data integration


Data integration is not easy




Data integration is not easy



Data integration is not easy



Data integration aspects



Remember: difference between
DB schema and DB state

- **Schema integration**
 - Bring different schemata together
 - Equal concepts should be represented with equal types
- **Object matching** / Entity identification
 - Equal entities should be equally identified across datasets (unless re-identification forbidden by policy)

Data integration aspects (cont.)

- Redundancy analysis
 - Sometimes data needs to be integrated because different sets are row-incomplete
 - Sometimes those sets don't form a partition \Rightarrow there will be repeated entities to be removed
- Resolution of value conflicts
 - Same entity, different attribute values

Data cleaning

Why data cleaning?

- Data collection technologies are inaccurate
 - Sensors
 - Optical character recognition
 - Speech-to-text data
- Privacy reasons
- Manual errors
- Data collection is expensive and inaccurate

What is data cleaning?

It is a process by which data records are
modified or deleted
until each record passes
data validity criteria

Data validity criteria (1)

- **Mandatory** constraints: certain columns cannot be empty.
- **Data-type** constraints: values in a column must be of a particular datatype
- **Range** constraints: numbers or dates should fall within a certain range
- **Regular expression** patterns: e.g., phone numbers `[0-9]{9}`

Data validity criteria (2)

- **Unique** constraints: a field, or a combination of fields, must be unique
- **Set-membership** constraints: values in a column come from a set of discrete values or codes
- **Foreign-key** constraints: set membership constraint where valid values in a column are defined in a column of another table that contains unique values

Data validity criteria (3)

- **Cross-field validation**: certain conditions that utilize multiple fields must hold, e.g.:
 - percentages add up to 1.0 or to 100
 - discounted price lower or equal to regular price
 - date of expiration after date of manufacturing

Data validity criteria (3 cont.)

You see this in a package ... how do you decide whether the product is expired or not?

生产日期: 2016 年 06 月 01 日	5/05/2015 تاريخ الذبح
▶ 保质期至: 2018 年 06 月 01 日	6/05/2015 تاريخ التعبئة
	13/07/2015 تاريخ انتهاء الصلاحية

賞味期限	17. 9.11
製造日	17. 5.11

G08006
2016.08.17 제조
2018.08.15 까지

Handling missing entries

Why is a value missing?

- **Missing Completely at Random (MCAR)**
 - Missingness of a value is independent of observable attributes
- **Missing at Random (MAR)**
 - Missingness has statistical dependencies with an observable attribute
 - We can fill in values based on other attributes, but this is likely to introduce a bias in the analysis
- **Missing Not at Random (MNAR)**
 - Missingness depends deterministically on an observable attribute
 - In general this is informative, non-ignorable missingness

In general, it is **not** possible to know which one is the case just by looking at the data

Handling missing entries: options

- **Delete** the data record containing missing entries
- **Estimate** or **Impute** the Missing Values
 - Additional errors may be introduced
 - Good under certain conditions (e.g., Matrix Completion)
- Some algorithms can work with missing data

Exercise

Handling missing data (specify your assumptions)

Q1. 5% of student records at a university have no “civil status” (single, married, ...)

Drop records? Impute value, how?

Q2. 5% of smokers in a study of the effects of tobacco on health had no year of birth

Drop records? Impute value, how?

Q3. 5% of records of sales of a company have zip code but no province

Drop records? Impute value, how?

Q4. Temperature sensor at weather station was failing at random intervals during one day, total downtime 6 hours, max continuous downtime 15 minutes

Drop that day? Impute values, how?

Q5. Same sensor failed during one night, downtime 6 hours continuous

Drop that day? Impute values, how?

Pin board: <https://upfbarcelona.padlet.org/chato/mgu47ssu5hxlxej8>



Handling Incorrect and Inconsistent Entries

- Inconsistency detection
 - E.g., full name and abbreviation don't match
- Domain knowledge
 - Human age cannot reach to 800 (yet?)
- Data-centric methods
 - Outlier detection


Scaling and normalization

- Features have different **scales**
 - Age versus Salary
- **Standardization** (“z-scoring”)
 - Mean 0 and stdev 1
- **Min-Max Scaling**
 - Map to [0,1]
 - Sensitive to noise

$$z_i = \frac{x_i - \mu}{\sigma}$$

$$z_i = \frac{x_i - \min}{\max - \min}$$


Example: seasonal standardization



Net Primary Production (NPP) is a measure of plant growth used by ecosystem scientists.

	Minneapolis	Atlanta	Sao Paulo
Minneapolis	1.0000	0.7591	-0.7581
Atlanta	0.7591	1.0000	-0.5739
Sao Paulo	-0.7581	-0.5739	1.0000


Example: seasonal standardization



Net Primary Production (NPP) is a measure of plant growth used by ecosystem scientists.

	Minneapolis	Atlanta	Sao Paulo
Minneapolis	1.0000	0.7591	-0.7581
Atlanta	0.7591	1.0000	-0.5739
Sao Paulo	-0.7581	-0.5739	1.0000

Example: seasonal standardization



Normalized using
monthly Z Score:

Subtract off
monthly mean and
divide by monthly
standard deviation

	Minneapolis	Atlanta	Sao Paulo
Minneapolis	1.0000	0.0492	0.0906
Atlanta	0.0492	1.0000	-0.0154
Sao Paulo	0.0906	-0.0154	1.0000

Adjusted correlations between time series

Summary

Things to remember

- Data cleaning
 - Specially: when and how to impute missing values

Exercises for TT03-TT05

- Exercises 3.7 of Data Mining Concepts and Techniques, 3rd edition (2011) by Han et al.
- Exercises 2.6 of Introduction to Data Mining, Second Edition (2019) by Tan et al.
 - Mostly the first exercises, say 1-6