Session 7

1. Create a table called Restaurant with columns: id, name, location, and cuisine. Apply NOT NULL constraint to name and location, and make id the PRIMARY KEY.

➔

```
USE db_restaurant;

CREATE TABLE data(
    id INT(11) AUTO_INCREMENT PRIMARY KEY,
    name VARCHAR(255) NOT NULL,
    location VARCHAR(255) NOT NULL,
    cuisine VARCHAR(255)
);

INSERT INTO data(name,location)
VALUES
('Agashiye','Ahmedaba');


INSERT INTO data(name,location,cuisine)
VALUES
('Idli Boat','Chennai','South Indian'),
('Chonkha','Punjab','Punjabi');
```

```
sql> • SELECT * FROM `db_restaurant`.`data`
```

id	name	location	cuisine
1	Agashiye	Ahmedaba	NULL
2	Idli Boat	Chennai	South Indian
3	Chonkha	Punjab	Punjabi

2. Create a table called FoodOrder with columns: order_id, restaurant_id, user_id, and order_total. Set order_id as PRIMARY KEY, and add a FOREIGN KEY constraint on restaurant_id referencing Restaurant(id).

➔ **Create Restaurant Table**

```
USE db_restaurant;

CREATE TABLE restaurent(
   id INT(11) PRIMARY KEY AUTO_INCREMENT,
   name VARCHAR(255) NOT NULL,
   city VARCHAR(255) NOT NULL,
   cuisine VARCHAR(255)
);

INSERT INTO restaurent(name,city,cuisine)
VALUES
('Agashiye', 'Ahmedabad', 'Gujarati'),
('Leopold Cafe', 'Mumbai', 'Continental'),
('Paradise Biryani', 'Hyderabad', 'Hyderabadi');
```

➔ **Create Foodorder Table**

```
USE db_restaurant;

CREATE TABLE foodorder(
   order_id INT(11) PRIMARY KEY AUTO_INCREMENT,
   restaurent_id INT(11),
   user_id INT(11),
   order_total DECIMAL(10,2),
   FOREIGN KEY (restaurent_id) REFERENCES restaurent(id)
);

INSERT INTO foodorder(restaurent_id,user_id,order_total)
VALUES
(1,201,750.50),
(1,202,1022.99),
(2,78,1800.00),
(3,23,9000.90);
```

➔ Restaurant Table Image

```
sql> SELECT * FROM `db_restaurant`.`restaurent`
```

id	name	city	cuisine
1	Agashiye	Ahmedabad	Gujarati
2	Leopold Cafe	Mumbai	Continental
3	Paradise Biryani	Hyderabad	Hyderabadi

➔ Foodorder Table Image

Output | Result #1

order_id	restaurent_id	user_id	order_total
1	1	201	750.50
2	1	202	1022.99
3	2	78	1800.00
4	3	23	9000.90

3. Insert 6 rows into a table called SpotifyUser with columns: user_id, username, email, and subscription_type. Ensure that username is UNIQUE and email is NOT NULL. Hint: Use the UNIQUE and NOT NULL constraints when creating the table.

➔

```
USE playlist;

CREATE TABLE SpotifyUser(
    user_id INT(11) PRIMARY KEY AUTO_INCREMENT,
    user_name VARCHAR(255) UNIQUE,
    user_email VARCHAR(255) NOT NULL,
    subscription_type VARCHAR(255)
);

INSERT INTO SpotifyUser(user_name,user_email,subscription_type)
VALUES
('Jay_M','jaymeghani@gmail.com','Student'),
('Henish_B','henishbhuva@gmail.com','Free'),
('Raj_A','rajadroja@gmail.com','Family'),
('Jay_A','jayadroja@gmail.com','Premium'),
('Bhavya_V','vamjabhavya@gmail.com','Free'),
('Arth_P','arthpatel@gmail.com','Premium');
```

Output | Result #4

user_id	user_name	user_email	subscription_type
1	Jay_M	jaymeghani@gmail.com	Student
2	Henish_B	henishbhuva@gmail.com	Free
3	Raj_A	rajadroja@gmail.com	Family
4	Jay_A	jayadroja@gmail.com	Premium
5	Bhavya_V	vamjabhavya@gmail.com	Free
6	Arth_P	arthpatel@gmail.com	Premium

4. Create a VIEW named TopSpendersView that shows usernames and order_total from a FoodOrder table where order_total is greater than 1000.

➔

```
USE db_restaurant;

CREATE TABLE foodorder(
   order_id INT(11) AUTO_INCREMENT PRIMARY KEY,
   username VARCHAR(255),
   order_total INT(11)
);

INSERT INTO foodorder(username,order_total)
VALUES
('Jay',2200),
('Henish',700),
('Raj',1800),
('Bhavya',2900),
('Jay',1200),
('Arth',300);

CREATE VIEW TopSpendersView AS
SELECT username, order_total
FROM foodorder
WHERE order_total > 1000;

SELECT * FROM TopSpendersView;
```

Output | Result #5

username	order_total
Jay	2200
Raj	1800
Bhavya	2900
Jay	1200

5. Write a SQL query to list all users from the TopSpendersView who have spent more than 2000, sorted by order_total descending. Constraint: Only use the TopSpendersView for your query, not the original FoodOrder table.

➔

```
USE db_restaurant;

SELECT username, order_total
FROM topspendersview
WHERE order_total > 2000
ORDER BY order_total DESC;

SELECT * FROM topspendersview;
```

Output | Result #2 | Result #3

username	order_total
Bhavya	2900
Jay	2200