

CODEBOOK

Jay

23/07/2020

“Getting and Cleaning Data” Course Project Code Book

Initial data for research

The data is taken from UCI HAR Dataset. This dataset provide the following variables for each activity:

subject - ID of participant activity - ID of activity type Mean and standart deviation for the following features (other values are presented in initial dataset, but for this reasearch only these parameters were used)

tBodyAcc-XYZ

tGravityAcc-XYZ

tBodyAccJerk-XYZ

tBodyGyro-XYZ

tBodyGyroJerk-XYZ

tBodyAccMag

tGravityAccMag

tBodyAccJerkMag

tBodyGyroMag

tBodyGyroJerkMag

fBodyAcc-XYZ

fBodyAccJerk-XYZ

fBodyGyro-XYZ

fBodyAccMag

fBodyAccJerkMag

fBodyGyroMag

fBodyGyroJerkMag

The features come from the accelerometer and gyroscope 3-axial raw signals tAcc-XYZ and tGyro-XYZ. These time domain signals (prefix ‘t’ to denote time) were captured at a constant rate of 50 Hz. Then they were filtered using a median filter and a 3rd order low pass Butterworth filter with a corner frequency of 20 Hz to remove noise. Similarly, the acceleration signal was then separated into body and gravity acceleration signals (tBodyAcc-XYZ and tGravityAcc-XYZ) using another low pass Butterworth filter with a corner frequency of 0.3 Hz.

Subsequently, the body linear acceleration and angular velocity were derived in time to obtain Jerk signals (tBodyAccJerk-XYZ and tBodyGyroJerk-XYZ). Also the magnitude of these three-dimensional signals were calculated using the Euclidean norm (tBodyAccMag, tGravityAccMag, tBodyAccJerkMag, tBodyGyroMag, tBodyGyroJerkMag).

Finally a Fast Fourier Transform (FFT) was applied to some of these signals producing fBodyAcc-XYZ, fBodyAccJerk-XYZ, fBodyGyro-XYZ, fBodyAccJerkMag, fBodyGyroMag, fBodyGyroJerkMag. (Note the 'f' to indicate frequency domain signals).

These signals were used to estimate variables of the feature vector for each pattern: '-XYZ' is used to denote 3-axial signals in the X, Y and Z directions.

CodeBook

The following data transformations were conducted to form a tidy dataset:

Added a new feature activitylabel - factor variable for activities with the following levels: WALKING, WALKING_UPSTAIRS, WALKING_DOWNSTAIRS, SITTING, STANDING, LAYING.

Tidy dataset was build as a mean values of features grouped by activitylabel and subject - for each subject and activity type determined mean values over all activities of that type.