

HTML & CSS Questions

1. What is difference between Tag and Element in HTML?
 - Element: The entire structure including the start tag, content, and end tag.
 - Tag: Refers specifically to the start tag, end tag, or both together.
 - Example
 - Tag: `<h1></h1>`
 - Element: `<h1>Hello World</h1>`
2. Which are void elements in HTML?
 - Elements without the body are known as void elements
 - Example
 - `img`
 - `br`
 - `hr`
 - `input`
 - `meta`
 - `link`
3. What is semantic code in HTML?
 - Semantic code in HTML refers to using elements like `<header>`, `<nav>`, `<article>`, `<section>`, `<aside>`, `<footer>` that convey the meaning and structure of the content.
4. What is the difference between pseudo class and pseudo elements in CSS?
 - Pseudo-classes target and style specific states or conditions of elements (e.g., `:hover`, `:active`).
 - Pseudo-elements style and target specific parts of an element (e.g., `::before`, `::after`), allowing for more fine-grained control over content.
5. Where in an HTML document is the correct place to refer to an external style sheet?
 - The `<link>` tag inside `<head>` section
6. Which HTML tag is used to define an internal style sheet?
 - `<style>` is used to define internal style sheet
7. Which HTML attribute is used to define inline styles?
 - style attributes of elements are used to define inline styles

8. How do you insert a comment in a CSS file?
 - CSS comment looks like this `/* this is css comment */`
9. Which property is used to change the background color?
 - Background-color property is used to change background color
10. How do you add a background color for all `<h1>` elements?
 - `h1{ background-color: red }`
11. Which CSS property controls the text size?
 - font-size property controls the text size
12. How do you display hyperlinks without an underline?
 - `google`
 - `a{ text-decoration: none; }`
13. How do you make each word in a text start with a capital letter?
 - `text-transform: capitalize`
14. How do you display a border like this:
The top border = 10 pixels
The dotted bottom border = 5 pixels
The dashed left border = 20 pixels
The right border = 1pixel?
 - `border-width: 10px 1px 5px 20px;`
 - `border-style: 1 px solid black;`
15. When using the padding property; are you allowed to use negative values?
 - No, negative values are not allowed
16. How do you group selectors?
 - Separate selectors with comma.
 - Example
 - `h1, h2, h3 { color: red; }`
17. What is the default value of the position property?
 - Default value of position property is static

18. How you can define pseudo element?

- We can define pseudo elements using '::'
- Example
 - ::before

19. What is box model?

- The box model is the layout concept in CSS that represents elements as rectangular boxes with content, padding, border, and margin.

20. What is flex model?

- The Flexbox model is a layout model in CSS that allows the design of flexible and efficient layouts where elements can dynamically adjust their size and alignment within a container.