





→ Previous Page
Next Page →

When user interacts with components, such as h:commandButton or h:link, the JSF fires a action events which can be handled in two ways.

Technique	Description
Method Binding	Pass the name of the managed bean method in actionListener attribute of UI Component.
ActionListener	Implement ActionListener interface and pass the implementation class name to <i>actionListener</i> attribute of UI Component.



Define a method

```
public void updateData(ActionEvent e){
  data="Hello World";
}
```

Use above method

```
<h:commandButton id="submitButton"
  value="Submit" action="#{userData.showResult}"
  actionListener="#{userData.updateData}" />
</h:commandButton>
```


Implement ActionListener

Use listener method

```
<h:commandButton id="submitButton1"
  value="Submit" action="#{userData.showResult}" >
  <f:actionListener type="com.tutorialspoint.test.UserActionListener" />
</h:commandButton>
```


Let us create a test JSF application to test the actionListener in JSF.

Step Description



Create a project with a name <i>helloworld</i> under a package <i>com.tutorialspoint.test</i> as explained in the <i>JSF - First Application</i> chapter. Modify <i>UserData.java</i> file as explained below. Create <i>UserActionListener.java</i> file under a package <i>com.tutorialspoint.test</i> . Modify it as explained below Modify <i>home.xhtml</i> as explained below. Keep rest of the files unchanged. Modify <i>result.xhtml</i> as explained below. Keep rest of the files unchanged. Compile and run the application to make sure business logic is working as per the requirements. Finally, build the application in the form of war file and deploy it in Apache Tomcat Webserver.			
Create <i>UserActionListener.java</i> file under a package <i>com.tutorialspoint.test</i> .Modify it as explained below Modify <i>home.xhtml</i> as explained below. Keep rest of the files unchanged. Modify <i>result.xhtml</i> as explained below. Keep rest of the files unchanged. Compile and run the application to make sure business logic is working as per the requirements.	1	Create a project with a name helloworld under a package com.tutorialspoint.test as explained in the JSF - First Application chapter.	
 Modify <i>home.xhtml</i> as explained below. Keep rest of the files unchanged. Modify <i>result.xhtml</i> as explained below. Keep rest of the files unchanged. Compile and run the application to make sure business logic is working as per the requirements. 	2	Modify <i>UserData.java</i> file as explained below.	
5 Modify <i>result.xhtml</i> as explained below. Keep rest of the files unchanged. 6 Compile and run the application to make sure business logic is working as per the requirements.	3	Create UserActionListener.java file under a package com.tutorialspoint.test.Modify it as explained below	
6 Compile and run the application to make sure business logic is working as per the requirements.	4	Modify home.xhtml as explained below. Keep rest of the files unchanged.	
	5	Modify result.xhtml as explained below. Keep rest of the files unchanged.	
7 Finally, build the application in the form of war file and deploy it in Apache Tomcat Webserver.	6	Compile and run the application to make sure business logic is working as per the requirements.	
	7	Finally, build the application in the form of war file and deploy it in Apache Tomcat Webserver.	
8 Launch your web application using appropriate URL as explained below in the last step.	8	Launch your web application using appropriate URL as explained below in the last step.	

alli ser Data java

```
package com.tutorialspoint.test;
import java.io.Serializable;
import java.util.LinkedHashMap;
import java.util.Map;
import javax.faces.bean.ManagedBean;
import javax.faces.bean.SessionScoped;
import javax.faces.event.ValueChangeEvent;
@ManagedBean(name = "userData", eager = true)
@SessionScoped
public class UserData implements Serializable {
private static final long serialVersionUID = 1L;
   private static Map<String,String> countryMap;
   private String data = "sample data";
   public String showResult(){
      return "result";
   public void updateData(ActionEvent e){
      data="Hello World";
   public String getData() {
      return data;
   public void setData(String data) {
     this.data = data;
```



libme.xhtml

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"</pre>
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml"</pre>
  xmlns:h="http://java.sun.com/jsf/html"
   xmlns:f="http://java.sun.com/jsf/core">
  <h:head>
      <title>JSF tutorial</title>
   </h:head>
   <h:body>
      <h2>actionListener Examples</h2>
      <h:form>
      <h2>Method Binding</h2>
      <hr/>
      <h:commandButton id="submitButton"
         value="Submit" action="#{userData.showResult}"
         actionListener="#{userData.updateData}" />
      </h:commandButton>
      <h2>ActionListener interface</h2>
      <h:commandButton id="submitButton1"
         value="Submit" action="#{userData.showResult}" >
         <f:actionListener
            type="com.tutorialspoint.test.UserActionListener" />
      </h:commandButton>
      </h:form>
    </h:body>
</html>
```

kesult.xhtml


```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml"
    xmlns:f="http://java.sun.com/jsf/core"
    xmlns:h="http://java.sun.com/jsf/html">
    <hhead>
    <title>JSF Tutorial!</title>
    </h:head>
    <h:body>
    <h2>Result</h2>
    <hr />
    #{userData.data}
    </h:body>
</html>
```

Once you are ready with all the changes done, let us compile and run the application as we did in JSF - First Application chapter. If everything is fine with your application, this will produce following result:



Click on any submit button. You will see the following result.





⊕ Previous Page
 Next Page
 ⊕

Advertisements

