$Normal_No_Variable_Loading_LIED32_describe.pdf_describe$

| | Current Line 'L1' | Current Line 'L2' | Current Line 'L3' | Voltage Phase 'L1-N' | Voltage Phase 'L2-N' | Voltage Phase 'L3-N' | Active Power | Reactive power | Frequency | Power Factor |
|-------|-------------------|-------------------|--------------------|----------------------|----------------------|----------------------|--------------------|--------------------|---------------------|----------------------|
| count | 600.0 | 600.0 | 600.0 | 600.0 | 600.0 | 600.0 | 600.0 | 600.0 | 600.0 | 600.0 |
| mean | 245.8566666666665 | 245.91 | 245.9533333333333 | 6350.783333333334 | 6350.883333333333 | 6351.113333333334 | 4000000.6666666665 | 2450001.3266666667 | 49.999583333333334 | 0.849999999999999 |
| std | 2.403973246073109 | 2.414874606601624 | 2.3601778792268053 | 6.247247585367257 | 5.939572354567916 | 5.982765081375034 | 237.60639768868432 | 298.91003993762865 | 0.03234300293138973 | 0.013928028694165932 |
| min | 241.0 | 241.0 | 241.0 | 6341.0 | 6341.0 | 6341.0 | 3999500.0 | 2449502.0 | 49.95 | 0.83 |
| 25% | 244.0 | 244.0 | 244.0 | 6345.0 | 6346.0 | 6346.0 | 3999872.5 | 2449742.75 | 49.97 | 0.84 |
| 50% | 246.0 | 246.0 | 246.0 | 6350.0 | 6351.0 | 6352.0 | 4000000.0 | 2449998.5 | 50.0 | 0.85 |
| 75% | 247.0 | 247.0 | 247.0 | 6356.0 | 6356.0 | 6356.0 | 4000145.0 | 2450268.75 | 50.03 | 0.86 |
| max | 251.0 | 251.0 | 251.0 | 6361.0 | 6361.0 | 6361.0 | 4000498.0 | 2450492.0 | 50.05 | 0.87 |