

Machine Learning for Signal Processing

Sparse and Overcomplete Representations

Bhiksha Raj
(slides from Sourish Chaudhuri and
Abelino Jimenez)

1


So far

Can we use linear composition to identify **basic units** that compose the signal?

Sparse and Overcomplete Representations

2

So far



Sparse and Overcomplete Representations

3

Just in case you missed it..

- Remember, #(Basis Vectors)= #unknowns

$$D \cdot \alpha = X$$

Diagram illustrating the equation $D \cdot \alpha = X$. D is labeled "Basis Vectors" (with an upward arrow), α is labeled "Weights" (with a downward arrow), and X is labeled "Input data" (with a rightward arrow).

Standard representations: number of bases <= dimension of data

Sparse and Overcomplete Representations

4

A limitation we saw earlier

- Mathematical restrictions on the number of bases have no connection to reality
 - Universe does not respect your mathematical representations of the data
 - In reality: number of building blocks that compose any kind of data is unlimited
- One solution we saw earlier: picking *one* "closest" building block to represent any input

Sparse and Overcomplete Representations

5

Poll 1

- Mark all true statements about the vector quantization model
 - It represents data as $v = Dw$ where D is a dictionary
 - The w vector in vector-quantization is required to be one-hot
 - K-means clustering is one way of computing the Dictionary for the VQ model
 - The Dictionary is assumed to represent semantically meaningful "bases" that can be used to compose the data
 - The Dictionary may be viewed as a collection of exemplars that all data instances are mapped onto
- What is the difference or similarity between VQ (Kmeans) based representations and KLT/PCA?
 - They are completely different concepts and cannot be compared
 - They are similar in that both of them minimize the L2 divergence between v and Dw
 - They differ in that in VQ w must be one-hot and the bases (dictionary) are unrestricted, whereas in KLT/PCA the bases (dictionary) must be orthogonal while w is unrestricted

Sparse and Overcomplete Representations

6

Poll 1

- Mark all true statements about the vector quantization model
 - It represents data as $v = Dw$ where D is a dictionary
 - The w vector in vector-quantization is required to be one-hot
 - K-means clustering is one way of computing the Dictionary for the VQ model
 - The Dictionary is assumed to represent semantically meaningful "bases" that can be used to compose the data
 - The Dictionary may be viewed as a collection of exemplars that all data instances are mapped onto
- What is the difference or similarity between VQ (Kmeans) based representations and KLT/PCA?
 - They are completely different concepts and cannot be compared
 - They are similar in that both of them minimize the L2 divergence between v and Dw
 - They differ in that in VQ w must be one-hot and the bases (dictionary) are unrestricted, whereas in KLT/PCA the bases (dictionary) must be orthogonal while w is unrestricted

Sparse and Overcomplete Representations

7

7

A limitation we saw earlier

- Mathematical restrictions on the number of bases have no connection to reality
 - Universe does not respect your mathematical representations of the data
 - In reality: number of building blocks that compose any kind of data is unlimited
- One solution we saw earlier: picking *one* "closest" building block to represent any input
- Today: Learning linear compositional representations without restrictions on the number of basic units

Sparse and Overcomplete Representations

8

8

Key Topics in this Lecture

- Basics – Component-based representations
 - Overcomplete** and Sparse Representations,
 - Dictionaries**
- Pursuit Algorithms
- How to learn a dictionary
- Why is an overcomplete representation powerful?


Sparse and Overcomplete Representations

9

9

Representing Data

Dictionary (codebook)




Sparse and Overcomplete Representations

10


10

Representing Data

Dictionary



Atoms




Sparse and Overcomplete Representations

11


11

Representing Data

Dictionary



Atoms




Sparse and Overcomplete Representations


12

12


Each atom is a basic unit that can be used to "compose" larger units.




13




14




15









16



17



18



Overcomplete Representations

- What is the dimensionality of the input image? (say 64x64 image)
 - 4096
- What is the dimensionality of the dictionary? (each image = 64x64 pixels)
 - 4096 x N

Sparse and Overcomplete Representations 25

25

Overcomplete Representations

- What is the dimensionality of the input image? (say 64x64 image)
 - 4096
- What is the dimensionality of the dictionary? (each image = 64x64 pixels)
 - 4096 x N

Sparse and Overcomplete Representations 26

26

Overcomplete Representations

- What is the dimensionality of the input image? (say 64x64 image)
 - 4096
- What is the dimensionality of the dictionary? (each image = 64x64 pixels)
 - 4096 x N

VERY LARGE!!!

Sparse and Overcomplete Representations 27

27

Overcomplete Representations

- What is the dimensionality of the input image? (say 64x64 image)
 - 4096
- What is the dimensionality of the dictionary? (each image = 64x64 pixels)
 - 4096 x N

VERY LARGE!!!

Sparse and Overcomplete Representations 28

28

Overcomplete Representations

- What is the dimensionality of the input image? (say 64x64 image)
 - 4096
- What is the dimensionality of the dictionary? (each image = 64x64 pixels)
 - 4096 x N

VERY LARGE!!!

Sparse and Overcomplete Representations 29

29

Quick Linear Algebra Refresher

- Remember, #(Basis Vectors) = #unknowns

$$D \cdot \alpha = X$$

Dictionary Units → D
 Weights → α
 Input data → X

Sparse and Overcomplete Representations 30

30

Dictionary based Representations

- Overcomplete “dictionary”-based representations are linear-composition-based representations with more “atomic building blocks” than the dimensionality of the data

Bases matrix is wide
(more bases than dimensions)

Input

31

Why Dictionary-based Representations?

- Dictionary based representations are semantically more meaningful
- Enable content-based description
 - Bases can capture entire structures in data
 - E.g. notes in music
 - E.g. image structures (such as faces) in images
- Enable content-based processing
 - Reconstructing, separating, denoising, manipulating speech/music signals
 - Coding, compression, etc.
- Statistical reasons: We will get to that shortly..

Sparse and Overcomplete Representations

32

Poll 2

- Dictionary-based representations are similar to vector-quantization based representations, except that the weights vector \mathbf{w} is no longer required to be one-hot
 - True
 - False
- Dictionary based representations are similar to PCA/KLT, except that the dictionary entries may exceed the dimensionality of the data in number and are not restricted to being orthogonal
 - True
 - False

Sparse and Overcomplete Representations

33

Poll 2

- Dictionary-based representations are similar to vector-quantization based representations, except that the weights vector \mathbf{w} is no longer required to be one-hot
 - True
 - False
- Dictionary based representations are similar to PCA/KLT, except that the dictionary entries may exceed the dimensionality of the data in number and are not restricted to being orthogonal
 - True
 - False

Sparse and Overcomplete Representations

34

Problems

- How to obtain the dictionary
 - Which will give us meaningful representations
- How to compute the weights?

Input

35

Problems

- How to obtain the dictionary
 - Which will give us meaningful representations
- How to compute the weights?

Input

36

Quick Linear Algebra Refresher

- Remember, $\#(\text{Basis Vectors}) = \# \text{unknowns}$

$$D \cdot \alpha = X$$

Dictionary entries $\rightarrow D$
 Weights $\rightarrow \alpha$
 Input data $\rightarrow X$

When can we solve for α ?

Sparse and Overcomplete Representations 37

37

Quick Linear Algebra Refresher

$$D \cdot \alpha = X$$

D: full rank

Unique solution

We may have no exact solution

Infinite Solutions

Sparse and Overcomplete Representations 38

38

Quick Linear Algebra Refresher

$$D \cdot \alpha = X$$

D: full rank

Unique solution

We may have no exact solution

Our Case
Infinite Solutions

Sparse and Overcomplete Representations 39

39

Using Pseudo-Inverse?

All points on the red line satisfy $D \cdot \alpha = X$

Point with the smallest ℓ_2 norm

This is equivalent to

minimize $\|\alpha\|_2$ subject to $D\alpha = X$

α will generally be "dense"

Sparse and Overcomplete Representations 40

40

Overcomplete Representation

Unknown α

$D \cdot \alpha = X$

$\#(\text{Basis Vectors}) > \text{dimensions of the input}$

Sparse and Overcomplete Representations 41

41

Representing Data

Using bases that we know...


But no more than $k=4$ bases

Sparse and Overcomplete Representations 42

42

Alternate view: Recall quantization

$$V = \sum_i w_i d_i$$

$$V = D\mathbf{w} \quad \begin{array}{l} |\mathbf{w}| = 1 \\ |\mathbf{w}|_0 = 1 \end{array}$$


- d_i are the “representative” vectors of each cluster
- Restriction: only one of the w_i is 1, the rest are 0
 - $\sum_i w_i = 1$
 - \mathbf{w} is unit length and one-sparse
- What if we let *more* than one entry of \mathbf{w} to be non zero?

43

Overcompleteness and Sparsity


- To solve an overcomplete system of the type:

$$D\alpha = X$$
 - Make assumptions about the data.
 - Suppose, we say that X is composed of no more than a fixed number (k) of “bases” from D ($k \leq \dim(X)$)
 - The term “bases” is an abuse of terminology..
 - Now, we can find the set of k bases that best fit the data point, X .

44

Representing Data

Using bases that we know...




But no more than $k=4$ bases

45

Overcompleteness and Sparsity

Atoms




But no more than $k=4$ bases are “active”

46

Overcompleteness and Sparsity


Atoms



But no more than $k=4$ bases

47

No more than 4 bases



$D \alpha = X$

48

No more than 4 bases

ONLY THE α COMPONENTS CORRESPONDING TO THE 4 KEY DICTIONARY ENTRIES ARE NON-ZERO

α

X

Sparse and Overcomplete Representations

49

No more than 4 bases

ONLY THE α COMPONENTS CORRESPONDING TO THE 4 KEY DICTIONARY ENTRIES ARE NON-ZERO

α

X

MOST OF α IS ZERO!!
 α IS SPARSE

Sparse and Overcomplete Representations

50

Sparsity- Definition

- Sparse representations* are representations that account for most or all information of a signal with a linear combination of a small number of atoms.

(from: www.see.ed.ac.uk/~tblumens/Sparse/Sparse.html)

Sparse and Overcomplete Representations

51

The Sparsity Problem

- We don't really know k
- You are given a signal X
- Assuming X was generated using the dictionary, can we find α that generated it?

Sparse and Overcomplete Representations

52

The Sparsity Problem

- We want to use as few dictionary entries as possible to do this.

$$\begin{array}{l} \underset{\alpha}{\text{Min}} \quad \|\alpha\|_0 \\ \text{s.t.} \quad X = D\alpha \end{array}$$

Sparse and Overcomplete Representations

53

The Sparsity Problem

- We want to use as few dictionary entries as possible to do this.

$$\begin{array}{l} \underset{\alpha}{\text{Min}} \quad \|\alpha\|_0 \\ \text{s.t.} \quad X = D\alpha \end{array}$$

Counts the number of non-zero elements in α

Sparse and Overcomplete Representations

54

The Sparsity Problem

- We want to use **as few dictionary entries** as possible to do this
 - Ockham's razor: Choose the simplest explanation invoking the fewest variables

$$\begin{array}{l} \text{Min}_{\underline{\alpha}} \|\underline{\alpha}\|_0 \\ \text{s.t. } \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

Sparse and Overcomplete Representations

55

55

Poll 3

- Overcomplete representations can be indeterminate
 - True
 - False
- It is essential to impose sparsity to obtain a unique representation in terms of an overcomplete dictionary
 - True
 - False

Sparse and Overcomplete Representations

56

56

Poll 3

- Overcomplete representations can be indeterminate
 - True**
 - False
- It is essential to impose sparsity to obtain a unique representation in terms of an overcomplete dictionary
 - True
 - False**

Sparse and Overcomplete Representations

57

57

The Sparsity Problem

- We want to use as few dictionary entries as possible to do this.

$$\begin{array}{l} \text{Min}_{\underline{\alpha}} \|\underline{\alpha}\|_0 \\ \text{s.t. } \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

How can we solve the above?

Sparse and Overcomplete Representations

58

58

Obtaining Sparse Solutions

- We will look at 2 algorithms:
 - Matching Pursuit (MP)
 - Basis Pursuit (BP)

Sparse and Overcomplete Representations

59

59

Matching Pursuit (MP)

- Greedy algorithm
- Finds an atom in the dictionary that best matches the input signal
- Remove the weighted value of this atom from the signal
- Again, find an atom in the dictionary that best matches the remaining signal.
- Continue till a defined stop condition is satisfied.


Sparse and Overcomplete Representations

60

60

Matching Pursuit

- Find the dictionary atom that best matches the given signal.



Sparse and Overcomplete Representations

61

61

Matching Pursuit

- Remove weighted image to obtain updated signal



Find best match for this signal from the dictionary


Sparse and Overcomplete Representations

62

62

Matching Pursuit

- Find best match for updated signal




Sparse and Overcomplete Representations

63

63

Matching Pursuit

- Find best match for updated signal



Iterate till you reach a stopping condition,
 $\text{norm}(\text{ResidualInputSignal}) < \text{threshold}$

Sparse and Overcomplete Representations

64

64

Matching Pursuit

```

Algorithm Matching Pursuit
Input: Signal:  $f(t)$ .
Output: List of coefficients:  $(a_n, g_{\gamma_n})$ .
Initialization:
 $Rf_1 \leftarrow f(t)$ ;
Repeat
  find  $g_{\gamma_n} \in D$  with maximum inner product  $\langle Rf_n, g_{\gamma_n} \rangle$ ;
   $a_n \leftarrow \langle Rf_n, g_{\gamma_n} \rangle$ ;
   $Rf_{n+1} \leftarrow Rf_n - a_n g_{\gamma_n}$ ;
   $n \leftarrow n+1$ ;
Until stop condition (for example:  $\|Rf_n\| < \text{threshold}$ )

```

From http://en.wikipedia.org/wiki/Matching_pursuit

Sparse and Overcomplete Representations

65

65

Matching Pursuit

- Problems ???

Sparse and Overcomplete Representations

66

66

Matching Pursuit

- Main Problem
 - Computational complexity
 - The entire dictionary has to be searched at every iteration

Sparse and Overcomplete Representations

67

Comparing MP and BP

Matching Pursuit	Basis Pursuit
Hard thresholding (remember the equations)	
Greedy optimization at each step	
Weights obtained using greedy rules	

Sparse and Overcomplete Representations

68

Basis Pursuit (BP)

- Remember,

$$\begin{array}{ll} \text{Min}_{\underline{\alpha}} & \|\underline{\alpha}\|_0 \\ \text{s.t.} & \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

Sparse and Overcomplete Representations

69

Basis Pursuit

- Remember,

$$\begin{array}{ll} \text{Min}_{\underline{\alpha}} & \|\underline{\alpha}\|_0 \\ \text{s.t.} & \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

In the general case, this is intractable

Sparse and Overcomplete Representations

70

Basis Pursuit

- Remember,

$$\begin{array}{ll} \text{Min}_{\underline{\alpha}} & \|\underline{\alpha}\|_0 \\ \text{s.t.} & \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

In the general case, this is intractable
Requires combinatorial optimization

Sparse and Overcomplete Representations

71

Basis Pursuit

- Replace the intractable expression by an expression that is solvable

$$\begin{array}{ll} \text{Min}_{\underline{\alpha}} & \|\underline{\alpha}\|_1 \\ \text{s.t.} & \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

Sparse and Overcomplete Representations

72

Basis Pursuit

- Replace the intractable expression by an expression that is solvable

$$\begin{array}{ll} \underset{\underline{\alpha}}{\text{Min}} & \|\underline{\alpha}\|_1 \\ \text{s.t.} & \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

This will provide identical solutions when \mathbf{D} obeys the **Restricted Isometry Property**.

Sparse and Overcomplete Representations

73

Basis Pursuit

- Replace the intractable expression by an expression that is solvable

$$\begin{array}{ll} \underset{\underline{\alpha}}{\text{Min}} & \|\underline{\alpha}\|_1 \\ \text{s.t.} & \underline{X} = \mathbf{D}\underline{\alpha} \end{array}$$

Objective

Constraint

Sparse and Overcomplete Representations

74

Basis Pursuit

- We can formulate the optimization term as:

$$\underset{\underline{\alpha}}{\text{Min}} \{ \|\underline{X} - \mathbf{D}\underline{\alpha}\|^2 + \lambda \|\underline{\alpha}\|_1 \}$$

Constraint

Objective

Sparse and Overcomplete Representations

75

Basis Pursuit

- We can formulate the optimization term as:

$$\underset{\underline{\alpha}}{\text{Min}} \{ \|\underline{X} - \mathbf{D}\underline{\alpha}\|^2 + \lambda \|\underline{\alpha}\|_1 \}$$

λ is a penalty term on the non-zero elements and promotes sparsity

Sparse and Overcomplete Representations

76

Basis Pursuit

Equivalent to LASSO; for more details, see [this paper by Tibshirani](http://www-stat.stanford.edu/~tibs/ftp/lasso.ps)
<http://www-stat.stanford.edu/~tibs/ftp/lasso.ps>

$$\underset{\underline{\alpha}}{\text{Min}} \{ \|\underline{X} - \mathbf{D}\underline{\alpha}\|^2 + \lambda \|\underline{\alpha}\|_1 \}$$

λ is a penalty term on the non-zero elements and promotes sparsity

Sparse and Overcomplete Representations

77

Basis Pursuit

$$\underset{\underline{\alpha}}{\text{Min}} \{ \|\underline{X} - \mathbf{D}\underline{\alpha}\|^2 + \lambda \|\underline{\alpha}\|_1 \} \quad \frac{\partial \|\underline{\alpha}\|_1}{\partial \alpha_j} = \begin{cases} +1 & \text{at } \alpha_j > 0 \\ [-1, 1] & \text{at } \alpha_j = 0 \\ -1 & \text{at } \alpha_j < 0 \end{cases}$$

- $\|\alpha\|_1$ is not differentiable at $\alpha_j = 0$
- Gradient of $\|\alpha\|_1$ for gradient descent update
- At optimum, following conditions hold

$$\begin{aligned} \nabla_j \|\underline{X} - \mathbf{D}\underline{\alpha}\|^2 + \lambda \text{sign}(\alpha_j) &= 0, & \text{if } |\alpha_j| > 0 \\ \nabla_j \|\underline{X} - \mathbf{D}\underline{\alpha}\|^2 &\leq \lambda, & \text{if } \alpha_j = 0 \end{aligned}$$

Sparse and Overcomplete Representations

78

Basis Pursuit

- There are efficient ways to solve the LASSO formulation.
 - http://web.stanford.edu/~hastie/glmnet_matlab/
- Simplest solution: Coordinate descent algorithms
 - On webpage..

Sparse and Overcomplete Representations


79

L_1 vs L_0

$$\underset{\alpha}{\text{Min}} \|\alpha\|_0$$

$$\text{s.t. } \underline{X} = \underline{D}\alpha$$

Overcomplete set of 6 "bases"



- L_0 minimization
 - Two-sparse solution
 - ANY pair of bases can explain X with 0 error


80

L_1 vs L_0

$$\underset{\alpha}{\text{Min}} \|\alpha\|_1$$

$$\text{s.t. } \underline{X} = \underline{D}\alpha$$

Overcomplete set of 6 "bases"



- L_1 minimization
 - Two-sparse solution
 - All else being equal, the two closest bases are chosen

Sparse and Overcomplete Representations

81

Comparing MP and BP

Matching Pursuit	Basis Pursuit
Hard thresholding	Soft thresholding
(remember the equations)	
Greedy optimization at each step	Global optimization
Weights obtained using greedy rules	Can force N-sparsity with appropriately chosen weights

Sparse and Overcomplete Representations

82

General Formalisms

- L_0 minimization
- L_0 constrained optimization

$$\underset{\alpha}{\text{Min}} \|\alpha\|_0$$

$$\text{s.t. } \underline{X} = \underline{D}\alpha$$

$$\underset{\alpha}{\text{Min}} \|\underline{X} - \underline{D}\alpha\|_2^2$$

$$\text{s.t. } \|\alpha\|_0 < C$$

- L_1 minimization
- L_1 constrained optimization

$$\underset{\alpha}{\text{Min}} \|\alpha\|_1$$

$$\text{s.t. } \underline{X} = \underline{D}\alpha$$

$$\underset{\alpha}{\text{Min}} \|\underline{X} - \underline{D}\alpha\|_2^2$$

$$\text{s.t. } \|\alpha\|_1 < C$$

Sparse and Overcomplete Representations

83

Many Other Methods..

- Iterative Hard Thresholding (IHT)
- CoSAMP
- OMP
- ...

Sparse and Overcomplete Representations

84

Poll 4

- Which of the following are valid ways of obtaining a sparse representation w
 - Minimize $|w|_0$ while constraining $X = Dw$
 - Minimize $|w|_0$ while constraining $X \leq Dw$
 - Minimize $\|X - Dw\|^2 + \lambda |w|_1$
 - Minimize $|w|_2$ while constraining $X \leq Dw$

Sparse and Overcomplete Representations

85

85

Poll 4

- Which of the following are valid ways of obtaining a sparse representation w
 - Minimize $|w|_0$ while constraining $X = Dw$
 - Minimize $|w|_0$ while constraining $X \leq Dw$
 - Minimize $\|X - Dw\|^2 + \lambda |w|_1$
 - Minimize $|w|_2$ while constraining $X \leq Dw$


Sparse and Overcomplete Representations

86

86

Problems

- How to obtain the dictionary
 - Which will give us meaningful representations
- How to compute the weights?



87

Trivial Solution

- $D = \text{Training data}$
- Impractical in most situations
 - Popular approach: sample random vectors from training data


Sparse and Overcomplete Representations

88

88

Dictionaries: Compressive Sensing

- Just random vectors!



Sparse and Overcomplete Representations

89

89

More Structured ways of Constructing Dictionaries


- Dictionary entries must be structurally "meaningful"
 - Represent true compositional units of data
- Have already encountered two ways of building dictionaries
 - NMF for non-negative data
 - K-means ..

Sparse and Overcomplete Representations

90

90

K-Means for Composing Dictionaries



Train the codebook from training data using K-means


- Every vector is approximated by the centroid of the cluster it falls into
- Cluster means are “codebook” entries
 - Dictionary entries
 - Also compositional units the compose the data

Sparse and Overcomplete Representations 91

91

K-Means for Dictionaries

Each column is a codeword (centroid) from the codebook




- α must be 1 sparse
- Only α entry must 1

$\|\alpha\|_0 = 1$ $\|\alpha\|_1 = 1$

Sparse and Overcomplete Representations 92

92

K-Means




- Learn Codewords to minimize the total squared length of the training vectors from the closest codeword

Sparse and Overcomplete Representations 93

93

Length-unconstrained K-Means for Dictionaries

Each column is a codeword (centroid) from the codebook




- α must be 1 sparse
- No restriction on α value

$\|\alpha\|_0 = 1$

Sparse and Overcomplete Representations 94

94

SVD K-Means



- Learn Codewords to minimize the total squared *projection error* of the training vectors from the closest codeword


Sparse and Overcomplete Representations 95

95

SVD K-means


1. Initialize a set of (unit-length) centroids randomly
2. For each data point x , find the projection from the centroid for each cluster
 - $p_{cluster} = |x^T m_{cluster}|$
3. Put data point in the cluster of the closest centroid
 - Cluster for which $p_{cluster}$ is maximum
4. When all data points are clustered, recompute centroids

$m_{cluster} = \text{Principal Eigenvector}(\{x \mid x \in cluster\})$




Sparse and Overcomplete Representations 96


96




97




98




99



100



101



102

Formalizing

Given training data

$$\{X_1, X_2, \dots, X_T\}$$

We want to find a dictionary D , such that

$$D\alpha_i = X_i$$

With α_i sparse

Sparse and Overcomplete Representations

103

103

Formalizing

Two objectives:

- Approximation $\|D\alpha_i - X_i\|$
- Sparsity in coefficients $\|\alpha_i\|_1$

$$\min_{D, \alpha_i} \sum_{i=1}^T \|X_i - D\alpha_i\|^2 + \|\alpha_i\|_1$$

NON-Convex!!!

Sparse and Overcomplete Representations

104

104

An iterative method

- Given D , estimate α_i to get sparse solution
 - We can use any method

$$\min_{\alpha_i} \sum_{i=1}^T \|X_i - D\alpha_i\|^2 + \|\alpha_i\|_1$$

- Given α_i , estimate D

$$\min_D \sum_{i=1}^T \|X_i - D\alpha_i\|^2$$

Difficult!

Sparse and Overcomplete Representations

105

105

K SVD

- Initialize Codebook

$D =$

1. For every vector, compute K-sparse alphas
 - Using any pursuit algorithm

$\alpha =$

Sparse and Overcomplete Representations

106

106

K-SVD

2. For each codeword (k):

- For each vector x that used k
 - Subtract the contribution of all other codewords to obtain $e_k(x)$
 - Codeword-specific residual
- Compute the principal Eigen vector of $\{e_k(x)\}$

3. Return to step 1

$D_j, j \neq 1$

$D =$

$\alpha =$

$$e_k(x) = x - \sum_{j \neq k} \alpha_j D_j$$

Sparse and Overcomplete Representations

107

107

K-SVD

- Termination of each iteration: Updated dictionary
- Conclusion: A dictionary where any data vector can be composed of at most K dictionary entries
 - More generally, sparse composition

Sparse and Overcomplete Representations

108

108

K-SVD algorithm (skip)

Initialization : Set the random normalized dictionary matrix $\mathbf{D}^{(0)} \in \mathbb{R}^{n \times K}$. Set $J = 1$. Repeat until convergence,
Sparse Coding Stage: Use any pursuit algorithm to compute \mathbf{x}_i for $i = 1, 2, \dots, N$

$$\min_{\mathbf{x}} \{ \|\mathbf{y}_i - \mathbf{D}\mathbf{x}\|_2^2 \} \quad \text{subject to} \quad \|\mathbf{x}\|_0 \leq T_0.$$

Codebook Update Stage: For $k = 1, 2, \dots, K$

- Define the group of examples that use \mathbf{d}_k ,
 $\omega_k = \{i | 1 \leq i \leq N, \mathbf{x}_i(k) \neq 0\}$.
- Compute

$$\mathbf{E}_k = \mathbf{Y} - \sum_{j \neq k} \mathbf{d}_j \mathbf{x}_j^T$$


- Restrict \mathbf{E}_k by choosing only the columns corresponding to those elements that initially used \mathbf{d}_k in their representation, and obtain \mathbf{E}_k^R .
- Apply SVD decomposition $\mathbf{E}_k^R = \mathbf{U}\mathbf{\Delta}\mathbf{V}^T$. Update:
 $\mathbf{d}_k = \mathbf{u}_1, \mathbf{x}_k^R = \mathbf{\Delta}(1, 1) \cdot \mathbf{v}_1$

Set $J = J + 1$. Sparse and Overcomplete Representations

109


Problems

- How to obtain the dictionary
 – Which will give us meaningful representations
- How to compute the weights?



110

So how does that work




- In case you forgot this music...
- 975 vectors (1025 dimensions)
- $N=12, K=5$

Sparse and Overcomplete Representations

111

K-SVD bases



Sparse and Overcomplete Representations

112

112

Applications of Sparse Representations

- Many many applications
 - Signal representation
 - Statistical modelling
 - ..
 - We've seen one: Compressive sensing
- Another popular use
 - **Denoising**

Sparse and Overcomplete Representations

113

113

Denoising

- As the name suggests, remove noise!

Sparse and Overcomplete Representations

114

114

Denoising


- As the name suggests, remove noise!
- We will look at image denoising as an example

Sparse and Overcomplete Representations

115

115

A toy example



Sparse and Overcomplete Representations


116

116

A toy example

$$D = [I \ G]$$

I Identity matrix
 G Translation of a Gaussian pulse




Sparse and Overcomplete Representations

117

117

Image Denoising

- Here's what we want





Sparse and Overcomplete Representations

118

118

Image Denoising

- Here's what we want



Sparse and Overcomplete Representations

119

119

Image Denoising

- Here's what we want



Sparse and Overcomplete Representations

120

120

The Image Denoising Problem


- Given an image
- Remove Gaussian additive noise from it

Sparse and Overcomplete Representations

121

121

Image Denoising



Sparse and Overcomplete Representations

122

122

Image Denoising

- Remove the noise from \mathbf{Y} , to obtain \mathbf{X} as best as possible.

Sparse and Overcomplete Representations

123

123

Image Denoising

- Remove the noise from \mathbf{Y} , to obtain \mathbf{X} as best as possible
- Using sparse representations over learned dictionaries

Sparse and Overcomplete Representations

124

124

Image Denoising

- Remove the noise from \mathbf{Y} , to obtain \mathbf{X} as best as possible
- Using sparse representations over learned dictionaries
- We will *learn* the dictionaries

Sparse and Overcomplete Representations

125

125

Image Denoising

- Remove the noise from \mathbf{Y} , to obtain \mathbf{X} as best as possible
- Using sparse representations over learned dictionaries
- We will *learn* the dictionaries
- What data will we use? *The corrupted image itself!*

Sparse and Overcomplete Representations

126

126

Image Denoising

- We use the data to be denoised to learn the dictionary.
- Training and denoising become an iterated process.
- We use image patches of size $\sqrt{n} \times \sqrt{n}$ pixels (i.e. if the image is 64x64, patches are 8x8)

Sparse and Overcomplete Representations

127

127

Image Denoising

- The data dictionary D
 - Size = $n \times k$ ($k > n$)
 - This is known and fixed, to start with
 - Every image patch can be sparsely represented using D

Sparse and Overcomplete Representations

128

128

Image Denoising

- Recall our equations from before.
- We want to find α so as to minimize the value of the equation below:

$$\underset{\alpha}{\text{Min}} \{ \|X - D\alpha\|^2 + \lambda \|\alpha\|_0 \}$$

$$\underset{\alpha}{\text{Min}} \{ \|X - D\alpha\|^2 + \lambda \|\alpha\|_1 \}$$

Sparse and Overcomplete Representations

129

129

Image Denoising

$$\underset{\alpha}{\text{Min}} \{ \|X - D\alpha\|^2 + \lambda \|\alpha\|_1 \}$$

- In the above, X is a patch.

Sparse and Overcomplete Representations

130

130

Image Denoising

$$\underset{\alpha}{\text{Min}} \{ \|X - D\alpha\|^2 + \lambda \|\alpha\|_1 \}$$

- In the above, X is a patch.
- If the larger image is fully expressed by the every patch in it, how can we go from patches to the image?

Sparse and Overcomplete Representations

131

131

Image Denoising

$$\underset{\alpha_{ij} \rightarrow X}{\text{Min}} \{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \}$$

Sparse and Overcomplete Representations

132

132

Image Denoising

$$\underset{\alpha_{ij}, X}{\text{Min}} \left\{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \right\}$$

(X - Y) is the error between the input and denoised image. μ is a penalty on the error.

Sparse and Overcomplete Representations 133

133

Image Denoising

$$\underset{\alpha_{ij}, X}{\text{Min}} \left\{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \right\}$$

Error bounding in each patch
 - R_{ij} selects the (ij)th patch
 - Terms in summation = no. of patches

Sparse and Overcomplete Representations 134

134

Image Denoising

$$\underset{\alpha_{ij}, X}{\text{Min}} \left\{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \right\}$$

λ forces sparsity

Sparse and Overcomplete Representations 135

135

Image Denoising

- But, we don't **"know"** our dictionary D.
- We want to estimate D as well.

Sparse and Overcomplete Representations 136

136

Image Denoising

- But, we don't **"know"** our dictionary D.
- We want to estimate D as well.

$$\underset{D, \alpha_{ij}, X}{\text{Min}} \left\{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \right\}$$

We can use the previous equation itself!!!

Sparse and Overcomplete Representations 137

137

Image Denoising

$$\underset{D, \alpha_{ij}, X}{\text{Min}} \left\{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \right\}$$

How do we estimate all 3 at once?

Sparse and Overcomplete Representations 138

138

Image Denoising

$$\underset{D, \alpha_{ij}, X}{Min} \{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \}$$

How do we estimate all 3 at once?

We cannot estimate them at the same time!

Sparse and Overcomplete Representations

139

139

Image Denoising

$$\underset{D, \alpha_{ij}, X}{Min} \{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \}$$

How do we estimate all 3 at once?

Fix 2, and find the optimal 3rd.

Sparse and Overcomplete Representations

140

140

Image Denoising

$$\underset{D, \alpha_{ij}, X}{Min} \{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \}$$

Initialize X = Y

Sparse and Overcomplete Representations

141

141

Image Denoising

$$\underset{\alpha_{ij}}{Min} \{ \mu \|X - Y\|_2^2 + \sum_{ij} \|R_{ij}X - D\alpha_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\alpha_{ij}\|_0 \}$$

Initialize X = Y, initialize D

You know how to solve the remaining portion for α – MP, BP!

Sparse and Overcomplete Representations

142

142

Image Denoising

- Now, update the dictionary D.
- Update D one column at a time, following the [K-SVD algorithm](#)
- K-SVD maintains the sparsity structure

Sparse and Overcomplete Representations

143

143

Image Denoising


- Now, update the dictionary D.
- Update D one column at a time, following the [K-SVD algorithm](#)
- K-SVD maintains the sparsity structure
- Iteratively update α and D

Sparse and Overcomplete Representations

144

144

Image Denoising



Learned Dictionary for Face Image denoising

From: M. Elad and M. Aharon, *Image denoising via learned dictionaries and sparse representation*, CVPR, 2006.

Sparse and Overcomplete Representations

145

Image Denoising

$$\underset{\underline{X}}{\text{Min}} \{ \mu \|\underline{X} - Y\|_2^2 + \sum_{ij} \|\underline{R}_{ij} \underline{X} - \underline{D} \underline{\alpha}_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\underline{\alpha}_{ij}\|_0 \}$$

→ Const. wrt X

We know D and α

The quadratic term above has a closed-form solution

Sparse and Overcomplete Representations

146

Image Denoising

$$\underset{\underline{X}}{\text{Min}} \{ \mu \|\underline{X} - Y\|_2^2 + \sum_{ij} \|\underline{R}_{ij} \underline{X} - \underline{D} \underline{\alpha}_{ij}\|_2^2 + \sum_{ij} \lambda_{ij} \|\underline{\alpha}_{ij}\|_0 \}$$

→ Const. wrt X

We know D and α

$$\underline{X} = (\mu I + \sum_{ij} \underline{R}_{ij}^T \underline{R}_{ij})^{-1} (\mu Y + \sum_{ij} \underline{R}_{ij}^T \underline{D} \underline{\alpha}_{ij})$$

Sparse and Overcomplete Representations

147

Image Denoising

- Summarizing... We wanted to obtain 3 things

Sparse and Overcomplete Representations

148

Image Denoising

- Summarizing... We wanted to obtain 3 things

- Weights α
- Dictionary D
- Denoised Image X

Sparse and Overcomplete Representations

149

Image Denoising

- Summarizing... We wanted to obtain 3 things

- Weights α – Your favorite pursuit algorithm
- Dictionary D – Using K-SVD
- Denoised Image X

Sparse and Overcomplete Representations

150

Image Denoising

- Summarizing... We wanted to obtain 3 things
 - Weights α – Your favorite pursuit algorithm
 - Dictionary D – Using K-SVD
 - Denoised Image X

Sparse and Overcomplete Representations

151

151

Image Denoising

- Summarizing... We wanted to obtain 3 things
 - Weights α
 - Dictionary D
 - Denoised Image X - Closed form solution


Sparse and Overcomplete Representations

152

152

Image Denoising

- Here's what we want



Sparse and Overcomplete Representations

153

153

Image Denoising

- Here's what we want



Sparse and Overcomplete Representations

154

154

Comparing to Other Techniques

Non-Gaussian data

PCA of ICA Which is which?

Images from Lewicki and Sejnowski, *Learning Overcomplete Representations*, 2000.

Sparse and Overcomplete Representations

155

155

Comparing to Other Techniques

Non-Gaussian data

PCA


ICA

Images from Lewicki and Sejnowski, *Learning Overcomplete Representations*, 2000.


Sparse and Overcomplete Representations

156


156



157



158



159