

Started on Thursday, 6 August 2026, 10:15 AM

State Finished

Completed on Thursday, 6 August 2026, 10:58 AM

Time taken 43 mins 7 secs

Grade 10.00 out of 10.00 (100%)

Question **1**

Correct

Mark 1.00 out of 1.00

Insert a student with RollNo **201**, Name **David Lee**, Gender **M**, Subject **Physics**, and MARKS **92** into the **Student_details** table.

For example:

Test	Result				
SELECT * FROM Student_details WHERE RollNo = 201;	RollNo	Name	Gender	Subject	
	MARKS				
	-----	-----	-----	-----	--
	201	David Lee	M	Physics	92

Answer: (penalty regime: 0 %)

```
1 INSERT INTO student_details
2 VALUES(201,'David Lee','M','Physics',92);
```

	Test	Expected			Got	
✓	SELECT * FROM Student_details WHERE RollNo = 201;	RollNo	Name		RollNo	
		Gender	Subject		Gender	
		MARKS			MARKS	
		-----	-----	---	-----	---
		-----	-----	-----	-----	-----
		----			-----	
		201	David Lee	M	201	David Lee
		Physics	92		Physics	92

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Write an SQL query to change the name of the column `id` to `employee_id` in the table `employee`.

For example:

Test	Result					
pragma table_info('employee');	cid	name	type	notnull	dflt_value	pk
	-----	-----	-----	-----	-----	----

	0	employee_id	integer	0		0
	1	salary	number	0		0

Answer: (penalty regime: 0 %)

```
1 ALTER TABLE employee
2 RENAME COLUMN id TO employee_id;
```

	Test	Expected		Got		
✓	pragma table_info('employee');	cid	name	cid	name	✓
		type	notnull	type	notnull	
		dflt_value	pk	dflt_value	pk	
		-----	-----	-----	-----	
		-----		-----		
		0	employee_id	0	employee_id	
		integer	0	integer	0	
		0		0		
		1	salary	1	salary	
		number	0	number	0	
		0		0		

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Write a SQL Query for inserting the below values in the table Customers

ID	NAME	AGE	ADDRESS	SALARY
-----	-----	---	-----	-----
1	Ramesh	32	Ahmedabad	2000
2	Khilan	25	Delhi	1500
3	Kaushik	23	Kota	2000

For example:

Test	Result				
SELECT * FROM Customers;	ID	NAME	AGE	ADDRESS	SALARY
	-----	-----	-----	-----	-----
	1	Ramesh	32	Ahmedabad	2000
	2	Khilan	25	Delhi	1500
	3	Kaushik	23	Kota	2000

Answer: (penalty regime: 0 %)

```
1 |INSERT INTO customers
2 |VALUES(1,'Ramesh',32,'Ahmedabad',2000);
3 |INSERT INTO customers
4 |VALUES(2,'Khilan',25,'Delhi',1500);
5 |INSERT INTO customers
6 |VALUES(3,'Kaushik',23,'Kota',2000);
```

	Test	Expected			Got			
✓	SELECT * FROM Customers;	ID	NAME	AGE	ID	NAME	AGE	✓
		ADDRESS	SALARY		ADDRESS	SALARY		
		-----	-----	-----	-----	-----	-----	
		1	Ramesh	32	1	Ramesh	32	
		Ahmedabad	2000		Ahmedabad	2000		
		2	Khilan	25	2	Khilan	25	
		Delhi	1500		Delhi	1500		
		3	Kaushik	23	3	Kaushik	23	
		Kota	2000		Kota	2000		

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of 1.00

Create a table named **Shipments** with the following constraints:

- **ShipmentID** as INTEGER should be the primary key.
- **ShipmentDate** as DATE.
- **SupplierID** as INTEGER should be a foreign key referencing **Suppliers(SupplierID)**.
- **OrderID** as INTEGER should be a foreign key referencing **Orders(OrderID)**.

For example:

Test	Result
INSERT INTO Shipments (ShipmentID, ShipmentDate, SupplierID, OrderID) VALUES (2, '2024-08-03', 99, 1);	Error: FOREIGN KEY constraint failed

Answer: (penalty regime: 0 %)

```
1 CREATE TABLE Shipments(  
2   ShipmentID INTEGER PRIMARY KEY,  
3  
4   ShipmentDate DATE,  
5   SupplierID INTEGER,  
6   OrderID INTEGER,  
7   FOREIGN KEY (SupplierID) REFERENCES Suppliers(SupplierID),  
8   FOREIGN KEY (OrderID) REFERENCES Orders(OrderID)  
9 );
```

	Test	Expected	Got	
✓	INSERT INTO Shipments (ShipmentID, ShipmentDate, SupplierID, OrderID) VALUES (2, '2024-08-03', 99, 1);	Error: FOREIGN KEY constraint failed	Error: FOREIGN KEY constraint failed	✓
✓	INSERT INTO Shipments (ShipmentID, ShipmentDate, SupplierID, OrderID) VALUES (3, '2024-08-04', 1, 99);	Error: FOREIGN KEY constraint failed	Error: FOREIGN KEY constraint failed	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Write a SQL query to **Add a new column Country as text in the Student_details table.**

Sample table: Student_details

cid	name	type	notnull	dflt_value	pk
0	RollNo	int	0		1
1	Name	VARCH	1	0	
2	Gender	TEXT	1	0	
3	Subject	VARCH	0	0	
4	MARKS	INT (	0	0	

For example:

Test	Result				
pragma table_info('Student_details');	cid	name	type	notnull	dflt_value
	pk				
	-----	-----	-----	-----	-----

	0	RollNo	int	0	
	1				
	1	Name	VARCHAR(10	1	
	0				
	2	Gender	TEXT	1	
	0				
	3	Subject	VARCHAR(30	0	
	0				
	4	MARKS	INT (3)	0	
0					
5	Country	TEXT	0		
0					

Answer: (penalty regime: 0 %)

```
1 ALTER TABLE Student_details
2 ADD COLUMN Country TEXT;
```

	Test	Expected		Got		
✓	pragma table_info('Student_details');	cid	name	cid	name	✓
		type	notnull	type	notnull	
		dflt_value	pk	dflt_value	pk	
		-----	-----	-----	-----	
		-----	-----	-----	-----	
		-----	-----	-----	-----	
		0	RollNo	0	RollNo	
		int	0	int	0	
		1		1		
		1	Name	1	Name	
		VARCHAR(10	1	VARCHAR(10	1	
		0		0		
		2	Gender	2	Gender	
		TEXT	1	TEXT	1	
		0		0		
		3	Subject	3	Subject	
		VARCHAR(30	0	VARCHAR(30	0	
		0		0		
		4	MARKS	4	MARKS	
		INT (3)	0	INT (3)	0	
		0		0		
		5	Country	5	Country	
		TEXT	0	TEXT	0	
		0		0		

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Insert the below data into the **Employee** table, allowing the **Department** and **Salary** columns to take their default values.

EmployeeID	Name	Position
-----	-----	-----
4	Emily White	Analyst

Note: The Department and Salary columns will use their default values.

For example:

Test	Result		
SELECT EmployeeID, Name, Position FROM Employee;	EmployeeID	Name	Position
	-----	-----	-----
	4	Emily White	Analyst

Answer: (penalty regime: 0 %)

```
1 INSERT INTO Employee(EmployeeID,Name,Position)
2 VALUES(4,'Emily White','Analyst');
```

	Test	Expected	Got	
✓	SELECT EmployeeID, Name, Position FROM Employee;	EmployeeID Name Position ----- ----- -- ----- 4 Emily White Analyst	EmployeeID Name Position ----- ----- -- ----- 4 Emily White Analyst	✓
✓	SELECT count(*) FROM Employee ;	count(*) ----- 1	count(*) ----- 1	✓

Passed all tests! ✓

Create a table named **Departments** with the following columns:

- **DepartmentID** as **INTEGER**
- **DepartmentName** as **TEXT**

For example:

Test	Result
pragma table_info('Departments');	cid name type notnull dflt_value pk ----- ----- 0 DepartmentID INTEGER 0 0 1 DepartmentName TEXT 0 0

Answer: (penalty regime: 0 %)

```

1 CREATE TABLE Departments(
2   DepartmentID  INTEGER,
3   DepartmentName TEXT
4 );

```

	Test	Expected	Got	
✓	pragma table_info('Departments');	cid name type notnull dflt_value pk ----- ----- 0 DepartmentID INTEGER 0 0 1 DepartmentName TEXT 0 0	cid name type notnull dflt_value pk ----- ----- 0 DepartmentID INTEGER 0 0 1 DepartmentName TEXT 0 0	✓
✓	INSERT INTO Departments (DepartmentID) VALUES (2); select * from Departments;	Depar DepartmentName ----- 2	Depar DepartmentName ----- 2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Create a new table named **products** with the following specifications:

- **product_id** as INTEGER and primary key.
- **product_name** as TEXT and not NULL.
- **list_price** as DECIMAL (10, 2) and not NULL.
- **discount** as DECIMAL (10, 2) with a default value of 0 and not NULL.
- A CHECK constraint at the table level to ensure:
 - **list_price** is greater than or equal to **discount**
 - **discount** is greater than or equal to 0
 - **list_price** is greater than or equal to 0

For example:

Test	Result
<pre>INSERT INTO products (product_id, product_name, list_price) VALUES (2, 'Product B', 50.00); SELECT * FROM products;</pre>	<pre>product_id product_name list_price discount ----- 2 Product B 50 0</pre>

Answer: (penalty regime: 0 %)

```
1 CREATE TABLE products(
2   product_id INTEGER PRIMARY KEY,
3   product_name TEXT NOT NULL,
4   list_price DECIMAL(10,2) NOT NULL,
5   discount DECIMAL(10,2) DEFAULT 0 NOT NULL,
6   CHECK(
7     list_price >= discount AND
8     discount >=0 AND
9     list_price >=0
10  )
11 );
```

	Test	Expected	Got	
✓	<pre>INSERT INTO products (product_id, product_name, list_price) VALUES (2, 'Product B', 50.00); SELECT * FROM products;</pre>	<pre>product_id product_name list_price discount ----- 2 Product B 50 0</pre>	<pre>product_id product_name list_price discount ----- 2 Product B 50 0</pre>	✓
✓	<pre>INSERT INTO products (product_id, product_name, list_price, discount) VALUES (3, 'Product C', 20.00, 30.00);</pre>	Error: CHECK constraint failed: products	Error: CHECK constraint failed: products	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Create a table named **Attendance** with the following constraints:

- **AttendanceID** as INTEGER should be the primary key.
- **EmployeeID** as INTEGER should be a foreign key referencing **Employees(EmployeeID)**.
- **AttendanceDate** as DATE.
- **Status** as TEXT should be one of 'Present', 'Absent', 'Leave'.

For example:

Test	Result
INSERT INTO Attendance (AttendanceID, EmployeeID, AttendanceDate, Status) VALUES (1, 1, '2024-08-01', 'Present'); SELECT * FROM Attendance;	AttendanceID EmployeeID AttendanceDate Status ----- 1 1 2024-08-01 Present

Answer: (penalty regime: 0 %)

```
1 CREATE TABLE Attendance(  
2 AttendanceID INTEGER PRIMARY KEY,  
3 EmployeeID INTEGER,  
4 AttendanceDate DATE,  
5 Status TEXT CHECK(Status IN('Present', 'Absent', 'Leave')),  
6 FOREIGN KEY (EmployeeID) REFERENCES Employees(EmployeeID)  
7 );
```

	Test	Expected	Got	
✓	INSERT INTO Attendance (AttendanceID, EmployeeID, AttendanceDate, Status) VALUES (1, 1, '2024-08-01', 'Present'); SELECT * FROM Attendance;	AttendanceID EmployeeID AttendanceDate Status ----- 1 1 2024-08-01 Present	AttendanceID EmployeeID AttendanceDate Status ----- 1 1 2024-08-01 Present	✓
✓	INSERT INTO Attendance (AttendanceID, EmployeeID, AttendanceDate, Status) VALUES (3, 99, '2024-08-03', 'Absent');	Error: FOREIGN KEY constraint failed	Error: FOREIGN KEY constraint failed	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Create a table named **Orders** with the following columns:

- **OrderID** as **INTEGER**
- **OrderDate** as **TEXT**
- **CustomerID** as **INTEGER**

For example:

Test	Result					
pragma table_info('Orders');	cid	name	type	notnull	dflt_value	pk
	---	-----	-----	-----	-----	-----
	0	OrderID	INTEGER	0		0
	1	OrderDate	TEXT	0		0
	2	CustomerID	INTEGER	0		0

Answer: (penalty regime: 0 %)

```
1 CREATE TABLE Orders(  
2 OrderID INTEGER,  
3 OrderDate TEXT,  
4 CustomerID INTEGER  
5 );  
6
```

	Test	Expected	Got	
✓	pragma table_info('Orders');	cid name type notnull dflt_value pk --- --- 0 OrderID INTEGER 0 0 1 OrderDate TEXT 0 0 2 CustomerID INTEGER 0 0	cid name type notnull dflt_value pk --- --- 0 OrderID INTEGER 0 0 1 OrderDate TEXT 0 0 2 CustomerID INTEGER 0 0	✓
✓	INSERT INTO Orders (OrderID, OrderDate, CustomerID) VALUES (1, '2024-08-01', 101); select * from Orders;	Orde OrderDate CustomerID --- --- 1 2024-08-01 101	Orde OrderDate CustomerID --- --- 1 2024-08-01 101	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.