

Started on Thursday, 13 August 2026, 10:56 AM

State Finished

Completed on Thursday, 13 August 2026, 11:40 AM

Time taken 44 mins 23 secs

Grade **90.00** out of 100.00

Question **1**

Correct

Mark 5.00 out of 5.00

Write a query to fetch details of employees with the address as "DELHI(DEL)" from EmployeeInfo table.

EmpID	EmpFname	EmpLname	Department	Project	Address	DOB	Gender
1	Sanjay	Mehra	HR	P1	Hyderabad(HYD)	01/12/1976	M
2	Ananya	Mishra	Admin	P2	Delhi(DEL)	02/05/1968	F

For example:

Result							
EmpID	EmpFname	EmpLname	Department	Project	Address	DOB	Gender
2	Ananya	Mishra	Admin	P2	Delhi(DEL)	1968-05-02	F
5	Ankit	Kapoor	Admin	P2	Delhi(DEL)	1994-07-03	M

Answer: (penalty regime: 0 %)

```
1 SELECT *
2 FROM EmployeeInfo
3 WHERE Address LIKE 'DELHI(DEL)';
```

	Expected					Got				
✓	EmpID	EmpFname	EmpLname	Department	DOB	EmpID	EmpFname	EmpLname	DOB	✓
	Project		Address			Project		Address		
	Gender					Gender				
	-----	-----	-----	-----	-----	-----	-----	-----	-----	
	-----	-----	-----	-----	-----	-----	-----	-----	-----	
	-----	-----	-----	-----	-----	-----	-----	-----	-----	
	2	Ananya	Mishra	Admin		2	Ananya	Mishra	Admin	
	P2	Delhi(DEL)	1968-05-02	F		P2	Delhi(DEL)	1968-05-02	F	
	5	Ankit	Kapoor	Admin		5	Ankit	Kapoor	Admin	
	P2	Delhi(DEL)	1994-07-03	M		P2	Delhi(DEL)	1994-07-03	M	

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a query to fetch all the records from the EmployeeInfo table ordered by EmpLname in descending order and Department in the ascending order.

EmpID	EmpFname	EmpLname	Department	Project	Address	DOB	Gender
1	Sanjay	Mehra	HR	P1	Hyderabad(HYD)	01/12/1976	M
2	Ananya	Mishra	Admin	P2	Delhi(DEL)	02/05/1968	F

For example:

Result							
EmpID	EmpFname	EmpLname	Department	Project	Address	DOB	Gender
--							
4	Sonia	Kulkarni	HR	P1	Hyderabad(HYD)	1992-05-02	F
1	Sanjay	Mehra	HR	P1	Hyderabad(HYD)	1976-12-01	M
3	Rohan	Diwan	Account	P3	Mumbai(BOM)	1980-01-01	M
5	Ankit	Kapoor	Admin	P2	Delhi(DEL)	1994-07-03	M
2	Ananya	Mishra	Admin	P2	Delhi(DEL)	1968-05-02	F

Answer: (penalty regime: 0 %)

```

1  SELECT
2      EmpID,
3      EmpFname,
4      EmpLname,
5      Department,
6      Project,
7      Address,
8      DOB,
9      Gender
10 FROM
11     EmployeeInfo
12 ORDER BY
13     Department ASC,
14     EmpLname DESC;
15

```

	Expected				Got				
✗	EmpID	EmpFname	EmpLname		EmpID	EmpFname	EmpLname		✗
	Department	Project	Address		Department	Project	Address		
	DOB	Gender			DOB	Gender			
	-----	-----	-----	-----	-----	-----	-----	-----	
	--				--				
	4	Sonia	Kulkarni	HR	3	Rohan	Diwan		
	P1	Hyderabad(HYD)	1992-05-02	F	Account	P3	Mumbai(BOM)		
	1	Sanjay	Mehra	HR	1980-01-01	M			
	P1	Hyderabad(HYD)	1976-12-01	M	2	Ananya	Mishra		
	3	Rohan	Diwan		Admin	P2	Delhi(DEL)		
	Account	P3	Mumbai(BOM)		1968-05-02	F			
	1980-01-01	M			5	Ankit	Kapoor		
	5	Ankit	Kapoor	Admin	Admin	P2	Delhi(DEL)		
	P2	Delhi(DEL)	1994-07-03	M	1994-07-03	M			
	2	Ananya	Mishra	Admin	1	Sanjay	Mehra	HR	
	P2	Delhi(DEL)	1968-05-02	F	P1	Hyderabad(H	1976-12-01	M	
					4	Sonia	Kulkarni	HR	
					P1	Hyderabad(H	1992-05-02	F	

Some hidden test cases failed, too.

Your code must pass all tests to earn any marks. Try again.

Show differences

Incorrect

Marks for this submission: 0.00/5.00.

Write a SQL query to Delete customers from 'customer' table where 'CUST_NAME' contains the substring 'Holmes'.

Sample table: Customer

CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE
C00013	Holmes	London	London	UK	2	6000.00	5000.00	7000.00	4000.00	BBBBBBB	A003
C00001	Micheal	New York	New York	USA	2	3000.00	5000.00	2000.00	6000.00	CCCCCCC	A008
C00020	Albert	New York	New York	USA	3	5000.00	7000.00	6000.00	6000.00	BBBBBBSB	A008

For example:

Test	Result																																				
select changes();	<table><tr><th>CUST_CODE</th><th>CUST_NAME</th><th>CUST_CITY</th><th>WORKING_AREA</th><th>CUST_COUNTRY</th><th>GRADE</th><th>OPENING_AMT</th><th>RECEIVE_AMT</th><th>PAYMENT_AMT</th><th>OUTSTANDING_AMT</th><th>PHONE_NO</th><th>AGENT_CODE</th></tr><tr><td colspan="12">-----</td></tr><tr><td>C00013</td><td>Holmes</td><td>London</td><td>London</td><td>UK</td><td>2</td><td>6000</td><td>5000</td><td>7000</td><td>4000</td><td>BBBBBBB</td><td>A003</td></tr></table> changes() ----- 1	CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE	-----												C00013	Holmes	London	London	UK	2	6000	5000	7000	4000	BBBBBBB	A003
CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE																										

C00013	Holmes	London	London	UK	2	6000	5000	7000	4000	BBBBBBB	A003																										

Answer: (penalty regime: 0 %)

```
1 | DELETE FROM customer
2 | WHERE CUST_NAME LIKE '%Holmes%';
3 |
```

	Test	Expected	Got	
✓	select changes();	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- ----- ----- - C00013 Holmes London London UK 2 6000 5000 7000 4000 BBBB BBB A003 changes() ----- 1	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- ----- ----- - C00013 Holmes London London UK 2 6000 5000 7000 4000 BBBB BBB A003 changes() ----- 1	✓
✓	select changes();	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- ----- ----- ----- C00013 SherlockHolmess London London UK 2 6000 5000 7000 4000 BBBB BBB A003 C00024 SherlockHolmess London London UK 2 4000 9000 7000 6000 FSDDSD F A006 C00015 SherlockHolmess London London UK 1 6000 8000 3000 11000 GFSGERS A003 C00023 SherlockHolmess London London UK 0 4000 6000 7000 3000 AAAABAA A006 changes() ----- 4	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- ----- ----- ----- C00013 SherlockHolmess London London UK 2 6000 5000 7000 4000 BBBB BBB A003 C00024 SherlockHolmess London London UK 2 4000 9000 7000 6000 FSDDSD F A006 C00015 SherlockHolmess London London UK 1 6000 8000 3000 11000 GFSGERS A003 C00023 SherlockHolmess London London UK 0 4000 6000 7000 3000 AAAABAA A006 changes() ----- 4	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL statement to change the **email** column of employees table with 'Unavailable' for all employees in **employees** table.

Employees table

employee_id
first_name
last_name
email
phone_number
hire_date
job_id
salary
commission_pct
manager_id
department_id

For example:

Test	Result		
SELECT EMPLOYEE_ID,FIRST_NAME,EMAIL FROM EMPLOYEES LIMIT 2 ;	EMPLOYEE_ID	FIRST_NAME	EMAIL
	-----	-----	-----
	100	Steven	Unavailable
	101	Neena	Unavailable

Answer: (penalty regime: 0 %)

1	UPDATE employees
2	SET email = 'Unavailable';

	Test	Expected	Got																															
✓	SELECT EMPLOYEE_ID,FIRST_NAME,EMAIL FROM EMPLOYEES LIMIT 2;	<table><thead><tr><th>EMPLOYEE_ID</th><th>FIRST_NAME</th><th>EMAIL</th></tr></thead><tbody><tr><td>-----</td><td>-----</td><td>-----</td></tr><tr><td>---</td><td>-----</td><td>-----</td></tr><tr><td>100</td><td>Steven</td><td>Unavailable</td></tr><tr><td>101</td><td>Neena</td><td>Unavailable</td></tr></tbody></table>	EMPLOYEE_ID	FIRST_NAME	EMAIL	-----	-----	-----	---	-----	-----	100	Steven	Unavailable	101	Neena	Unavailable	<table><thead><tr><th>EMPLOYEE_ID</th><th>FIRST_NAME</th><th>EMAIL</th></tr></thead><tbody><tr><td>-----</td><td>-----</td><td>-----</td></tr><tr><td>---</td><td>-----</td><td>-----</td></tr><tr><td>100</td><td>Steven</td><td>Unavailable</td></tr><tr><td>101</td><td>Neena</td><td>Unavailable</td></tr></tbody></table>	EMPLOYEE_ID	FIRST_NAME	EMAIL	-----	-----	-----	---	-----	-----	100	Steven	Unavailable	101	Neena	Unavailable	✓
EMPLOYEE_ID	FIRST_NAME	EMAIL																																
-----	-----	-----																																
---	-----	-----																																
100	Steven	Unavailable																																
101	Neena	Unavailable																																
EMPLOYEE_ID	FIRST_NAME	EMAIL																																
-----	-----	-----																																
---	-----	-----																																
100	Steven	Unavailable																																
101	Neena	Unavailable																																

	Test	Expected	Got	
✓	SELECT EMPLOYEE_ID,FIRST_NAME,EMAIL FROM EMPLOYEES LIMIT 5;	EMPLOYEE_ID FIRST_NAME EMAIL ----- 100 Steven Unavailable 101 Neena Unavailable 102 Lex Unavailable 103 Alexander Unavailable 104 Bruce Unavailable	EMPLOYEE_ID FIRST_NAME EMAIL ----- 100 Steven Unavailable 101 Neena Unavailable 102 Lex Unavailable 103 Alexander Unavailable 104 Bruce Unavailable	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to calculate the number of years each employee has been with the company till '2024-08-30'.

Calculations table

cid	name	type
0	empno	INT
1	ename	VARCHAR(100)
2	job	VARCHAR(50)
3	mgr	INT
4	hiredate	DATE
5	sal	DECIMAL(10,2)
6	comm	DECIMAL(10,2)
7	deptno	INT

For example:

Result	
ename	Tenure
JONES	43
MARTIN	42
BLAKE	43
CLARK	43
SCOTT	41
KING	42
TURNER	42

Answer: (penalty regime: 0 %)

```
1 SELECT
2     ename,
3     (CAST(strftime('%Y', '2024-08-30') AS INT) - CAST(strftime('%Y', hiredate) AS INT)
4     (strftime('%m-%d', '2024-08-30') < strftime('%m-%d', hiredate))) AS Tenure
5 FROM
6     emp;
```

	Expected		Got		
✓	ename	Tenure	ename	Tenure	✓
	-----	-----	-----	-----	
	JONES	43	JONES	43	
	MARTIN	42	MARTIN	42	
	BLAKE	43	BLAKE	43	
	CLARK	43	CLARK	43	
	SCOTT	41	SCOTT	41	
	KING	42	KING	42	
	TURNER	42	TURNER	42	

Passed all tests! ✓

Write a SQL query to Delete customers from 'customer' table where 'WORKING_AREA' is 'New York'.

Sample table: Customer

CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE
C00013	Holmes	London	London	UK	2	6000.00	5000.00	7000.00	4000.00	BBBBBBB	A003
C00001	Micheal	New York	New York	USA	2	3000.00	5000.00	2000.00	6000.00	CCCCCCC	A008
C00020	Albert	New York	New York	USA	3	5000.00	7000.00	6000.00	6000.00	BBBBSBB	A008

For example:

Test	Result																																																												
select changes();	<table><tr><th>CUST_CODE</th><th>CUST_NAME</th><th>CUST_CITY</th><th>WORKING_AREA</th><th>CUST_COUNTRY</th><th>GRADE</th><th>OPENING_AMT</th><th>RECEIVE_AMT</th><th>PAYMENT_AMT</th><th>OUTSTANDING_AMT</th><th>PHONE_NO</th><th>AGENT_CODE</th></tr><tr><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td><td>-----</td></tr><tr><td>C00001</td><td>Micheal</td><td>New York</td><td>New York</td><td>USA</td><td>2</td><td>3000</td><td>5000</td><td>2000</td><td>6000</td><td>CCCCCCC</td><td>A008</td></tr><tr><td>C00020</td><td>Albert</td><td>New York</td><td>New York</td><td>USA</td><td>3</td><td>5000</td><td>7000</td><td>6000</td><td>6000</td><td>BBBBSBB</td><td>A008</td></tr><tr><td>C00002</td><td>Bolt</td><td>New York</td><td>New York</td><td>USA</td><td>3</td><td>5000</td><td>7000</td><td>9000</td><td>3000</td><td>DDNRDRH</td><td>A008</td></tr></table> changes() ----- 3	CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	C00001	Micheal	New York	New York	USA	2	3000	5000	2000	6000	CCCCCCC	A008	C00020	Albert	New York	New York	USA	3	5000	7000	6000	6000	BBBBSBB	A008	C00002	Bolt	New York	New York	USA	3	5000	7000	9000	3000	DDNRDRH	A008
CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE																																																		
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----																																																		
C00001	Micheal	New York	New York	USA	2	3000	5000	2000	6000	CCCCCCC	A008																																																		
C00020	Albert	New York	New York	USA	3	5000	7000	6000	6000	BBBBSBB	A008																																																		
C00002	Bolt	New York	New York	USA	3	5000	7000	9000	3000	DDNRDRH	A008																																																		

Answer: (penalty regime: 0 %)

```

1 | DELETE FROM customer
2 | WHERE WORKING_AREA = 'New York';
3 |

```

	Test	Expected	Got	
✓	select changes();	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- --- ----- ----- C00001 Micheal New York New York USA 2 3000 5000 2000 6000 CCCCCC A008 C00020 Albert New York New York USA 3 5000 7000 6000 6000 BBBBSBB A008 C00002 Bolt New York New York USA 3 5000 7000 9000 3000 DDNRDRH A008 changes() ----- 3	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- --- ----- ----- C00001 Micheal New York New York USA 2 3000 5000 2000 6000 CCCCCC A008 C00020 Albert New York New York USA 3 5000 7000 6000 6000 BBBBSBB A008 C00002 Bolt New York New York USA 3 5000 7000 9000 3000 DDNRDRH A008 changes() ----- 3	✓

	Test	Expected	Got	
✓	select changes();	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- --- ----- ----- ----- ----- C00013 Holmes London New York UK 2 6000 5000 7000 4000 BBBB BBB A003 C00001 Micheal New York New York USA 2 3000 5000 2000 6000 CCCCCC A008 C00020 Albert New York New York USA 3 5000 7000 6000 6000 BBBBSBB A008 C00025 Ravindran Bangalore New York India 2 5000 7000 4000 8000 AVAVAVA A011 C00024 Cook London New York UK 2 4000 9000 7000 6000 FSDDSD F A006 C00002 Bolt New York New York USA 3 5000 7000 9000 3000 DDNRDRH A008 C00018 Fleming Brisban New York Australia 2 7000 7000 9000 5000 NHBGVFC A005 C00022 Avinash Mumbai New York India 2 7000 11000 9000 9000 113-123456 A002 C00017 Srinivas Bangalore New York India 2 8000 4000 3000 9000 AAAAAB A007 C00003 Martin Torento New York Canada 2 8000 7000 7000 8000 MJYURFD A004 C00014 Rangarappa Bangalore New York India 2 8000 11000 7000 12000 AAAATGF A001 C00016 Venkatpati Bangalore New York India 2 8000 11000 7000 12000 JRTVFDD A007 changes() ----- 12	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- --- ----- ----- ----- ----- C00013 Holmes London New York UK 2 6000 5000 7000 4000 BBBB BBB A003 C00001 Micheal New York New York USA 2 3000 5000 2000 6000 CCCCCC A008 C00020 Albert New York New York USA 3 5000 7000 6000 6000 BBBBSBB A008 C00025 Ravindran Bangalore New York India 2 5000 7000 4000 8000 AVAVAVA A011 C00024 Cook London New York UK 2 4000 9000 7000 6000 FSDDSD F A006 C00002 Bolt New York New York USA 3 5000 7000 9000 3000 DDNRDRH A008 C00018 Fleming Brisban New York Australia 2 7000 7000 9000 5000 NHBGVFC A005 C00022 Avinash Mumbai New York India 2 7000 11000 9000 9000 113-123456 A002 C00017 Srinivas Bangalore New York India 2 8000 4000 3000 9000 AAAAAB A007 C00003 Martin Torento New York Canada 2 8000 7000 7000 8000 MJYURFD A004 C00014 Rangarappa Bangalore New York India 2 8000 11000 7000 12000 AAAATGF A001 C00016 Venkatpati Bangalore New York India 2 8000 11000 7000 12000 JRTVFDD A007 changes() ----- 12	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL statement to Increase the selling price by 10% for all products in the 'Bakery' category in the products table.

Products table

product_id
product_name
category
cost_price
sell_price
reorder_lvl
quantity
supplier_id

Answer: (penalty regime: 0 %)

1	UPDATE products
2	SET sell_price = sell_price * 1.10
3	WHERE category = 'Bakery';
4	

	Test	Expected	Got	
✓	select changes();	changes() ----- 3	changes() ----- 3	✓

	Test	Expected	Got	
✓	<pre>select * from products where category='Bakery'; select changes();</pre>	<pre>product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- - ----- ----- 5 Black Forest Cake Bakery 20 50 10 100 2 6 Red Velvet Cake Bakery 20 55 20 100 2 product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- - ----- ----- 5 Black Forest Cake Bakery 20 55.0 10 100 2 6 Red Velvet Cake Bakery 20 60.5 20 100 2 changes() ----- 2</pre>	<pre>product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- - ----- ----- 5 Black Forest Cake Bakery 20 50 10 100 2 6 Red Velvet Cake Bakery 20 55 20 100 2 product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- - ----- ----- 5 Black Forest Cake Bakery 20 55.0 10 100 2 6 Red Velvet Cake Bakery 20 60.5 20 100 2 changes() ----- 2</pre>	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Question 8

Correct

Mark 5.00 out of 5.00

Write a SQL statement to Update the `product_name` to 'Premium Bread' whose product ID is 5 in the `products` table.

Products table

```

-----
product_id
product_name
category
cost_price
sell_price
reorder_lvl
quantity
supplier_id

```

Answer: (penalty regime: 0 %)

```

1 UPDATE products
2 SET product_name = 'Premium Bread'
3 WHERE product_id = 5;
4

```

	Test	Expected	Got	
✓	select changes();	changes() ----- 1	changes() ----- 1	✓
✓	select * from products WHERE product_id=5; select changes();	product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- ----- - ----- ----- 5 Premium Bread Category A 20 50 10 1010 2 changes() ----- 1	product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- ----- - ----- ----- 5 Premium Bread Category A 20 50 10 1010 2 changes() ----- 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Increase the reorder level by 30% for products from 'Food' category having quantity in stock less than 50% of existing reorder level in the products table

name	type

product_id	INT
product_name	VARCHAR(10)
category	VARCHAR(50)
cost_price	DECIMAL(10)
sell_price	DECIMAL(10)
reorder_lvl	INT
quantity	INT
supplier_id	INT

For example:

Test	Result
select changes();	changes() ----- 4

Answer: (penalty regime: 0 %)

```
1 UPDATE products
2 SET reorder_lvl = CAST(reorder_lvl * 1.30 AS INT)
3 WHERE category = 'Food'
4 AND quantity < (reorder_lvl * 0.50);
5
```

	Test	Expected	Got	
✓	select changes();	changes() ----- 4	changes() ----- 4	✓

	Test	Expected			Got			
✓	SELECT*FROM Products WHERE supplier_id = 10;	product_id	product_name		product_id	product_name		✓
		category	cost_price		category	cost_price		
		sell_price	reorder_lvl		sell_price	reorder_lvl		
		quantity	supplier_id		quantity	supplier_id		
		-----	-----	----	-----	-----	----	
		-----	-----	-----	-----	-----	-----	
		-----	-----	-----	-----	-----	-----	
		-----	-----	-----	-----	-----	-----	
		6	Sandwich	Food	6	Sandwich	Food	
		60	80	26	60	80	26	
		5	10		5	10		
		7	Chat Items	Food	7	Chat Items	Food	
		85	100	13	85	100	13	
		2	10		2	10		
		8	Chapathi	Food	8	Chapathi	Food	
		85	100	13	85	100	13	
		0	10		0	10		
		9	Idly	Food	9	Idly	Food	
		85	100	13	85	100	13	
		3	10		3	10		

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to determine the status of `decimal` in the `Calculations` table as 'Below Average', 'Average', or 'Above Average' based on whether it is below 50, exactly 50, or above 50.

cid	name	type	notnull	dflt_value	pk
0	id	INTEGER	0		1
1	value1	REAL	0		0
2	value2	REAL	0		0
3	base	INTEGER	0		0
4	exponent	INTEGER	0		0
5	number	REAL	0		0
6	decimal	REAL	0		0

For example:

Result		
id	decimal	status
1	123.4567	Above Average
2	567.891	Above Average
3	78.234	Above Average
4	45.78	Below Average

Answer: (penalty regime: 0 %)

```
1 SELECT
2   id,
3   decimal,
4   CASE
5     WHEN decimal < 50 THEN 'Below Average'
6     WHEN decimal = 50 THEN 'Average'
7     ELSE 'Above Average'
8   END AS status
9 FROM
10  mathfunc;
11
```

	Expected	Got	
✗	<pre> id decimal status ----- -- 1 123.4567 Above Average 2 567.891 Above Average 3 78.234 Above Average 4 45.78 Below Average </pre>	<pre> ***Run error*** Error: near line 5: no such table: mathfunc Traceback (most recent call last): File "__tester__.python3", line 43, in <module> output = subprocess.check_output(['sqlite3', db_working], input=text_input, File "/usr/lib/python3.8/subprocess.py", line 415, in check_output return run(*popenargs, stdout=PIPE, timeout=timeout, check=True, File "/usr/lib/python3.8/subprocess.py", line 516, in run raise CalledProcessError(retcode, process.args, subprocess.CalledProcessError: Command '['sqlite3', 'mathfuncdb']' returned non-zero exit status 1. During handling of the above exception, another exception occurred: Traceback (most recent call last): File "__tester__.python3", line 47, in <module> raise Exception("sqlite3 error: " + str(e)) Exception: sqlite3 error: Command '['sqlite3', 'mathfuncdb']' returned non-zero exit status 1. </pre>	✗

Testing was aborted due to error.

Your code must pass all tests to earn any marks. Try again.

Show differences

Incorrect

Marks for this submission: 0.00/5.00.

Find Products with a Discounted Price Greater than a Given Amount:

Write a query to list all products that have a discounted price greater than \$100. Return product_id, original_price, discount_percentage, and discounted_price.

Sample table: Products

product_id | original_price | discount_percentage

"101" "50" "0.1"

"102" "150" "0.15"

"103" "200" "0.2"

"104" "300" "0.25"

For example:

Result			
product_id	original_price	discount_percentage	discounted_price
-----	-----	-----	-----
102	150.0	0.15	127.5
103	200.0	0.2	160.0
104	300.0	0.25	225.0

Answer: (penalty regime: 0 %)

```
1 SELECT
2     product_id,
3     original_price,
4     discount_percentage,
5     (original_price * (1 - discount_percentage)) AS discounted_price
6 FROM
7     Products
8 WHERE
9     (original_price * (1 - discount_percentage)) > 100;
10
```

	Expected	Got	
✓	<pre>product_id original_price discount_percentage discounted_price ----- 102 150.0 0.15 127.5 103 200.0 0.2 160.0 104 300.0 0.25 225.0</pre>	<pre>product_id original_price discount_percentage discounted_price ----- 102 150.0 0.15 127.5 103 200.0 0.2 160.0 104 300.0 0.25 225.0</pre>	✓

Passed all tests! ✓

write a SQL query to find customers who are either from the city 'New York' or who do not have a grade greater than 100. Return customer_id, cust_name, city, grade, and salesman_id.

Sample table: customer

customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	New York	100	5001
3007	Brad Davis	New York	200	5001
3005	Graham Zusi	California	200	5002

For example:

Result				
customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	Chennai	100	5001
3001	Brad Guzan	London	100	5005

Answer: (penalty regime: 0 %)

```

1  SELECT
2      customer_id,
3      cust_name,
4      city,
5      grade,
6      salesman_id
7  FROM
8      customer
9  WHERE
10     city = 'New York'
11     OR grade <= 100;
12

```

	Expected			Got			
✓	customer_id grade -----	cust_name salesman_id -----	city -----	customer_id grade -----	cust_name salesman_id -----	city -----	✓
	3002 100	Nick 5001	Rimando Chennai	3002 100	Nick 5001	Rimando Chennai	
	3001 100	Brad 5005	Guzan London	3001 100	Brad 5005	Guzan London	
	3007 200	Brad 5001	Davis New York	3007 200	Brad 5001	Davis New York	
	3009 100	Geoff 5003	Camero Berlin	3009 100	Geoff 5003	Camero Berlin	
✓	customer_id grade -----	cust_name salesman_id -----	city -----	customer_id grade -----	cust_name salesman_id -----	city -----	✓
	3002 100	Nick 5001	Rimando Chennai	3002 100	Nick 5001	Rimando Chennai	
	3001 100	Brad 5005	Guzan London	3001 100	Brad 5005	Guzan London	

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to Delete customers from 'customer' table where 'GRADE' is less than 2.

Sample table: Customer

CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE
C00013	Holmes	London	London	UK	2	6000.00	5000.00	7000.00	4000.00	BBBBBBB	A003
C00001	Micheal	New York	New York	USA	2	3000.00	5000.00	2000.00	6000.00	CCCCCCC	A008
C00020	Albert	New York	New York	USA	3	5000.00	7000.00	6000.00	6000.00	BBBBBBSB	A008

For example:

Test	Result
select distinct(grade)from customer;	GRADE ----- 2 3 1 0 GRADE ----- 2 3

Answer: (penalty regime: 0 %)

```
1 | DELETE FROM customer
2 | WHERE GRADE < 2;
3 |
```

	Test	Expected	Got	
✓	select distinct(grade)from customer;	GRADE ----- 2 3 1 0 GRADE ----- 2 3	GRADE ----- 2 3 1 0 GRADE ----- 2 3	✓
✓	SELECT count(*) from customer;	count(*) ----- 25 count(*) ----- 15	count(*) ----- 25 count(*) ----- 15	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL statement to Increase the selling price by 15% in the products table where quantity in stock is less than 50 and supplier ID is 10.

Products Table

name	type
-----	-----
product_id	INT PRIMARY KEY
product_name	VARCHAR(10)
category	VARCHAR(50)
cost_price	DECIMAL(10)
sell_price	DECIMAL(10)
reorder_lv	INT
quantity	INT
supplier_id	INT

For example:

Test	Result
select changes();	changes() ----- 4

Answer: (penalty regime: 0 %)

```
1 UPDATE products
2 SET sell_price = sell_price * 1.15
3 WHERE quantity < 50
4   AND supplier_id = 10;
5
```

	Test	Expected	Got	
✓	select changes();	changes() ----- 4	changes() ----- 4	✓

	Test	Expected	Got	
✓	SELECT*FROM Products WHERE supplier_id = 10;	<pre> product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- ----- -- ----- 6 Detergent Powder Snacks 60 80 20 40 10 7 Surf Excel Deter Snacks 85 100 10 40 10 8 Detergent Ariel Items 85 100 10 40 10 product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- ----- -- ----- 6 Detergent Powder Snacks 60 92 20 40 10 7 Surf Excel Deter Snacks 85 115.0 10 40 10 8 Detergent Ariel Items 85 115.0 10 40 10 </pre>	<pre> product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- ----- -- ----- 6 Detergent Powder Snacks 60 80 20 40 10 7 Surf Excel Deter Snacks 85 100 10 40 10 8 Detergent Ariel Items 85 100 10 40 10 product_id product_name category cost_price sell_price reorder_lvl quantity supplier_id ----- ----- -- ----- 6 Detergent Powder Snacks 60 92 20 40 10 7 Surf Excel Deter Snacks 85 115.0 10 40 10 8 Detergent Ariel Items 85 115.0 10 40 10 </pre>	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to retrieve all employee names in lower case.

Table name: emp

name	type
-----	-----
empno	INT
ename	VARCHAR(100)
job	VARCHAR(50)
mgr	INT
hiredate	DATE
sal	DECIMAL(10,2)
comm	DECIMAL(10,2)
deptno	INT

For example:

Result
EmpName

king
jones
clark
scott
ford
miller

Answer: (penalty regime: 0 %)

```
1 | SELECT
2 |     LOWER(ename) AS EmpName
3 | FROM
4 |     emp;
5 |
```

	Expected	Got	
✓	EmpName	EmpName	✓
	-----	-----	
	king	king	
	jones	jones	
	clark	clark	
	scott	scott	
	ford	ford	
	miller	miller	

	Expected	Got	
✓	EmpName ----- blake turner james martin allen ward	EmpName ----- blake turner james martin allen ward	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to retrieve the year, month, and day from the **hiredate** column in the **emp** table.

For example:

Result		
Year	Month	Day
-----	-----	-----
1981	04	02
1981	09	28
1981	05	01
1981	06	09
1982	12	09
1981	11	17
1981	09	08

Answer: (penalty regime: 0 %)

```
1 SELECT
2     strftime('%Y', hiredate) AS Year,
3     strftime('%m', hiredate) AS Month,
4     strftime('%d', hiredate) AS Day
5 FROM
6     emp;
7
```

	Expected			Got			
✓	Year	Month	Day	Year	Month	Day	✓
	-----	-----	-----	-----	-----	-----	
	1981	04	02	1981	04	02	
	1981	09	28	1981	09	28	
	1981	05	01	1981	05	01	
	1981	06	09	1981	06	09	
	1982	12	09	1982	12	09	
	1981	11	17	1981	11	17	
	1981	09	08	1981	09	08	

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to Delete customers with 'GRADE' 3 or 'AGENT_CODE' 'A008' whose 'OUTSTANDING_AMT' is less than 5000

Sample table: Customer

CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE
C00013	Holmes	London	London	UK	2	6000.00	5000.00	7000.00	4000.00	BBBBBB	A003
C00001	Micheal	New York	New York	USA	2	3000.00	5000.00	2000.00	6000.00	CCCCCC	A008
C00020	Albert	New York	New York	USA	3	5000.00	7000.00	6000.00	6000.00	BBBBSB	A008

For example:

Test	Result
select changes();	changes() ----- 1

Answer: (penalty regime: 0 %)

```
1 DELETE FROM customer
2 WHERE (GRADE = 3 OR AGENT_CODE = 'A008')
3 AND OUTSTANDING_AMT < 5000;
4
```

	Test	Expected	Got	
✓	select changes();	changes() ----- 1	changes() ----- 1	✓

	Test	Expected	Got	
✓	select changes();	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- --- ----- ----- - ----- C00002 Bolt New York New York USA 3 5000 7000 9000 3000 DDNRDRH A008 changes() ----- 1	CUST_CODE CUST_NAME CUST_CITY WORKING_AREA CUST_COUNTRY GRADE OPENING_AMT RECEIVE_AMT PAYMENT_AMT OUTSTANDING_AMT PHONE_NO AGENT_CODE ----- ----- --- ----- ----- - ----- C00002 Bolt New York New York USA 3 5000 7000 9000 3000 DDNRDRH A008 changes() ----- 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a query to find the top 2 products with the highest discount percentage. Return product_id, original_price, discount_percentage, and discounted_price.

Sample table: Products

product_id | original_price | discount_percentage

"101" "50" "0.1"

"102" "150" "0.15"

"103" "200" "0.2"

"104" "300" "0.25"

For example:

Result			
product_id	original_price	discount_percentage	discounted_price
-----	-----	-----	-----
104	300.0	0.25	225.0
103	200.0	0.2	160.0

Answer: (penalty regime: 0 %)

```
1 SELECT
2   product_id,
3   original_price,
4   discount_percentage,
5   (original_price * (1 - discount_percentage)) AS discounted_price
6 FROM
7   Products
8 ORDER BY
9   discount_percentage DESC
10 LIMIT 2;
11
```

	Expected	Got	
✓	<pre>product_id original_price discount_percentage discounted_price ----- 104 300.0 0.25 225.0 103 200.0 0.2 160.0</pre>	<pre>product_id original_price discount_percentage discounted_price ----- 104 300.0 0.25 225.0 103 200.0 0.2 160.0</pre>	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to Delete customers from 'customer' table where 'AGENT_CODE' is either 'A003' or 'A008'.

Sample table: Customer

CUST_CODE	CUST_NAME	CUST_CITY	WORKING_AREA	CUST_COUNTRY	GRADE	OPENING_AMT	RECEIVE_AMT	PAYMENT_AMT	OUTSTANDING_AMT	PHONE_NO	AGENT_CODE
C00013	Holmes	London	London	UK	2	6000.00	5000.00	7000.00	4000.00	BBBBBBB	A003
C00001	Micheal	New York	New York	USA	2	3000.00	5000.00	2000.00	6000.00	CCCCCCC	A008
C00020	Albert	New York	New York	USA	3	5000.00	7000.00	6000.00	6000.00	BBBBSBB	A008

For example:

Test	Result
select distinct(agent_code)from customer;	AGENT_CODE ----- A003 A008 A011 A006 A005 A010 A002 A004 A009 A007 A012 A001 AGENT_CODE ----- A011 A006 A005 A010 A002 A004 A009 A007 A012 A001

Answer: (penalty regime: 0 %)

```
1 | DELETE FROM customer
2 | WHERE AGENT_CODE IN ('A003', 'A008');
3 |
```

	Test	Expected	Got	
✓	select distinct(agent_code)from customer;	AGENT_CODE ----- A003 A008 A011 A006 A005 A010 A002 A004 A009 A007 A012 A001 AGENT_CODE ----- A011 A006 A005 A010 A002 A004 A009 A007 A012 A001	AGENT_CODE ----- A003 A008 A011 A006 A005 A010 A002 A004 A009 A007 A012 A001 AGENT_CODE ----- A011 A006 A005 A010 A002 A004 A009 A007 A012 A001	✓
✓	SELECT count(*) from customer;	count(*) ----- 25 count(*) ----- 20	count(*) ----- 25 count(*) ----- 20	✓
✓	SELECT count(*) from customer;	count(*) ----- 25 count(*) ----- 17	count(*) ----- 25 count(*) ----- 17	✓

Passed all tests! ✓

Correct

Marks for this submission: 5.00/5.00.

Write a SQL query to find customers who are either from the city 'New York' or who have a grade greater than 200. Return customer_id, cust_name, city, grade, and salesman_id.

Sample table: customer

customer_id	cust_name	city	grade	salesman_id
3002	Nick Rimando	New York	100	5001
3007	Brad Davis	New York	200	5001
3005	Graham Zusi	California	200	5002

For example:

Result				
customer_id	cust_name	city	grade	salesman_id
3004	Fabian Johns	Paris	300	5006
3007	Brad Davis	New York	200	5001
3008	Julian Green	London	300	5002

Answer: (penalty regime: 0 %)

```
1 SELECT
2     customer_id,
3     cust_name,
4     city,
5     grade,
6     salesman_id
7 FROM
8     customer
9 WHERE
10    city = 'New York'
11    OR grade > 200;
12
```

	Expected			Got			
✓	customer_id	cust_name	city	customer_id	cust_name	city	✓
	grade	salesman_id		grade	salesman_id		
	-----	-----	-----	-----	-----	-----	
	3004	Fabian Johns	Paris	3004	Fabian Johns	Paris	
	300	5006		300	5006		
	3007	Brad Davis	New York	3007	Brad Davis	New York	
	200	5001		200	5001		
	3008	Julian Green	London	3008	Julian Green	London	
	300	5002		300	5002		