<u>Dashboard</u> / <u>My courses</u> / <u>CS23331-DAA-2023-CSE</u> / <u>Dynamic Programming</u> / <u>2-DP-Playing with chessboard</u>

Started on	Tuesday, 22 October 2024, 2:26 PM
State	Finished
Completed on	Monday, 28 October 2024, 2:12 PM
Time taken	5 days 23 hours
Grade	10.00 out of 10.00 (100 %)

```
Question 1
Correct
Mark 10.00 out of 10.00
```

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

871

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
 2
 3
    int maxPathSum(int n, int matrix[n][n]) {
 4
        int dp[n][n];
 5
        dp[0][0] = matrix[0][0];
 6
 8
        for (int i = 1; i < n; i++) {</pre>
 9
             dp[i][0] = dp[i - 1][0] + matrix[i][0];
10
11
12
        for (int j = 1; j < n; j++) {
13
             dp[0][j] = dp[0][j - 1] + matrix[0][j];
14
15
        for (int i = 1; i < n; i++) {</pre>
16
17
             for (int j = 1; j < n; j++) {
                 dp[i][j] = matrix[i][j] + (dp[i - 1][j] > dp[i][j - 1] ? dp[i - 1][j] : dp[i]
18
19
20
        }
21
22
        return dp[n - 1][n - 1];
23
24
25
    int main() {
26
        int n:
        scanf("%d",&n);
27
28
        int m[n][n];
29
        for(int i=0;i<n;i++){</pre>
30
             for(int j=0;j<n;j++){</pre>
                 scanf("%d",&m[i][j]);
31
32
             }
33
34
35
        int result = maxPathSum(n,m);
        printf("%d", result);
```

		-		
	Input	Expected	Got	
~	3	19	19	~
	1 2 4			
	2 3 4			
	8 7 1			
~	3	12	12	~
	1 3 1			
	1 5 1			
	4 2 1			
~	4	28	28	~
	1 1 3 4			
	1 5 7 8			
	2 3 4 6			
	1690			

Passed all tests! 🗸

Correct

Marks for this submission: 10.00/10.00.

■ 1-DP-Playing with Numbers

Jump to...

3-DP-Longest Common Subsequence