

Connect360: An Intelligent and Secure Platform for Skilled Labour Booking

DIVYA M

Assistant Professor

Department of Computer Science and Engineering

divya.m@rajalakshmi.edu.in

<https://orcid.org/0009-0006-8170-4668>

Rajalakshmi Engineering College

Chennai, Tamil Nadu

DHARSHINI R S

Department of Computer Science and Engineering

230701076@rajalakshmi.edu.in

Rajalakshmi Engineering College

Chennai, Tamil Nadu

JAYADHARSINI M

Department of Computer Science and Engineering

230701127@rajalakshmi.edu.in

Rajalakshmi Engineering College

Chennai, Tamil Nadu

ENIYA B A

Department of Computer Science and Engineering

230701085@rajalakshmi.edu.in

Rajalakshmi Engineering College

Chennai, Tamil Nadu

JAYAPRADHA P

Department of Computer Science and Engineering

230701130@rajalakshmi.edu.in

Rajalakshmi Engineering College

Chennai, Tamil Nadu

Abstract - Finding trusted skilled service workers remains a significant problem in the informal home-services space. Customers are usually reliant on private referrals or manual searches to find suitable workers for a specific service that meet their skills, availability, experience, trust, and distance requirements. Skilled workers, on the other hand, have few opportunities for digital exposure of their abilities and do not have access to a robust platform to handle requests and build credibility. The situation becomes even more challenging for urgent service requests, requiring identifying an appropriate worker within a short period.

This paper proposes the Connect360 smart worker matching algorithm and a context-aware platform that offers skilled worker discovery, worker verification, service finding, Scheduled Booking, and Priority Booking. The Connect360 Smart Worker Matching Algorithm ranks potential candidates in accordance with different factors with varied weights depending on the request type, including Scheduled Booking and Priority Booking. The proposed approach provides a Priority Booking option for handling urgent service requirements. In addition, the paper implements a system that secures worker verification documents and offers role-based access control. The proposed solution is evaluated using Amazon Web Services serverless infrastructure to measure matching latency, ranking sensitivity, transactional concurrency, spatial

routing, and personally identifiable information redaction experiments. The results demonstrate the ability of the context-aware platform to enable worker discovery and booking in a serverless home-service environment.

Index Terms— Skilled service workers, worker matching, service recommendation, serverless computing, Priority Booking.

I. INTRODUCTION

The proliferation of digital service platforms has transformed the ways in which customers search and access services. Nevertheless, the problem of finding an appropriate skilled service worker for home-service needs such as electrical, plumbing, carpentry, cleaning, or equipment maintenance still persists. Unlike products, the process of choosing a service worker requires considering a number of factors. For example, in addition to the service scope, a customer may want to take into account the worker's skills, availability, experience, reliability, reputation, verification status, and proximity. Since a worker may be available but located far from the customer's residence or provide high-quality service but be unwilling to work at a specific time, choosing the most suitable worker based on multiple criteria is critical. As can be seen, the task of picking up a home-service worker based on the

provided service description and personal preferences involves a complex multifactorial decision-making process.

As the informal home-services market poses a significant challenge to both customers and service workers, it is necessary to address it through a comprehensive solution. In the current situation, where customers resort to word-of-mouth, local networks, and Google search to find a worker, a multifactorial recommendation system would help sort service providers according to customers' individual preferences. At the same time, since informal workers do not have a strong digital presence, a recommendation system would allow skilled workers to advertise their services and attract clients by showcasing their qualifications, working conditions, and other characteristics. Overall, the abovementioned considerations contribute to the necessity of building such a system, which would enable both buyers and sellers of home-services in local networks to communicate, share information, and conduct transactions more efficiently.

The problem becomes more complicated when service requirements are different in terms of urgency. For a Scheduled Booking, the customers will have enough time to evaluate the suitability, trust, experience, availability, reliability, and distance of a worker before making a decision. However, for a Priority Booking, the allocation process should be more time-critical since the worker's availability and proximity to the service location are significant factors. Therefore, a worker may be suitable for a certain planned service, but at the same time, he may be unavailable or located too far from the customer's location to provide an immediate service. Thus, a home-service marketplace should consider different booking contexts to maintain service suitability and trust.

This paper proposes Connect360, the serverless home-services marketplace, which connects customers with skilled service workers through a central platform. It offers role-based workflows for customers, workers, and administrators. With a customer's interface, one can search for the trusted workers, check their skills, experience, availability, and perform a Scheduled or Priority Booking. Using the worker's interface, they can manage his professional account, check customers' requests, accept or deny booking requests, update booking status, and upload documents for verification. Administrators are responsible for managing workers and service categories, reviewing workers' documents, and storing booking-related information. Connect360 uses AWS serverless infrastructure to ensure the safety of customer data and provide a solid foundation for service management.

In this regard, the Connect360 platform uses a Connect360 Smart Worker Matching Algorithm (CSWMA) to rank the appropriate worker using various attributes related to service and worker. Since scheduled services and priority services have unique needs, different weighing techniques are used for Scheduled and Priority Booking so that the process of ranking can take into account the unique needs of these two types of services. Apart from worker matching, Connect360 also offers worker verification, auto rematching for Priority Booking, booking control to prevent double booking, and road-based live tracking for active Priority Bookings. It uses a role-aware conversational assistant based on Google Gemini to give service interaction that is structured and multilingual, with rule-based fallback. Furthermore, the platform handles the process of worker verification securely using private storage and access control for the documents along with role-based authentication and authorization.

For customer to worker communication, the existing implementation provides calling via device's native dialer from active bookings.

This paper's significant contributions include a serverless skilled home-service platform involving customers, skilled workers, and administrators; the Connect360 Smart Worker Matching Algorithm (CSWMA) that ranks workers on the basis of contextual information; different weighting schemes used in Scheduled and Priority Booking modes; Priority Booking transactions where server-side availability validation, slot locking, and re-matching is performed to minimize booking conflicts and address cases where workers reject or are unavailable for the booking; and an evaluation framework that measures the performance in terms of matching time delay, ranking sensitivity, transactional concurrency, routing, and PII redaction.

This study explores whether an approach based on a context-aware matching mechanism combined with transactional booking control and serverless infrastructure can support reliable worker selection and Priority Booking in a competent home-service scenario.

II. LITERATURE REVIEW

The related literature falls under local service-provider recommendation, service recommendation, skill-based matching, spatial worker allocation, trust-aware recommendation, artificial intelligence, and cloud-based service systems. Each of the research directions focuses on distinct aspects of recommending appropriate service providers to users. The literature considers the service requirements, worker capabilities, user preferences, trust, location, and task constraints, providing the foundation for developing a skilled home-service booking platform. To find an appropriate local service provider, customers often need to assess the

capabilities and reliability of the workers before they request services. Ezhilnilavan et al. [1] propose a machine learning local community service-provider system that recommends local providers while considering providers' information, verification, preferences, and reviews. Munir et al. [13] examine the developer recommendation and team formation for collaborative crowdsourcing platforms by encoding the developers' skills and task requirements to perform the matching. Kumar et al. [19] suggest a skill-based rule matching approach to job recommendation by considering the qualification and skills of the workers. These studies focus on the importance of representing the capabilities of the service providers and matching them with the users' requirements. However, skilled home-service recommendation needs to consider worker availability, trust, location, booking requirements, and service urgency.

The service recommendation literature increasingly focuses on user preferences and utilizes multiple sources of information for accurate recommendations. Sun et al. [2] propose a weighted preference optimization approach based on knowledge graphs and large language models for personalized service recommendation. Ge et al. [6] develop a new approach called LLMGCL that utilizes graph contrastive learning and large language models for recommendation. Zhao et al. [14] explore the recommender systems in the age of large language models, whereas Zheng et al. [15] investigate the collaborative semantics and large language models for recommendation. The approaches highlight the potential of using semantic information and language models for capturing structured data and user preferences for recommendation. However, a skilled home-service request requires that the capabilities of the selected worker satisfy the customer requirements and service conditions.

When choosing a service provider, customers often seek trustworthy and reliable workers. Khelloufi et al. [11] propose a hybrid feature and trust aggregation recommender system that incorporates trust information into the recommendation process. Chen et al. [12] examine reliable personalized recommendation with uncertain missing modalities, addressing the challenge of making accurate recommendations using available information. The approaches highlight the importance of trustworthy information for making accurate recommendations. In the context of home service, worker trust is critical and should be considered during recommendation, worker verification, and previous booking records.

When allocating workers to tasks that require traveling to a customer's location, the spatial aspect of the task adds complexity to the service provision process. Zhao et al. [3] propose heterogeneous graph reinforcement learning for dependency-aware multi-task allocation in

spatial crowdsourcing by modeling the relationship between workers and tasks. Wu et al. [5] investigate adaptive task assignment through a human-in-the-loop approach. Deng et al. [7] explore the task recommendation in spatial crowdsourcing by considering the balance between diversity and coverage. Wu et al. [8] develop a prediction-aware adaptive task assignment approach, whereas Zhao et al. [9] propose a geo-partition framework for spatial crowdsourcing task allocation. These studies address the importance of incorporating spatial information and worker-task relationships into the task allocation process. However, home service allocation requires considering these factors in addition to the professional skills, worker trust, experience, and availability to ensure effective service delivery.

In addition, the time factor often plays an essential role in task allocation. Ma et al. [10] propose a clustering-based priority queue approach to spatial task assignment by considering task priorities. Chen et al. [4] examine the fairness-aware task recommendation and allocation, establishing the connection between the recommendation and allocation processes. These studies consider task priority and fairness in task allocation. For home service, the time factor determines the urgency of the service request. As such, it is essential to adjust the worker matching strategy according to the booking requirements. For example, the proximity of the worker to the customer's location is more critical for a Priority Booking than a Scheduled Booking.

Lastly, artificial intelligence can be utilized to develop an intelligent system that interacts with customers and allocates workers to service requests. The approaches mentioned above demonstrate the potential of using large language models and graph neural networks to capture semantic information and improve recommendation accuracy. The local service-provider literature [1] also demonstrates how artificial intelligence can be utilized to discover local workers. However, the focus of the approaches is on the recommendation or artificial intelligence aspects of the service system, thus limiting their application in developing a skilled home-service booking platform that involves customer preference understanding, worker ranking, booking, and service execution.

The cloud-based service literature provides insights into developing the computational infrastructure that supports the service system. Refonaa et al. [16] examine the serverless infrastructure for cloud automation, whereas Ekwe-Ekwe and Amos [17] compare public cloud Function-as-a-Service providers. Adeppady et al. [18] study the dynamic management of cloud computing resources with constrained serverless platforms. Pasam et al. [20] investigate scalable AI pipeline development using cloud-native technologies

for building intelligent transactional systems. The approaches highlight the potential of utilizing cloud-native and serverless technologies for developing distributed and scalable service systems. However, the focus of the literature is on the technical aspects of serverless infrastructures and does not address the end-to-end skilled home-service discovery, booking, and execution processes.

In summary, the literature provides the foundation for developing a skilled home-service booking platform by addressing local provider discovery, skill-based job recommendation, personalized recommendation, trust, spatial allocation, time-based allocation, artificial intelligence, and cloud-based service systems. However, each of the research directions primarily focuses on a distinct aspect of the skilled home-service platform, thus leaving the comprehensive approach to skilled worker discovery, matching, booking, and service execution as an area for future research.

The research gap that the proposed solution addresses includes the need to develop a skilled home-service platform that integrates local provider discovery, multi-factor worker matching, transactional booking control, and automatic rematching. Connect360 utilizes the Connect360 Smart Worker Matching Algorithm (CSWMA) to rank eligible skilled service workers based on service match, trust, experience, availability, reliability, and proximity. CSWMA utilizes different worker ranking weights for Scheduled Booking and Priority Booking to ensure that the matching considers the requirements of each booking type. Connect360 also offers worker verification, booking lifecycle management, transactional worker-slot locking mechanism, worker auto-rematching for Priority Booking, and road-based tracking for active Priority Booking to enhance the service delivery process. As such, the proposed solution builds on the related literature by developing an end-to-end skilled home-service marketplace that considers worker discovery, multi-factor worker matching, transactional booking control, and automatic rematching.

III. METHODOLOGY

The methodology adopted for the Connect360 follows a modular serverless architecture, and it incorporates the user authentication, worker verification, recommendation, booking management, AI assistance, and admin monitoring components. It is developed using three major user roles namely customer, worker, and administrator, and AWS managed services to facilitate the users with authentication, computing, storage, database, and deployment resources. The overall system design includes the React based front end, API layer, serverless back end, DynamoDB, document storage, and AI assistant.

A. System Architecture

The Connect360 application is designed based on the three-layer serverless architecture namely presentation, application, and data and intelligence services. The front end is built using the React 18 framework and the Vite tool and deployed using the Amazon S3 and the CloudFront service with HTTPS protocol. The user requests are received by the API gateway, which is protected using the AWS Cognito User Pool Authorizer. The seven AWS Lambda functions are used for the back end, which are deployed using the Python 3.11 programming language. The Lambda functions are grouped according to the application’s needs and implement the service, worker, booking, verification, administration, and other logic; the authentication and authorization are managed by the Amazon Cognito and API Gateway. The data and intelligence layer consist of DynamoDB with single-table design and two GSIs, Amazon S3 for the document storage, and Google Gemini for the AI assistant, which are accessed using the API key stored in the AWS Secrets Manager. The resulting system architecture is shown in Fig. 1.



Fig. 1. System architecture of Connect360

This architecture reduces dependence on continuously running servers and enables independent scaling of backend functions.

B. User Authentication and Role Management

The user authentication is achieved through the AWS Cognito service, where the users can log in to the system using their email-address and password. The JWT claims are used to identify the user after the successful log in, and the backend functions accept the claims as the input to determine the action performed by the user. The API Gateway protects the API endpoints with the Cognito User Pool Authorizer, which allows authorized users only to gain access to the restricted resources. The user roles namely Customer, Worker, and Administrator have different permissions in the system, which are outlined below:

- Customer: discover workers, make bookings, monitor services, and leave reviews.
- Worker: update worker information, manage availability, view booking requests, upload verification documents.

- Administrator: control users, services, verification, revenues, and other information.

C. Worker Verification and trust model:

Workers submit their identifying, residence, and credential papers for verification. Their documents are securely stored in the private encrypted S3 bucket through pre-signed URLs. The documents are then reviewed and approved by the system administrator, and the verification results are added to the worker's trust score.

D. Connect360 Smart Worker Matching Algorithm (CSWMA)

The Connect360 Smart Worker Matching Algorithm (CSWMA) ranks eligible service workers according to six attributes: service match, trust, experience, availability, reliability, and distance. Every attribute has a normalized score between 0 and 1, with higher values indicating a better fit.

Let M, T, E, A, R, and D denote normalized scores of these attributes. Service match is assigned a score of 1 if the service selected is an exact match relative to the request, and 0 otherwise. For trust, T is calculated using the worker's average rating out of 5 stars, with a 0.2 bonus for verified workers, and a neutral score of 0.5 for unrated workers. The experience score E is normalized against a 10-year maximum, while the availability score A is determined based on the availability status and schedule of the worker. The reliability score R is computed using the ratio between completed and total number of bookings, while the number of reviews is used as a substitute if the latter statistics are unavailable. The distance score uses an inverse linear function, with lower physical distances resulting in higher scores:

$$D = \begin{cases} 1, & d \leq 2 \\ 1 - \frac{d-2}{23}, & 2 < d < 25 \\ 0, & d \geq 25 \end{cases}$$

where d is the distance in kilometers. If the distance information is unavailable, a score of 1 is assigned to the same city and 0.2 to a different city, whereas 0.5 is given if the location information is unavailable.

CSWMA develops two weighted scoring models. For Scheduled Booking, service match, trust, and experience receive greater importance:

$$SN = 0.30M + 0.25T + 0.15E + 0.15A + 0.10R + 0.05D$$

For priority booking, importance is given to availability and distance to support urgent requests:

$$SP = 0.20M + 0.15T + 0.05E + 0.30A + 0.05R + 0.25D$$

The final score is obtained by summing the products of each normalized attribute and its weight. Workers are sorted by their score in descending order, and the topmost worker not yet attempted is picked for Priority Booking assignment.

E. Booking Management:

The application offers Scheduled Booking and Priority Booking. The latter implies that the matching engine detects an appropriate available worker and automatically presents the request to him. In case of a worker's rejection, unavailability at the moment, or timeout, the matching engine initiates rematching. The use of Atomic DynamoDB Transactions and Server-side Availability Check ensures that double booking is prevented.

F. AI Assistant:

The application employs a basic role-aware AI assistant built with Google Gemini to provide service-specific assistance and deliver structured information, including service type, urgency, and booking details. An urgent request confirmation will trigger a Priority Booking, whereas a confirmed non-urgent request will offer worker recommendations based on similar cases. A rules-based fallback is also provided in case the AI service is unavailable.

G. Data Management and Security:

The application utilizes DynamoDB single-table with two GSIs for the core application data. User authentication and authorization are handled by Cognito JWT Claims, whereas verification documents are stored in encrypted private S3 buckets. IAM policies and Secrets Manager are used to control access to the application's AWS resources and AI credentials.

H. Priority Tracking and Communication:

Connect360 offers real-time tracking capabilities for Priority Booking with Leaflet.js and OpenStreetMap (OSRM) for real-road routing and ETA calculation. The calling feature allows making a call to a worker directly from an active booking using the device's default dialer, where the phone number will be offered by the calling application instead of being embedded in the Connect360 software.

I. Serverless:

The application is built with AWS's serverless technologies. The infrastructure was set up with Terraform, whereas the CloudFront service delivers the contents over HTTPS. The API Gateway serves REST API endpoints, Lambda handles the backend logic, DynamoDB stores the application's data, and S3 saves the documents.

IV. RESULTS AND ANALYSIS

Connect360 system was tested according to six experimental criteria associated with matching performance, ranking, transactional concurrency, spatial routing and PII redaction. All figures are taken from actual evaluation runs and benchmarks of the system.

TABLE I
COMPARISON OF SELECTED APPROACHES AND RESEARCH GAP

Approach	Service Recommendation	Skill/Task Matching	Trust/Reliability	Spatial Allocation	Priority Booking	AI/ML Methods
Local service-provider using ML [1]	✓	✓	✓	—	—	✓
Weighted preference optimization [2]	✓	—	✓	—	—	✓
Heterogeneous graph RL for task allocation [3]	—	✓	—	✓	✓	✓
Fairness-aware task assignment [4]	✓	✓	—	✓	—	—
Human-in-the-loop task assignment [5]	—	✓	—	✓	✓	—
LLMGCL for recommendation [6]	✓	—	—	—	—	✓
Prediction-aware task assignment [8]	—	✓	—	✓	✓	—
Geographic partition framework [9]	—	✓	—	✓	—	—
Priority queue task assignment [10]	—	✓	—	✓	✓	—
Trust-aware recommender (SIoT) [11]	✓	—	✓	—	—	—
Reliable personalized recommendation [12]	✓	—	✓	—	—	✓
Skill-based job recommendation [19]	✓	✓	—	—	—	—
Cloud-native AI pipelines [20]	—	—	—	—	—	✓
Connect360 (Proposed)	✓	✓	✓	✓	✓	✓

Where ✓ indicates that the capability is explicitly addressed, — indicates that it is not a primary focus of the cited approach. The comparison shows that existing approaches mainly focus on individual aspects such as service recommendation, skill matching, trust, spatial allocation and AI-based support. However, bringing these capabilities together within a complete skilled home-service booking workflow is less directly explored in the literature reviewed. Connect360 addresses this research gap by integrating service recommendation, skill-based matching, trust and reliability, location-based allocation, priority booking, and AI/ML methods into one unified platform. This enables more personalized, reliable, and efficient service-provider matching.

A. Matching Engine Latency

Matching engine was tested according to candidate pools consisting of 10 – 2500 workers using Scheduled and Priority Booking weights. Each configuration was run 1000 times.

10	Priority	0.3500	1.1470	0.3770
100	Priority	2.6933	9.7360	3.1465
1000	Priority	29.1044	65.9845	30.0948
2500	Priority	72.9826	215.5545	85.2716

TABLE II
MATCHING ALGORITHM EXECUTION LATENCY

Candidate	Type	P50(ms)	P99(ms)	Mean
10	Scheduled	0.1711	0.4729	0.2106
100	Scheduled	2.5522	4.7392	2.4670
1000	Scheduled	19.2856	50.3750	22.7084
2500	Scheduled	54.9163	118.0583	60.8471

Matching engine showed millisecond-level performance latency up to 1000 workers. At 100 candidates, the average latencies of 2.467 ms for Scheduled and 3.147 ms for Priority Booking at 100 candidates, but significant jumps were seen past 2500 candidates which is an argument in favor of necessity to perform candidate filtering in big pools.

B. Rank Sensitivity of Dual Weighting System

The 100-worker pool was tested for rank differences when applying Scheduled and Priority Booking weights.

Rank similarity was evaluated using Spearman's correlation, Kendall's tau coefficient and count of rank displacement.

TABLE III
RANK SENSITIVITY OF CSWMA

Distance Tier	Spearman	Kendall	Mean Rank Shift	Promoted	Demoted
Overall	0.8359	0.6497	13.18	50.0%	46.0%
Near (<5 km)	0.9111	0.7885	11.50	66.7%	26.7 %
Mid (5–15 km)	0.8227	0.6615	12.72	55.0%	42.5%
Far (>15 km)	0.8364	0.6460	15.47	98%	70.0%




Fig. 2. Rank Sensitivity and Inversion analysis

The average rank displacement was equal to 13.18 with maximum value of 40 while closeness of workers was more often than not a reason for their prioritizing (66.7%) while the opposite was true (70.0%) for distant workers.

C. Transactional Concurrency

The booking acceptance system was tested according to number of concurrently arriving booking requests. Around 50 runs were executed for each level of concurrency.

TABLE IV
TRANSACTIONAL CONCURRENCY EVALUATION

Concurrent	Attempt	Success	Conflict Rate	Double Booking
1	50	50	0%	0
10	500	50	90%	0
20	1000	50	95%	0

50	2500	50	98%	0
100	5000	50	99%	0

Across all concurrency experiments, 9,050 booking attempts were evaluated, with no double booking observed, while 99% of booking requests were refused at a concurrency level of 100 due to transactional conflicts.

D. Spatial Routing Assessment

About 50 routes of Chennai metro city were assessed by computing the Haversine distance and OSRM road distance.




Fig. 3. Haversine vs OSRM distance by region




Fig. 4. Distribution of Empirical Tortuosity Index

In general, the OSRM road distance was 28.48% larger than the Haversine distance, with an average tortuosity of 1.2848. Nonetheless, Haversine distance calculation required only 0.0296 ms, while OSRM routing required 1036.94 ms. The findings suggest that Haversine distance can be used in matching, and OSRM distance in routing.

E. Privacy Redaction Evaluation

Redaction filter was evaluated on 500 unique test cases (250 cases with PII and 250 cases benign) to classify these test cases with the PII detection filter and measure the performance. Each of the 500 test cases were executed 100 times (50,000 total executions) to measure the computational latency. The PII detection yielded 248 true positives (TP), 2 false negatives (FN), 25 false positives (FP), and 225 true negatives (TN), which represents 90.84% precision, 99.20% recall, 94.84% F1-score, and 94.60% accuracy. On average, each execution took 1.919 μ s to process with P99 at 6.021 μ s.

TABLE V
PII REDACTION PERFORMANCE

<i>Metric</i>	<i>Result</i>
<i>Precision</i>	90.84%
<i>Recall</i>	99.20%
<i>F1-Score</i>	94.84%
<i>Accuracy</i>	94.60%
<i>Mean Latency</i>	1.919 μ s
<i>P99 Latency</i>	6.021 μ s

F. Overall Analysis

The assessment shows three main aspects of the Connect360. Firstly, the CSWMA has different rankings for workers based on the context of the booking. The difference is evident in cases where Scheduled and Priority booking options were used. Secondly, the matching algorithm's execution time varied with the size of the candidate pool, taking longer to process larger sets of workers. Thirdly, the system was able to prevent double bookings from happening despite the intense use of the system.

The routing analysis and the AI assistant evaluation can be seen as separate validation tests for the Priority Booking feature and conversational-type assistance, respectively. Both were used to demonstrate the actual execution of the Connect360 features without engaging in performance claims that could be invalid for the customer.

V. DISCUSSION

From the evaluation results, it is clear that the CSWMA is capable of changing the ranking of the worker depending on the context of the booking process due to different weightings in the case of the Scheduled and Priority Booking.

The evaluation showed that the matching algorithm took longer to process larger candidate sets, particularly beyond 2500 candidates. This means that the optimization of the candidate set becomes crucial in terms of high concurrency.

Based on the results of the concurrency evaluation, it is possible to say that the transactional booking procedure

is enough to prevent the double-booking. This means that there were no examples of double-booking in all concurrency scenarios that were evaluated.

The evaluation results in terms of the spatial routing demonstrate that OSRM provides a road-based distance that is more representative of actual road than the straight line distance since the roads are the main means of transportation for the majority of the workers. What is more, it is important to note that the distance calculation is very important for the accuracy of the Priority Booking ranking because the possibility of the arrival of the worker to the booking location depends on their transportation possibilities.

In general, according to the results of the AI evaluation, it is possible to say that the system is capable of handling the service-specific interactions and ensuring the privacy of the contact information of the workers. First of all, in terms of the PII redaction evaluation, the high recall of the system was observed along with some space for the reduction of the number of false positives. Besides, the evaluation of the structured output demonstrated the adequacy of the service, urgency level, confirmation instruction, and structured response of the system.

VI. CONCLUSION

Connect360 is a proof-of-concept serverless skilled home-service platform that helps its customers to find, select, and book verified service workers. The Connect360 Smart Worker Matching Algorithm for Scheduled and Priority Booking is applied to the platform in accordance with the different scoring settings in the specific context of requested services.

As can be seen from the proof-of-concept prototype implementation, the possibility of using the service-worker matching, transactional booking, worker verification, road-based routing, AI-driven service interaction, and serverless computing on a single home-service platform exists. The findings of this research have demonstrated the possibility to effectively rank workers by different criteria, ensure booking consistency when there is a great number of service requests, support service allocation and user interactions based on role-based access control, protected storage of verification documents, and PII redaction.

The next steps in the development of the implemented solution include optimization of the candidate selection settings in case of a large number of service workers, minimization of the routing delay, setting up of the AI parameters in ambiguous cases of service contexts, and using of the prototype in other applications.

REFERENCES

- [1] A. Ezhilnilavan, S. Gopikrishnan, V. Harish Aravindh, S. Mithun, and M. Saratha, "Local community service provider using machine learning," in *Proc. 4th Int. Conf. Autom., Comput. Renewable Syst. (ICACRS)*, 2025, pp. 849–856, doi: 10.1109/ICACRS67045.2025.11324297.
- [2] H. Sun, F. Wang, Z. Tu, D. Sui, Y. Xing, K. Zhang, B. Zhao, and X. Xu, "A weighted preference optimization service recommendation method based on knowledge graph and large language model," in *Proc. IEEE Int. Conf. Web Services (ICWS)*, 2025, doi: 10.1109/ICWS67624.2025.00014.
- [3] Y. Zhao, Z. Zhu, C. Gao, E. Wang, J. Huang, and F.-Y. Wang, "Heterogeneous graph reinforcement learning for dependency-aware multi-task allocation in spatial crowdsourcing," *IEEE Trans. Mobile Comput.*, vol. 25, no. 3, pp. 3417–3434, Mar. 2026, doi: 10.1109/TMC.2025.3616027.
- [4] J. Chen, H. Miao, L. Jia, G. Yin, Y. Zhao, and K. Zheng, "Balancing competition for fairness-aware task recommendation and assignment in spatial crowdsourcing," in *Proc. IEEE 42nd Int. Conf. Data Eng. (ICDE)*, 2026, pp. 2984–2996, doi: 10.1109/ICDE65706.2026.00222.
- [5] Q. Wu, Y. Li, J. Yan, M. Zhang, J. Xu, and M. Xu, "Adaptive task assignment in spatial crowdsourcing: A human-in-the-loop approach," *IEEE Trans. Mobile Comput.*, vol. 24, no. 4, pp. 2726–2739, Apr. 2025, doi: 10.1109/TMC.2024.3501734.
- [6] S. Ge, S. Meng, J. Zhou, L. Qi, X. Xu, and X. Zhang, "LLMGCL: Graph contrastive learning with large language models for recommendation," in *Proc. IEEE Int. Conf. Web Services (ICWS)*, 2025, doi: 10.1109/ICWS67624.2025.00016.
- [7] L. Deng, Y. Zhao, Y. Cui, Y. Xia, J. Chen, and K. Zheng, "Task recommendation in spatial crowdsourcing: A trade-off between diversity and coverage," in *Proc. IEEE 40th Int. Conf. Data Eng. (ICDE)*, 2024, doi: 10.1109/ICDE60146.2024.00028.
- [8] Q. Wu, Y. Li, G. Zhu, B. Mei, J. Xu, and M. Xu, "Prediction-aware adaptive task assignment for spatial crowdsourcing," *IEEE Trans. Mobile Comput.*, vol. 23, no. 12, pp. 13048–13061, Dec. 2024, doi: 10.1109/TMC.2024.3423396.
- [9] Y. Zhao, X. Chen, G. Ye, F. Guo, K. Zheng, and X. Zhou, "Task allocation in spatial crowdsourcing: An efficient geographic partition framework," *IEEE Trans. Knowl. Data Eng.*, vol. 36, no. 9, pp. 4943–4955, Sep. 2024, doi: 10.1109/TKDE.2024.3374086.
- [10] Y. Ma, X. Gao, S. S. Bhatti, and G. Chen, "Clustering based priority queue algorithm for spatial task assignment in crowdsourcing," *IEEE Trans. Services Comput.*, vol. 17, no. 2, pp. 452–465, Mar.–Apr. 2024, doi: 10.1109/TSC.2024.3353293.
- [11] A. Khelloufi, A. Khelil, A. Naouri, A. Ben Sada, H. Ning, N. Aung, and S. Dhelim, "A hybrid feature and trust-aggregation recommender system in the social Internet of Things," *IEEE Access*, vol. 12, pp. 126460–126477, 2024, doi: 10.1109/ACCESS.2024.3411887.
- [12] J. Chen, R. Yang, J. Guo, H. Wang, K. Wu, and L.-J. Zhang, "Reliable service recommendation: A multi-modal adversarial method for personalized recommendation under uncertain missing modalities," *IEEE Trans. Services Comput.*, vol. 18, no. 3, pp. 1724–1738, May–Jun. 2025, doi: 10.1109/TSC.2025.3556640.
- [13] Y. Munir, Q. Umer, M. Faheem, S. Akram, and A. Jaffar, "Developer recommendation and team formation in collaborative crowdsourcing platforms," *IEEE Access*, vol. 13, pp. 63170–63185, 2025, doi: 10.1109/ACCESS.2025.3558557.
- [14] Z. Zhao, W. Fan, J. Li, Y. Liu, X. Mei, Y. Wang, Z. Wen, F. Wang, X. Zhao, J. Tang, and Q. Li, "Recommender systems in the era of large language models (LLMs)," *IEEE Trans. Knowl. Data Eng.*, vol. 36, no. 11, pp. 6889–6907, Nov. 2024, doi: 10.1109/TKDE.2024.3392335.
- [15] B. Zheng, Y. Hou, H. Lu, Y. Chen, W. X. Zhao, M. Chen, and J.-R. Wen, "Adapting large language models by integrating collaborative semantics for recommendation," in *Proc. IEEE 40th Int. Conf. Data Eng. (ICDE)*, 2024, pp. 1435–1448, doi: 10.1109/ICDE60146.2024.00118.
- [16] Refonaa, D. K. Yadav, G. Sood, S. K. Sonbhadra, and S. R. Reddy, "Exploring the potential of serverless architecture for cloud automation," in *Proc. Int. Conf. Autom. Comput. (AUTOCOM)*, 2025, doi: 10.1109/AUTOCOM64127.2025.10957197.
- [17] N. N. Ekwe-Ekwe and L. Amos, "The state of FaaS: An analysis of public functions-as-a-service providers," in *Proc. IEEE 17th Int. Conf. Cloud Comput. (CLOUD)*, 2024, pp. 430–438, doi: 10.1109/CLOUD62652.2024.00055.
- [18] M. Adeppady, A. Conte, P. Giaccone, H. Karl, and C. F. Chiasserini, "Dynamic management of constrained computing resources for serverless

services," *IEEE Trans. Netw. Service Manag.*, vol. 22, no. 2, pp. 1646–1663, Apr. 2025, doi: 10.1109/TNSM.2024.3497155.

[19] P. M. Kumar, P. Joshi, U. Dubey, A. Srivastava, and B. P. Kavin, "Enhanced job recommendation system using skill based rule matching algorithm," in *Proc. Int. Conf. Data Sci. Bus. Syst. (ICDSBS)*, 2025, doi: 10.1109/ICDSBS63635.2025.11031850.

[20] V. R. Pasam, P. Devaraju, V. Methuku, K. Dharamshi, and S. M. Veerapaneni, "Engineering scalable AI pipelines: A cloud-native approach for intelligent transactional systems," in *Proc. Int. Conf. Comput. Technol. (ICOCT)*, 2025, doi: 10.1109/ICOCT64433.2025.11118443.