

Looking at Non-Linear Dimension Reductions as Models in the Data Space

Jayani P.G. Lakshika

Econometrics & Business Statistics, Monash University
and

Dianne Cook

Econometrics & Business Statistics, Monash University
and

Paul Harrison

MGBP, BDInstitute, Monash University
and

Michael Lydeamore

Econometrics & Business Statistics, Monash University
and

Thiyanga S. Talagala

Statistics, University of Sri Jayewardenepura

April 20, 2024

Abstract

Nonlinear dimension reduction (NLDR) techniques such as tSNE, and UMAP provide a low-dimensional representation of high-dimensional (high-D) data using non-linear transformation. The methods and parameter choices can create wildly different representations, making it difficult to decide which is best, or whether any or all are accurate or misleading. NLDR often exaggerates random patterns, sometimes due to the samples observed. But NLDR views have an important role in data analysis because, if done well, they provide a concise visual (and conceptual) summary of high-D distributions. To help evaluate the NLDR we have developed an algorithm to show the 2D NLDR model in the high-D space, viewed with a tour. One can see if the model fits everywhere or better in some subspaces, or completely mismatches the data. It is used to evaluate which 2D layout is the best representation of the high-D distribution and see how different methods may have similar summaries or quirks.

Keywords: high-dimensional data, dimension reduction, hexagonal binning, low-dimensional manifold, tour, data vizualization, model in the data space

1 Introduction

Non-linear dimension reduction (NLDR) is popular for making a convenient low-dimensional (k -D) representation of high-dimensional (p -D) data. Recently developed methods include t-distributed stochastic neighbor embedding (tSNE) (van der Maaten & Hinton 2008), uniform manifold approximation and projection (UMAP) (McInnes & Healy 2018), potential of heat-diffusion for affinity-based trajectory embedding (PHATE) algorithm (Moon et al. 2019), large-scale dimensionality reduction Using triplets (TriMAP) (Amid & Warmuth 2022), and pairwise controlled manifold approximation (PaCMAP) (Wang et al. 2021). However, the representation generated can vary dramatically from method to method, and with different choices of parameters or random seeds made using the same method (Figure 1). The dilemma for the analyst is then, **which representation to use**. The choice might result in different procedures used in the downstream analysis, or different inferential conclusions. The research described here provides new visual tools to aid with this decision.



Figure 1: Six different NLDR representations of the same data. Different techniques and different parameter choices are used. Researchers may have seen any of these in their analysis of this data, depending on their choice of method, or typical parameter choice. Would they make different decisions downstream in the analysis depending on which version seen? Which is the most accurate representation of the structure in high dimensions?

The paper is organised as follows. Section 2 provides a summary of the literature on NLDR, and high-dimensional data visualization methods. Section 3 contains the details of the new methodology, including simulated data examples. Two applications illustrating the use of the new methodology for bioinformatics and image classification are in Section 4. Limitations and future directions are provided in Section 5.

2 Background

Historically, k - D representations of p - D data have been computed using multidimensional scaling (MDS) (Borg & Groenen 2005), which includes principal components analysis (PCA) (Jolliffe 2011) as a special case. The k - D representation can be considered to be a layout of points in k - D produced by an embedding procedure that maps the data from p - D . In MDS, the k - D layout is constructed by minimizing a stress function that differences distances between points in p - D with potential distances between points in k - D . Various formulations of the stress function result in non-metric scaling (Saeed et al. 2018) and isomap (Silva & Tenenbaum 2002). Challenges in working with high-dimensional data, including visualization, are outlined in Johnstone & Titterton (2009).

Many new methods for NLDR have emerged in recent years, all designed to better capture specific structures potentially existing in p - D . Here we focus on five currently popular techniques, tSNE, UMAP, PHATE, TriMAP and PaCMAP. tSNE and UMAP can be considered to produce the k - D minimizing the divergence between two distributions, where the distributions are modeling the inter-point distances. PHATE, TriMAP and PaCMAP are examples of diffusion processes (Coifman et al. 2005) spreading to capture geometric shapes, that include both global and local structure.

The array of layouts in Figure 1 illustrate what can emerge from the choices of method and parameters, and the random seed that initiates the computation. Key structures interpreted from these views suggest: (1) highly **separated clusters** (a, b, e, g, h) with the number ranging from 3-6; (2) **stringy branches** (f), and (3) **barely separated clusters** (c, d) which would **contradict** the other representations.

It happens because these methods and parameter choices provide different lenses on the interpoint distances in the data.

The alternative approach to visualizing the high-dimensional data is to use linear projections. PCA is the classical approach, resulting in a set of new variables which are linear combinations of the original variables. Tours, defined by Lee et al. (2021), broaden the scope by providing movies of linear projections, that provide views the data from all directions. Lee et al. (2021) provides an review of the main developments in tours. There are many tour algorithms implemented, with many available in the R package `tourr` (Wickham et al. 2011), and versions enabling better interactivity in `langevitour` (Harrison 2023) and `detourr` (Hart & Wang 2022). Linear projections are a safe way to view high-dimensional data, because they do not warp the space, so they are more faithful representations of the structure. However, linear projections can be cluttered, and global patterns can obscure local structure. The simple activity of projecting data from p - D suffers from piling (Laa et al. 2022), where data concentrates in the center of projections. NLDR is designed to escape these issues, to exaggerate structure so that it can be observed. But as a result NLDR can hallucinate wildly, to suggest patterns that are not actually present in the data.

The solution is to use the tour to examine how the NLDR is warping the space. This approach follows what Wickham et al. (2015) describes as *model-in-the-data-space*. The fitted model should be overlaid on the data, to examine the fit relative the spread of the observations. While this is straightforward, and commonly done when data is 2D, it is also possible in p - D , for many models, when a tour is used.

Wickham et al. (2015) provides several examples of models overlaid on the data in p - D . In hierarchical clustering, a representation of the dendrogram using points and lines can be constructed by augmenting the data with points marking merging of clusters. Showing the movie of linear projections reveals how the algorithm sequentially fitted the cluster model to the data. For linear discriminant analysis or model-based clustering the model can be indicated by $(p - 1)$ - D ellipses. It is possible to see whether the elliptical shapes appropriately matches the variance of the relevant clusters, and to compare and contrast different fits. For PCA, one can display the k - D plane of the reduced dimension using wireframes of transformed cubes. Using a wireframe is the approach we take here, to represent the NLDR model in p - D .

3 Method

3.1 What is the NLDR model?

At first glance, thinking of NLDR as a modeling technique might seem strange. It is a simplified representation or abstraction of a system, process, or phenomenon in the real world. The p - D observations are the realization of the phenomenon, and the k - D NLDR layout is the simplified representation. From a statistical perspective we can consider the distances between points in the k - D layout to be variance that the model explains, and the (relative) difference with their distances in p - D is the error, or unexplained variance. We can also imagine that the positioning of points in 2D represent the fitted values, that will have some prescribed position in p - D that can be compared with their observed values. This is the conceptual framework underlying the more formal versions of factor analysis (Jöreskog 1969) and multidimensional scaling (MDS) (Borg & Groenen 2005). (Note that, for this thinking the full p - D data needs to be available, not just the interpoint distances.)

We define the NLDR as a function $g: \mathbb{R}^{n \times p} \rightarrow \mathbb{R}^{n \times k}$, with (hyper-)parameters θ . The parameters, θ , depend on the choice of g , and can be considered part of model fitting in the traditional sense. Common choices for g include functions used in tSNE, UMAP, PHATE, TriMAP, PaCMAP, or MDS, although in theory any function that does this mapping is suitable.

With our goal being to make a representation of this 2D layout that can be lifted into high-dimensional space, the layout needs to be augmented to include neighbour information. A simple approach would be to triangulate the points and add edges. A more stable approach is to first hexagonally bin the data, and connect the bin centroids. This process serves to reduce some noisiness in the resulting surface shown in p - D . The steps in this process are shown in Figure 2, and documented below.

To illustrate the method, we use 7- D simulated data, which we call the “S-curve”. It is constructed by setting $X_1 = \sin(a)$, $X_2 = U(0, 2)$, $X_3 = \text{sign}(a) \times (\cos(a) - 1)$, $\forall a \in [-3\pi/2, 3\pi/2]$. The remaining variables X_4, X_5, X_6, X_7 are all uniform error, with small variance. We would consider $T = (X_1, X_2, X_3)$ to be the true model.

Notation	Description
n, p, k, m	number of observations, variables, embedding dimension, number of non-empty bins, respectively
\mathbf{X}, \mathbf{x}	p -dimensional data (population, sample)
\mathbf{y}	k -dimensional layout
P	orthonormal basis, generating a d -dimensional linear projection of p -dimensional data
T	true model
g	functional mapping from p -D to k -D, especially as prescribed by NLDR
θ	(Hyper-) parameters for NLDR method
y_{\max}	maximum value of the scaled second embedding component
r	ranges of the embedding components
b	bins
a_r	aspect ratio of the 2D layout before scaling
s	hexagonal size (defined as the radius of the outer circle surrounding the hexagon)
(x_s, y_s)	starting coordinates of the hexagonal grid
q_x, q_y	buffer amount along the x and y axes
h_s, v_s	horizontal and vertical distance between adjacent hexagon bin centroids
d_x, d_y	horizontal spacing and adjusted vertical spacing for hexagonal coordinates
b_x, b_y	number of hexagon bins along the x and y axes
b, b'	total and non-empty hexagon bins in the grid
n_k	number of observations within the k^{th} hexagon
$(h_{x_i}^k, h_{y_i}^k)$	hexagonal grid coordinates of the k^{th} hexagon
$C^{(j)}$	j -dimensional bin centers

Table 1: Summary of notation for describing new methodology.




Figure 2: Key steps for constructing the model on the UMAP layout ($k = 2$) of the S-curve data: (a) data, (b) hexagon bins, (c) bin centroids, and (d) triangulated centroids.

3.1.1 Scaling the data

It is beneficial to define the algorithm on data having a standard scale. Here we use $[0, 1]$ scaling, but by default include the aspect ratio produced by the NLDR (r_1, r_2, \dots, r_k) , by allowing for the upper bound to vary, $(y_{1,\max}, y_{2,\max}, \dots, y_{k,\max})$.

When $k = 2$ which is assumed for hexagon binning, $(y_{1,\max} = 1$ and $y_{2,\max} = \frac{r_2}{r_1} \times \frac{2}{\sqrt{3}}$. (The $\frac{2}{\sqrt{3}}$ accounts for the different height and width of a regular hexagon.)

3.1.2 Computing hexagonal grid configurations

To define a hexagonal grid across the k -D space, using hexagons with fixed height (h_b), width (w_b), need to compute the how many hexagons should be represented by each axes in k -D space.

When $k = 2$, the number of bins along the x and y axes, b_1 and b_2 is computed by accounting r_1, r_2 , offset along the axes (q_1, q_2), and height (h_b), width (w_b) of a regular hexagon.

$(b_1 = \frac{r_1 + q_1}{w_b}, b_2 = \frac{r_2 + q_2}{0.75 \times h_b})$: $0.75 \times h_b$ accommodate to have the tessellation without spacing.

3.1.3 Hexagon binning

Define a hexagonal grid across the k -D space, using hexagons with fixed height (h_b), width (w_b).

When $k = 2$,

The starting coordinates (s_1, s_2) mark the lower left of the grid. This is the bottom left bin centroid. By starting from there, points are generated to fill the grid accounting b_1 and b_2 .

Each of the k -D points will belong to a hexagonal bin. That is, for each $y \in \mathbf{Y}$, we can (uniquely) identify the hexagon that the point belongs to. This identification is done finding the nearest bin centroid for the k -D points by considering the k -D Euclidean distance.

3.1.4 Obtaining bin centroids

Let $h : \mathbb{R}^{n \times k} \rightarrow \mathbb{R}^{m \times k}$ be the function that maps a point in k -D space to its hexagonal centroid ($C^{(k)}$).

3.1.5 Generating edges

computes a set of simplices such that no data points of \mathbf{X} are contained in any circumspheres of the simplices.

When $k = 2$

Delaunay triangulation of $C^{(k)}$ is a triangulation of the convex hull of $C^{(k)}$ such that the circumcircle of every triangle in the triangulation contains no other points from $C^{(k)}$.

3.2 Displaying the model in p -D

The final step of the algorithm is *lifting* the k -D model back to p -D, completing the *model-in-the-data-space* picture. For this, define the set H^k to be the set of points that belong to centroid k . That is, $H^k = \{y \mid g(y) = (h_x^k, h_y^k)\}$. We use the p -D Euclidean mean of the points in H^k to map the centroid (h_x^k, h_y^k) to a point in p -D. Let the i -th component of the p -D mean be

$$f_i = \frac{1}{|H^k|} \sum_{y \in H^k} y_i,$$

with corresponding p -D vector \vec{f}_i . Then, $f(h \circ g)(x)$ maps a p -D point to the p -D model estimate, completing the model cycle.

When $k = 2$, which bin centroids should be connected are identified as a result of triangulation. Therefore, corresponding p -D points should be connected in the same order.

3.3 Measuring the fit

3.4 What can be learned

- Overview: Generate a form that maps the model, that is the interpoint distances. What is the model?
- Notation
- Create a representation of the model
 - using hex-binning in 2D,
 - parameters,

- tuning,
 - pre-processing
- How does this map to the representation in high-d
 - Centroids,
 - Edges
- Measuring fit
 - Fitted values
 - Error calculation
- What is learned about simulated examples
 - Interesting organisation of points in UMAP
 -

4 Applications

4.1 pbmc

- NLDR view used to illustrate clusters
- Use our method to assess is it a reasonable representation
- Demonstrate that it is not
- Illustrate how to use our method to get a better representation

4.2 digits: 1

- NLDR is used to illustrate different ways 1's are drawn
- Use our method to assess is it a reasonable representation
- Demonstrate that it is, except for the anomalies

5 Discussion

- Summarise contributions
- Explain where it is expected or not expected to work, eg higher dimensional relationships
- Human behaviour, the desire to have more certainty, and a tendency to prefer the well-separated views
- Predicting new observations in k -D
- Extending layouts beyond k -D, when 2D is clearly inadequate.

- Diagnostic app to explore differences in distances
- What might be useful enhancements

References

- Amid, E. & Warmuth, M. K. (2022), ‘Trimap: Large-scale dimensionality reduction using triplets’.
- Borg, I. & Groenen, P. J. F. (2005), *Modern Multidimensional Scaling Theory and Applications*, Springer, New York.
- Coifman, R., Lafon, S., Lee, A., Maggioni, M., Nadler, B., Warner, F. & Zucker, S. (2005), ‘Geometric diffusions as a tool for harmonic analysis and structure definition of data: Diffusion maps’, *Proceedings of the National Academy of Sciences of the United States of America* **102**, 7426–31.
- Harrison, P. (2023), ‘langevitour: Smooth interactive touring of high dimensions, demonstrated with scRNA-seq data’, *The R Journal* **15**, 206–219. <https://doi.org/10.32614/RJ-2023-046>.
- Hart, C. & Wang, E. (2022), *detourr: Portable and Performant Tour Animations*. R package version 0.1.0.
URL: <https://casperhart.github.io/detourr/>
- Johnstone, I. M. & Titterton, D. M. (2009), ‘Statistical challenges of high-dimensional data’, *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences* **367**(1906), 4237–4253.
URL: <https://royalsocietypublishing.org/doi/abs/10.1098/rsta.2009.0159>
- Jolliffe, I. (2011), *Principal Component Analysis*, Springer Berlin Heidelberg, Berlin, Heidelberg, pp. 1094–1096.
URL: https://doi.org/10.1007/978-3-642-04898-2_455
- Jöreskog, K. G. (1969), ‘A general approach to confirmatory maximum likelihood factor analysis’, *Psychometrika* pp. 183–202.
URL: <https://doi.org/10.1007/BF02289343>
- Laa, U., Cook, D. & Lee, S. (2022), ‘Burning sage: Reversing the curse of dimensionality in the visualization of high-dimensional data’, *J. Comput. Graph. Stat.* **31**(1), 40–49.
URL: <https://doi.org/10.1080/10618600.2021.1963264>
- Lee, S., Cook, D., da Silva, N., Laa, U., Wang, E., Spyrisson, N. & Zhang, H. S. (2021), ‘A review of the state-of-the-art on tours for dynamic visualization of high-dimensional data’.
- McInnes, L. & Healy, J. (2018), ‘Umap: Uniform manifold approximation and projection for dimension reduction’, *ArXiv* **abs/1802.03426**.
- Moon, K. R., van Dijk, D., Wang, Z., Gigante, S. A., Burkhardt, D. B., Chen, W. S., Yim, K., van den Elzen, A., Hirn, M. J., Coifman, R. R., Ivanova, N. B., Wolf, G.

- & Krishnaswamy, S. (2019), ‘Visualizing structure and transitions in high-dimensional biological data’, *Nature Biotechnology* **37**, 1482 – 1492.
- Saeed, N., Nam, H., Haq, M. I. U. & Muhammad Saqib, D. B. (2018), ‘A survey on multidimensional scaling’, *ACM Comput. Surv.* **51**(3).
URL: <https://doi.org/10.1145/3178155>
- Silva, V. & Tenenbaum, J. (2002), ‘Global versus local methods in nonlinear dimensionality reduction’, *Advances in neural information processing systems* **15**.
- van der Maaten, L. & Hinton, G. E. (2008), ‘Visualizing data using t-sne’, *Journal of Machine Learning Research* **9**, 2579–2605.
- Wang, Y., Huang, H., Rudin, C. & Shaposhnik, Y. (2021), ‘Understanding how dimension reduction tools work: An empirical approach to deciphering t-sne, umap, trimap, and pacmap for data visualization’, *Journal of Machine Learning Research* **22**(201), 1–73.
URL: <http://jmlr.org/papers/v22/20-1061.html>
- Wickham, H., Cook, D. & Hofmann, H. (2015), ‘Visualizing statistical models: Removing the blindfold’, *Statistical Analysis and Data Mining: The ASA Data Science Journal* **8**(4), 203–225.
URL: <https://onlinelibrary.wiley.com/doi/abs/10.1002/sam.11271>
- Wickham, H., Cook, D., Hofmann, H. & Buja, A. (2011), ‘tourr: An r package for exploring multivariate data with projections’, *Journal of Statistical Software* **40**(2), 1–18.
URL: <http://www.jstatsoft.org/v40/i02/>