

Design And Analysis of Algorithms Lab Exercise:

Ex1: Implement Bubble Sort

```
def bubbleSort(arr):
    n = len(arr)

    # Traverse through all array elements
    for i in range(n):

        # Last i elements are already in place
        for j in range(0, n-i-1):

            # traverse the array from 0 to n-i-1
            # Swap if the element found is greater
            # than the next element
            if arr[j] > arr[j+1] :
                arr[j], arr[j+1] = arr[j+1], arr[j]

# Driver code to test above
arr = [64, 34, 25, 12, 22, 11, 90]

bubbleSort(arr)

print ("Sorted array is:")
for i in range(len(arr)):
    print ("%d" %arr[i],end=" ")
```

Traversal:

i = 0	j	0	1	2	3	4	5	6	7
	0	5	3	1	9	8	2	4	7
	1	3	5	1	9	8	2	4	7
	2	3	1	5	9	8	2	4	7
	3	3	1	5	9	8	2	4	7
	4	3	1	5	8	9	2	4	7
	5	3	1	5	8	2	9	4	7
	6	3	1	5	8	2	4	9	7
i = 1	0	3	1	5	8	2	4	7	9
	1	1	3	5	8	2	4	7	
	2	1	3	5	8	2	4	7	
	3	1	3	5	8	2	4	7	
	4	1	3	5	2	8	4	7	
	5	1	3	5	2	4	8	7	
i = 2	0	1	3	5	2	4	7	8	
	1	1	3	5	2	4	7		
	2	1	3	5	2	4	7		
	3	1	3	2	5	4	7		
	4	1	3	2	4	5	7		
i = 3	0	1	3	2	4	5	7		
	1	1	3	2	4	5			
	2	1	2	3	4	5			
	3	1	2	3	4	5			
i = 4	0	1	2	3	4	5			
	1	1	2	3	4				
	2	1	2	3	4				
i = 5	0	1	2	3	4				
	1	1	2	3					
i = 6	0	1	2	3					
	1	2							

1. Measure the number of Comparisons and swap for the program and plot a chart.
2. Modify the program to have best case Efficiency.
3. Check whether the algorithm has the 2 properties.
4. Implement recursive bubble sort.
5. Implement Insertion sort and answer Q1 to q4 for the same.