

# ENTITY RELATIONAL MODEL

Mirunalini.P

SSNCE

March 29, 2022

# Table of Contents

1 ER Model

2 Reference

# Session Objective

- Understand ER model concepts
- Understand ER diagram notations

# Session Outcome

At the end of this session, participants will be able to

- To Understand ER model concepts
- To Understand ER diagram notations
- Able to draw ER diagram for any schema


- **Entity-Relational (ER)** model is a popular high level conceptual data model and is used for **conceptual design** of database applications
- E-R facilitate **database design** by representing overall logical structure of a database.
- E-R data model employs three basic notions :
  - **Entity sets**
  - **Relationship sets**
  - **Attributes**
- The E-R model is usually expressed as an **E-R diagram**

# Entities and Attributes

- **Entity:** An entity is a thing or an object in the miniworld that are represented in databases.
- Eg: Employee, Department.
- **Attributes:** Properties used to describe the entity.
- Eg: EMPLOYEE Entity has four attributes Name, Address, Age, Phone.
- **Value:** Each entity has a value for each of its attributes.
- Eg: Name='JONES', Address='Harrington Road', Age=40, Phone=01-44-3470727

# Entity and Attributes

Two entities Employee and Company and their attributes



# Types of Attributes


Attributes can be

- Composite / Simple (atomic)
- Single-valued / Multivalued
- Stored / Derived
- Key / Nonkey



# Types of Attributes

- **Simple:** Attribute that has a **single atomic value or not divisible**.
- Example: SSN or age.
- **Composite:** The attribute that can be **divided into smaller subparts**.
- Example: Address (Apt\_No, House\_No, Street, City, State, ZipCode, Country) .



# Types of Attributes

- **Single Valued:** Attributes with **single value** for a particular entity
- Ex: Age of a student is a single valued attribute.
- **Multi-valued :**An entity may have **multiple values** for an attribute.It may have upper and lower bounds on the number of values.
- Example: Color of a CAR Denoted as Color
- **Stored vs Derived attribute :** The values for this type of attribute are **derived from the values of other related attributes or entities.**
- Age can be determined from the current date and the value of person's BirthDate .
- Hence the **age attribute is derived attribute** and **BirthDate is called stored attribute**

# Entity Types and Entity Set

- **Entity Type**

- It is a **collection of entities** that share common properties or characteristics.
- Each entity type is described by name and its attributes.
- An entity type is represented as a **rectangular box enclosing the entity type name**
- Example: the EMPLOYEE entity type or the PROJECT entity type.

- **Entity Set:**

- The **collection of all entities of a particular entity type in the DB at any point in time**
- Entity set uses the same name as the entity type.

# Entity Types and Entity Set

**ENTITY TYPE NAME:**

EMPLOYEE

COMPANY

Name, Age, Salary

Name, Headquarters, President

**ENTITY SET:  
(EXTENSION)**

$e_1$  •

(John Smith, 55, 80k)

$e_2$  •

(Fred Brown, 40, 30K)

$e_3$  •

(Judy Clark, 25, 20K)

⋮

$c_1$  •

(Sunco Oil, Houston, John Smith)

$c_2$  •

(Fast Computer, Dallas, Bob King)

⋮

# Keys

- An attribute whose values that **uniquely identifies** individual instances of an entity type is key attribute
- Eg: SSN of EMPLOYEE.
- A key attribute may be composite.
- Eg: VehicleTagNumber is a key of the CAR entity type with components (Number, State).
- The Key attribute is **underlined inside the oval** in ER Diagram.
- A weak entity type is one **without any key attributes** of its own.

# Entity Types and Entity Set

**CAR**  
**Registration(RegistrationNumber, State), VehicleID, Make, Model, Year, {Color}**

**car<sub>1</sub>** •

((ABC 123, TEXAS), TK629, Ford Mustang, convertible, 1998, {red, black})

**car<sub>2</sub>** •










((ABC 123, NEW YORK), WP9872, Nissan Maxima, 4-door, 1999, {blue})

**car<sub>3</sub>** •


((VSY 720, TEXAS), TD729, Chrysler LeBaron, 4-door, 1995, {white, blue})

•  
•  
•

# ER Diagram Notation

<u>Symbol</u>	<u>Meaning</u>
	ENTITY TYPE
	WEAK ENTITY TYPE
	RELATIONSHIP TYPE
	IDENTIFYING RELATIONSHIP TYPE
	ATTRIBUTE
	KEY ATTRIBUTE
	MULTIVALUED ATTRIBUTE
	COMPOSITE ATTRIBUTE
	DERIVED ATTRIBUTE

# ER Diagram -Example






# RelationshipTypes, sets and Instances


- An attribute of one entity type refers to another entity type, some relationship exists.
- A relationship **relates two or more distinct entities** with a specific meaning.
- Relationship Type defines **meaningful association** or a relationship set between (or among) entities from the entity types.
- The relationship set R is a set of relationship instances  $r_i$
- Example: The Attribute Manager of DEPARTMENT refers to an employee who manages the department
- It is denoted by a **diamond symbol** in E-R Diagram.
- It is connected by straight lines to the rectangular boxes representing the participating entity types.

# Example - Relationship Type




# Relationship Degree

- The **degree** of a relationship type is the **number of participating entity types**.
- Example: WORKS\_FOR relationship is degree of two.
- A relationship type of degree two is called **binary**, and three is called **ternary**




# Relationship Degree - Ternary



Each relationship instance  $r_i$  associates three entities a supplier  $s_i$ , part  $p_i$  and project  $j_i$


# Role Names

- Role name signifies the **role that a participating entity** from the entity type plays in each relationship instance.
- Example : The works\_for relationship type, EMPLOYEE plays the role of employee or worker and DEPARTMENT plays the role of department or employer.



# Recursive Relationship


- Recursive relationship type: Same entity type participate in the relationship type **more than once in different roles**.
- Example: SUPERVISION relationships between EMPLOYEE (in role of supervisor or boss) and EMPLOYEE (in role of subordinate or worker).



# Constraints on Relationship Types

- Relationship types usually have certain constraints that limit the possible combinations of entities.
- These constraints are determined from the situation from the relationship that represent.
- Two main types of relationship constraints
  - **Cardinality Ratio**
  - **Participation**
- Cardinality Ratio of binary relationship specifies the **number of relationship instances** that an entity can participate in.
- The Cardinality Ratio for binary relationship types are **1:1, 1:N, N:1 AND M:N**
- Shown By Placing Appropriate Number On The Link.


# 1: 1 Relationship Types






# 1: N Relationship Types

- The 1:N relationship : WORKS\_FOR




# M: N Relationship Types



# Participation Constraints on Relationship Types

- Determines **whether all or only some entity** occurrences participate in a relationship
- Two types of participation constraints
  - **Total participation**
  - **Partial participation**
- total = every entity needs to be 'related'
- e.g. EMPLOYEE works\_in DEPARTMENT
- Total participation displayed as double line in ER Diagram
- partial = some entities are involved
- e.g. EMPLOYEE manages DEPARTMENT
- Partial participation displayed as single line in ER Diagram

# Example for participation















Note: double lines represent total participation

# Weak Entity Type

- A weak entity type is one **without any key attributes** of its own.
- Entity types having key attribute — > strong entity types
- Entities belonging to a weak entity type are **identified** by being related to another entity type called **identifying owner**
- The relationship type that relates a weak entity type to its owner is called **identifying relationship of weak entity type**
- A weak entity type has **total participation** constraint w.r.t. its identifying relationship

# ER Notations

## ER Notations

Symbol	Meaning
	ENTITY
	WEAK ENTITY
	RELATIONSHIP
	IDENTIFYING RELATIONSHIP
	ATTRIBUTE
	KEY ATTRIBUTE
	MULTIVALUED ATTRIBUTE
	COMPOSITE ATTRIBUTE
	DERIVED ATTRIBUTE
	TOTAL PARTICIPATION OF $E_2$ IN $R$
	CARDINALITY RATIO 1: $N$ FOR $E_1:E_2$ IN $R$
	STRUCTURAL CONSTRAINT (min, max) ON PARTICIPATION OF $E$ IN $R$


The company is organized into DEPARTMENTS:

- Each department has a name, number, locations, an employee who manages the department and Manager\_start\_date. Locations is the only multivalued attribute. Also specify that both Name and Number are (separate) key attributes because each was specified to be unique.
- Each department controls a number of PROJECTs. Each project has a name, number and is located at a single location and controlling\_department. Both Name and Number are (separate) key attributes because each was specified to be unique.

- Store each EMPLOYEE's social security number, address, salary, sex, and birthdate. Name may be composite attributes. Each employee works for one department but may work on several projects. We keep track of the number of hours per week that an employee currently works on each project. We also keep track of the direct supervisor of each employee.
- Each employee may have a number of DEPENDENTs. For each dependent, we keep track of their name, sex, birthdate, and relationship to employee.



# ER Notations



**Figure 3.8**

Preliminary design of entity types for the COMPANY database. Some of the shown attributes will be refined into relationships.

# Refining the COMPANY database schema by introducing relationships

- By examining the requirements, six relationship types are identified
- All are binary relationships( degree 2)
- Listed below with their participating entity types:
  - **WORKS\_FOR** (between EMPLOYEE, DEPARTMENT)
  - **MANAGES** (also between EMPLOYEE, DEPARTMENT)
  - **CONTROLS** (between DEPARTMENT, PROJECT)
  - **WORKS\_ON** (between EMPLOYEE, PROJECT)
  - **SUPERVISION** (between EMPLOYEE (as subordinate), EMPLOYEE (as supervisor))
  - **DEPENDENTS\_OF** (between EMPLOYEE, DEPENDENT)

# Discussion on Relationship Types

Some attributes from the initial entity types are refined into relationships:

- Manager of DEPARTMENT – > MANAGES
- Works\_on of EMPLOYEE – > WORKS\_ON
- Department of EMPLOYEE – > WORKS\_FOR

More than one relationship type can exist between the same participating entity types

- MANAGES and WORKS\_FOR are distinct relationship types between EMPLOYEE and DEPARTMENT

EMPLOYEE participates twice in two distinct roles:


- Supervisor (or boss) role
- Supervisee (or subordinate) role

# Discussion on Relationship Types

## Weak Entity type

- A DEPENDENT entity is identified by the dependent's first name, and the specific EMPLOYEE with whom the dependent is related
- Name of DEPENDENT is the partial key
- DEPENDENT is a weak entity type
- EMPLOYEE is its identifying entity type via the identifying relationship type DEPENDENT\_OF


# ER DIAGRAM



# Structural Constraints

- Alternative notation for specifying structural constraints on relations.
- Involves associating pair of integer numbers (min,max) with each participation.
  - $0 \leq min \leq max$  and  $max \geq 1$
  - $Min = 0$  partial participation
  - $Min > 0$  total participation

# Alternative notation of ER DIAGRAM



# Reference



Fundamentals of Database systems 7<sup>th</sup> Edition by Ramez Elmasri.



Oracle 9i SQL