

Module M2

Partha Pratir Das

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding
Dynamic Binding

Polymorphic Type

Aodule Summar

Programming in Modern C++

Module M27: Polymorphism: Part 2: Static and Dynamic Binding

Partha Pratim Das

Department of Computer Science and Engineering Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional



Module Recap

Objectives & Outlines

Introduced type casting

- Understood the difference between implicit and explicit type casting
- Introduced the notions of type casting in a class hierarchy upcast and downcast

Partha Pratim Das M27.2



Module Objectives

Module M2

Partha Pratii Das

Objectives & Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding

Polymorphic Type

Module Summa

• Understand Static and Dynamic Binding

• Understand Polymorphic Type



Module Outline

Objectives & Outlines

- Type Binding
 - Type of an Object
 - Static and Dynamic Binding
 - Comparison of Static and Dynamic Binding
 - Static Binding
 - Dynamic Binding
- Polymorphic Type
- Module Summary



Type Binding

Module M2

Partha Pratir Das

Objectives Outlines

Type Binding

Type of an Object Static and Dynamic Binding Comparison Static Binding

Polymorphic Type

Module Summai



Type Binding



Type of an Object

Module M2

Partha Pratir Das

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding
Dynamic Binding

Polymorphic Type

- The *static type* of the object is the type declared for the object while writing the code
- Compiler sees static type
- The *dynamic type* of the object is determined by the type of the object to which it refers at run-time
- Compiler does not see dynamic type



Static and Dynamic Binding

....

Das


Objectives Outlines

Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding
Dynamic Binding

Polymorphic Type

.

- Static binding (early binding): When a function invocation binds to the function definition based on the static type of objects
 - This is done at compile-time
 - Normal function calls, overloaded function calls, and overloaded operators are examples of static binding
- **Dynamic binding** (late binding): When a function invocation binds to the function definition based on the dynamic type of objects
 - This is done at run-time
 - Function pointers, Virtual functions are examples of late binding





Comparison of Static and Dynamic Binding

Module M3

Partha Prati Das

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding

Comparison Static Binding Dynamic Binding

Polymorphic Type

• Event

Basis

Information

- Advantage
- Time
- Actual Object
- Alternate name
- Example

Static Binding

• Events occur at compile time – Static Binding

- All information needed to call a function is known at *compile time*
- Efficiency
- Fast execution
- Actual object is not used for binding
- Early Binding

Method Overloading
 Normal function call,
 Overloaded function call,
 Overloaded operators

Dynamic Binding
 Events occur at run time – Dynamic

All information needed to call a function is known only at run time

- Flexibility
- Slow execution
- Actual object is used for binding
- Late Binding
- Method Overriding Virtual functions



Static Binding

Static Binding

```
Inherited Method
```

Overridden Method

```
#include<iostream>
using namespace std;
class B { public:
   void f() { }
class D : public B { public:
    void g() { } // new function
int main() { B b; D d;
   b.f(); // B::f()
   d.f(); // B::f() ---- Inherited
   d.g(); // D::g() ---- Added
```

- Object d of derived class inherits the base class function f() and has its own function g()
- Function calls are resolved at compile time based on static type

- #include<iostream> using namespace std; class B { public: void f() { } class D : public B { public: void f() { } int main() { B b: D d: b.f(); // B::f() d.f(): // D::f() ---- Overridden // masks the base class function
- If a member function of a base class is redefined in a derived class with the same signature then it masks the base class method
- The derived class method f() is linked to the object d. As f() is redefined in the derived class, the base class version cannot be called with the object of a derived class



Member Functions: Overrides and Overloads: RECAP (Module 22)

Override & Overload

Inheritance

Static Binding

```
class B { public: // Base Class
 class B { public: // Base Class
     void f(int i):
                                                        void f(int):
                                                        void g(int i);
     void g(int i);
                                                    };
 };
 class D: public B { public: // Derived Class
                                                    class D: public B { public: // Derived Class
     // Inherits B::f(int)
                                                        // Inherits B::f(int)
                                                        void f(int): // Overrides B::f(int)
                                                        void f(string&); // Overloads B::f(int)
                                                        // Inherits B::g(int)
     // Inherits B::g(int)
                                                        void h(int i): // Adds D::h(int)
                                                    };
 B b:
                                                    B b:
                                                    D d:
 D d:
 b.f(1): // Calls B::f(int)
                                                    b.f(1):
                                                                // Calls B::f(int)
                                                    b.g(2):
                                                                // Calls B::g(int)
 b.g(2): // Calls B::g(int)
                                                    d.f(3):
                                                                // Calls D::f(int)
 d.f(3): // Calls B::f(int)
                                                    d.g(4):
                                                                // Calls B::g(int)
 d.g(4); // Calls B::g(int)
                                                    d.f("red"): // Calls D::f(string&)
                                                    d.h(5): // Calls D::h(int)
 • D::f(int) overrides B::f(int)
 • D::f(string&) overloads B::f(int)
Programming in Modern C++
```



using Construct - Avoid Method Hiding

Partha Pratin Das

Objectives of Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding

Polymorphic Type

. олушогрше турс

```
#include<iostream>
using namespace std;
class A { public:
    void f() { }
};
class B : public A { public:
    // To overload, rather than hide the base class function f(),
    // it is introduced into the scope of B with a using declaration
   using A::f:
   void f(int) { } // Overloads f()
int main() {
   B b: // function calls resolved at compile time
    b.f(3): // B::f(int)
   b.f(): // A::f()
```

 Object b of derived class linked to with inherited base class function f() and the overloaded version defined by the derived class f(int), based on the input parameters – function calls resolved at compile time



Dynamic Binding

Module M2

Partha Pratii Das

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding
Dynamic Binding

Polymorphic Type

Module Summar

```
Non-Virtual Method Virtual Method
```

```
#include<iostream>
#include<iostream>
using namespace std;
                                         using namespace std;
class B { public:
                                         class B { public:
    void f() { }
                                             virtual void f() { }
                                         };
class D : public B { public:
                                         class D : public B { public:
    void f() { }
                                             virtual void f() { }
                                         1;
int main() {
                                         int main() {
    B b:
                                             B b:
   D d:
                                             D d:
    B *p;
                                             B *p;
    p = &b: p -> f(): // B::f()
                                               = \&b: p->f(): // B::f()
    p = &d; p > f(); // B::f()
                                             p = &d: p > f(): // D::f()
```

- p->f() always binds to B::f()
- Binding is decided by the type of pointer
 Static Binding
- Binding is decided by the type of object
- Dynamic Binding

• p->f() binds to B::f() for a B object, and to D::f() for a D object



Static and Dynamic Binding

Dynamic Binding

```
#include <iostream>
using namespace std;
class B { public:
    void f() { cout << "B::f()" << endl: }</pre>
    virtual void g() { cout << "B::g()" << endl; }</pre>
}:
class D: public B { public:
    void f() { cout << "D::f()" << endl; }</pre>
    virtual void g() { cout << "D::g()" << endl:</pre>
}:
 int main() { B b; D d;
                                                    pb->f(); // B::f() -- Static Binding
                                                    pb->g(); // B::g() -- Dynamic Binding
     B *pb = &b;
                                                    pd->f(); // B::f() -- Static Binding
     B *pd = &d: // UPCAST
                                                    pd->g(): // D::g() -- Dynamic Binding
     B \& rb = b:
                                                    rb.f(): // B::f() -- Static Binding
     B \&rd = d: // UPCAST
                                                    rb.g(): // B::g() -- Dynamic Binding
                                                    rd.f(): // B::f() -- Static Binding
     b.f(); // B::f()
                                                    rd.g(); // D::g() -- Dynamic Binding
     b.g(); // B::g()
     d.f(): // D::f()
                                                    return 0:
     d.g(): // D::g()
```



Polymorphic Type

Module M2

Partha Pratir Das

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding

Polymorphic Type

Module Summar

Polymorphic Type



Polymorphic Type: Virtual Functions

Module Ma

Partha Pratii Das

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding
Dynamic Binding

Polymorphic Type

• *Dynamic binding* is possible only for pointer and reference data types and for member functions that are declared as virtual in the base class

- These are called Virtual Functions
- If a member function is declared as virtual, it can be overridden in the derived class
- If a member function is not virtual and it is re-defined in the derived class then the latter definition hides the former one
- Any class containing a virtual member function by definition or by inheritance is called a Polymorphic Type
- A hierarchy may be *polymorphic* or *non-polymorphic*
- A non-polymorphic hierarchy has little value



Polymorphism Rule

#include <iostream>

Module M27

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding
Dynamic Binding

Polymorphic Type

```
using namespace std;
class A { public:
    void f()
                      { cout << "A::f()" << endl; } // Non-Virtual
                       cout << "A::g()" << endl; } // Virtual
    virtual void g()
    void h()
                       cout << "A::h()" << endl: } // Non-Virtual
class B : public A { public:
    void f()
                       cout << "B::f()" << endl; } // Non-Virtual</pre>
    void g()
                       cout << "B::g()" << endl: } // Virtual
    virtual void h() { cout << "B::h()" << endl; } // Virtual</pre>
}:
class C : public B { public:
    void f()
                       cout << "C::f()" << endl: } // Non-Virtual
                       cout << "C::g()" << endl; } // Virtual
    void g()
    void h()
                        cout << "C::h()" << endl: } // Virtual
};
                                                    A::f()
 int main() {
     B *q = new C; A *p = q;
                                                    C::g()
                                                    A::h()
     p->f();
                                                    B::f()
                                                    C::g()
     p->g():
                                      q->h();
     p->h():
                                                    C::h()
```



Module Summary

Module M2

Partha Pratii Das

Objectives Outlines

Type Binding
Type of an Object
Static and Dynamic
Binding
Comparison
Static Binding
Dynamic Binding

Polymorphic Type

Module Summary

• Discussed Static and Dynamic Binding

• Polymorphic type introduced

