



Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Programming in Modern C++

Module M14: Copy Constructor and Copy Assignment Operator

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional



Module Recap

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- Objects are initialized by Constructors that can be Parameterized and / or Overloaded
- Default Constructor does not take any parameter – necessary for arrays of objects
- Objects are cleaned-up by Destructors. Destructor for a class is unique
- Compiler provides *free* Default Constructor and Destructor, if not provides by the program
- Objects have a well-defined lifetime spanning from execution of the beginning of the body of a constructor to the execution till the end of the body of the destructor
- Memory for an object must be available before its construction and can be released only after its destruction



Module Objectives

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- More on Object Lifetime
- Understand Copy Construction
- Understand Copy Assignment Operator
- Understand Shallow and Deep Copy



Module Outline

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- 1 Object Lifetime Examples
 - String
 - Date: Practice
 - Rect: Practice
 - Name & Address: Practice
 - CreditCard: Practice
- 2 Copy Constructor
 - Call by Value
 - Signature
 - Data Members
 - Free Copy Constructor and Pitfalls
- 3 Copy Assignment Operator
 - Copy Objects
 - Self-Copy
 - Signature
 - Free Assignment Operator
- 4 Comparison of Copy Constructor and Copy Assignment Operator
- 5 Class as a Data-type
- 6 Module Summary



Object Lifetime Examples

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Object Lifetime Examples



Program 14.01/02: Order of Initialization: Order of Data Members

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
using namespace std;
int init_m1(int m) { // Func. to init m1_
    cout << "Init m1_: " << m << endl;
    return m;
}
int init_m2(int m) { // Func. to init m2_
    cout << "Init m2_: " << m << endl;
    return m;
}
class X { int m1_; // Initialize 1st
         int m2_; // Initialize 2nd
public: X(int m1, int m2) :
        m1_(init_m1(m1)), // Called 1st
        m2_(init_m2(m2)) // Called 2nd
        { cout << "Ctor: " << endl; }
        ~X() { cout << "Dtor: " << endl; } };
int main() { X a(2, 3); return 0; }
```

```
-----
Init m1_: 2
Init m2_: 3
Ctor:
Dtor:
```

```
#include <iostream>
using namespace std;
int init_m1(int m) { // Func. to init m1_
    cout << "Init m1_: " << m << endl;
    return m;
}
int init_m2(int m) { // Func. to init m2_
    cout << "Init m2_: " << m << endl;
    return m;
}
class X { int m2_; // Order of data members swapped
         int m1_;
public: X(int m1, int m2) :
        m1_(init_m1(m1)), // Called 2nd
        m2_(init_m2(m2)) // Called 1st
        { cout << "Ctor: " << endl; }
        ~X() { cout << "Dtor: " << endl; } };
int main() { X a(2, 3); return 0; }
```

```
-----
Init m2_: 3
Init m1_: 2
Ctor:
Dtor:
```

● *Order of initialization does not depend on the order in the initialization list. It depends on the order of data members in the definition*

Programming in Modern C++



Program 14.03/04: A Simple String Class

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

C Style

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;
struct String { char *str_; // Container
               size_t len_; // Length
};
void print(const String& s) {
    cout << s.str_ << ": "
         << s.len_ << endl;
}
int main() { String s;

    // Init data members
    s.str_ = strdup("Partha");
    s.len_ = strlen(s.str_);
    print(s);
    free(s.str);
}
-----
```

Partha: 6

• Note the order of initialization between *str_* and *len_*. What if we swap them?

C++ Style

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;
class String { char *str_; // Container
              size_t len_; // Length
public: String(char *s) : str_(strdup(s)), // Uses malloc()
                      len_(strlen(str_))
    { cout << "ctor: "; print(); }
    ~String() { cout << "dtor: "; print();
              free(str_); // To match malloc() in strdup()
    }
    void print() { cout << "(" << str_ << ": "
                  << len_ << ")" << endl; }
    size_t len() { return len_; }
};
int main() { String s = "Partha"; // Ctor called
            s.print();
}
-----
```

ctor: (Partha: 6)

(Partha: 6)

dtor: (Partha: 6)



Program 14.05: A Simple String Class:

Fails for wrong order of data members

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;

class String {
    size_t len_; // Swapped members cause garbage to be printed or program crash (unhandled exception)
    char *str_;
public:
    String(char *s) : str_(strdup(s)), len_(strlen(str_)) { cout << "ctor: "; print(); }
    ~String() { cout << "dtor: "; print(); free(str_); }
    void print() { cout << "(" << str_ << ": " << len_ << ")" << endl; }
};

int main() { String s = "Partha";
    s.print();
}

----- // May produce garbage or crash
ctor: (Partha: 20)
(Partha: 20) // Garbage
dtor: (Partha: 20)
```

- **len_ precedes str_ in list of data members**
- **len_(strlen(str_)) is executed before str_(strdup(s))**
- **When strlen(str_) is called str_ is still uninitialized**
- **May causes the program to crash**



Practice: Program 14.06: A Simple Date Class

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
using namespace std;

char monthNames[][4]={ "Jan", "Feb", "Mar", "Apr", "May", "Jun", "Jul", "Aug", "Sep", "Oct", "Nov", "Dec" };
char dayNames[][10] ={ "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday", "Sunday" };
class Date {
    enum Month { Jan = 1, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, Nov, Dec };
    enum Day { Mon, Tue, Wed, Thr, Fri, Sat, Sun };
    typedef unsigned int UINT;
    UINT date_; Month month_; UINT year_;
public:
    Date(UINT d, UINT m, UINT y) : date_(d), month_((Month)m), year_(y) { cout << "ctor: "; print(); }
    ~Date() { cout << "dctor: "; print(); }
    void print() { cout << date_ << "/" << monthNames[month_ - 1] << "/" << year_ << endl; }
    bool validDate() { /* Check validity */ return true; } // Not implemented
    Day day() { /* Compute day from date using time.h */ return Mon; } // Not implemented
};

int main() {
    Date d(30, 7, 1961);
    d.print();
}

-----
ctor: 30/Jul/1961
30/Jul/1961
dctor: 30/Jul/1961
```



Practice: Program 14.07: Point and Rect Classes: Lifetime of Data Members or Embedded Objects

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
using namespace std;
class Point { int x_; int y_; public:
    Point(int x, int y):
        x_(x), y_(y)
    { cout << "Point ctor: ";
      print(); cout << endl; }
    ~Point() { cout << "Point dtor: ";
              print(); cout << endl; }
    void print() { cout << "(" << x_ << ", "
                  << y_ << ")"; }
};

int main() {
    Rect r (0, 2, 5, 7);

    cout << endl; r.print(); cout << endl;

    cout << endl;
}
```

```
class Rect { Point TL_; Point BR_; public:
    Rect(int tlx, int tly, int brx, int bry):
        TL_(tlx, tly), BR_(brx, bry)
    { cout << "Rect ctor: ";
      print(); cout << endl; }
    ~Rect() { cout << "Rect dtor: ";
              print(); cout << endl; }
    void print() { cout << "["; TL_.print();
                  cout << " "; BR_.print(); cout << "]"; }
};

-----
Point ctor: (0, 2)
Point ctor: (5, 7)
Rect ctor: [(0, 2) (5, 7)]

[(0, 2) (5, 7)]

Rect dtor: [(0, 2) (5, 7)]
Point dtor: (5, 7)
Point dtor: (0, 2)
```

- Attempt is to construct a Rect object
- That, in turn, needs constructions of Point data members (or embedded objects) – TL_ and BR_ respectively
- Destruction, initiated at the end of scope of destructor's body, naturally follows a reverse order



Practice: Program 14.08: Name & Address Classes

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
using namespace std;

#include "String.h" // Containing class String from slide 14.7
#include "Date.h"

class Name { String firstName_, lastName_;
public: Name(char* fn, char* ln) : firstName_(fn), lastName_(ln)
    { cout << "Name ctor: "; print(); cout << endl; }
    ~Name() { cout << "Name dtor: "; print(); cout << endl; }
    void print() { firstName_.print(); cout << " "; lastName_.print(); }
};

class Address { unsigned int houseNo_;
    String street_, city_, pin_;
public: Address(unsigned int hn, char* sn, char* cn, char* pin) :
    houseNo_(hn), street_(sn), city_(cn), pin_(pin)
    { cout << "Address ctor: "; print(); cout << endl; }
    ~Address() { cout << "Address dtor: "; print(); cout << endl; }
    void print() {
        cout << houseNo_ << " ";
        street_.print(); cout << " ";
        city_.print(); cout << " ";
        pin_.print();
    }
};
```



Practice: Program 14.08: CreditCard Class

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
class CreditCard { typedef unsigned int UINT;
    char cardNumber_[17]; // 16-digit (character) card number as C-string
    Name holder_; Address addr_;
    Date issueDate_, expiryDate_;
    UINT cvv_;
public:
    CreditCard(char* cNumber, char* fn, char* ln, unsigned int hn, char* sn, char* cn, char* pin,
        UINT issueMonth, UINT issueYear, UINT expiryMonth, UINT expiryYear, UINT cvv) :
        holder_(fn, ln), addr_(hn, sn, cn, pin),
        issueDate_(1, issueMonth, issueYear),
        expiryDate_(1, expiryMonth, expiryYear), cvv_(cvv)
        { strcpy(cardNumber_, cNumber); cout << "CC ctor: "; print(); cout << endl; }
    ~CreditCard() { cout << "CC dtor: "; print(); cout << endl; }
    void print() {
        cout << cardNumber_ << " "; holder_.print(); cout << " "; addr_.print(); cout << " ";
        issueDate_.print(); cout << " "; expiryDate_.print(); cout << " "; cout << cvv_;
    }
};

int main() {
    CreditCard cc("5321711934640027", "Sharlock", "Holmes",
        221, "Baker Street", "London", "NW1 6XE", 7, 2014, 12, 2016, 811);
    cout << endl; cc.print(); cout << endl << endl;
}
```



Practice: Program 14.08: CreditCard Class: Lifetime Chart

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Construction of Objects

String: Sherlock

String: Holmes

Name: Sherlock Holmes

String: Baker Street

String: London

String: NW1 6XE

Address: 221 Baker Street London NW1 6XE

Date: 1/Jul/2014

Date: 1/Dec/2016

CC: 5321711934640027 Sherlock Holmes 221 Baker Street London NW1 6XE 1/Jul/2014 1/Dec/2016 811

Use of Object

5321711934640027 Sherlock Holmes 221 Baker Street London NW1 6XE 1/Jul/2014 1/Dec/2016 811

Destruction of Objects

~CC: 5321711934640027 Sherlock Holmes 221 Baker Street London NW1 6XE 1/Jul/2014 1/Dec/2016 811

~Date: 1/Dec/2016

~Date: 1/Jul/2014

~Address: 221 Baker Street London NW1 6XE

~String: NW1 6XE

~String: London

~String: Baker Street

~Name: Sherlock Holmes

~String: Holmes

~String: Sherlock

```
typedef unsigned int UINT;
class CreditCard { char cardNumber_[17];
    Name holder_; Address addr_;
    Date issueDate_, expiryDate_; UINT cvv_; };
class Name { String firstName_, lastName_; };
class Address { unsigned int houseNo_;
    String street_, city_, pin_; };
class Date { enum Month;
    UINT date_; Month month_; UINT year_; };
```



Copy Constructor

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Copy Constructor



Copy Constructor

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- We know:

```
Complex c1(4.2, 5.9);
```

invokes

```
Constructor Complex::Complex(double, double);
```

- Which constructor is invoked for?

```
Complex c2(c1);
```

Or for?

```
Complex c2 = c1;
```

- It is the **Copy Constructor** that takes an object of the same type and constructs a copy:

```
Complex::Complex(const Complex &);
```



Program 14.09: Complex: Copy Constructor

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cmath>
using namespace std;
class Complex { double re_, im_; public:
    // Constructor
    Complex(double re, double im):
        re_(re), im_(im)
    { cout << "Complex ctor: "; print(); }
    // Copy Constructor
    Complex(const Complex& c):
        re_(c.re_), im_(c.im_)
    { cout << "Complex copy ctor: "; print(); }
    // Destructor
    ~Complex()
    { cout << "Complex dtor: "; print(); }
    double norm() { return sqrt(re_*re_ + im_*im_); }
    void print() { cout << "|" << re_ << "+j" << im_ << "| = " << norm() << endl; }
};

int main() {
    Complex c1(4.2, 5.3), // Constructor - Complex(double, double)
           c2(c1),        // Copy Constructor - Complex(const Complex&)
           c3 = c2;       // Copy Constructor - Complex(const Complex&)

    c1.print(); c2.print(); c3.print();
}
```

```
Complex ctor: |4.2+j5.3| = 6.7624 // Ctor: c1
Complex copy ctor: |4.2+j5.3| = 6.7624 // CCtor: c2 of c1
Complex copy ctor: |4.2+j5.3| = 6.7624 // CCtor: c3 of c2
|4.2+j5.3| = 6.7624 // c1
|4.2+j5.3| = 6.7624 // c2
|4.2+j5.3| = 6.7624 // c3
Complex dtor: |4.2+j5.3| = 6.7624 // Dtor: c3
Complex dtor: |4.2+j5.3| = 6.7624 // Dtor: c2
Complex dtor: |4.2+j5.3| = 6.7624 // Dtor: c1
```




Why do we need Copy Constructor?

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- Consider the **function call mechanisms** in C++:
 - **Call-by-reference**: Set a reference to the actual parameter as a formal parameter. Both the formal parameter and the actual parameter share the same location (object). *No copy is needed*
 - **Return-by-reference**: Set a reference to the computed value as a return value. Both the computed value and the return value share the same location (object). *No copy is needed*
 - **Call-by-value**: Make a *copy* or *clone* of the actual parameter as a formal parameter. This needs a **Copy Constructor**
 - **Return-by-value**: Make a *copy* or *clone* of the computed value as a return value. This needs a **Copy Constructor**
- **Copy Constructor** is needed for *initializing the data members* of a UDT from an existing value



Program 14.10: Complex: Call by value

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cmath>
using namespace std;
class Complex { double re_, im_; public:
    Complex(double re, double im): re_(re), im_(im) // Constructor
    { cout << "ctor: "; print(); }
    Complex(const Complex& c): re_(c.re_), im_(c.im_) // Copy Constructor
    { cout << "copy ctor: "; print(); }
    ~Complex() { cout << "dtor: "; print(); }
    double norm() { return sqrt(re_*re_ + im_*im_); }
    void print() { cout << "|" << re_ << "+j" << im_ << " | = " << norm() << endl; }
};

void Display(Complex c_param) { // Call by value
    cout << "Display: "; c_param.print();
}

int main() { Complex c(4.2, 5.3); // Constructor - Complex(double, double)

    Display(c); // Copy Constructor called to copy c to c_param
}

-----
ctor: |4.2+j5.3| = 6.7624 // Ctor of c in main()
copy ctor: |4.2+j5.3| = 6.7624 // Ctor c_param as copy of c, call Display()
Display: |4.2+j5.3| = 6.7624 // c_param
dtor: |4.2+j5.3| = 6.7624 // Dtor c_param on exit from Display()
dtor: |4.2+j5.3| = 6.7624 // Dtor of c on exit from main()
```



Signature of Copy Constructors

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- Signature of a *Copy Constructor* can be one of:

```
MyClass(const MyClass& other);           // Common
                                         // Source cannot be changed
MyClass(MyClass& other);                 // Occasional
                                         // Source needs to change. Like in smart pointers
MyClass(volatile const MyClass& other);  // Rare
MyClass(volatile MyClass& other);        // Rare
```

- None of the following are copy constructors, though they can copy:

```
MyClass(MyClass* other);
MyClass(const MyClass* other);
```

- *Why the parameter to a copy constructor must be passed as Call-by-Reference?*

```
MyClass(MyClass other);
```

The above is an infinite recursion of copy calls as the call to copy constructor itself needs to make copy for the Call-by-Value mechanism



Program 14.11: Point and Rect Classes: Embedded Objects

Default, Copy and Overloaded Constructors

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
using namespace std;
class Point { int x_; int y_; public:
    Point(int x, int y): x_(x), y_(y) { cout << "Point ctor: "; print(); cout << endl; } // Ctor
    Point(): x_(0), y_(0) { cout << "Point ctor: "; print(); cout << endl; } // Dctor
    Point(const Point& p): x_(p.x_), y_(p.y_) { cout << "Point cctor: "; print(); cout << endl; } // CCtor
    ~Point() { cout << "Point dtor: "; print(); cout << endl; } // Dtor
    void print() { cout << "(" << x_ << ", " << y_ << ")"; } // Class Point
class Rect { Point TL_; Point BR_; public:
    Rect(int tlx, int tly, int brx, int bry): TL_(tlx, tly), BR_(brx, bry) // Ctor of Rect: 4 coords
    { cout << "Rect ctor: "; print(); cout << endl; } // Uses Ctor for Point
    Rect(const Point& p_tl, const Point& p_br): TL_(p_tl), BR_(p_br) // Ctor of Rect: 2 Points
    { cout << "Rect ctor: "; print(); cout << endl; } // Uses CCtor for Point
    Rect(const Point& p_tl, int brx, int bry): TL_(p_tl), BR_(brx, bry) // Ctor of Rect: Point + 2 coords
    { cout << "Rect ctor: "; print(); cout << endl; } // Uses CCtor for Point
    Rect() { cout << "Rect ctor: "; print(); cout << endl; } // Dctor of Rect: // Dctor Point
    Rect(const Rect& r): TL_(r.TL_), BR_(r.BR_) // CCtor of Rect
    { cout << "Rect cctor: "; print(); cout << endl; } // Uses CCtor for Point
    ~Rect() { cout << "Rect dtor: "; print(); cout << endl; } // Dtor
    void print() { cout << "["; TL_.print(); cout << " "; BR_.print(); cout << "]"; } // Class Rect
```

- When parameter (tlx, tly) is set to TL_ by TL_(tlx, tly): parameterized Ctor of Point is invoked
- When parameter p_tl is set to TL_ by TL_(p_tl): CCtor of Point is invoked
- When TL_ is set by default in Dctor of Rect: Dctor of Point is invoked
- When member r.TL_ is set to TL_ by TL_(r.TL_) in CCtor of Rect: CCtor of Point is invoked



Practice: Program 14.11: Rect Class: Trace of Object Lifetimes

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Code	Output	Lifetime	Remarks
<pre>int main() { Rect r1(0, 2, 5, 7); //Rect(int, int, int, int) Rect r2(Point(3, 5), Point(6, 9)); //Rect(Point&, Point&) Rect r3(Point(2, 2), 6, 4); //Rect(Point&, int, int) Rect r4; //Rect() return 0; }</pre>	<pre>Point ctor: (0, 2) Point ctor: (5, 7) Rect ctor: [(0, 2) (5, 7)] Point ctor: (6, 9) Point ctor: (3, 5) Point ctor: (3, 5) Point ctor: (6, 9) Rect ctor: [(3, 5) (6, 9)] Point ctor: (3, 5) Point ctor: (6, 9) Point ctor: (2, 2) Point ctor: (2, 2) Point ctor: (6, 4) Rect ctor: [(2, 2) (6, 4)] Point ctor: (2, 2) Point ctor: (0, 0) Point ctor: (0, 0) Rect ctor: [(0, 0) (0, 0)] Rect dtor: [(0, 0) (0, 0)] Point dtor: (0, 0) Point dtor: (0, 0) Rect dtor: [(2, 2) (6, 4)] Point dtor: (6, 4) Point dtor: (2, 2) Rect dtor: [(3, 5) (6, 9)] Point dtor: (6, 9) Point dtor: (3, 5) Rect dtor: [(0, 2) (5, 7)] Point dtor: (5, 7) Point dtor: (0, 2)</pre>	<pre>Point r1.TL_ Point r1.BR_ Rect r1 Point t1 Point t2 r2.TL_ = t2 r2.BR_ = t1 Rect r2 ~Point t2 ~Point t1 Point t3 r3.TL_ = t3 Point r3.BR_ Rect r3 ~Point t3 Point r4.TL_ Point r4.BR_ Rect r4 ~Rect r4 ~Point r4.BR_ ~Point r4.TL_ ~Rect r3 ~Point r3.BR_ ~Point r3.TL_ ~Rect r2 ~Point r2.BR_ ~Point r2.TL_ ~Rect r1 ~Point r1.BR_ ~Point r1.TL_</pre>	<pre>Second parameter First parameter Copy to r2.TL_ Copy to r2.BR_ First parameter Second parameter First parameter Copy to r3.TL_ First parameter</pre>



Free Copy Constructor

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature


Free Assignment

Comparison

Class as Type

Module Summary

- If no copy constructor is provided by the user, the compiler supplies a *free* one
- *Free* copy constructor cannot initialize the object to proper values. It performs *Shallow Copy*
- **Shallow Copy** aka *bit-wise copy*, *field-by-field copy*, *field-for-field copy*, or *field copy*
 - An object is created by simply *copying the data of all variables* of the original object
 - Works well if *none of the variables of the object are defined in heap / free store*
 - For dynamically created variables, the *copied object refers to the same memory location*
 - Creates *ambiguity* (changing one changes the copy) and *run-time errors* (dangling pointer)
- **Deep Copy** or its variants *Lazy Copy* and *Copy-on-Write*
 - An object is created by copying data of all variables except the ones on heap
 - Allocates similar memory resources with the same value to the object
 - **Need to explicitly define the copy constructor and assign dynamic memory as required**
 - **Required to dynamically allocate memory to the variables in the other constructors**





Pitfalls of Bit-wise Copy: Shallow Copy

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- Consider a class:

```
class A { int i_;      // Non-pointer data member
        int* p_;     // Pointer data member
public:
    A(int i, int j) : i_(i), p_(new int(j)) { } // Init. with pointer to dynamically created object
    ~A() { cout << "Destruct " << this << ": "; // Object identity
          cout << "i_ = " << i_ << " p_ = " << p_ << " *p = " << *p_ << endl; // Object state
          delete p_; // Release resource
        }
};
```

- As no copy constructor is provided, the implicit copy constructor does a bit-wise copy. So when an **A** object is copied, **p_** is copied and continues to point to the same dynamic int:

```
int main() { A a1(2, 3); A a2(a1); // Construct a2 as a copy of a1. Done by bit-wise copy
            cout << "&a1 = " << &a1 << " &a2 = " << &a2 << endl;
}
```

- The output is wrong, as **a1.p_ = a2.p_** points to the same **int** location. Once **a2** is destructed, **a2.p_** is released, and **a1.p_** becomes dangling. **The program may print garbage or crash:**

```
&a1 = 008FF838 &a2 = 008FF828 // Identities of objects
Destruct 008FF828: i_ = 2 p_ = 00C15440 *p = 3 // Dtor of a2. Note that a2.p_ = a1.p_
Destruct 008FF838: i_ = 2 p_ = 00C15440 *p = -17891602 // Dtor of a1. a1.p_=a2.p_ points to garbage
```

- The bit-wise copy of members is known as **Shallow Copy**



Pitfalls of Bit-wise Copy: Deep Copy

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- Now suppose we provide a user-defined copy constructor:

```
class A { int i_;      // Non-pointer data member
        int* p_;     // Pointer data member
public:
    A(int i, int j) : i_(i), p_(new int(j)) { } // Init. with pointer to dynamically created object
    A(const A& a) : i_(a.i_),                  // Copy Constructor
                  p_(new int(*a.p_)) { }       // Allocation done and value copied - Deep Copy
    ~A() { cout << "Destruct " << this << ": "; // Object identity
          cout << "i_ = " << i_ << " p_ = " << p_ << " *p = " << *p_ << endl; // Object state
          delete p_;                          // Release resource
        }
};
```

- The output now is correct, as `a1.p_ ≠ a2.p_` points to the different `int` locations with the values `*a1.p_ = *a2.p_` properly copied:

```
&a1 = 00B8F9E0 &a2 = 00B8F9D0 // Identities of objects
Destruct 00B8F9D0: i_ = 2 p_ = 00C95480 *p = 3 // Dtor of a2. a2.p_ is different from a1.p_
Destruct 00B8F9E0: i_ = 2 p_ = 00C95440 *p = 3 // Dtor of a1. Works correctly!
```

- This is known as **Deep Copy** where every member is copied properly. Note that:
 - In every class, provide copy constructor to adopt to deep copy which is always safe
 - Naturally, shallow copy is cheaper than deep copy. So some languages support variants as *Lazy Copy* or *Copy-on-Write* for efficiency



Practice: Program 14.12: Complex: Free Copy Constructor

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cmath>
using namespace std;
class Complex { double re_, im_; public:
    Complex(double re, double im) : re_(re), im_(im) { cout << "ctor: "; print(); } // Ctor
    // Complex(const Complex& c) : re_(c.re_), im_(c.im_) { cout<<"copy ctor: "; print(); } // CCtor: Free only
    ~Complex() { cout << "dtor: "; print(); } // Dtor
    double norm() { return sqrt(re_*re_ + im_*im_); }
    void print() { cout << "|" << re_ << "+j" << im_ << "| = " << norm() << endl; }
};
void Display(Complex c_param) { cout << "Display: "; c_param.print(); }
int main() { Complex c(4.2, 5.3); // Constructor - Complex(double, double)
    Display(c); // Free Copy Constructor called to copy c to c_param
}
```

User-defined CCtor

```
ctor: |4.2+j5.3| = 6.7624
copy ctor: |4.2+j5.3| = 6.7624
Display: |4.2+j5.3| = 6.7624
dtor: |4.2+j5.3| = 6.7624
dtor: |4.2+j5.3| = 6.7624
```

Free CCtor

```
ctor: |4.2+j5.3| = 6.7624
    No message from free CCtor
Display: |4.2+j5.3| = 6.7624
dtor: |4.2+j5.3| = 6.7624
dtor: |4.2+j5.3| = 6.7624
```

- User has provided *no copy constructor*
- Compiler provides *free copy constructor*
- Compiler-provided copy constructor *performs bit-wise copy* - hence there is no message
- *Correct in this case* as members are of built-in type and there is no dynamically allocated data



Practice: Program 14.13: String: User-defined Copy Constructor

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cstdlib>
#include <cstring>
using namespace std;
class String { public: char *str_; size_t len_;
    String(char *s) : str_(strdup(s)), len_(strlen(str_)) { }           // Ctor
    String(const String& s) : str_(strdup(s.str_)), len_(s.len_) { }    // CCtor: User provided
    ~String() { free(str_); }                                           // Dtor
    void print() { cout << "(" << str_ << ": " << len_ << ")" << endl; }
};
void strToUpper(String a) { // Make the string uppercase
    for (int i = 0; i < a.len_; ++i) { a.str_[i] = toupper(a.str_[i]); }
    cout << "strToUpper: "; a.print();
} // a.~String() is invoked releasing a.str_. s.str_ remains intact
int main() { String s = "Partha"; s.print(); strToUpper(s); s.print(); }
---
```

(Partha: 6)
strToUpper: (PARTHA: 6)
(Partha: 6)

- User has *provided copy constructor*. So Compiler *does not provide free copy constructor*
- When actual parameter *s* is copied to formal parameter *a*, space is allocated for *a.str_* and then it is copied from *s.str_*. On exit from *strToUpper*, *a* is destructed and *a.str_* is deallocated. But in *main*, *s* remains intact and access to *s.str_* is valid.
- **Deep Copy**: While copying the object, the pointed object is copied in a fresh allocation. *This is safe*



Practice: Program 14.14: String: Free Copy Constructor

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;
class String { public: char *str_; size_t len_;
    String(char *s) : str_(strdup(s)), len_(strlen(str_)) { }           // Ctor
    // String(const String& s) : str_(strdup(s.str_)), len_(s.len_) { } // CCtor: Free only
    ~String() { free(str_); }                                           // Dtor
    void print() { cout << "(" << str_ << ": " << len_ << ")" << endl; }
};
void strToUpper(String a) { // Make the string uppercase
    for (int i = 0; i < a.len_; ++i) { a.str_[i] = toupper(a.str_[i]); } cout<<"strToUpper: "; a.print();
} // a.~String() is invoked releasing a.str_ and invalidating s.str_ = a.str_
int main() { String s = "Partha"; s.print(); strToUpper(s); s.print(); } // Last print fails
```

User-defined CCtor

```
(Partha: 6)
strToUpper: (PARTHA: 6)
(Partha: 6)
```

Free CCtor

```
(Partha: 6)
strToUpper: (PARTHA: 6)
(?????????????????????????????????: 6)
```

- User has provided *no copy constructor*. Compiler provides *free copy constructor*
- Free copy constructor performs *bit-copy* - hence no allocation is done for *str_* when actual parameter *s* is copied to formal parameter *a*. *s.str_* is merely copied to *a.str_* and both continue to point to the same memory. On exit from *strToUpper*, *a* is destructed and *a.str_* is deallocated. Hence in *main* access to *s.str_* is dangling. Program prints garbage and / or crashes
- **Shallow Copy:** With bit-copy, only the pointer is copied - not the pointed object. *This is risky*



Copy Assignment Operator

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Copy Assignment Operator



Copy Assignment Operator

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- We can copy an existing object to another existing object as

```
Complex c1 = (4.2, 5.9), c2(5.1, 6.3);
```

```
c2 = c1;    // c1 becomes { 4.2, 5.9 }
```

This is like normal assignment of built-in types and overwrites the old value with the new value

- It is the **Copy Assignment** that takes an object of the same type and overwrites into an existing one, and returns that object:

```
Complex::Complex& operator= (const Complex &);
```



Program 14.15: Complex: Copy Assignment

```
#include <iostream>
#include <cmath>
using namespace std;
class Complex { double re_, im_; public:
    Complex(double re, double im) : re_(re), im_(im) { cout << "ctor: "; print(); } // Ctor
    Complex(const Complex& c) : re_(c.re_), im_(c.im_) { cout << "cctor: "; print(); } // CCtor
    ~Complex() { cout << "dtor: "; print(); } // Dtor
    Complex& operator=(const Complex& c) // Copy Assignment Operator
    { re_ = c.re_; im_ = c.im_; cout << "copy: "; print(); return *this; } // Return *this for chaining
    double norm() { return sqrt(re_*re_ + im_*im_); }
    void print() { cout << "|" << re_ << "+j" << im_ << "| = " << norm() << endl; } }; // Class Complex
int main() { Complex c1(4.2, 5.3), c2(7.9, 8.5); Complex c3(c2); // c3 Copy Constructed from c2
    c1.print(); c2.print(); c3.print();
    c2 = c1; c2.print(); // Copy Assignment Operator
    c1 = c2 = c3; c1.print(); c2.print(); c3.print(); // Copy Assignment Chain
}

ctor: |4.2+j5.3| = 6.7624 // c1 - ctor
ctor: |7.9+j8.5| = 11.6043 // c2 - ctor
cctor: |7.9+j8.5| = 11.6043 // c3 - ctor
|4.2+j5.3| = 6.7624 // c1
|7.9+j8.5| = 11.6043 // c2
|7.9+j8.5| = 11.6043 // c3
copy: |4.2+j5.3| = 6.7624 // c2 <- c1
|4.2+j5.3| = 6.7624 // c2

copy: |7.9+j8.5| = 11.6043 // c2 <- c3
copy: |7.9+j8.5| = 11.6043 // c1 <- c2
|7.9+j8.5| = 11.6043 // c1
|7.9+j8.5| = 11.6043 // c2
|7.9+j8.5| = 11.6043 // c3
dtor: |7.9+j8.5| = 11.6043 // c3 - dtor
dtor: |7.9+j8.5| = 11.6043 // c2 - dtor
dtor: |7.9+j8.5| = 11.6043 // c1 - dtor
```

• Copy assignment operator should *return the object to make chain assignments possible*



Program 14.16: String: Copy Assignment

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;
class String { public: char *str_; size_t len_;
    String(char *s) : str_(strdup(s)), len_(strlen(str_)) { }           // Ctor
    String(const String& s) : str_(strdup(s.str_)), len_(s.len_) { }    // CCtor
    ~String() { free(str_); }                                           // Dtor
    String& operator=(const String& s) {                               // Copy Assignment Operator
        free(str_);                                                    // Release existing memory
        str_ = strdup(s.str_);                                          // Perform deep copy
        len_ = s.len_;                                                  // Copy data member of built-in type
        return *this;                                                  // Return object for chain assignment
    }
    void print() { cout << "(" << str_ << ": " << len_ << ")" << endl; }
};
int main() { String s1 = "Football", s2 = "Cricket"; s1.print(); s2.print(); s2 = s1; s2.print(); }
---
```

(Football: 8)
(Cricket: 7)
(Football: 8)

- In copy assignment operator, `str_ = s.str_` should not be done for two reasons:
 - 1) Resource held by `str_` will *leak*
 - 2) *Shallow copy* will result with its related issues
- What happens if a self-copy `s1 = s1` is done?



Program 14.17: String: Self Copy

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;
class String { public: char *str_; size_t len_;
    String(char *s) : str_(strdup(s)), len_(strlen(str_)) { }           // Ctor
    String(const String& s) : str_(strdup(s.str_)), len_(s.len_) { }    // CCtor
    ~String() { free(str_); }                                           // Dtor
    String& operator=(const String& s) {                               // Copy Assignment Operator
        free(str_);                                                    // Release existing memory
        str_ = strdup(s.str_);                                          // Perform deep copy
        len_ = s.len_;                                                 // Copy data member of built-in type
        return *this;                                                  // Return object for chain assignment
    }
    void print() { cout << "(" << str_ << ": " << len_ << ")" << endl; }
};
int main() { String s1 = "Football", s2 = "Cricket"; s1.print(); s2.print(); s1 = s2; s1.print(); }
---
```

(Football: 8)
 (Cricket: 7)
 (?????????: 8) // Garbage is printed. May crash too

- Hence, `free(str_)` first releases the memory, and then `strdup(s.str_)` tries to copy from released memory
- This may crash or produce garbage values
- Self-copy must be detected and guarded

• For self-copy



Program 14.18: String: Self Copy: Safe

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;
class String { public: char *str_; size_t len_;
    String(char *s) : str_(strdup(s)), len_(strlen(str_)) { }           // Ctor
    String(const String& s) : str_(strdup(s.str_)), len_(s.len_) { }    // CCtor
    ~String() { free(str_); }                                           // Dtor
    String& operator=(const String& s) {                               // Copy Assignment Operator
        if (this != &s) { // Check if the source and destination are same
            free(str_);
            str_ = strdup(s.str_);
            len_ = s.len_;
        }
        return *this;
    }
    void print() { cout << "(" << str_ << ": " << len_ << ")" << endl; }
};
int main() { String s1 = "Football", s2 = "Cricket"; s1.print(); s2.print(); s1 = s2; s1.print(); }
---
```

(Football: 8)
(Cricket: 7)
(Football: 8)

• In case of self-copy, do nothing

• Check for self



Signature and Body of Copy Assignment Operator

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- For class `MyClass`, typical copy assignment operator will be:

```
MyClass& operator=(const MyClass& s) {  
    if (this != &s) { // Check if the source and destination are same  
        // Release resources held by *this  
        // Copy members of s to members of *this  
    }  
    return *this;    // Return object for chain assignment  
}
```

- Signature of a *Copy Assignment Operator* can be one of:

```
MyClass& operator=(const MyClass& rhs); // Common. No change in Source  
MyClass& operator=(MyClass& rhs);    // Occasional. Change in Source
```

- The following *Copy Assignment Operators* are occasionally used:

```
MyClass& operator=(MyClass rhs);  
const MyClass& operator=(const MyClass& rhs);  
const MyClass& operator=(MyClass& rhs);  
const MyClass& operator=(MyClass rhs);  
MyClass operator=(const MyClass& rhs);  
MyClass operator=(MyClass& rhs);  
MyClass operator=(MyClass rhs);
```



Free Assignment Operator

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- If no copy assignment operator is provided / overloaded by the user, the compiler supplies a *free* one
- *Free* copy assignment operator cannot copy the object with proper values. It performs *Shallow Copy*
- In every class, provide copy assignment operator to adopt to deep copy which is always safe



Comparison of Copy Constructor and Copy Assignment Operator

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Comparison of Copy Constructor and Copy Assignment Operator



Comparison of Copy Constructor and Copy Assignment Operator

Module M14

Partha Pratim Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Copy Constructor

- An overloaded constructor
- Initializes a new object with an existing object
- Used when a new object is created with some existing object
- Needed to support call-by-value and return-by-value
- Newly created object use new memory location
- If not defined in the class, the compiler provides one with bitwise copy

Copy Assignment Operator

- An operator overloading
- Assigns the value of one existing object to another existing object
- Used when we want to assign existing object to another object
- Memory location of destination object is reused with pointer variables being released and reallocated
- Care is needed for self-copy
- If not overloaded, the compiler provides one with bitwise copy



Class as a Data-type

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

Class as a Data-type



Class as a Data-type

- We add the copy construction and assignment to a class being a composite data type in C++

```
// declare i to be of int type
int i;
```

```
// initialise i
int i = 5;
int j = i;
int k(j);
```

```
// print i
cout << i;
```

```
// add two ints
int i = 5, j = 6;
i+j;
```

```
// copy value of i to j
int i = 5, j;
j = i;
```

```
// declare c to be of Complex type
Complex c;
```

```
// initialise the real and imaginary components of c
Complex c = (4, 5); // Ctor
Complex c1 = c;      // CCtor
Complex c2(c1);      // CCtor
```

```
// print the real and imaginary components of c
cout << c.re << c.im;
OR c.print(); // Method Complex::print() defined for printing
OR cout << c; // operator<<() overloaded for printing
```

```
// add two Complex objects
Complex c1 = (4, 5), c2 = (4, 6);
c1.add(c2); // Method Complex::add() defined to add
OR c1+c2; // operator+() overloaded to add
```

```
// copy value of one Complex object to another
Complex c1 = (4, 5), c2 = (4, 6);
c2 = c1; // c2.re <- c1.re and c2.im <- c1.im by copy assignment
```



Module Summary

Module M14

Partha Pratim
Das

Obj. & Outlines

Obj. Lifetime

String

Date

Rect

Name & Address

CreditCard

Copy Constructor

Call by Value

Signature

Data Members

Free Copy & Pitfall

Assignment Op.

Copy Objects

Self-Copy

Signature

Free Assignment

Comparison

Class as Type

Module Summary

- **Copy Constructors**

- A new object is created
- The new object is initialized with the value of data members of another object

- **Copy Assignment Operator**

- An object is already existing (and initialized)
- The members of the existing object are replaced by values of data members of another object
- Care is needed for self-copy

- **Deep and Shallow Copy for Pointer Members**

- Deep copy allocates new space for the contents and copies the pointed data
- Shallow copy merely copies the pointer value – hence, the new copy and the original pointer continue to point to the same data