



Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor

Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy

Pure Virtual
Function with Body

Module Summary

Programming in Modern C++

Module M28: Polymorphism: Part 3: Abstract Base Class

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional



Module Recap

Module M28

Partha Pratim
Das

Objectives & Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary

- Discussed Static and Dynamic Binding
- Polymorphic type introduced

NPTEL



Module Objectives

Module M28

Partha Pratim
Das

Objectives & Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary

- Understand why destructor must be **virtual** in a class hierarchy
- Learn to work with class hierarchy

NPTEL



Module Outline

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary

- 1 Virtual Destructor
 - Slicing
- 2 Pure Virtual Function
- 3 Abstract Base Class
 - Shape Hierarchy
 - Pure Virtual Function with Body
- 4 Module Summary



Virtual Destructor

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor

Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy

Pure Virtual
Function with Body

Module Summary

Virtual Destructor



Virtual Destructor

Module M28

Partha Pratim Das

Objectives & Outlines

Virtual Destructor

Slicing

Pure Virtual Function

Abstract Base Class

Shape Hierarchy

Pure Virtual Function with Body

Module Summary

```
#include <iostream>
using namespace std;

class B { int data_; public:
    B(int d) :data_(d) { cout << "B()" << endl; }
    ~B() { cout << "~B()" << endl; }
    virtual void Print() { cout << data_; }
};

class D: public B { int *ptr_; public:
    D(int d1, int d2) :B(d1), ptr_(new int(d2)) { cout << "D()" << endl; }
    ~D() { cout << "~D()" << endl; delete ptr_; }
    void Print() { B::Print(); cout << " " << *ptr_; }
};

int main() {
    B *p = new B(2);
    B *q = new D(3, 5);

    p->Print(); cout << endl;
    q->Print(); cout << endl;

    delete p;
    delete q;
}
```

Output:

```
B()
B()
D()
2
3 5
~B()
~B()
```

Destructor of d (type D) not called!



Virtual Destructor

Module M28

Partha Pratim Das

Objectives & Outlines

Virtual Destructor

Slicing

Pure Virtual Function

Abstract Base Class

Shape Hierarchy

Pure Virtual Function with Body

Module Summary

```
#include <iostream>
using namespace std;

class B { int data_; public:
    B(int d) :data_(d) { cout << "B()" << endl; }
    virtual ~B() { cout << "~B()" << endl; } // Destructor made virtual
    virtual void Print() { cout << data_; }
};

class D: public B { int *ptr_; public:
    D(int d1, int d2) :B(d1), ptr_(new int(d2)) { cout << "D()" << endl; }
    ~D() { cout << "~D()" << endl; delete ptr_; }
    void Print() { B::Print(); cout << " " << *ptr_; }
};

int main() {
    B *p = new B(2);
    B *q = new D(3, 5);

    p->Print(); cout << endl;
    q->Print(); cout << endl;

    delete p;
    delete q;
}
```

Output:

```
B()
B()
D()
2
3 5
~B()
~D()
~B()
```

Destructor of d (type D) is called!



Virtual Destructor: Slicing

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor

Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy

Pure Virtual
Function with Body

Module Summary

- **Slicing** is where we assign an object of a derived class to an instance of a base class, thereby losing part of the information - some of it is **sliced** away

```
#include <iostream>
using namespace std;
class Base { protected: int i; public:
    Base(int a)      i = a;
    virtual void display() { cout << "I am Base class object, i = " << i << endl; }
};
class Derived : public Base { int j; public:
    Derived(int a, int b) : Base(a) { j = b; }
    virtual void display() { cout<< "I am Derived class object, i = " << i << ", j = " << j <<endl; }
};
// Global method, Base class object is passed by value
void somefunc (Base obj) { obj.display(); }
int main() { Base b(33); Derived d(45, 54);
    somefunc(b);
    somefunc(d); // Object Slicing, the member j of d is sliced off
}

I am Base class object, i = 33
I am Base class object, i = 45
```

- If the destructor is not **virtual** in a polymorphic hierarchy, it leads to **Slicing**
- **Destructor must be declared virtual in the base class**



Pure Virtual Function

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary

Pure Virtual Function



Hierarchy of Shapes

Module M28

Partha Pratim
Das

Objectives &
Outlines


Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary



- We want to have a polymorphic `draw()` function for the hierarchy
- `draw()` will be overridden in every class based on the drawing algorithms
- What is the `draw()` function for the root `Shapes` class?



Pure Virtual Function

Module M28

Partha Pratim Das

Objectives & Outlines

Virtual Destructor
Slicing

Pure Virtual Function

Abstract Base Class

Shape Hierarchy
Pure Virtual Function with Body

Module Summary

- For the polymorphic hierarchy of **Shapes**, we need **draw()** to be a **virtual** function
- **draw()** must be a member of **Shapes** class for polymorphic dispatch to work
- But we cannot define the body of **draw()** function for the root **Shapes** class as we do not have an algorithm to draw an arbitrary shape. In fact, we cannot even have a representation for shapes in general!
- **Pure Virtual Function** solves the problem
- A **Pure Virtual Function** has a signature but no body!
- Example:

```
class Root { public:  
    void f();           // Non-Virtual Function  
    virtual void g();   // Virtual Function  
    virtual void h() = 0; // Pure Virtual Function  
};
```



Abstract Base Class

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary

Abstract Base Class



Abstract Base Class

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary

- A class containing at least one **Pure Virtual Function** is called an **Abstract Base Class**
- **Pure Virtual Functions** may be inherited or defined in the class
- No instance can be created for an **Abstract Base Class**
- Naturally it may not have a constructor or a **virtual** destructor
- An **Abstract Base Class**, however, may have other **virtual** (non-pure) and non-**virtual** member functions as well as data members
- Data members in an **Abstract Base Class** should be **protected**. Of course, **private** and **public** data are also allowed
- Member functions in an **Abstract Base Class** should be **public**. Of course, **private** and **protected** methods are also allowed
- A **Concrete Class** must override and implement all **Pure Virtual Functions** so that it can be instantiated



Shape Hierarchy

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy
Pure Virtual
Function with Body

Module Summary

```
#include <iostream> // Abstract Base Class shown in red
using namespace std; // Concrete Class shown in green

class Shapes { public:                                // Abstract Base Class
    virtual void draw() = 0; // Pure Virtual Function
};
class Polygon: public Shapes { public: void draw() { cout<< "Polygon: Draw by Triangulation" <<endl; } };
class ClosedConics: public Shapes { public:           // Abstract Base Class
    // draw() inherited - Pure Virtual
};
class Triangle: public Polygon { public: void draw() { cout << "Triangle: Draw by Lines" << endl; } };
class Quadrilateral: public Polygon { public:
    void draw() { cout << "Quadrilateral: Draw by Lines" << endl; }
};
class Circle: public ClosedConics { public:
    void draw() { cout << "Circle: Draw by Bresenham Algorithm" << endl; }
};
class Ellipse: public ClosedConics { public: void draw() { cout << "Ellipse: Draw by ..." << endl; } };
int main() {
    Shapes *arr[] = { new Triangle, new Quadrilateral, new Circle, new Ellipse };

    for (int i = 0; i < sizeof(arr) / sizeof(Shapes *); ++i)
        arr[i]->draw();
    // ...
}
```

Programming in Modern C++



Shape Hierarchy

Module M28

Partha Pratim
Das

Objectives &
Outlines

Virtual
Destructor
Slicing

Pure Virtual
Function

Abstract Base
Class

Shape Hierarchy

Pure Virtual
Function with Body

Module Summary

```
int main() {  
    Shapes *arr[] = { new Triangle, new Quadrilateral, new Circle, new Ellipse };  
  
    for (int i = 0; i < sizeof(arr) / sizeof(Shapes *); ++i)  
        arr[i]->draw();  
    // ...  
    return 0;  
}
```

Triangle: Draw by Lines

Quadrilateral: Draw by Lines

Circle: Draw by Bresenham Algorithm

Ellipse: Draw by ...

- Instances for class **Shapes** and class **ClosedConics** cannot be created



Shape Hierarchy: A Pure Virtual Function may have a body!

Module M28

Partha Pratim Das

Objectives & Outlines

Virtual Destructor
Slicing

Pure Virtual Function

Abstract Base Class

Shape Hierarchy

Pure Virtual Function with Body

Module Summary

```
#include <iostream>
using namespace std;
class Shapes { public:                                // Abstract Base Class
    virtual void draw() = 0 // Pure Virtual Function
    { cout << "Shapes: Init Brush" << endl; }
};
class Polygon: public Shapes { public:                // Concrete Class
    void draw() { Shapes::draw(); cout << "Polygon: Draw by Triangulation" << endl; }
};
class ClosedConics: public Shapes { public:           // Abstract Base Class
    // draw() inherited - Pure Virtual
};
class Triangle: public Polygon { public:              // Concrete Class
    void draw() { Shapes::draw(); cout << "Triangle: Draw by Lines" << endl; }
};
class Quadrilateral: public Polygon { public:         // Concrete Class
    void draw() { Shapes::draw(); cout << "Quadrilateral: Draw by Lines" << endl; }
};
class Circle: public ClosedConics { public:           // Concrete Class
    void draw() { Shapes::draw(); cout << "Circle: Draw by Bresenham Algorithm" << endl; }
};
class Ellipse: public ClosedConics { public:          // Concrete Class
    void draw() { Shapes::draw(); cout << "Ellipse: Draw by ..." << endl; }
};
```




Shape Hierarchy

Module M28

Partha Pratim Das

Objectives & Outlines

Virtual Destructor
Slicing

Pure Virtual Function

Abstract Base Class

Shape Hierarchy

Pure Virtual Function with Body

Module Summary

```
int main() {  
    Shapes *arr[] = { new Triangle, new Quadrilateral, new Circle, new Ellipse };  
  
    for (int i = 0; i < sizeof(arr) / sizeof(Shapes *); ++i)  
        arr[i]->draw();  
}
```

Shapes: Init Brush

Triangle: Draw by Lines

Shapes: Init Brush

Quadrilateral: Draw by Lines

Shapes: Init Brush

Circle: Draw by Bresenham Algorithm

Shapes: Init Brush

Ellipse: Draw by ...

- Instances for class **Shapes** and class **ClosedConics** cannot be created
- Some compilers do not allow to inline the function body for a pure **virtual** function

```
class Shapes { public: virtual void draw() = 0 { cout << "Shapes: Init Brush" << endl; } };
```

Outline the function body:

```
class Shapes { public: virtual void draw() = 0; };  
void Shapes::draw() { cout << "Shapes: Init Brush" << endl; }
```



Module Summary

Module M28

Partha Pratim Das

Objectives & Outlines

Virtual Destructor
Slicing

Pure Virtual Function

Abstract Base Class

Shape Hierarchy
Pure Virtual Function with Body

Module Summary

- Discussed why destructors must be **virtual** in a polymorphic hierarchy
- Introduced Pure Virtual Functions
- Introduced Abstract Base Class

NPTEL