



Module M15

Partha Pratim
Das

Objectives &
Outlines

`const` Objects
Example

`const` Member
Functions
Example

`const` Data
Members
Example

Credit Card
String
Date
Name
Address
CreditClass

`mutable`
Members

Example
`mutable` Guidelines

Module Summary

Programming in Modern C++

Module M15: Const-ness

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional



Module Recap

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members
Example

Credit Card
String
Date
Name
Address
CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

- **Copy Constructors**

- A new object is created
- The new object is initialized with the value of data members of another object

- **Copy Assignment Operator**

- An object is already existing (and initialized)
- The members of the existing object are replaced by values of data members of another object
- Care is needed for self-copy

- **Deep and Shallow Copy for Pointer Members**

- Deep copy allocates new space for the contents and copies the pointed data
- Shallow copy merely copies the pointer value – hence, the new copy and the original pointer continue to point to the same data



Module Objectives

Module M15

Partha Pratim
Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

- Understand const-ness of objects in C++
- Understand the use of const-ness in class design

NPTEL



Module Outline

Module M15

Partha Pratim
Das

Objectives & Outlines

const Objects

Example

const Member
Functions

Example

const Data
Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

- 1 Constant Objects
 - Simple Example
- 2 Constant Member Functions
 - Simple Example
- 3 Constant Data Members
 - Simple Example
 - Credit Card Example: Putting it all together
 - String
 - Date
 - Name
 - Address
 - CreditClass
- 4 mutable Members
 - Simple Example
 - mutable Guidelines
- 5 Module Summary



Constant Objects

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects

Example

const Member
Functions

Example

const Data
Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

Constant Objects



Constant Objects

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

- Like objects of built-in type, objects of user-defined types can also be made constant
- If an object is constant, none of its data members can be changed
- The type of the `this` pointer of a constant object of class, say, `MyClass` is:

```
// const Pointer to const Object  
const MyClass * const this;
```

instead of

```
// const Pointer to non-const Object  
MyClass * const this;
```

as for a non-constant object of the same class

- A constant objects cannot invoke normal methods of the class lest these methods change the object



Program 15.01: Non-Constant Objects

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
class MyClass { int myPriMember_;
public: int myPubMember_;
    MyClass(int mPri, int mPub) : myPriMember_(mPri), myPubMember_(mPub) { }
    int getMember() { return myPriMember_; }
    void setMember(int i) { myPriMember_ = i; }
    void print() { cout << myPriMember_ << ", " << myPubMember_ << endl; }
};
int main() { MyClass myObj(0, 1); // Non-constant object

    cout << myObj.getMember() << endl;
    myObj.setMember(2);
    myObj.myPubMember_ = 3;
    myObj.print();
}
---
```

0
2, 3

- It is okay to invoke methods for non-constant object **myObj**
- It is okay to make changes in non-constant object **myObj** by method (**setMember()**)
- It is okay to make changes in non-constant object **myObj** directly (**myPubMember_**)



Program 15.02: Constant Objects

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
```

```
class MyClass { int myPriMember_; public: int myPubMember_;
    MyClass(int mPri, int mPub) : myPriMember_(mPri), myPubMember_(mPub) { }
    int getMember() { return myPriMember_; }
    void setMember(int i) { myPriMember_ = i; }
    void print() { cout << myPriMember_ << ", " << myPubMember_ << endl; }
};

int main() { const MyClass myConstObj(5, 6); // Constant object

    cout << myConstObj.getMember() << endl; // Error 1
    myConstObj.setMember(7);                // Error 2
    myConstObj.myPubMember_ = 8;             // Error 3
    myConstObj.print();                     // Error 4
}
```

- It is not allowed to invoke methods or make changes in constant object **myConstObj**
- Error (1, 2 & 4) on method invocation typically is:
cannot convert 'this' pointer from 'const MyClass' to 'MyClass &'
- Error (3) on member update typically is:
'myConstObj' : you cannot assign to a variable that is const
- With **const**, **this** pointer is **const MyClass * const** while the methods expects **MyClass * const**
- Consequently, we cannot print the data member of the class (even without changing it)
- Fortunately, constant objects can invoke (select) methods if they are **constant member functions**



Constant Member Functions

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

**const Member
Functions**
Example

const Data
Members
Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

Constant Member Functions



Constant Member Function

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

- To declare a constant member function, we use the keyword `const` between the function header and the body. Like:

```
void print() const { cout << myMember_ << endl; }
```

- A constant member function expects a `this` pointer as:

```
const MyClass * const this;
```

and hence can be invoked by constant objects

- In a constant member function no data member can be changed. Hence,

```
void setMember(int i) const  
{ myMember_ = i; } // data member cannot be changed
```

gives an error

- Interesting, *non-constant objects* can invoke *constant member functions* (by casting – we discuss later) and, of course, *non-constant member functions*
- *Constant objects*, however, can **only** invoke *constant member functions*
- **All member functions that do not need to change an object must be declared as constant member functions**



Program 15.03: Constant Member Functions

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
class MyClass { int myPriMember_; public: int myPubMember_;
    MyClass(int mPri, int mPub) : myPriMember_(mPri), myPubMember_(mPub) { }
    int getMember() const { return myPriMember_; } // const Member Func.
    void setMember(int i) { myPriMember_ = i; } // non-const Member Func.
    void print() const { cout << myPriMember_ << ", " << myPubMember_ << endl; } // const Member Func.
};
int main() { MyClass myObj(0, 1); // non-const object
    const MyClass myConstObj(5, 6); // const object
    // non-const object can invoke all member functions and update data members
    cout << myObj.getMember() << endl;
    myObj.setMember(2);
    myObj.myPubMember_ = 3;
    myObj.print();
    // const object cannot allow any change
    cout << myConstObj.getMember() << endl;
    // myConstObj.setMember(7); // Cannot invoke non-const member functions
    // myConstObj.myPubMember_ = 8; // Cannot update data member
    myConstObj.print();
}
```

Output

```
0
2, 3
5
5, 6
```

- Now **myConstObj** can invoke **getMember()** and **print()**, but cannot invoke **setMember()**
- Naturally **myConstObj** cannot update **myPubMember_**
- **myObj** can invoke all of **getMember()**, **print()**, and **setMember()**



Constant Data Members

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members
Example

Credit Card
String
Date
Name
Address
CreditClass

mutable
Members

Example
mutable Guidelines

Module Summary

Constant Data Members



Constant Data members

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members
Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

- Often we need part of an object, that is, one or more data members to be constant (non-changeable after construction) while the rest of the data members should be changeable. For example:
 - For an **Employee**: **employee ID** and **DoB** should be *non-changeable* while **designation, address, salary** etc. should be *changeable*
 - For a **Student**: **roll number** and **DoB** should be *non-changeable* while **year of study, address, gpa** etc. should be *changeable*
 - For a **Credit Card**¹: **card number** and **name of holder** should be *non-changeable* while **date of issue, date of expiry, address, cvv number** etc. should be *changeable*
- We do this by making the *non-changeable* data members as constant by putting the **const** keyword before the declaration of the member in the class
- **A constant data member cannot be changed even in a non-constant object**
- **A constant data member must be initialized on the initialization list**

¹May not hold for a card that changes number on re-issue



Program 15.04: Constant Data Member

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members
Example

Credit Card
String
Date
Name
Address
CreditClass

mutable
Members

Example
mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
class MyClass { const int cPriMem_; /* const data member */ int priMem_; public:
    const int cPubMem_; /* const data member */ int pubMem_;
    MyClass(int cPri, int ncPri, int cPub, int ncPub) :
        cPriMem_(cPri), priMem_(ncPri), cPubMem_(cPub), pubMem_(ncPub) { }
    int getcPri() { return cPriMem_; }
    void setcPri(int i) { cPriMem_ = i; } // Error 1: Assignment to const data member
    int getPri() { return priMem_; }
    void setPri(int i) { priMem_ = i; }
};
int main() { MyClass myObj(1, 2, 3, 4);

    cout << myObj.getcPri() << endl; myObj.setcPri(6);
    cout << myObj.getPri() << endl; myObj.setPri(6);

    cout << myObj.cPubMem_ << endl;
    myObj.cPubMem_ = 3; // Error 2: Assignment to const data member

    cout << myObj.pubMem_ << endl; myObj.pubMem_ = 3;
}
```

- It is not allowed to make changes to constant data members in **myObj**
- Error 1: **l-value specifies const object**
- Error 2: '**myObj**' : you cannot assign to a variable that is **const**



Credit Card Example

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members
Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

We now illustrate constant data members with a complete example of `CreditCard` class with the following supporting classes:

- `String` class
- `Date` class
- `Name` class
- `Address` class



Program 15.05: String Class: String.h

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members

Example
Credit Card

String
Date
Name

Address
CreditClass

mutable
Members

Example
mutable Guidelines

Module Summary

```
#include <iostream>
#include <cstring>
#include <cstdlib>
using namespace std;

class String { char *str_; size_t len_;
public:
    String(const char *s) : str_(strdup(s)), len_(strlen(str_))           // Ctor
    { cout << "String ctor: "; print(); cout << endl; }
    String(const String& s) : str_(strdup(s.str_)), len_(strlen(str_))    // CCtor
    { cout << "String cctor: "; print(); cout << endl; }
    String& operator=(const String& s) {
        if (this != &s) {
            free(str_);
            str_ = strdup(s.str_);
            len_ = s.len_;
        }
        return *this;
    }
    ~String() { cout << "String dtor: "; print(); cout << endl; free(str_); } // Dtor
    void print() const { cout << str_; }
};
```

- Copy Constructor and Copy Assignment Operator added
- `print()` made a constant member function



Program 15.05: Date Class: Date.h

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;

char monthNames[][4]={ "Jan", "Feb", "Mar", "Apr", "May", "Jun", "Jul", "Aug", "Sep", "Oct", "Nov", "Dec" };
char dayNames[][10]={ "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday", "Sunday" };
class Date {
    enum Month { Jan = 1, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, Nov, Dec };
    enum Day { Mon, Tue, Wed, Thr, Fri, Sat, Sun };
    typedef unsigned int UINT;
    UINT date_; Month month_; UINT year_;
public:
    Date(UINT d, UINT m, UINT y) : date_(d), month_((Month)m), year_(y)
    { cout << "Date ctor: "; print(); cout << endl; }
    Date(const Date& d) : date_(d.date_), month_(d.month_), year_(d.year_)
    { cout << "Date cctor: "; print(); cout << endl; }
    Date& operator=(const Date& d) { date_ = d.date_; month_ = d.month_; year_ = d.year_; return *this; }
    ~Date() { cout << "Date dtor: "; print(); cout << endl; }
    void print() const { cout << date_ << "/" << monthNames[month_ - 1] << "/" << year_; }
    bool validDate() const { /* Check validity */ return true; } // Not Implemented
    Day day() const { /* Compute day from date using time.h */ return Mon; } // Not Implemented
};
```

- Copy Constructor and Copy Assignment Operator added
- `print()`, `validDate()`, and `day()` made constant member functions



Program 15.05: Name Class: Name.h

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects

Example

const Member
Functions

Example

const Data
Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;

#include "String.h"

class Name { String firstName_, lastName_;
public:
    Name(const char* fn, const char* ln) : firstName_(fn), lastName_(ln)    // Uses Ctor of String class
    { cout << "Name ctor: "; print(); cout << endl; }
    Name(const Name& n) : firstName_(n.firstName_), lastName_(n.firstName_) // Uses Cctor of String class
    { cout << "Name cctor: "; print(); cout << endl; }
    Name& operator=(const Name& n) {
        firstName_ = n.firstName_; // Uses operator=() of String class
        lastName_ = n.lastName_;   // Uses operator=() of String class
        return *this;
    }
    ~Name() { cout << "Name dtor: "; print(); cout << endl; } // Uses Dtor of String class
    void print() const // Uses print() of String class
    { firstName_.print(); cout << " "; lastName_.print(); }
};
```

- Copy Constructor and Copy Assignment Operator added
- `print()` made a constant member function



Program 15.05: Address Class: Address.h

Module M15

Partha Pratim
Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
#include "String.h"
```

```
class Address { unsigned int houseNo_; String street_, city_, pin_;
public:
```

```
    Address(unsigned int hn, const char* sn, const char* cn, const char* pin): // Uses Ctor of String class
```

```
        houseNo_(hn), street_(sn), city_(cn), pin_(pin)
```

```
    { cout << "Address ctor: "; print(); cout << endl; }
```

```
    Address(const Address& a): // Uses CCTor of String class
```

```
        houseNo_(a.houseNo_), street_(a.street_), city_(a.city_), pin_(a.pin_)
```

```
    { cout << "Address ctor: "; print(); cout << endl; }
```

```
    Address& operator=(const Address& a) { // Uses operator=() of String class
```

```
        houseNo_ = a.houseNo_; street_ = a.street_; city_ = a.city_; pin_ = a.pin_; return *this; }
```

```
    ~Address() { cout << "Address dtor: "; print(); cout << endl; } // Uses Dtor of String class
```

```
    void print() const { // Uses print() of String class
```

```
        cout << houseNo_ << " "; street_.print(); cout << " ";
```

```
        city_.print(); cout << " "; pin_.print();
```

```
    }
```

```
};
```

- Copy Constructor and Copy Assignment Operator added
- `print()` made a constant member function



Program 15.05: Credit Card Class: CreditCard.h

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects Example

const Member Functions Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
#include "Date.h"
#include "Name.h"
#include "Address.h"
class CreditCard { typedef unsigned int UINT; char *cardNumber_;
    Name holder_; Address addr_; Date issueDate_, expiryDate_; UINT cvv_;
public: CreditCard(const char* cNumber, const char* fn, const char* ln, unsigned int hn, const char* sn,
    const char* cn, const char* pin, UINT issueMonth, UINT issueYear, UINT expiryMonth, UINT expiryYear,
    UINT cvv): holder_(fn, ln), addr_(hn, sn, cn, pin), issueDate_(1, issueMonth, issueYear),
    expiryDate_(1, expiryMonth, expiryYear), cvv_(cvv) // Uses Ctor's of Date, Name, Address
    { cardNumber_ = new char[strlen(cNumber) + 1]; strcpy(cardNumber_, cNumber);
        cout << "CC ctor: "; print(); cout << endl; }
    // Uses Dtor's of Date, Name, Address
    ~CreditCard() { cout << "CC dtor: "; print(); cout << endl; delete[] cardNumber_; }
    void setHolder(const Name& h) { holder_ = h; } // Change holder name
    void setAddress(const Address& a) { addr_ = a; } // Change address
    void setIssueDate(const Date& d) { issueDate_ = d; } // Change issue date
    void setExpiryDate(const Date& d) { expiryDate_ = d; } // Change expiry date
    void setCVV(UINT v) { cvv_ = v; } // Change cvv number
    void print() const { cout<<cardNumber_<<" "; holder_.print(); cout<<" "; addr_.print();
        cout<<" "; issueDate_.print(); cout<<" "; expiryDate_.print(); cout<<" "; cout<<cvv_; }
};
• Set methods added
• print() made a constant member function
```



Program 15.05: Credit Card Class Application

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
#include "CreditCard.h"

int main() { CreditCard cc("5321711934640027", "Sherlock", "Holmes",
                          221, "Baker Street", "London", "NW1 6XE", 7, 2014, 6, 2016, 811);
    cout << endl; cc.print(); cout << endl << endl;;

    cc.setHolder(Name("David", "Cameron"));
    cc.setAddress(Address(10, "Downing Street", "London", "SW1A 2AA"));
    cc.setIssueDate(Date(1, 7, 2017));
    cc.setExpiryDate(Date(1, 6, 2019));
    cc.setCVV(127);
    cout << endl; cc.print(); cout << endl << endl;;
}

// Construction of Data Members & Object
5321711934640027 Sherlock Holmes 221 Baker Street London NW1 6XE 1/Jul/2014 1/Jun/2016 811

// Construction & Destruction of temporary objects
5321711934640027 David Cameron 10 Downing Street London SW1A 2AA 1/Jul/2017 1/Jun/2019 127

// Destruction of Data Members & Object
```

- We could change address, issue date, expiry date, and cvv. This is fine
- We could change the name of the holder! This should not be allowed



Program 15.06: Credit Card Class: Constant data members

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions

Example

const Data
Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

```
// Include <iostream>, "String.h", "Date.h", "Name.h", "Address.h"
using namespace std;

class CreditCard { typedef unsigned int UINT;
    char *cardNumber_;
    const Name holder_;           // Holder name cannot be changed after construction
    Address addr_; Date issueDate_, expiryDate_; UINT cvv_;
public: CreditCard(...) : ... { ... } ~CreditCard() { ... }

    void setHolder(const Name& h)    { holder_ = h; }           // Change holder name
    // error C2678: binary '=' : no operator found which takes a left-hand operand
    // of type 'const Name' (or there is no acceptable conversion)

    void setAddress(const Address& a) { addr_ = a; }           // Change address
    void setIssueDate(const Date& d)  { issueDate_ = d; }      // Change issue date
    void setExpiryDate(const Date& d) { expiryDate_ = d; }     // Change expiry date
    void setCVV(UINT v)               { cvv_ = v; }            // Change cvv number

    void print() { ... }
};
```

- We prefix `Name holder_` with `const`. Now the holder name cannot be changed after construction
- In `setHolder()`, we get a compilation error for `holder_ = h`; in an attempt to change `holder_`
- With `const` prefix `Name holder_` becomes constant – unchangeable



Program 15.06: Credit Card Class: Clean

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

```
// Include <iostream>, "String.h", "Date.h", "Name.h", "Address.h"
using namespace std;

class CreditCard { typedef unsigned int UINT;
    char *cardNumber_;
    const Name holder_;           // Holder name cannot be changed after construction
    Address addr_;
    Date issueDate_, expiryDate_; UINT cvv_;
public:
    CreditCard(...) : ... { ... }
    ~CreditCard() { ... }

    void setAddress(const Address& a)  addr_ = a;           // Change address
    void setIssueDate(const Date& d)    issueDate_ = d;      // Change issue date
    void setExpiryDate(const Date& d)   expiryDate_ = d;     // Change expiry date
    void setCVV(UINT v)                 cvv_ = v;           // Change cvv number

    void print() { ... }
};
```

- Method `setHolder()` removed



Program 15.06: Credit Card Class Application: Revised

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects

Example

const Member
Functions

Example

const Data
Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
#include "CreditCard.h"
int main() {
    CreditCard cc("5321711934640027", "Sherlock", "Holmes",
                  221, "Baker Street", "London", "NW1 6XE", 7, 2014, 6, 2016, 811);
    cout << endl; cc.print(); cout << endl << endl;;

    // cc.setHolder(Name("David", "Cameron"));
    cc.setAddress(Address(10, "Downing Street", "London", "SW1A 2AA"));
    cc.setIssueDate(Date(1, 7, 2017));
    cc.setExpiryDate(Date(1, 6, 2019));
    cc.setCVV(127);
    cout << endl; cc.print(); cout << endl << endl;;
}

// Construction of Data Members & Object
5321711934640027 Sherlock Holmes 221 Baker Street London NW1 6XE 1/Jul/2014 1/Jun/2016 811

// Construction & Destruction of temporary objects
5321711934640027 Sherlock Holmes 10 Downing Street London SW1A 2AA 1/Jul/2017 1/Jun/2019 127

// Destruction of Data Members & Object

• Now holder_ cannot be changed. So we are safe
• However, it is still possible to replace or edit the card number. This, too, should be disallowed
```




Program 15.07: Credit Card Class: `cardNumber_` Issue

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
// Include <iostream>, "String.h", "Date.h", "Name.h", "Address.h"
using namespace std;

class CreditCard { typedef unsigned int UINT;
    char *cardNumber_;           // Card number is editable as well as replaceable
    const Name holder_;          // Holder name cannot be changed after construction
    Address addr_;
    Date issueDate_, expiryDate_; UINT cvv_;
public:
    CreditCard(...) : ... { ... }
    ~CreditCard() { ... }

    void setAddress(const Address& a) { addr_ = a; }           // Change address
    void setIssueDate(const Date& d) { issueDate_ = d; }       // Change issue date
    void setExpiryDate(const Date& d) { expiryDate_ = d; }     // Change expiry date
    void setCVV(UINT v) { cvv_ = v; }                          // Change cvv number

    void print() { ... }
};
```

- It is still possible to replace or edit the card number
- To make the `cardNumber_` *non-replaceable*, we need to make this *constant pointer*
- Further, to make it *non-editable* we need to make `cardNumber_` point to a *constant string*
- Hence, we change `char *cardNumber_` to `const char * const cardNumber_`



Program 15.07: Credit Card Class: cardNumber_ Issue

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects

Example

const Member
Functions

Example

const Data
Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable
Members

Example

mutable Guidelines

Module Summary

```
// Include <iostream>, "String.h", "Date.h", "Name.h", "Address.h"
using namespace std;
class CreditCard {
    typedef unsigned int UINT;
    const char * const cardNumber_; // Card number cannot be changed after construction
    const Name holder_;             // Holder name cannot be changed after construction
    Address addr_; Date issueDate_, expiryDate_; UINT cvv_;
public: CreditCard(const char* cNumber, const char* fn, const char* ln,
    unsigned int hn, const char* sn, const char* cn, const char* pin,
    UINT issueMonth, UINT issueYear, UINT expiryMonth, UINT expiryYear, UINT cvv) :
    holder_(fn, ln), addr_(hn, sn, cn, pin), issueDate_(1, issueMonth, issueYear),
    expiryDate_(1, expiryMonth, expiryYear), cvv_(cvv) {
    cardNumber_ = new char[strlen(cNumber) + 1]; // ERROR: No assignment to const pointer
    strcpy(cardNumber_, cNumber);                // ERROR: No copy to const C-string
    cout << "CC ctor: "; print(); cout << endl;
}
~CreditCard() { cout << "CC dtor: "; print(); cout << endl; delete[] cardNumber_; }

    // Set methods and print method skipped ...
};
```

- `cardNumber_` is now a *constant pointer to a constant string*
- With this the allocation for the C-string fails in the body as constant pointer cannot be assigned
- Further, copy of C-string (`strcpy()`) fails as copy of constant C-string is not allowed
- We need to move these codes to the initialization list



Program 15.07: Credit Card Class: cardNumber_ Issue: Resolved

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

```
// Include <iostream>, "String.h", "Date.h", "Name.h", "Address.h"
using namespace std;
class CreditCard { typedef unsigned int UINT;
    const char * const cardNumber_; // Card number cannot be changed after construction
    const Name holder_;             // Holder name cannot be changed after construction
    Address addr_; Date issueDate_, expiryDate_; UINT cvv_;
public: CreditCard(const char* cNumber, const char* fn, const char* ln,
    unsigned int hn, const char* sn, const char* cn, const char* pin,
    UINT issueMonth, UINT issueYear, UINT expiryMonth, UINT expiryYear, UINT cvv) :
    cardNumber_(strcpy(new char[strlen(cNumber)+1], cNumber)),
    holder_(fn, ln), addr_(hn, sn, cn, pin), issueDate_(1, issueMonth, issueYear),
    expiryDate_(1, expiryMonth, expiryYear), cvv_(cvv)
    { cout << "CC ctor: "; print(); cout << endl; }
    ~CreditCard() { cout << "CC dtor: "; print(); cout << endl; delete[] cardNumber_; }
    void setAddress(const Address& a) { addr_ = a; } // Change address
    void setIssueDate(const Date& d) { issueDate_ = d; } // Change issue date
    void setExpiryDate(const Date& d) { expiryDate_ = d; } // Change expiry date
    void setCVV(UINT v) { cvv_ = v; } // Change cvv number
    void print() const { cout<<cardNumber_<<" "; holder_.print(); cout<<" "; addr_.print();
        cout<<" "; issueDate_.print(); cout<<" "; expiryDate_.print(); cout<<" "; cout<<cvv_; }
};
```

- Note the initialization of cardNumber_ in initialization list
- All constant data members must be initialized in initialization list



mutable Members

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members
Example

Credit Card
String
Date
Name
Address
CreditClass

**mutable
Members**

Example
mutable Guidelines

Module Summary

mutable Members



mutable Data Members

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects
Example

const Member Functions
Example

const Data Members
Example

Credit Card
String
Date
Name
Address
CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

- While a *constant* data member is *not changeable* even in a *non-constant object*, a **mutable** data member is *changeable* in a *constant object*
- **mutable** is provided to model *Logical (Semantic) const-ness* against the default *Bit-wise (Syntactic) const-ness* of C++
- Note that:
 - **mutable** is applicable only to *data members* and *not to variables*
 - *Reference data members* cannot be declared **mutable**
 - *Static data members* cannot be declared **mutable**
 - *const data members* cannot be declared **mutable**
- If a data member is declared **mutable**, then it is legal to assign a value to it from a **const** member function



Program 15.08: mutable Data Members

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members

Example
Credit Card
String
Date
Name
Address
CreditClass

mutable
Members

Example
mutable Guidelines

Module Summary

```
#include <iostream>
using namespace std;
class MyClass {
    int mem_;
    mutable int mutableMem_;
public:
    MyClass(int m, int mm) : mem_(m), mutableMem_(mm) { }
    int getMem() const { return mem_; }
    void setMem(int i) { mem_ = i; }
    int getMutableMem() const { return mutableMem_; }
    void setMutableMem(int i) const { mutableMem_ = i; } // Okay to change mutable
};
int main() { const MyClass myConstObj(1, 2);

    cout << myConstObj.getMem() << endl;
    // myConstObj.setMem(3); // Error to invoke

    cout << myConstObj.getMutableMem() << endl;
    myConstObj.setMutableMem(4);
}
```

- **setMutableMem()** is a constant member function so that constant **myConstObj** can invoke it
- **setMutableMem()** can still set **mutableMem_** because **mutableMem_** is **mutable**
- In contrast, **myConstObj** cannot invoke **setMem()** and hence **mem_** cannot be changed



Logical vis-a-vis Bit-wise Const-ness

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects

Example

const Member Functions

Example

const Data Members

Example

Credit Card

String

Date

Name

Address

CreditClass

mutable

Members

Example

mutable Guidelines

Module Summary

- `const` in C++, models *bit-wise* constant. Once an object is declared `const`, no part (actually, *no bit*) of it can be changed after construction (and initialization)
- However, while programming we often need an object to be *logically* constant. That is, the concept represented by the object should be constant; but if its representation need more data members for computation and modeling, these have no reason to be constant.
- `mutable` allows such surrogate data members to be changeable in a (bit-wise) constant object to model logically const objects
- To use `mutable` we shall look for:
 - A logically constant concept
 - A need for data members outside the representation of the concept; but are needed for computation



Program 15.09: When to use mutable Data Members?

Module M15

Partha Pratim Das

Objectives & Outlines

const Objects
Example

const Member Functions
Example

const Data Members
Example

Credit Card
String
Date
Name
Address
CreditClass

mutable Members

Example

mutable Guidelines

Module Summary

- Typically, when a class represents a constant concept, and
- It computes a value first time and caches the result for future use

```
// Source: http://www.highprogrammer.com/alan/rants/mutable.html
#include <iostream>
using namespace std;
class MathObject {                                // Constant concept of PI
    mutable bool piCached_;                       // Needed for computation
    mutable double pi_;                           // Needed for computation
public:
    MathObject() : piCached_(false) { }           // Not available at construction
    double pi() const {                           // Can access PI only through this method
        if (!piCached_) {                         // An insanely slow way to calculate pi
            pi_ = 4;
            for (long step = 3; step < 1000000000; step += 4) {
                pi_ += ((-4.0 / (double)step) + (4.0 / ((double)step + 2)));
            }
            piCached_ = true;                       // Now computed and cached
        }
        return pi_;
    }
};
int main() { const MathObject mo; cout << mo.pi() << endl; /* Access PI */ }
```

- Here a `MathObject` is logically constant; but we use `mutable` members for computation



Program 15.10: When *not* to use mutable Data Members?

- **mutable** should be rarely used – only when it is really needed. A bad example follows:

Improper Design (**mutable**)

```
class Employee { string _name, _id;
    mutable double _salary;
public: Employee(string name = "No Name",
    string id = "000-00-0000",
    double salary = 0): _name(name), _id(id)
    { _salary = salary; }
    string getName() const;
    void setName(string name);
    string getId() const;
    void setId(string id);
    double getSalary() const;
    void setSalary(double salary);
    void promote(double salary) const
    { _salary = salary; }
};
---
const Employee john("JOHN","007",5000.0);
// ...
john.promote(20000.0);
```

Proper Design (**const**)

```
class Employee { const string _name, _id;
    double _salary;
public: Employee(string name = "No Name",
    string id = "000-00-0000",
    double salary = 0): _name(name), _id(id)
    { _salary = salary; }
    string getName() const;
    // void setName(string name); // _name is const
    string getId() const;
    // void setId(string id); // _id is const
    double getSalary() const;
    void setSalary(double salary);
    void promote(double salary)
    { _salary = salary; }
};
---
Employee john("JOHN","007",5000.0);
// ...
john.promote(20000.0);
```

- **Employee** is not logically constant. If it is, then **_salary** should also be **const**
- Design on right makes that explicit



Module Summary

Module M15

Partha Pratim
Das

Objectives &
Outlines

const Objects
Example

const Member
Functions
Example

const Data
Members
Example

Credit Card
String
Date
Name
Address
CreditClass

mutable
Members

Example
mutable Guidelines

Module Summary

- Studied const-ness in C++
- In C++, there are three forms of const-ness
 - **Constant Objects**
 - ▷ No change is allowed after construction
 - ▷ Cannot invoke normal member functions
 - **Constant Member Functions**
 - ▷ Can be invoked by constant (as well as non-constant) objects
 - ▷ Cannot make changes to the object
 - **Constant Data Members**
 - ▷ No change is allowed after construction
 - ▷ Must be initialized in the initialization list
- Further, learnt how to model *logical const-ness* over *bit-wise const-ness* by proper use of `mutable` members