Programming in Modern C++

Module M21: Inheritance: Part 1: Inheritance Semantics

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional

Weekly Recap

- Understood `static` data members and member functions; and their use in modeling, especially Singleton Classes
- Understood `friend` function and `friend` class
- Noted its benefits vis-a-vis potential risk on breaking encapsulation
- Introduced operator overloading for user-defined types
- Outlined semantics for overloading binary and unary operators
- Learnt to build overloaded operators for UDTs using global, member or `friend` functions
- Understood `namespace` as a lexical scoping tool in C++

Module Objectives

- Understand `ISA` Relationship in OOAD and understand how hierarchy can be created in C++ with Inheritance

Module Outline

ISA Relationship

ISA Relationship

- We often find one object is a *specialization* / *generalization* of another
- OOAD models this using **ISA** relationship
- C++ models **ISA** relationship by *Inheritance* of classes

ISA Relationship

- Rose **ISA** Flower
  - Rose has the properties of Flower – like fragrance, having petals etc.
  - Rose has some additional properties – like rosy fragrance
  - Rose is a *specialization* of Flower
  - Flower is a *generalization* of Rose
- Red Rose **ISA** Rose
  - Red Rose has the properties of Rose – like rosy fragrance etc.
  - Red Rose has some additional properties – like it is red
  - Red Rose is a *specialization* of Rose
  - Rose is a *generalization* of Red Rose



- TwoWheeler **ISA** Vehicle; ThreeWheeler **ISA** Vehicle
- Manager **ISA** Employee

Inheritance in C++

Inheritance in C++: Hierarchy

- Manager **ISA** Employee [**Single Inheritance**]


```
class Employee;                 // Base Class = Employee
class Manager: public Employee; // Derived Class = Manager; Base Class = Employee
```

- TwoWheeler **ISA** Vehicle; ThreeWheeler **ISA** Vehicle [**Hybrid Inheritance**]




```
class Vehicle;                  // Base Class = Vehicle -- Root
class TwoWheeler: public Vehicle;    // Derived Class = TwoWheeler; Base Class = Vehicle
class ThreeWheeler: public Vehicle;  // Derived Class = ThreeWheeler; Base Class = Vehicle
```

- Red Rose **ISA** Rose **ISA** Flower [**Multi-Level Inheritance**]


```
class Flower;                // Base Class = Flower -- Root
class Rose: public Flower;   // Derived Class = Rose; Base Class = Flower
class RedRose: public Rose;  // Derived Class = RedRose; Base Class = Rose
```

Inheritance in C++: Phones

- **Landline Phone**
  - Call: By dial / keyboard
  - Answer
  - Caller ID (with special attached device)
- **Mobile Phone**
  - Call: By keyboard – shows number
    - By Number
    - By Name
  - Answer
  - Caller ID
  - Redial
  - Set Ring Tone
  - Add Contact
    - Number
    - Name
- **Smart Phone**
  - Call: By touchscreen – shows number & photo
    - By Number
    - By Name
  - Answer
  - Caller ID
  - Redial
  - Set Ring Tone
  - Add Contact
    - Number
    - Name
    - Photo

- There exists a substantial overlap between the functionality of the phones
- A mobile phone is more capable than a land line phone and can perform (almost) all its functions
- A smart phone is more capable than a mobile phone and can perform (almost) all its functions
- **These phones belong to a Specialization / Generalization Hierarchy**

Inheritance in C++: Semantics

- Derived **ISA** Base




```
class Base;                     // Base Class = Base
class Derived: public Base;     // Derived Class = Derived
```

- Use keyword `public` after class name to denote inheritance
- Name of the Base class follow the keyword

Public inheritance means "is-a." Everything that applies to base classes must also apply to derived classes, because every derived class object is a base class object

– Scott Meyers in Item 32, Effective C++ (3rd. Edition)

Inheritance in C++: Semantics

- Derived **ISA** Base
- **Data Members**
  - Derived class *inherits* all data members of Base class
  - Derived class may *add* data members of its own
- **Member Functions**
  - Derived class *inherits* all member functions of Base class
  - Derived class may *override* a member function of Base class by *redefining* it with the same signature
  - Derived class may *overload* a member function of Base class by *redefining* it with the *same name*; but *different signature*
  - Derived class *may add* new member functions
- **Access Specification**
  - Derived class *cannot access* private members of Base class
  - Derived class *can access* protected members of Base class
- **Construction-Destruction**
  - A *constructor* of the Derived class *must first* call a *constructor* of the Base class to construct the Base class instance of the Derived class
  - The *destructor* of the Derived class *must* call the *destructor* of the Base class to destruct the Base class instance of the Derived class

Module Summary

- Understood Hierarchy or `ISA` Relationship in OOAD
- Introduced the Semantics of Inheritance in C++