

SSN COLLEGE OF ENGINEERING, KALAVAKKAM
DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING
UCS1711 - MOBILE APPLICATION DEVELOPMENT LAB

Assignment 1

Name: Jayannthan P T

Dept: CSE 'A'

Roll No.: 205001049

Generate a Health Insurance registration form to register the patient details under each group.

Patient Details

a. Assign a title for the registration form (TextView- textSize, textStyle, typeface)

Group1 Patient Details

b. Patient Name. Specify some font and colour. (use TextView, EditText-standard)

c. Patient Phone Number (Mobile or Landline use Checkbox)

d. Address (use TextView, EditText-standard)

e. Age (TextView, EditText)

f. Date of Birth (DatePicker)

g. Gender (RadioButton)

h. Marital Status (Spinner)

Employer Details

a) Patient Employer

b) Employment Status (full time, parttime, unemployed, retired, student, other Checkbox)

Emergency contact Details

a) Name (EditText)

b) Relationship (EditText)

c) Address (Textarea)

d) Phone Number (EditText- inputType, phoneNumber)

Use Submit (Button) to submit the details and display the contents. Use Reset button to clear the form.

Additional: Display using Table layout create an output window using OPENGGL and to draw the following basic output primitives:

Title of the Program: Generate a Health Insurance registration form to register the patient details under each group

Objective:

The objective of the Health Insurance Android App project is to create a user-friendly application that allows users to input their personal details, employment information, and emergency contact details. The entered data is then displayed in a well-organized manner for the user's review.

Algorithm:

1. Create the main activity layout (**activity_main.xml**) with input fields for patient details, employment information, and emergency contact details.
2. Implement the logic to retrieve user input from the main activity, including handling radio buttons, checkboxes, and date picker.
3. Design the display data activity layout (**activity_display_data.xml**) using a **ScrollView**, **TableLayout**, and **TableRow** structure to display the entered data in a tabular format.
4. Pass the collected data from the main activity to the display data activity using an intent with extras.
5. In the display data activity, retrieve the data from the intent and populate the appropriate **TextView** elements in the layout.

Features used:

1. **EditText** widgets for user input.
2. **RadioGroup** and **RadioButton** widgets for gender selection.
3. **Spinner** widget for selecting marital status.
4. **CheckBox** widgets for selecting multiple options (employment status).
5. **DatePicker** widget for selecting the date of birth.
6. Passing data between activities using intents with extras.

Source code:

- MainActivity.java

```
package com.example.healthinsurance;

import androidx.appcompat.app.AppCompatActivity;

import android.content.Intent;
import android.os.Bundle;
import android.view.View;
import android.widget.AdapterView;
import android.widget.ArrayAdapter;
import android.widget.Button;
import android.widget.CheckBox;
import android.widget.DatePicker;
import android.widget.EditText;
import android.widget.RadioButton;
import android.widget.RadioGroup;
import android.widget.Spinner;

import java.text.SimpleDateFormat;
```

```
import java.util.Calendar;

public class MainActivity extends AppCompatActivity {

    // Declare your view elements
    EditText patientNameEditText, addressEditText, ageEditText, employerEditText,
        emergencyNameEditText, relationshipEditText, emergencyAddressEditText,
        emergencyPhoneNumberEditText;

    RadioGroup genderRadioGroup;
    RadioButton maleRadioButton, femaleRadioButton, otherRadioButton;

    Spinner maritalStatusSpinner;

    CheckBox mobileCheckBox, landlineCheckBox, fullTimeCheckBox, partTimeCheckBox;

    DatePicker dateOfBirthDatePicker;

    Button submitButton, resetButton;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        // Initialize your view elements
        patientNameEditText = findViewById(R.id.patientNameEditText);
        addressEditText = findViewById(R.id.addressEditText);
        ageEditText = findViewById(R.id.ageEditText);
        employerEditText = findViewById(R.id.employerEditText);
        emergencyNameEditText = findViewById(R.id.emergencyNameEditText);
        relationshipEditText = findViewById(R.id.relationshipEditText);
        emergencyAddressEditText = findViewById(R.id.emergencyAddressEditText);
        emergencyPhoneNumberEditText = findViewById(R.id.emergencyPhoneNumberEditText);

        genderRadioGroup = findViewById(R.id.genderRadioGroup);
        maleRadioButton = findViewById(R.id.maleRadioButton);
        femaleRadioButton = findViewById(R.id.femaleRadioButton);
        otherRadioButton = findViewById(R.id.otherRadioButton);

        mobileCheckBox = findViewById(R.id.mobileCheckBox);
        landlineCheckBox = findViewById(R.id.landlineCheckBox);
        fullTimeCheckBox = findViewById(R.id.fullTimeCheckBox);
        partTimeCheckBox = findViewById(R.id.partTimeCheckBox);

        dateOfBirthDatePicker = findViewById(R.id.dateOfBirthDatePicker);

        submitButton = findViewById(R.id.submitButton);
        resetButton = findViewById(R.id.resetButton);

        // Outside the OnClickListener block
        Spinner maritalStatusSpinner = findViewById(R.id.displayMaritalStatusSpinner);
        ArrayAdapter<CharSequence> adapter = ArrayAdapter.createFromResource(
```

```

        MainActivity.this, R.array.marital_status_options,
        android.R.layout.simple_spinner_item);
        adapter.setDropDownViewResource(android.R.layout.simple_spinner_dropdown_item);
        maritalStatusSpinner.setAdapter(adapter);

// Inside the OnClickListener block
submitButton.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View view) {
        String patientName = patientNameEditText.getText().toString();
        String address = addressEditText.getText().toString();
        String ageStr = ageEditText.getText().toString();
        int age = 0;
        if (!ageStr.isEmpty()) {
            age = Integer.parseInt(ageStr);
        }
        String employer = employerEditText.getText().toString();
        String employmentStatus = "";
        if (fullTimeCheckBox.isChecked()) {
            employmentStatus = "Full Time";
        } else if (partTimeCheckBox.isChecked()) {
            employmentStatus = "Part Time";
        }

        String maritalStatus = maritalStatusSpinner.getSelectedItem().toString();

        String emergencyContactName = emergencyNameEditText.getText().toString();
        String relationship = relationshipEditText.getText().toString();
        String emergencyContactAddress =
emergencyAddressEditText.getText().toString();
        String emergencyContactPhoneNumber =
emergencyPhoneNumberEditText.getText().toString();

// Get selected radio button from genderRadioGroup
int selectedGenderId = genderRadioGroup.getCheckedRadioButtonId();
RadioButton selectedGenderRadioButton = findViewById(selectedGenderId);
String gender = selectedGenderRadioButton.getText().toString();

// Get selected date from dateOfBirthDatePicker
int year = dateOfBirthDatePicker.getYear();
int month = dateOfBirthDatePicker.getMonth() + 1; // DatePicker month is
0-based

int day = dateOfBirthDatePicker.getDayOfMonth();
String dateOfBirth = year + "-" + month + "-" + day;

Intent intent = new Intent(MainActivity.this, DisplayDataActivity.class);

// Pass data to the intent using extras
intent.putExtra("patientName", patientName);
intent.putExtra("address", address);
intent.putExtra("age", age);
intent.putExtra("employer", employer);
intent.putExtra("employmentStatus", employmentStatus);
intent.putExtra("emergencyContactName", emergencyContactName);

```

```

        intent.putExtra("relationship", relationship);
        intent.putExtra("emergencyContactAddress", emergencyContactAddress);
        intent.putExtra("emergencyContactPhoneNumber",
emergencyContactPhoneNumber);
        intent.putExtra("gender", gender);
        intent.putExtra("maritalStatus", maritalStatus);
        intent.putExtra("dateOfBirth", dateOfBirth);

        // Start the new activity
        startActivity(intent);
    }
});

resetButton.setOnClickListener(new View.OnClickListener() {
    @Override
    public void onClick(View view) {
        // Clear all input fields
        patientNameEditText.getText().clear();
        addressEditText.getText().clear();
        ageEditText.getText().clear();
        employerEditText.getText().clear();
        emergencyNameEditText.getText().clear();
        relationshipEditText.getText().clear();
        emergencyAddressEditText.getText().clear();
        emergencyPhoneNumberEditText.getText().clear();
        genderRadioGroup.clearCheck();
        maritalStatusSpinner.setSelection(0); // Reset to the first item in the
spinner

        mobileCheckBox.setChecked(false);
        landlineCheckBox.setChecked(false);
        fullTimeCheckBox.setChecked(false);
        partTimeCheckBox.setChecked(false);

        // Reset the date picker to today's date
        Calendar calendar = Calendar.getInstance();
        int year = calendar.get(Calendar.YEAR);
        int month = calendar.get(Calendar.MONTH);
        int day = calendar.get(Calendar.DAY_OF_MONTH);
        dateOfBirthDatePicker.updateDate(year, month, day);
    }
});

// Set the default date of birth in the date picker to today's date
Calendar calendar = Calendar.getInstance();
SimpleDateFormat dateFormat = new SimpleDateFormat("yyyy-MM-dd");
String currentDate = dateFormat.format(calendar.getTime());
String[] dateParts = currentDate.split("-");
int year = Integer.parseInt(dateParts[0]);
int month = Integer.parseInt(dateParts[1]) - 1; // Month is 0-based
int day = Integer.parseInt(dateParts[2]);
dateOfBirthDatePicker.init(year, month, day, null);
}
}

```

- activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>

<ScrollView xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent" android:layout_height="wrap_content">

    <LinearLayout android:layout_width="match_parent" android:layout_height="wrap_content"
        android:orientation="vertical" android:padding="16dp">

        <TextView android:layout_width="wrap_content" android:layout_height="wrap_content"
            android:text="@string/health_insurance_registration_form" android:textSize="24sp"
            android:textStyle="bold" android:typeface="serif" android:layout_gravity="center"
            android:layout_marginBottom="16dp"/>

        <TableLayout android:layout_width="match_parent"
            android:layout_height="wrap_content">

            <!-- Group: Patient Details -->
            <TableRow>

                <TextView android:layout_width="wrap_content"
                    android:layout_height="wrap_content" android:text="Patient Details"
                    android:textStyle="bold" android:layout_span="2" android:paddingBottom="8dp"
                    android:paddingTop="16dp"/>

            </TableRow>

            <TableRow>

                <TextView android:layout_width="wrap_content"
                    android:layout_height="wrap_content" android:text="Patient Name:"
                    android:textColor="#000000" android:paddingEnd="8dp"/>

                <EditText android:id="@+id/patientNameEditText" android:layout_width="0dp"
                    android:layout_height="wrap_content" android:hint="Enter patient name"
                    android:layout_weight="1"/>

            </TableRow>

            <TableRow>

                <TextView android:layout_width="wrap_content"
                    android:layout_height="wrap_content" android:text="Patient Phone Number:"
                    android:textColor="#000000" android:paddingEnd="8dp"/>

                <CheckBox android:id="@+id/mobileCheckBox"
                    android:layout_width="wrap_content" android:layout_height="wrap_content"
                    android:text="Mobile"/>

                <CheckBox android:id="@+id/landlineCheckBox"
                    android:layout_width="wrap_content" android:layout_height="wrap_content"
                    android:text="Landline"/>

            </TableRow>

            <TableRow>

                <TextView android:layout_width="wrap_content"
                    android:layout_height="wrap_content" android:text="Address:" android:textColor="#000000"
                    android:paddingEnd="8dp"/>

            </TableRow>

        </TableLayout>

    </LinearLayout>

</ScrollView>
```

```

        <EditText android:id="@+id/addressEditText" android:layout_width="0dp"
android:layout_height="wrap_content" android:hint="Enter address"
android:layout_weight="1"/>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Age:" android:textColor="#000000"
android:paddingEnd="8dp"/>
        <EditText android:id="@+id/ageEditText" android:layout_width="0dp"
android:layout_height="wrap_content" android:hint="Enter age" android:inputType="number"
android:layout_weight="1"/>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Date of Birth:"
android:textColor="#000000" android:paddingEnd="8dp"/>
        <DatePicker android:id="@+id/dateOfBirthDatePicker"
android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1"/>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Gender:" android:textColor="#000000"
android:paddingEnd="8dp"/>
        <RadioGroup android:id="@+id/genderRadioGroup" android:layout_width="0dp"
android:layout_height="wrap_content" android:orientation="horizontal"
android:layout_weight="1">

            <RadioButton android:id="@+id/maleRadioButton"
android:layout_width="wrap_content" android:layout_height="wrap_content"
android:text="Male"/>
            <RadioButton android:id="@+id/femaleRadioButton"
android:layout_width="wrap_content" android:layout_height="wrap_content"
android:text="Female"/>
            <RadioButton android:id="@+id/otherRadioButton"
android:layout_width="wrap_content" android:layout_height="wrap_content"
android:text="Other"/>
        </RadioGroup>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Marital Status:"
android:textColor="#000000" android:paddingEnd="8dp"/>
        <Spinner android:id="@+id/displayMaritalStatusSpinner"
android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1"/>
    </TableRow>

    <!-- Group: Employer Details -->
    <TableRow>

```



```

        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Employer Details"
android:textStyle="bold" android:layout_span="2" android:paddingBottom="8dp"
android:paddingTop="16dp"/>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Patient Employer:"
android:textColor="#000000" android:paddingEnd="8dp"/>
        <EditText android:id="@+id/employerEditText" android:layout_width="0dp"
android:layout_height="wrap_content" android:hint="Enter employer"
android:layout_weight="1"/>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Employment Status:"
android:textColor="#000000" android:paddingEnd="8dp"/>
        <CheckBox android:id="@+id/fullTimeCheckBox"
android:layout_width="wrap_content" android:layout_height="wrap_content"
android:text="Full Time"/>
        <CheckBox android:id="@+id/partTimeCheckBox"
android:layout_width="wrap_content" android:layout_height="wrap_content"
android:text="Part Time"/>
        <!-- Add more checkboxes for other options -->
    </TableRow>

    <!-- Group: Emergency Contact Details -->
    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Emergency Contact Details"
android:textStyle="bold" android:layout_span="2" android:paddingBottom="8dp"
android:paddingTop="16dp"/>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Name:" android:textColor="#000000"
android:paddingEnd="8dp"/>
        <EditText android:id="@+id/emergencyNameEditText"
android:layout_width="0dp" android:layout_height="wrap_content" android:hint="Enter
emergency contact name" android:layout_weight="1"/>
    </TableRow>

    <TableRow>
        <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Relationship:"
android:textColor="#000000" android:paddingEnd="8dp"/>
        <EditText android:id="@+id/relationshipEditText"
android:layout_width="0dp" android:layout_height="wrap_content" android:hint="Enter
relationship" android:layout_weight="1"/>
    </TableRow>

```



```

        <TableRow>
            <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Address:" android:textColor="#000000"
android:paddingEnd="8dp"/>
            <EditText android:id="@+id/emergencyAddressEditText"
android:layout_width="0dp" android:layout_height="wrap_content" android:hint="Enter
emergency contact address" android:layout_weight="1"/>
        </TableRow>

        <TableRow>
            <TextView android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Phone Number:"
android:textColor="#000000" android:paddingEnd="8dp"/>
            <EditText android:id="@+id/emergencyPhoneNumberEditText"
android:layout_width="0dp" android:layout_height="wrap_content" android:hint="Enter
emergency contact phone number" android:inputType="phone" android:layout_weight="1"/>
        </TableRow>

        <TableRow>
            <Button android:id="@+id/submitButton" android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Submit" android:layout_gravity="center"
android:layout_span="2" android:layout_marginTop="16dp"/>
        </TableRow>

        <TableRow>
            <Button android:id="@+id/resetButton" android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Reset" android:layout_gravity="center"
android:layout_span="2" android:layout_marginTop="8dp"/>
        </TableRow>
    </TableLayout>

</LinearLayout>
</ScrollView>

```

- DisplayDataActivity.java

```

package com.example.healthinsurance;

import android.content.Intent;
import android.os.Bundle;
import android.widget.TextView;
import androidx.appcompat.app.AppCompatActivity;

public class DisplayDataActivity extends AppCompatActivity {
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_display_data);

        // Retrieve data from the intent
        Intent intent = getIntent();
        String patientName = intent.getStringExtra("patientName");
        String address = intent.getStringExtra("address");
    }
}

```

```

        int age = intent.getIntExtra("age", 0);
        String employer = intent.getStringExtra("employer");
        String employmentStatus = intent.getStringExtra("employmentStatus");
        String emergencyContactName = intent.getStringExtra("emergencyContactName");
        String relationship = intent.getStringExtra("relationship");
        String emergencyContactAddress = intent.getStringExtra("emergencyContactAddress");
        String emergencyContactPhoneNumber =
intent.getStringExtra("emergencyContactPhoneNumber");
        String gender = intent.getStringExtra("gender");
        String maritalStatus = intent.getStringExtra("maritalStatus");
        String dateOfBirth = intent.getStringExtra("dateOfBirth");

        // Find TextViews in the layout and set their text
        TextView displayPatientName = findViewById(R.id.displayPatientName);
        TextView displayAddress = findViewById(R.id.displayAddress);
        TextView displayAge = findViewById(R.id.displayAge);
        TextView displayEmployer = findViewById(R.id.displayEmployer);
        TextView displayEmploymentStatus = findViewById(R.id.displayEmploymentStatus);
        TextView displayEmergencyContactName =
findViewById(R.id.displayEmergencyContactName);
        TextView displayRelationship = findViewById(R.id.displayRelationship);
        TextView displayEmergencyContactAddress =
findViewById(R.id.displayEmergencyContactAddress);
        TextView displayEmergencyContactPhoneNumber =
findViewById(R.id.displayEmergencyContactPhoneNumber);
        TextView displayGender = findViewById(R.id.displayGender);
        TextView displayMaritalStatus = findViewById(R.id.displayMaritalStatus);
        TextView displayDateOfBirth = findViewById(R.id.displayDateOfBirth);

        displayPatientName.setText("Patient Name: " + patientName);
        displayAddress.setText("Address: " + address);
        displayAge.setText("Age: " + age);
        displayEmployer.setText("Employer: " + employer);
        displayEmploymentStatus.setText("Employment Status: " + employmentStatus);
        displayEmergencyContactName.setText("Emergency Contact Name: " +
emergencyContactName);
        displayRelationship.setText("Relationship: " + relationship);
        displayEmergencyContactAddress.setText("Emergency Contact Address: " +
emergencyContactAddress);
        displayEmergencyContactPhoneNumber.setText("Emergency Contact Phone: " +
emergencyContactPhoneNumber);
        displayGender.setText("Gender: " + gender);
        displayMaritalStatus.setText("Marital Status: " + maritalStatus);
        displayDateOfBirth.setText("Date of Birth: " + dateOfBirth);
    }
}

```

- activity_display_data.xml

```
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent" android:layout_height="match_parent"
    android:orientation="vertical" android:padding="16dp">

    <TextView android:id="@+id/displayPatientName" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayAddress" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayAge" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="16dp"/>

    <TextView android:id="@+id/displayGender" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayMaritalStatus" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayDateOfBirth" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="16dp"/>

    <TextView android:id="@+id/displayEmployer" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayEmploymentStatus"
    android:layout_width="wrap_content" android:layout_height="wrap_content" android:text=""
    android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayEmergencyContactName"
    android:layout_width="wrap_content" android:layout_height="wrap_content" android:text=""
    android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayRelationship" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="" android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayEmergencyContactAddress"
    android:layout_width="wrap_content" android:layout_height="wrap_content" android:text=""
    android:paddingBottom="8dp"/>

    <TextView android:id="@+id/displayEmergencyContactPhoneNumber"
    android:layout_width="wrap_content" android:layout_height="wrap_content" android:text=""
    android:paddingBottom="16dp"/>

</LinearLayout>
```

Output:

11:49

Health Insurance

27 28 29 30 31

Gender:

☐ Male ☐ Female ☐ Other

Marital Status: ▼

Employer Details

Patient Employer:

Employment Status: ☐ Full Time ☐ Part Time

Emergency Contact Details

Name:

Relationship:

Address:

Phone Number:

SUBMIT

RESET

11:48



Health Insurance

Health Insurance Registration Form

Patient Details

Patient Name:

Patient Phone Number: ☐ Mobile ☐ Landline

Address:

Age:

Date of Birth:

2023

Thu, Aug
24

< August 2023 >


S M T W T F S

1 2 3 4 5

6 7 8 9 10 11 12

13 14 15 16 17 18 19

20 21 22 23 24 25 26



Result:

The mobile application was completed successfully

Best Practices:

1. Use appropriate variable naming conventions for readability.
2. Implement input validation to ensure data accuracy.
3. Utilize layout resources for UI consistency and responsiveness.
4. Organize the code with comments and logical structure.
5. Implement proper error handling to prevent crashes.

Learning Outcomes:

1. Designing Android user interfaces using XML layouts.
2. Data passing between activities.
3. Handling diverse user input elements (text fields, radio buttons, checkboxes, spinners, date pickers).
4. Creating organized layouts with ScrollView, TableLayout, and TableRow.
5. Enhancing Java coding skills for Android development.
6. Managing user interactions and events.

SSN COLLEGE OF ENGINEERING, KALAVAKKAM
DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING
UCS1711 - MOBILE APPLICATION DEVELOPMENT LAB

Assignment 2


Name: Jayannthan P T

Dept: CSE 'A'

Roll No.: 205001049

Create an Android mobile application which simulates a virtual keyboard with following features use intents to navigate between multiple activities.

- a. Use Grid Layout with each cell containing individual characters / numbers / special characters
- b. A TextView (multiple lines) to display the typed content.
- c. Design the keyboard as shown in Fig. 1.



- d. On press number key toggle to digits and special character view as in Fig. 2.
 - e. On pressing each symbol, display the corresponding character in the textview.
 - f. On pressing enter, move to newline in textview.
 - g. On pressing backspace, erase a character in the textview.
 - h. On pressing spacebar button provide single space
- Additional: On press Up arrow, toggle between uppercase and lowercase letters.

Title of the Program: Create an Android mobile application which simulates a virtual keyboard with following features use intents to navigate between multiple activities.

Objective:

The objective of the Keyboard Android App project is to create a user-friendly keyboard application that allows users to input text efficiently using a virtual keyboard. Users can switch between letter and symbol modes, type letters and symbols, use capitalization, handle space, backspace, and enter, and eventually submit the typed text to be displayed in another activity..

Algorithm:

1. Create the main activity layout (activity_main.xml) with buttons for letters, symbols, and special functions like capitalization, space, backspace, and enter.
2. Implement the logic to handle button clicks for both letter and symbol modes.
3. Toggle between letter and symbol modes when the "Change" button is clicked.
4. Implement capitalization logic when the "Caps" button is clicked.
5. Handle space, backspace, and enter button clicks to modify the text in the EditText field.
6. Create a separate display activity layout (activity_display_data.xml) to display the typed text.
7. Pass the typed text from the main activity to the display activity using an intent with extras.
8. In the display activity, retrieve the text from the intent and display it in a TextView.

Features used:

1. Buttons for letter and symbol input.
2. Button for switching between letter and symbol modes.
3. Button for capitalization.
4. Buttons for space, backspace, and enter.
5. EditText widget for displaying typed text.
6. Passing data between activities using intents.

Source code:

- MainActivity.java

```
package com.example.keyboard;

import androidx.appcompat.app.AppCompatActivity;
import android.content.Intent;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;

public class MainActivity extends AppCompatActivity {
    Button a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z;
    Button caps, backspace, space, enter, change;
    Button submit_btn, clear_btn;
    EditText editor;

    @Override
```

```
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
    caps = findViewById(R.id.caps);
    change = findViewById(R.id.change);
    a = findViewById(R.id.a);
    b = findViewById(R.id.b);
    c = findViewById(R.id.c);
    d = findViewById(R.id.d);
    e = findViewById(R.id.e);
    f = findViewById(R.id.f);
    g = findViewById(R.id.g);
    h = findViewById(R.id.h);
    i = findViewById(R.id.i);
    j = findViewById(R.id.j);
    k = findViewById(R.id.k);
    l = findViewById(R.id.l);
    m = findViewById(R.id.m);
    n = findViewById(R.id.n);
    o = findViewById(R.id.o);
    p = findViewById(R.id.p);
    q = findViewById(R.id.q);
    r = findViewById(R.id.r);
    s = findViewById(R.id.s);
    t = findViewById(R.id.t);
    u = findViewById(R.id.u);
    v = findViewById(R.id.v);
    w = findViewById(R.id.w);
    x = findViewById(R.id.x);
    y = findViewById(R.id.y);
    z = findViewById(R.id.z);
    final boolean[] isUpperCase = { false };
    final boolean[] isSymbolMode = { false };
    caps.setOnClickListener(view -> {
        if (isSymbolMode[0]) {
            a.setText(isUpperCase[0] ? "A" : "a");
            b.setText(isUpperCase[0] ? "B" : "b");
            c.setText(isUpperCase[0] ? "C" : "c");
            d.setText(isUpperCase[0] ? "D" : "d");
            e.setText(isUpperCase[0] ? "E" : "e");
            f.setText(isUpperCase[0] ? "F" : "f");
            g.setText(isUpperCase[0] ? "G" : "g");
            h.setText(isUpperCase[0] ? "H" : "h");
            i.setText(isUpperCase[0] ? "I" : "i");
            j.setText(isUpperCase[0] ? "J" : "j");
            k.setText(isUpperCase[0] ? "K" : "k");
            l.setText(isUpperCase[0] ? "L" : "l");
            m.setText(isUpperCase[0] ? "M" : "m");
            n.setText(isUpperCase[0] ? "N" : "n");
            o.setText(isUpperCase[0] ? "O" : "o");
            p.setText(isUpperCase[0] ? "P" : "p");
            q.setText(isUpperCase[0] ? "Q" : "q");
            r.setText(isUpperCase[0] ? "R" : "r");
            s.setText(isUpperCase[0] ? "S" : "s");
```

```

        t.setText(isUpperCase[0] ? "T" : "t");
        u.setText(isUpperCase[0] ? "U" : "u");
        v.setText(isUpperCase[0] ? "V" : "v");
        w.setText(isUpperCase[0] ? "W" : "w");
        x.setText(isUpperCase[0] ? "X" : "x");
        y.setText(isUpperCase[0] ? "Y" : "y");
        z.setText(isUpperCase[0] ? "Z" : "z");
    } else {

        a.setText(isUpperCase[0] ? "a" : "A");
        b.setText(isUpperCase[0] ? "b" : "B");
        c.setText(isUpperCase[0] ? "c" : "C");
        d.setText(isUpperCase[0] ? "d" : "D");
        e.setText(isUpperCase[0] ? "e" : "E");
        f.setText(isUpperCase[0] ? "f" : "F");
        g.setText(isUpperCase[0] ? "g" : "G");
        h.setText(isUpperCase[0] ? "h" : "H");
        i.setText(isUpperCase[0] ? "i" : "I");
        j.setText(isUpperCase[0] ? "j" : "J");
        k.setText(isUpperCase[0] ? "k" : "K");
        l.setText(isUpperCase[0] ? "l" : "L");
        m.setText(isUpperCase[0] ? "m" : "M");
        n.setText(isUpperCase[0] ? "n" : "N");
        o.setText(isUpperCase[0] ? "o" : "O");
        p.setText(isUpperCase[0] ? "p" : "P");
        q.setText(isUpperCase[0] ? "q" : "Q");
        r.setText(isUpperCase[0] ? "r" : "R");
        s.setText(isUpperCase[0] ? "s" : "S");
        t.setText(isUpperCase[0] ? "t" : "T");
        u.setText(isUpperCase[0] ? "u" : "U");
        v.setText(isUpperCase[0] ? "v" : "V");
        w.setText(isUpperCase[0] ? "w" : "W");
        x.setText(isUpperCase[0] ? "x" : "X");
        y.setText(isUpperCase[0] ? "y" : "Y");
        z.setText(isUpperCase[0] ? "z" : "Z");
    }
    isUpperCase[0] = !isUpperCase[0];
});
change.setOnClickListener(view -> {
    if (isSymbolMode[0]) {
        // Switching from symbol mode to letter mode
        a.setText(isUpperCase[0] ? "A" : "a");
        b.setText(isUpperCase[0] ? "B" : "b");
        c.setText(isUpperCase[0] ? "C" : "c");
        d.setText(isUpperCase[0] ? "D" : "d");
        e.setText(isUpperCase[0] ? "E" : "e");
        f.setText(isUpperCase[0] ? "F" : "f");
        g.setText(isUpperCase[0] ? "G" : "g");
        h.setText(isUpperCase[0] ? "H" : "h");
        i.setText(isUpperCase[0] ? "I" : "i");
        j.setText(isUpperCase[0] ? "J" : "j");
        k.setText(isUpperCase[0] ? "K" : "k");
        l.setText(isUpperCase[0] ? "L" : "l");
        m.setText(isUpperCase[0] ? "M" : "m");
    }
});

```

```

        n.setText(isUpperCase[0] ? "N" : "n");
        o.setText(isUpperCase[0] ? "O" : "o");
        p.setText(isUpperCase[0] ? "P" : "p");
        q.setText(isUpperCase[0] ? "Q" : "q");
        r.setText(isUpperCase[0] ? "R" : "r");
        s.setText(isUpperCase[0] ? "S" : "s");
        t.setText(isUpperCase[0] ? "T" : "t");
        u.setText(isUpperCase[0] ? "U" : "u");
        v.setText(isUpperCase[0] ? "V" : "v");
        w.setText(isUpperCase[0] ? "W" : "w");
        x.setText(isUpperCase[0] ? "X" : "x");
        y.setText(isUpperCase[0] ? "Y" : "y");
        z.setText(isUpperCase[0] ? "Z" : "z");
        // Change the text of the special button
        change.setText("?123");
    } else {
        // Switching to symbol mode
        a.setText("");
        b.setText("9");
        c.setText("7");
        d.setText("4");
        e.setText("1");
        f.setText("5");
        g.setText("6");
        h.setText("+");
        i.setText("*");
        j.setText("%");
        k.setText("!");
        l.setText("@");
        m.setText("#");
        n.setText("$");
        o.setText("0");
        p.setText("^");
        q.setText("&");
        r.setText("2");
        s.setText("(");
        t.setText("3");
        u.setText("-");
        v.setText("8");
        w.setText("=");
        x.setText("/");
        y.setText("?");
        z.setText("'");
        // Change the text of the special button
        change.setText("ABC");
    }
    isSymbolMode[0] = !isSymbolMode[0];
});
editor = findViewById(R.id.editor);
View.OnClickListener alphabetClickListener = new View.OnClickListener() {
    @Override
    public void onClick(View v) {
        Button clickedButton = (Button) v;
        String buttonText = clickedButton.getText().toString();

```

```

        String currentText = editor.getText().toString();
        editor.setText(currentText + buttonText);
    }
};
int[] alphabetButtonIds = {
    R.id.a, R.id.b, R.id.c, R.id.d, R.id.e, R.id.f, R.id.g, R.id.h,
    R.id.i, R.id.j, R.id.k, R.id.l, R.id.m, R.id.n, R.id.o, R.id.p,
    R.id.q, R.id.r, R.id.s, R.id.t, R.id.u, R.id.v, R.id.w, R.id.x,
    R.id.y, R.id.z
};
for (int buttonId : alphabetButtonIds) {
    Button alphabetButton = findViewById(buttonId);
    alphabetButton.setOnClickListener(alphabetClickListener);
}
space = findViewById(R.id.space);
space.setOnClickListener(view -> {
    String currentText = editor.getText().toString();
    editor.setText(currentText + " ");
});
enter = findViewById(R.id.enter);
enter.setOnClickListener(view -> {
    String currentText = editor.getText().toString();
    editor.setText(currentText + "\n");
});
backspace = findViewById(R.id.backspace);
backspace.setOnClickListener(view -> {
    String currentText = editor.getText().toString();
    if (!currentText.isEmpty()) {
        String newText = currentText.substring(0, currentText.length() - 1);
        editor.setText(newText);
    }
});
submit_btn = findViewById(R.id.submit_btn);
submit_btn.setOnClickListener(view -> {
    Intent navigate = new Intent(MainActivity.this, DisplayActivity.class);
    navigate.putExtra("input_value", editor.getText().toString());
    startActivity(navigate);
});
clear_btn = findViewById(R.id.clear_btn);
clear_btn.setOnClickListener(view -> {
    String currentText = editor.getText().toString();
    if (!currentText.isEmpty()) {
        editor.setText("");
    }
});
}
}

```

- activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools" android:layout_width="match_parent"
android:layout_height="match_parent" tools:context=".MainActivity">
    <androidx.constraintlayout.widget.ConstraintLayout android:id="@+id/key_holder"
android:layout_width="match_parent" android:layout_height="280dp"
android:layout_margin="18dp" app:layout_constraintBottom_toBottomOf="parent"
app:layout_constraintEnd_toEndOf="parent" app:layout_constraintStart_toStartOf="parent">
        <TableLayout android:layout_width="wrap_content"
android:layout_height="match_parent" app:layout_constraintBottom_toBottomOf="parent"
app:layout_constraintEnd_toEndOf="parent" app:layout_constraintStart_toStartOf="parent"
app:layout_constraintTop_toTopOf="parent" android:stretchColumns="*">
            <TableRow android:layout_gravity="center">

                <Button android:id="@+id/q" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="q" />

                <Button android:id="@+id/w" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="w" />

                <Button android:id="@+id/e" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="e" />

                <Button android:id="@+id/r" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="r" />

                <Button android:id="@+id/t" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="t" />

                <Button android:id="@+id/y" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="y" />

                <Button android:id="@+id/u" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="u" />
            </TableRow>
            <TableRow android:layout_gravity="center">
                <Button android:id="@+id/a" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:layout_weight="1" android:text="a" />
            </TableRow>
        </TableLayout>
    </androidx.constraintlayout.widget.ConstraintLayout>
</androidx.constraintlayout.widget.ConstraintLayout>
```


[illegible]

```

        </TableRow>
        <TableRow android:layout_gravity="center">
            <Button android:id="@+id/caps" android:layout_margin="2dp"
android:layout_weight="1" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="⬆" />
            <Button android:id="@+id/l" android:layout_margin="2dp"
android:layout_weight="1" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="l" />
            <Button android:id="@+id/i" android:layout_margin="2dp"
android:layout_weight="1" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="i" />
            <Button android:id="@+id/o" android:layout_margin="2dp"
android:layout_weight="1" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="o" />
            <Button android:id="@+id/p" android:layout_margin="2dp"
android:layout_weight="1" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="p" />
            <Button android:id="@+id/k" android:layout_margin="2dp"
android:layout_weight="1" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="k" />
            <Button android:id="@+id/backspace" android:layout_margin="2dp"
android:layout_weight="1" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="⬅" />
        </TableRow>
        <TableRow>
            <Button android:id="@+id/change" android:layout_margin="2dp"
android:backgroundTint="@color/button_background" android:text="\?123"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" />
            <Button android:id="@+id/space" android:layout_margin="2dp"
android:layout_weight="6" android:textAllCaps="false"
android:textColor="@color/button_text" android:textSize="18sp" android:textStyle="bold"
android:backgroundTint="@color/button_background" android:text="Space" />
            <Button android:id="@+id/enter" android:layout_margin="2dp"
android:textAllCaps="false" android:textColor="@color/button_text" android:textSize="18sp"
android:textStyle="bold" android:backgroundTint="@color/button_background"
android:text="↵" />
        </TableRow>
    </TableLayout>
</androidx.constraintlayout.widget.ConstraintLayout>
<EditText android:id="@+id/editor" android:layout_width="match_parent"
android:layout_height="wrap_content" android:layout_margin="24dp" android:hint="Type
here..." android:text="" app:layout_constraintBottom_toTopOf="@+id/submit_btn"
app:layout_constraintEnd_toEndOf="parent" app:layout_constraintStart_toStartOf="parent"
app:layout_constraintTop_toTopOf="parent" />
    <Button android:id="@+id/submit_btn" android:layout_width="180dp"
android:layout_height="wrap_content" android:layout_margin="12dp" android:text="Submit"

```

```

app:layout_constraintBottom_toTopOf="@+id/clear_btn"
app:layout_constraintEnd_toEndOf="parent" app:layout_constraintStart_toStartOf="parent" />
    <Button android:id="@+id/clear_btn" android:layout_width="180dp"
android:layout_height="wrap_content" android:layout_margin="12dp" android:text="Clear"
app:layout_constraintBottom_toTopOf="@+id/key_holder"
app:layout_constraintEnd_toEndOf="parent" app:layout_constraintStart_toStartOf="parent" />
</androidx.constraintlayout.widget.ConstraintLayout>

```

- DisplayDataActivity.java

```

package com.example.keyboard;

import android.content.Intent;
import android.os.Bundle;
import android.widget.TextView;
import androidx.appcompat.app.AppCompatActivity;

public class DisplayActivity extends AppCompatActivity {
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_display);
        Intent intent = getIntent();
        String editText = intent.getStringExtra("input_value");
        TextView preview = findViewById(R.id.preview_text);
        preview.setText(editText);
    }
}

```

- activity_display_data.xml


```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
android:layout_width="match_parent" android:layout_height="match_parent">
    <TextView android:id="@+id/title" android:layout_width="wrap_content"
android:layout_height="wrap_content" android:layout_marginTop="36dp" android:text="You
typed..." android:textSize="24sp" android:textStyle="bold"
app:layout_constraintEnd_toEndOf="parent" app:layout_constraintStart_toStartOf="parent"
app:layout_constraintTop_toTopOf="parent" />

    <TextView android:id="@+id/preview_text" android:layout_width="match_parent"
android:layout_height="wrap_content" android:layout_margin="36dp" android:gravity="center"
android:text="" app:layout_constraintBottom_toBottomOf="parent"
app:layout_constraintEnd_toEndOf="parent" app:layout_constraintStart_toStartOf="parent"
app:layout_constraintTop_toBottomOf="@+id/title" />
</androidx.constraintlayout.widget.ConstraintLayout>

```

Output:




Keyboard

Type here...

SUBMIT

CLEAR



6:53



Keyboard

Type here...

SUBMIT

CLEAR

Q

W

E

R

T

Y

U

A

S

D

F

G

H

J

Z

X

C

V

B

N

M

↑

L

I

O

P

K

←

?123

Space

↩



Result:

The mobile application was completed successfully

Best Practices:

1. Use meaningful variable names and comments for better code readability.
2. Implement input validation to ensure that the user interface behaves correctly.
3. Utilize layout resources (XML) for UI consistency and responsiveness.
4. Organize the code with comments and logical structure to enhance maintainability.
5. Implement proper error handling to prevent crashes and provide a smooth user experience.

Learning Outcomes:

1. Designing Android user interfaces using XML layouts for a virtual keyboard.
2. Implementing interactive elements like buttons and EditText fields.
3. Handling user input events, including button clicks and text modifications.
4. Passing data between activities using intents with extras.
5. Enhancing Java coding skills for Android app development.
6. Managing user interactions and events effectively within the app.

SSN COLLEGE OF ENGINEERING, KALAVAKKAM
DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING
UCS1711 - MOBILE APPLICATION DEVELOPMENT LAB

Assignment 3

Name: Jayannthan P T

Dept: CSE 'A'

Roll No.: 205001049

Application using graphical primitives

Design a CAR using Shape drawable with the help of relevant shapes such as Line, Circle, Rectangle and Arc.

- a. Move the car forward by pressing forward button so that car moves from a predefined starting point to the predefined endpoint.
- b. On pressing backward button, rotate the car to 180 degrees from the current point to the starting point.
- c. Implement a Tap-to-zoom animation on any image
- d. Implement the Card flipping animation.

Title of the Program: Design a CAR using Shape drawable with the help of relevant shapes such as Line, Circle, Rectangle and Arc.

Objective:

The objective of the Keyboard Android App project is to create a user-friendly keyboard application that allows users to input text efficiently using a virtual keyboard. Users can switch between letter and symbol modes, type letters and symbols, use capitalization, handle space, backspace, and enter, and eventually submit the typed text to be displayed in another activity.

Algorithm:

1. Create the main activity layout (activity_main.xml) with buttons for moving the car forward and backward, and a RelativeLayout to hold the car image.
2. Implement the logic to handle button clicks for moving the car forward and backward.
3. Implement logic to handle clicks on the car image to toggle zooming in and out.
4. Create XML shape resources for defining the car body, wheels, and other components.
5. Initialize the initial state of the car (position, zoom level, and rotation) in the MainActivity.
6. Implement methods for zooming in, zooming out, moving the car, and flipping the car.
7. Calculate the maximum translation distance to prevent the car from moving off the screen.
8. Use ObjectAnimator to animate the car's movement and rotation.
9. Update the current position and rotation values as the car moves and rotates.

Features used:

1. Buttons for moving the car forward and backward.
2. Button for toggling zoom on the car image.
3. Use of XML shape resources to define the car's appearance.
4. ObjectAnimator for animating car movement and rotation.
5. Handling clicks events on the car image.
6. Calculation of the maximum translation distance.

Source code:

- MainActivity.java

```
package com.example.ex3;

import android.animation.ObjectAnimator;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.RelativeLayout;
import androidx.appcompat.app.AppCompatActivity;

public class MainActivity extends AppCompatActivity {

    private RelativeLayout carLayout;
    private Button moveButton;
    private Button moveBack;
```

```
private int currentPosition = 0;
private boolean isFlipped = false;
private boolean isZoomed = false;

@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);

    carLayout = findViewById(R.id.carLayout);
    moveButton = findViewById(R.id.moveForwardButton);
    moveBack = findViewById(R.id.moveBackButton);

    carLayout.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            toggleZoom();
        }
    });

    moveButton.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            moveCar();
        }
    });

    moveBack.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            moveCarBackward();
        }
    });
}

private void toggleZoom() {
    if (isZoomed) {
        zoomOut();
    } else {
        zoomIn();
    }
}

private void zoomIn() {
    carLayout.setScaleX(1.2f);
    carLayout.setScaleY(1.2f);
    isZoomed = true;
}

private void zoomOut() {
    carLayout.setScaleX(1f);
    carLayout.setScaleY(1f);
    isZoomed = false;
}
```

```

private void moveCar() {
    int start = currentPosition;
    int maxTranslation = getMaxTranslation();

    int end;
    if (isFlipped) {
        end = Math.max(start - 100, -maxTranslation);
    } else {
        end = Math.min(start + 100, maxTranslation);
    }

    ObjectAnimator animator;
    animator = ObjectAnimator.ofFloat(carLayout, "translationX", start, end);
    animator.setDuration(100);
    animator.start();

    currentPosition = end;
}

private int getMaxTranslation() {
    int screenWidth = getResources().getDisplayMetrics().widthPixels;
    int carWidth = (int) (200 * getResources().getDisplayMetrics().density);

    return (screenWidth - carWidth) / 2;
}

private void moveCarBackward() {
    ObjectAnimator rotationAnimator;
    int rotation;
    if (isFlipped == true) {
        rotation = 180;
        rotationAnimator = ObjectAnimator.ofFloat(carLayout, "rotationY", rotation,
0);
        isFlipped = false;
    } else {
        rotation = 0;
        rotationAnimator = ObjectAnimator.ofFloat(carLayout, "rotationY", rotation,
180);
        isFlipped = true;
    }
    rotationAnimator.setDuration(100);
    rotationAnimator.start();
}
}

```

- activity_main.xml

```

<?xml version="1.0" encoding="utf-8"?>
<FrameLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent" android:layout_height="match_parent">

```

```

<!-- Buttons for moving forward and backward -->

<RelativeLayout android:id="@+id/carLayout" android:layout_width="match_parent"
android:layout_height="match_parent">

    <ImageView android:id="@+id/car" android:layout_width="200dp"
android:layout_height="80dp" android:layout_marginLeft="100dp"
android:layout_marginTop="100dp" android:src="@drawable/car" />

    <ImageView android:id="@+id/carwin" android:layout_width="89dp"
android:layout_height="30dp" android:layout_marginLeft="190dp"
android:layout_marginTop="105dp" android:src="@drawable/carwin" />
    android:layout_marginTop="168dp"

    <ImageView android:id="@+id/rightWheel" android:layout_width="42dp"
android:layout_height="42dp" android:layout_marginLeft="248dp"
android:layout_marginTop="168dp" android:src="@drawable/carwheel" />

    <ImageView android:id="@+id/leftWheel" android:layout_width="42dp"
android:layout_height="42dp" android:layout_marginLeft="120dp"
android:layout_marginTop="168dp" android:src="@drawable/carwheel" />

</RelativeLayout>

<Button android:id="@+id/moveForwardButton" android:layout_width="55dp"
android:layout_height="wrap_content" android:layout_gravity="bottom|start"
android:layout_marginStart="20dp" android:layout_marginBottom="20dp" android:text="GO" />

<Button android:id="@+id/moveBackButton" android:layout_width="130dp"
android:layout_height="wrap_content" android:layout_gravity="bottom|end"
android:layout_marginEnd="20dp" android:layout_marginBottom="20dp" android:text="REVERSE"
/>

</FrameLayout>

```

```

<shape xmlns:android="http://schemas.android.com/apk/res/android"
android:shape="rectangle">
    <gradient android:drawable="@drawable/car_body_gradient" android:type="linear"
android:angle="0" />
    <solid android:color="#4444f4" />
    <size android:width="200dp" android:height="80dp" />
    <corners android:topRightRadius="90dp" />
</shape>

```

```


<shape xmlns:android="http://schemas.android.com/apk/res/android" android:shape="oval">
    <solid android:color="#000000" />
    <size android:width="42dp" android:height="42dp" />

```

```
</shape>
```

```
<shape xmlns:android="http://schemas.android.com/apk/res/android"  
android:shape="rectangle">  
    <solid android:color="#000000" />  
    <size android:width="160dp" android:height="60dp" />  
    <corners android:topRightRadius="70dp" />  
</shape>
```

Output:



GO


REVERSE



6:31



ex3



GO


REVERSE



6:31



ex3



GO


REVERSE



6:31



ex3



GO


REVERSE



6:31



ex3



GO

REVERSE



Result:

The mobile application was completed successfully

Best Practices:

1. Use meaningful variable names and comments to improve code readability.
2. Utilize XML layouts for defining the UI components to maintain consistency.
3. Organize code logically and use comments for better code maintenance.
4. Implement error handling to handle unexpected scenarios gracefully.
5. Ensure smooth user interactions and animations for a better user experience.
6. Follow Android coding conventions and design guidelines.

Learning Outcomes:

1. Designing Android user interfaces using XML layouts.
2. Implementing interactive elements like buttons and click event handling.
3. Performing animations using ObjectAnimator to enhance user experience.
4. Handling user interactions effectively within the app.
5. Utilizing XML shape resources to define drawable components.
6. Enhancing Java coding skills for Android app development.
7. Understanding and implementing best practices for Android app development.

SSN COLLEGE OF ENGINEERING, KALAVAKKAM
DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING
UCS1711 - MOBILE APPLICATION DEVELOPMENT LAB

Assignment 4

Name: Jayannthan P T

Dept: CSE 'A'

Roll No.: 205001049

Develop a Product information application in Android that enables to perform CRUD operations on data stored in SQLite Database.

In main activity display the following buttons: Create, Insert, Update, Delete, Retrieve, Retrieve All

1. On clicking Create Button, create a new database to store the Product details. (Use SQLite Database)
 - a. Product ID (Make this field as primary key)
 - b. Product Name
 - c. Product Brand
 - d. Description
 - e. Product Price
2. On Clicking Insert, move to a new view which contains the following details: (Insert new Product to the database)
 - a. Product ID (EditText-Validation checking- 4 digit Numbers)
 - b. Product Name (Spinner)
 - c. Product Brand (RadioButton)
 - d. Description (EditText-Alphanumeric characters)
 - e. Product Price (EditText-Validation checking Numbers)
 - f. Submit (Button) – On press, Insert the data into database.
3. On clicking Update, move to a new view which contains above details and Update Product Price using Product ID.
4. On clicking Delete, Delete the whole row in the table by Product ID.
5. On clicking Retrieve, Retrieve the product using Product ID.
6. On clicking Retrieve All, retrieve the details of all the products in a particular brand.

Title of the Program: Android Application Development using Database**Objective:**

The objective of the provided Android application is to manage a list of products. Users can perform various operations such as inserting new products, updating product prices, deleting products, searching for product details by ID, and viewing products grouped by brand.

Algorithm:

1. MainActivity:
 - Set up buttons for inserting, deleting, updating, searching, and viewing products.
 - On button click, navigate to the respective activities.
2. InsertActivity:
 - Provide input fields for product ID, name, brand, description, and price.
 - On the "INSERT" button click:
 - Validate user input.
 - Insert a new product into the database.
3. UpdateActivity:
 - Allow users to input a product ID and a new price.
 - On the "UPDATE" button click:
 - Validate user input.
 - Update the price of the specified product in the database.
4. DeleteActivity:
 - Allow users to input a product ID for deletion.
 - On the "DELETE" button click:
 - Validate user input.
 - Delete the specified product from the database.
5. SearchActivity:
 - Enable users to search for product details by entering a product ID.
 - On the "SEARCH" button click:
 - Retrieve and display product details if found.
6. ViewActivity:
 - Display a list of product brands in a ListView.
 - On selecting a brand:
 - Retrieve and display a list of products for that brand.
7. DatabaseHelper:
 - Manage the SQLite database for storing product information.
 - Define database schema and operations for creating, querying, updating, and deleting records.

Features used:

- Android activities for user interaction.
- SQLite database for data storage.
- Input validation for user data.

- Navigation between activities.
- ListView for displaying lists of items.
- Custom XML layouts for UI design.

Source code:

- MainActivity.java

```
package com.example.products;

import androidx.appcompat.app.AppCompatActivity;
import android.content.Intent;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

public class MainActivity extends AppCompatActivity {

    Button insertButton;
    Button deleteButton;
    Button updateButton;
    Button searchButton;
    Button viewButton;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        // Initialize buttons inside the onCreate method
        insertButton = findViewById(R.id.insert);
        deleteButton = findViewById(R.id.delete);
        updateButton = findViewById(R.id.update);
        searchButton = findViewById(R.id.search);
        viewButton = findViewById(R.id.view);

        insertButton.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                Intent intent = new Intent(MainActivity.this, InsertActivity.class);
                startActivity(intent);
            }
        });

        deleteButton.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View v) {
                Intent intent = new Intent(MainActivity.this, DeleteActivity.class);
                startActivity(intent);
            }
        });

        updateButton.setOnClickListener(new View.OnClickListener() {
```

```

        @Override
        public void onClick(View v) {
            Intent intent = new Intent(MainActivity.this, UpdateActivity.class);
            startActivity(intent);
        }
    });

    searchButton.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            Intent intent = new Intent(MainActivity.this, SearchActivity.class);
            startActivity(intent);
        }
    });

    viewButton.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            Intent intent = new Intent(MainActivity.this, ViewActivity.class);
            startActivity(intent);
        }
    });
}
}

```

- activity_main.xml

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools" android:layout_width="match_parent"
    android:layout_height="match_parent" tools:context=".MainActivity"
    tools:ignore="ExtraText">

    <TextView android:id="@+id/Heading" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="Product Database"
    app:layout_constraintBottom_toBottomOf="parent" app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintStart_toStartOf="parent" app:layout_constraintTop_toTopOf="parent"
    app:layout_constraintVertical_bias="0.06" android:textSize="35sp" />

    <Button android:id="@+id/insert" android:layout_width="122dp"
    android:layout_height="55dp" android:text="Insert"
    app:layout_constraintTop_toBottomOf="@+id/Heading"
    app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
    android:layout_marginTop="16dp" android:textSize="20sp" />

```



```

<Button android:id="@+id/delete" android:layout_width="122dp"
android:layout_height="55dp" android:text="Delete"
app:layout_constraintTop_toBottomOf="@+id/insert"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
android:layout_marginTop="16dp" android:textSize="20sp" />

<Button android:id="@+id/update" android:layout_width="122dp"
android:layout_height="55dp" android:text="Update"
app:layout_constraintTop_toBottomOf="@+id/delete"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
android:layout_marginTop="16dp" android:textSize="20sp" />

<Button android:id="@+id/search" android:layout_width="122dp"
android:layout_height="55dp" android:text="Search"
app:layout_constraintTop_toBottomOf="@+id/update"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
android:layout_marginTop="16dp" android:textSize="20sp" />

<Button android:id="@+id/view" android:layout_width="122dp"
android:layout_height="55dp" android:text="View"
app:layout_constraintTop_toBottomOf="@+id/search"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
android:layout_marginTop="16dp" android:textSize="20sp" />

</androidx.constraintlayout.widget.ConstraintLayout>

```

- InsertActivity.java

```

package com.example.products;

import android.content.ContentValues;
import android.database.sqlite.SQLiteDatabase;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;
import android.widget.Toast;
import androidx.appcompat.app.AppCompatActivity;

public class InsertActivity extends AppCompatActivity {

    private EditText productIdEditText, productNameEditText, productBrandEditText,
    productDescriptionEditText, productPriceEditText;
    private Button submitButton;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.insert);

        // Initialize UI elements
        productIdEditText = findViewById(R.id.id);
    }
}

```

```

        productNameEditText = findViewById(R.id.name);
        productBrandEditText = findViewById(R.id.brand);
        productDescriptionEditText = findViewById(R.id.desc);
        productPriceEditText = findViewById(R.id.price);
        submitButton = findViewById(R.id.submit);

        // Set click listener for the Submit button
        submitButton.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View view) {
                // Get user input
                String productId = productIdEditText.getText().toString();
                String productName = productNameEditText.getText().toString();
                String productBrand = productBrandEditText.getText().toString();
                String productDescription =
productDescriptionEditText.getText().toString();
                String productPriceStr = productPriceEditText.getText().toString();

                // Check if any of the fields are empty
                if (productId.isEmpty() || productName.isEmpty() || productBrand.isEmpty()
|| productDescription.isEmpty() || productPriceStr.isEmpty()) {
                    Toast.makeText(InsertActivity.this, "Please fill in all fields",
Toast.LENGTH_SHORT).show();
                    return;
                }

                // Convert product price to double
                double productPrice = Double.parseDouble(productPriceStr);

                // Insert data into the database
                insertProduct(productId, productName, productBrand, productDescription,
productPrice);

                // Show success message
                Toast.makeText(InsertActivity.this, "Product inserted successfully",
Toast.LENGTH_SHORT).show();

                // Clear input fields
                productIdEditText.getText().clear();
                productNameEditText.getText().clear();
                productBrandEditText.getText().clear();
                productDescriptionEditText.getText().clear();
                productPriceEditText.getText().clear();
            }
        });
    }

    private void insertProduct(String productId, String productName, String productBrand,
String productDescription, double productPrice) {
        // Create or open the database for writing
        DatabaseHelper dbHelper = new DatabaseHelper(this);
        SQLiteDatabase db = dbHelper.getWritableDatabase();

        // Create a new map of values, where column names are the keys

```

```

        ContentValues values = new ContentValues();
        values.put(DatabaseContract.ProductEntry.COLUMN_PRODUCT_ID, productId);
        values.put(DatabaseContract.ProductEntry.COLUMN_PRODUCT_NAME, productName);
        values.put(DatabaseContract.ProductEntry.COLUMN_PRODUCT_BRAND, productBrand);
        values.put(DatabaseContract.ProductEntry.COLUMN_PRODUCT_DESCRIPTION,
productDescription);
        values.put(DatabaseContract.ProductEntry.COLUMN_PRODUCT_PRICE, productPrice);

        // Insert the new row, returning the primary key value of the new row
        long newRowId = db.insert(DatabaseContract.ProductEntry.TABLE_NAME, null, values);

        // Close the database
        db.close();
    }
}

```

- Insert.xml

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools" android:id="@+id/linearLayout"
android:layout_width="match_parent" android:layout_height="match_parent">

    <TextView android:id="@+id/Heading" android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Insert" android:textSize="35sp"
app:layout_constraintBottom_toBottomOf="parent" app:layout_constraintEnd_toEndOf="parent"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintTop_toTopOf="parent"
app:layout_constraintVertical_bias="0.06" />

    <TableLayout android:layout_width="0dp" android:layout_height="0dp"
app:layout_constraintTop_toBottomOf="@+id/Heading"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
app:layout_constraintBottom_toBottomOf="parent" android:layout_marginTop="16dp">

        <!-- First Row -->
        <TableRow android:layout_height="wrap_content">
            <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product ID" android:gravity="center" />

            <EditText android:id="@+id/id" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
        </TableRow>

        <!-- Second Row -->
        <TableRow android:layout_height="wrap_content">
            <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Name" android:gravity="center" />

```

```

        <EditText android:id="@+id/name" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
    </TableRow>

    <!-- Third Row (and so on) -->
    <TableRow android:layout_height="wrap_content">
        <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Brand" android:gravity="center" />

        <EditText android:id="@+id/brand" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
    </TableRow>

    <TableRow android:layout_height="wrap_content">
        <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Description" android:gravity="center" />

        <EditText android:id="@+id/desc" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
    </TableRow>

    <TableRow android:layout_height="wrap_content">
        <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Price" android:gravity="center" />

        <EditText android:id="@+id/price" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="numberDecimal" android:text="" />
    </TableRow>

    <TableRow android:layout_height="wrap_content">
        <Button android:id="@+id/submit" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:text="INSERT"
android:background="@color/black" android:textColor="@color/white"/>
    </TableRow>
</TableLayout>
</androidx.constraintlayout.widget.ConstraintLayout>

```

- UpdateActivity.java

```

package com.example.products;

import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;
import android.widget.Toast;

```

```

import androidx.appcompat.app.AppCompatActivity;

public class UpdateActivity extends AppCompatActivity {

    private EditText productIdEditText;
    private EditText newPriceEditText;
    private Button updateButton;
    private DatabaseHelper dbHelper;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.update);

        productIdEditText = findViewById(R.id.id);
        newPriceEditText = findViewById(R.id.price);
        updateButton = findViewById(R.id.submit);
        dbHelper = new DatabaseHelper(this);

        updateButton.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View view) {
                // Get the product ID and new price from the EditText fields
                String productIdText = productIdEditText.getText().toString().trim();
                String newPriceText = newPriceEditText.getText().toString().trim();

                if (productIdText.isEmpty() || newPriceText.isEmpty()) {
                    // Product ID or new price field is empty, show an error message
                    Toast.makeText(UpdateActivity.this, "Product ID and new price are
required", Toast.LENGTH_SHORT)
                        .show();
                } else {
                    try {
                        // Parse the product ID and new price as needed (integer and
double)

                        int productId = Integer.parseInt(productIdText);
                        double newPrice = Double.parseDouble(newPriceText);

                        // Update the product price in the database
                        boolean isUpdated = dbHelper.updateProductPrice(productId,
newPrice);

                        if (isUpdated) {
                            // Show a success message
                            Toast.makeText(UpdateActivity.this, "Price updated
successfully", Toast.LENGTH_SHORT)
                                .show();
                        } else {
                            // Show an error message if the update failed
                            Toast.makeText(UpdateActivity.this, "Failed to update price.
Product not found.",
                                Toast.LENGTH_SHORT).show();
                        }
                    }
                }
            }
        });
    }
}

```

```

        // Clear the EditText fields
        productIdEditText.setText("");
        newPriceEditText.setText("");
    } catch (NumberFormatException e) {
        // Handle invalid input (non-integer or non-double)
        Toast.makeText(UpdateActivity.this, "Invalid Product ID or new
price", Toast.LENGTH_SHORT)
            .show();
    }
}
});
}
}
}

```

- update.xml

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools" android:id="@+id/linearLayout"
    android:layout_width="match_parent" android:layout_height="match_parent">

    <TextView android:id="@+id/Heading" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="Update" android:textSize="35sp"
    app:layout_constraintBottom_toBottomOf="parent" app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintStart_toStartOf="parent" app:layout_constraintTop_toTopOf="parent"
    app:layout_constraintVertical_bias="0.06" />

    <TableLayout android:id="@+id/searchTable" android:layout_width="0dp"
    android:layout_height="wrap_content" app:layout_constraintTop_toBottomOf="@+id/Heading"
    app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
    android:layout_marginTop="16dp">

        <!-- Row for Product ID Search -->
        <TableRow android:layout_height="wrap_content">
            <TextView android:layout_width="0dp" android:layout_height="wrap_content"
            android:layout_weight="1" android:text="Product ID" android:gravity="center" />

            <EditText android:id="@+id/id" android:layout_width="0dp"
            android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
            android:inputType="text" android:text="" />
        </TableRow>

        <TableRow android:layout_height="wrap_content">
            <TextView android:layout_width="0dp" android:layout_height="wrap_content"
            android:layout_weight="1" android:text="Product Price" android:gravity="center" />

            <EditText android:id="@+id/price" android:layout_width="0dp"
            android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
            android:inputType="numberDecimal" android:text="" />
        </TableRow>
    </TableLayout>

```

```

        </TableRow>
        <TableRow android:layout_height="wrap_content">
            <Button android:id="@+id/submit" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:text="UPDATE PRICE"
android:background="@color/black" android:textColor="@color/white"
app:layout_constraintTop_toBottomOf="@id/price" />
        </TableRow>

    </TableLayout>
</androidx.constraintlayout.widget.ConstraintLayout>

```

- DeleteActivity.java

```

package com.example.products;

import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;
import android.widget.Toast;

import androidx.appcompat.app.AppCompatActivity;

public class DeleteActivity extends AppCompatActivity {

    private EditText productIdEditText;
    private Button deleteButton;
    private DatabaseHelper dbHelper;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.delete);

        productIdEditText = findViewById(R.id.id);
        deleteButton = findViewById(R.id.submit);
        dbHelper = new DatabaseHelper(this);

        deleteButton.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View view) {
                // Get the product ID from the EditText
                String productIdText = productIdEditText.getText().toString().trim();

                if (productIdText.isEmpty()) {
                    // Product ID field is empty, show an error message
                    Toast.makeText(DeleteActivity.this, "Product ID is required",
Toast.LENGTH_SHORT).show();
                } else {
                    try {
                        // Parse the product ID as an integer

```

```

        int productId = Integer.parseInt(productIdText);

        // Attempt to delete the product by ID
        boolean isDeleted = dbHelper.deleteProductById(productId);

        if (isDeleted) {
            // Product deleted successfully
            Toast.makeText(DeleteActivity.this, "Product deleted
successfully", Toast.LENGTH_SHORT).show();

            // Clear the product ID EditText
            productIdEditText.setText("");
        } else {
            // Product not found, show an error message
            Toast.makeText(DeleteActivity.this, "Product not found for
deletion", Toast.LENGTH_SHORT).show();
        }
    } catch (NumberFormatException e) {
        // Handle invalid input (non-integer)
        Toast.makeText(DeleteActivity.this, "Invalid Product ID",
Toast.LENGTH_SHORT).show();
    }
}

});
}
}

```

- delete.xml

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools" android:id="@+id/linearLayout"
    android:layout_width="match_parent" android:layout_height="match_parent">

    <TextView android:id="@+id/Heading" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="Delete" android:textSize="35sp"
    app:layout_constraintBottom_toBottomOf="parent" app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintStart_toStartOf="parent" app:layout_constraintTop_toTopOf="parent"
    app:layout_constraintVertical_bias="0.06" />

    <TableLayout android:id="@+id/searchTable" android:layout_width="0dp"
    android:layout_height="wrap_content" app:layout_constraintTop_toBottomOf="@+id/Heading"
    app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
    android:layout_marginTop="16dp">

        <!-- Row for Product ID Search -->
        <TableRow android:layout_height="wrap_content">

```



```

        <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product ID" android:gravity="center" />

        <EditText android:id="@+id/id" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
    </TableRow>

    <TableRow android:layout_height="wrap_content">
        <Button android:id="@+id/submit" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:text="DELETE"
android:background="@color/black" android:textColor="@color/white"
app:layout_constraintTop_toBottomOf="@id/id" />
    </TableRow>
</TableLayout>
</androidx.constraintlayout.widget.ConstraintLayout>

```

- SearchActivity.java

```

package com.example.products;

import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import android.widget.EditText;
import android.widget.TableLayout;
import android.widget.TextView;
import android.widget.Toast;

import androidx.appcompat.app.AppCompatActivity;

public class SearchActivity extends AppCompatActivity {

    private EditText productIdEditText;
    private TableLayout outputTable;
    private TextView nameTextView;
    private TextView brandTextView;
    private TextView descriptionTextView;
    private TextView priceTextView;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.search);

        // Initialize UI elements
        productIdEditText = findViewById(R.id.id);
        outputTable = findViewById(R.id.outputTable);
        nameTextView = findViewById(R.id.name);
        brandTextView = findViewById(R.id.brand);
        descriptionTextView = findViewById(R.id.desc);
        priceTextView = findViewById(R.id.price);
    }
}

```

```

        Button searchButton = findViewById(R.id.submit);

        searchButton.setOnClickListener(new View.OnClickListener() {
            @Override
            public void onClick(View view) {
                searchProduct();
            }
        });
    }

    private void searchProduct() {
        // Get the product ID entered by the user
        String productIdText = productIdEditText.getText().toString();

        if (productIdText.isEmpty()) {
            // Product ID field is empty, show an error message or handle it as needed
            Toast.makeText(this, "Please enter a Product ID", Toast.LENGTH_SHORT).show();
            return;
        }

        int productId = Integer.parseInt(productIdText);

        // Use the DatabaseHelper to search for the product by ID
        DatabaseHelper databaseHelper = new DatabaseHelper(this);
        Product product = databaseHelper.searchProductById(productId);

        if (product != null) {
            // Display the product information in the outputTable
            nameTextView.setText(product.getName());
            brandTextView.setText(product.getBrand());
            descriptionTextView.setText(product.getDescription());
            priceTextView.setText(String.valueOf(product.getPrice()));

            // Make the outputTable visible
            outputTable.setVisibility(View.VISIBLE);
        } else {
            // Product not found, you can display an error message or handle it as needed
            Toast.makeText(this, "Product not found", Toast.LENGTH_SHORT).show();

            // For now, let's hide the outputTable
            outputTable.setVisibility(View.GONE);
        }
    }
}

```

- search.xml

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"

```

```

xmlns:app="http://schemas.android.com/apk/res-auto"
xmlns:tools="http://schemas.android.com/tools" android:id="@+id/linearLayout"
android:layout_width="match_parent" android:layout_height="match_parent">

    <!-- Heading TextView -->
    <TextView android:id="@+id/Heading" android:layout_width="wrap_content"
android:layout_height="wrap_content" android:text="Search" android:textSize="35sp"
app:layout_constraintBottom_toBottomOf="parent" app:layout_constraintEnd_toEndOf="parent"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintTop_toTopOf="parent"
app:layout_constraintVertical_bias="0.06" />

    <TableLayout android:id="@+id/searchTable" android:layout_width="0dp"
android:layout_height="wrap_content" app:layout_constraintTop_toBottomOf="@+id/Heading"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
android:layout_marginTop="16dp">

        <!-- Row for Product ID Search -->
        <TableRow android:layout_height="wrap_content">
            <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product ID" android:gravity="center" />

            <EditText android:id="@+id/id" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
        </TableRow>

        <!-- Row for Search Button -->
        <TableRow android:layout_height="wrap_content">
            <Button android:id="@+id/submit" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:text="Search"
android:background="@color/black" android:textColor="@color/white"
app:layout_constraintTop_toBottomOf="@id/id" />
        </TableRow>
    </TableLayout>

    <TableLayout android:id="@+id/outputTable" android:layout_width="0dp"
android:layout_height="0dp" app:layout_constraintTop_toBottomOf="@+id/searchTable"
app:layout_constraintStart_toStartOf="parent" app:layout_constraintEnd_toEndOf="parent"
app:layout_constraintBottom_toBottomOf="parent" android:layout_marginTop="16dp"
android:visibility="gone">

        <TableRow android:layout_height="wrap_content">
            <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Name" android:gravity="center" />

            <EditText android:id="@+id/name" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
        </TableRow>

        <TableRow android:layout_height="wrap_content">
            <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Brand" android:gravity="center" />

```

```

        <EditText android:id="@+id/brand" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
    </TableRow>

    <TableRow android:layout_height="wrap_content">
        <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Description" android:gravity="center" />

        <EditText android:id="@+id/desc" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="text" android:text="" />
    </TableRow>

    <TableRow android:layout_height="wrap_content">
        <TextView android:layout_width="0dp" android:layout_height="wrap_content"
android:layout_weight="1" android:text="Product Price" android:gravity="center" />

        <EditText android:id="@+id/price" android:layout_width="0dp"
android:layout_height="wrap_content" android:layout_weight="1" android:ems="10"
android:inputType="numberDecimal" android:text="" />
    </TableRow>
</TableLayout>
</androidx.constraintlayout.widget.ConstraintLayout>

```

- ViewActivity.java

```

package com.example.products;

import android.os.Bundle;

import androidx.appcompat.app.AppCompatActivity;

import android.view.ViewGroup;
import android.widget.AdapterView;
import android.widget.AdapterView.OnItemClickListener;
import android.widget.ArrayAdapter;
import android.widget.LinearLayout;
import android.widget.ListView;
import android.widget.TextView;
import java.util.List;

public class ViewActivity extends AppCompatActivity {
    private DatabaseHelper databaseHelper;
    private LinearLayout rightSideLayout;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.view);

        ListView brandListView = findViewById(R.id.brandListView);
    }
}

```

```

rightSideLayout = findViewById(R.id.rightSideLayout);

databaseHelper = new DatabaseHelper(this);

List<String> brandList = databaseHelper.getBrandList();

ArrayAdapter<String> adapter = new ArrayAdapter<>(this,
android.R.layout.simple_list_item_1, brandList);

brandListView.setAdapter(adapter);

brandListView.setOnItemClickListener(new AdapterView.OnItemClickListener() {
    @Override
    public void onItemClick(AdapterView<?> parent, android.view.View view, int
position, long id) {
        String selectedBrand = brandList.get(position);

        List<Product> productList =
databaseHelper.getProductsByBrand(selectedBrand);

        // Clear the existing product information
        rightSideLayout.removeAllViews();

        // ...

        if (!productList.isEmpty()) {
            for (Product product : productList) {
                // Create a TextView for each product
                TextView productTextView = new TextView(ViewActivity.this);
                productTextView.setLayoutParams(new ViewGroup.LayoutParams(
                    ViewGroup.LayoutParams.MATCH_PARENT,
                    ViewGroup.LayoutParams.WRAP_CONTENT // Set height to
wrap_content

                ));
                productTextView.setText("Product ID: " + product.getId() + "\n" +
                    "Product Name: " + product.getName() + "\n" +
                    "Product Price: " + product.getPrice());

                // Add the TextView to the rightSideLayout
                rightSideLayout.addView(productTextView);

                // Add space (spacer TextView)
                TextView spacer = new TextView(ViewActivity.this);
                spacer.setLayoutParams(new ViewGroup.LayoutParams(
                    ViewGroup.LayoutParams.MATCH_PARENT,
                    50

                ));
                rightSideLayout.addView(spacer);
            }
        } else {
            // Display a message if no products are available for the selected
brand

            TextView noProductsTextView = new TextView(ViewActivity.this);
            noProductsTextView.setLayoutParams(new ViewGroup.LayoutParams(

```

```

        ViewGroup.LayoutParams.MATCH_PARENT,
        ViewGroup.LayoutParams.WRAP_CONTENT
    ));
    noProductsTextView.setText("No products available for this brand.");

    // Add the message to the rightSideLayout
    rightSideLayout.addView(noProductsTextView);
}

}

});
}
}
}

```

- view.xml

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.core.widget.NestedScrollView
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools" android:id="@+id/linearLayout"
    android:layout_width="match_parent" android:layout_height="match_parent">

    <LinearLayout android:layout_width="match_parent" android:layout_height="wrap_content"
    android:orientation="vertical">

        <!-- Heading TextView -->
        <TextView android:id="@+id/Heading" android:layout_width="wrap_content"
    android:layout_height="wrap_content" android:text="View" android:textSize="35sp"
    android:layout_gravity="center" android:layout_marginTop="16dp"
    android:layout_marginBottom="16dp" />

        <LinearLayout android:layout_width="match_parent" android:layout_height="600dp"
    android:orientation="horizontal">

            <!-- Left side: List of Brands -->
            <ListView android:id="@+id/brandListView" android:layout_width="0dp"
    android:layout_height="wrap_content" android:layout_weight="1"
    android:divider="@android:color/darker_gray" android:dividerHeight="1dp" />

            <View android:layout_width="1dp" android:layout_height="match_parent"
    android:background="@android:color/darker_gray" />

            <LinearLayout android:id="@+id/rightSideLayout" android:layout_width="0dp"
    android:layout_height="wrap_content" android:orientation="vertical"
    android:layout_weight="1">

                </LinearLayout>
            </LinearLayout>
        </LinearLayout>
    </LinearLayout>

```

```
        </LinearLayout>
    </LinearLayout>
</androidx.core.widget.NestedScrollView>
```

- DatabaseHelper.java

```
// DatabaseHelper.java
package com.example.products;

import android.content.ContentValues;
import android.content.Context;
import android.database.Cursor;
import android.database.sqlite.SQLiteDatabase;
import android.database.sqlite.SQLiteOpenHelper;
import android.util.Log;

import java.util.ArrayList;
import java.util.List;

public class DatabaseHelper extends SQLiteOpenHelper {
    private static final String DATABASE_NAME = "products";
    private static final int DATABASE_VERSION = 1;

    public static final String TABLE_NAME = "products";

    public static final String COLUMN_PRODUCT_ID = "product_id";
    public static final String COLUMN_PRODUCT_NAME = "product_name";
    public static final String COLUMN_PRODUCT_BRAND = "product_brand";
    public static final String COLUMN_PRODUCT_DESCRIPTION = "product_description";
    public static final String COLUMN_PRODUCT_PRICE = "product_price";

    private static final String SQL_CREATE_PRODUCT_TABLE =
        "CREATE TABLE " + TABLE_NAME + " (" +
            COLUMN_PRODUCT_ID + " INTEGER PRIMARY KEY AUTOINCREMENT," +
            COLUMN_PRODUCT_NAME + " TEXT," +
            COLUMN_PRODUCT_BRAND + " TEXT," +
            COLUMN_PRODUCT_DESCRIPTION + " TEXT," +
            COLUMN_PRODUCT_PRICE + " REAL)";

    private static final String SQL_DELETE_PRODUCT_TABLE =
        "DROP TABLE IF EXISTS " + TABLE_NAME;

    public DatabaseHelper(Context context) {
        super(context, DATABASE_NAME, null, DATABASE_VERSION);
    }

    @Override
    public void onCreate(SQLiteDatabase db) {
        db.execSQL(SQL_CREATE_PRODUCT_TABLE);
    }
}
```

```

@Override
public void onUpgrade(SQLiteDatabase db, int oldVersion, int newVersion) {
    db.execSQL(SQL_DELETE_PRODUCT_TABLE);
    onCreate(db);
}

public Product searchProductById(int productId) {
    SQLiteDatabase db = this.getReadableDatabase();

    String[] projection = {
        COLUMN_PRODUCT_NAME,
        COLUMN_PRODUCT_BRAND,
        COLUMN_PRODUCT_DESCRIPTION,
        COLUMN_PRODUCT_PRICE
    };

    String selection = COLUMN_PRODUCT_ID + " = ?";
    String[] selectionArgs = {String.valueOf(productId)};

    Cursor cursor = db.query(
        TABLE_NAME,
        projection,
        selection,
        selectionArgs,
        null,
        null,
        null
    );

    Product product = null;
    if (cursor != null && cursor.moveToFirst()) {
        String name =
cursor.getString(cursor.getColumnIndexOrThrow(COLUMN_PRODUCT_NAME));
        String brand =
cursor.getString(cursor.getColumnIndexOrThrow(COLUMN_PRODUCT_BRAND));
        String description =
cursor.getString(cursor.getColumnIndexOrThrow(COLUMN_PRODUCT_DESCRIPTION));
        double price =
cursor.getDouble(cursor.getColumnIndexOrThrow(COLUMN_PRODUCT_PRICE));

        product = new Product(productId, name, brand, description, price);
        cursor.close();
    }

    db.close();
    return product;
}

public boolean deleteProductById(int productId) {
    SQLiteDatabase db = this.getWritableDatabase();
    String whereClause = COLUMN_PRODUCT_ID + " = ?";
    String[] whereArgs = {String.valueOf(productId)};

    int rowsDeleted = db.delete(TABLE_NAME, whereClause, whereArgs);
}

```



```

        // Close the database
        db.close();

        // Check if any rows were deleted (deletion successful)
        return rowsDeleted > 0;
    }

    public boolean updateProductPrice(int productId, double newPrice) {
        SQLiteDatabase db = this.getWritableDatabase();

        ContentValues values = new ContentValues();
        values.put(COLUMN_PRODUCT_PRICE, newPrice);

        String whereClause = COLUMN_PRODUCT_ID + " = ?";
        String[] whereArgs = {String.valueOf(productId)};

        int rowsUpdated = db.update(TABLE_NAME, values, whereClause, whereArgs);

        // Close the database
        db.close();

        // Check if any rows were updated (update successful)
        return rowsUpdated > 0;
    }

    public List<String> getBrandList() {
        List<String> brandList = new ArrayList<>();
        SQLiteDatabase db = this.getReadableDatabase();

        // SQL query to select distinct brands
        String query = "SELECT DISTINCT " + COLUMN_PRODUCT_BRAND + " FROM " + TABLE_NAME;

        Cursor cursor = db.rawQuery(query, null);

        if (cursor != null && cursor.moveToFirst()) {
            do {
                String brand = cursor.getString(0); // 0 is the column index for brand
                brandList.add(brand);
                Log.d("DatabaseHelper", "Brand: " + brand); // Add this line for debugging
            } while (cursor.moveToNext());

            cursor.close();
        }

        db.close();
        return brandList;
    }

    // Add a method to select all items in a brand
    public List<Product> getProductsByBrand(String brandName) {
        List<Product> productList = new ArrayList<>();
        SQLiteDatabase db = this.getReadableDatabase();

        String[] projection = {

```

```

        COLUMN_PRODUCT_ID,
        COLUMN_PRODUCT_NAME,
        COLUMN_PRODUCT_PRICE
    };

    String selection = COLUMN_PRODUCT_BRAND + " = ?";
    String[] selectionArgs = {brandName};

    Cursor cursor = db.query(
        TABLE_NAME,
        projection,
        selection,
        selectionArgs,
        null,
        null,
        null
    );

    if (cursor != null && cursor.moveToFirst()) {
        do {
            int productId =
cursor.getInt(cursor.getColumnIndexOrThrow(COLUMN_PRODUCT_ID));
            String name =
cursor.getString(cursor.getColumnIndexOrThrow(COLUMN_PRODUCT_NAME));
            double price =
cursor.getDouble(cursor.getColumnIndexOrThrow(COLUMN_PRODUCT_PRICE));

            Product product = new Product(productId, name, brandName, null, price);
            productList.add(product);
        } while (cursor.moveToNext());

        cursor.close();
    }

    db.close();
    return productList;
}
}

```

- DatabaseContract.java

```

// DatabaseContract.java
package com.example.products;

import android.provider.BaseColumns;

public final class DatabaseContract {

    private DatabaseContract() {}

    public static class ProductEntry implements BaseColumns {
        public static final String TABLE_NAME = "products";
    }
}

```

```

        public static final String COLUMN_PRODUCT_ID = "product_id";
        public static final String COLUMN_PRODUCT_NAME = "product_name";
        public static final String COLUMN_PRODUCT_BRAND = "product_brand";
        public static final String COLUMN_PRODUCT_DESCRIPTION = "product_description";
        public static final String COLUMN_PRODUCT_PRICE = "product_price";
    }
}

```

- Product.java

```

// Product.java
package com.example.products;

public class Product {
    private int id;
    private String name;
    private String brand;
    private String description;
    private double price;

    public Product(int id, String name, String brand, String description, double price) {
        this.id = id;
        this.name = name;
        this.brand = brand;
        this.description = description;
        this.price = price;
    }

    public int getId() {
        return id;
    }

    public String getName() {
        return name;
    }

    public String getBrand() {
        return brand;
    }

    public String getDescription() {
        return description;
    }

    public double getPrice() {
        return price;
    }
}

```

Output:

9:31

2.00 KB/s 5G 47%

Delete

Product ID 001

DELETE



9:30

7.00 KB/s 5G 47%

Search

Product ID 001

Search

Product Name Mouse

Product Brand Dell

Product Description mouse

Product Price 250.0

9:31

  0.03 KB/S VoLTE 5G 47% 



Search

Product ID

Search

Product Name Product Brand Product Description Product Price

9:30

  0.33 KB/S VoLTE 5G 47% 

Update

Product ID Product Price

UPDATE PRICE

1

2

3

-

4



Price updated successfully



7

8

9



,

0

.



9:31

0.30 KB/S 5G 47%

Search

Product ID 001

Search

Product not found

9:31

2.00 KB/S 5G 47%

Update

Product ID 001

Product Price 600

UPDATE PRICE

1

2

3

-

4

5

6

_

7

8

9



✖

,

0

.

✓



Result:

The mobile application was completed successfully

Best Practices:

- Using SQLite for local data storage.
- Input validation to ensure data integrity.
- Separation of concerns by using different activities for various operations.
- Reusable database helper class.

Learning Outcomes:

- Creating and managing Android activities.
- Working with SQLite databases in Android.
- Implementing input validation in Android applications.
- Navigating between different activities.
- Designing user interfaces with XML layout files.
- Handling user input and performing database operations.