

31/01/23

HTML

HTML - Hyper text Markup language.

- It is a method where ordinary text can be converted into hyper text, it is a set of special code included to control the layout and appearance of text.

- HTML is not a programming language, it combines instructions with data to tell a displayed program called browser to render the data that the document contains.

- The content can be pictures, text, sound, video clips.

- It delivers the content to multiple platforms.

History of HTML :-

- Tim Berner's Lee is specified HTML and Role and server software in the part of 1990

- The first publicly available version of HTML was document called L tags, first mentioned on the internet by Berner's Lee 1990.

- It describes 20 elements comprising the initial simple design of HTML.

- HTML is a subset of SGML (Standard Generalized Markup Language). SGML originated in 1960's at IBM to overcome the problems in moving the documents across the multiple hardware platforms, operating system.

Structure of HTML:-

- HTML generally has two parts which have on-code, off-code, which contains the text to be defined.

Syntax:-

<tagname> </tagname>

Skeleton of HTML document:-

```
<HTML>
<Head>                                </body>
<Title>
</Title>                             </HTML>
</Head>
<Body>
```

- In every html document `<html>` and `</html>` are used to mark the beginning and end of the document.

- These tags inform the browser that the document is an html file.

- All other tags must reside within the HTML tags.

- The html document can be divided into two sections:

Section 1 :- Head

Section 2 :- Body

Section 1 :- Head:-

- HTML includes a pair of tags `<head>` and `</head>` to identify the heading of the document.

- The tag `<Title>` and `</Title>` can appear in this section.

- The text that exists between the title tag appears as the title in the browser window and it should not exceed 60 characters.

Body Section

Section 2:- Body

- The body section is enclosed within `<body>` and `</body>` tags.

- It gives the description of documents layout and structure.

- Features should be kept in mind while writing html documents.

- Each tag is enclosed within a left bracket and right bracket, these special characters are which differentiate the tags from ordinary text.

- Opening is denoted by greater or less than `<>`

for eg:- `<b>` it display the text in bold style.

- Closing tag is denoted by `</>`
for eg:- `</b>` is a closing tag of bold tag.

- Tag names are not a case sensitive but generally they are written

in appearance to differentiate them from normal text.

Heading tags:

- The heading tags are used to display the headings on webpages in various sizes.

- These tags can be used for providing main headings and sub headings in web pages.

- HTML documents supports 6 Level of headings :- $\langle H1 \rangle$ to $\langle H6 \rangle$

- The size of the text within the largest and $\langle H6 \rangle$ & the smallest

$\langle H1 \rangle$

$\langle H2 \rangle$

$\langle H3 \rangle$

⋮

$\langle H6 \rangle$

4/1/23.

Paragraph tag :- $\langle p \rangle$

- To organize a text into paragraphs $\langle p \rangle$ and $\langle /p \rangle$.

- Normally in text documents paragraphs appear with blank lines on the top and bottom.

- It default display a blank line both on top and bottom of the paragraph.

Attribute for paragraph

- Align attribute :- Align attribute of $\langle p \rangle$ is used to align the paragraph on the webpage.

Syntax: $\langle p \text{ align} = \text{"value"} \rangle$

- The possible values are RIGHT, LEFT, CENTER.

- Instead of align = center attribute $\langle center \rangle$ and $\langle /center \rangle$ tag

- Size Attribute:

font tag is used to specify the size attribute of the text.

Syntax:

```
<FONT size="value">  
sample text  
</FONT>
```

- The possible values are 1, 2, 3, and so on. when we specify font size = '1' then the text will be displayed in 1 font size is the size in 2 it will be displayed as 3 is 12pt, 4 is 14pt and so on.

- Color Attribute:

color attribute of the font tag is used to specify the color of the text.

Syntax:

Sample text

.

Eg:

Sample text

.

• The variety of colors available, the colors either by the name or by using the corresponding hexadecimal value.

The following table gives the color name and corresponding hexadecimal value.

Color	Hexadecimal value
Red	# FF 00
Green	# 00 FF 00
Blue	# 00 00 FF
White	# FF FF FF
Black	# 00 00 00.

Grey	# 808080.
Dark Red	# 800000.
Dark Green	# 008000.
Dark blue	# 000080.
Yellow	# FFFF00.
Magenta	# FF00FF.
Cyan	# 00FFFF.
Pink	# FFC0CB.
Orange	# FFA500.
Brown	# 8B4513.
Neon	# FF00FF.

Write a HTML code incorporating
font break
 <P> and
its attributes.

• <Division tag <DIV> :-

<DIV> Division tag is used for applying alignment and style characteristics to only a section of a document.

Syntax:-

<DIV align = "value"

Sample text
</DIV>

• The possible values for <DIV> tag are right, left and center similar to an paragraph.

Eg: <HTML>

<DIV align = "right" >

<H1> Aligning the block of content to the right </H1>.

<P> We can use the <div> tag to align a block of content to the right </div>

<P> the content can include
tables images list and so on

</DIV>

</HTML>

Pre-formatted tag :

• It is used to display
a block of pre-formatted text including all
the spaces and formatting the ~~pre~~

The primary use of <PRE>
tag is to display the text into
a tabular or columnar format in
which the columns remain properly
align.

Eg: <HTML>

<HEAD>

<TITLE>

Sales details of
2022.

</TITLE>

</HEAD>

<BODY>

<PRE>

```
Sales Details of 2022
      Jan   Feb   Mar   Apr
XXX   10,000 10,000 18,000 30,000
YYY
ZZZ
```

</PRE>

</BODY>

</HTML>

Creating list:

• Headings and paragraph text elements are most commonly used than list.

• Many web pages are a collection of hypertext links.

• There are two types

list namely:

- * ordered
- * Unordered.

• An ordered list is a number list and unordered list is a bulleted list.

Ordered list tag:

• Ordered list defines sequentially number list of items.

• It is used along with the tag which defines list item.

eg:- <HTML>

<HEAD>

<HEAD>

<TITLE>

eg of ordered list

</TITLE>

</HEAD>

<BODY>

 MA

 WD

 DM

 R.

output :

1. MA

2. WD

3. PT

4. R.

 does not have the tag for the is implied

Unordered list :

Unordered List defines a bulleted list of items, the item is nested inside the tag

Eg:

<HTML>

<HEAD>

<TITLE>

Eg of Unordered List

<HEAD>

<TITLE>

<BODY>

 MA

 WD

 PT

 R

</BODY>

</HTML>

output:-

• MA

• WD

• PT

• R