

# Speech Command Model

Pradeep Moturi (es16btech11016)

May 2020

# Contents

1	Introduction	
2	Create Data	
3	Loading Data	
4	Split dataset	
5	Augment data	
6	Feature Extraction	
7	Building Model	
7.1	Concept . . . . .	3
7.2	Hyper parameters . . . . .	3
7.3	Notations . . . . .	3
7.4	Math . . . . .	3
8	Training	
9	Testing	
10	Visualize Attention	
11	Observations	
12	Files	
13	Further	

## 1 Introduction

This is the report of my work done under Dr. G V V Sharma on building a speech command recognition model for a voice bot. The model used is based on concepts of Convolution, LSTM and Attention and is derived from [1].

## 2 Create Data

1. Set 16KHz as sampling rate
2. Record 80 utterances of each command.
3. Trim each utterance to one second.
4. Save samples of each command in different folders  
Dataset/forward  
Dataset/back  
Dataset/left  
Dataset/right  
Dataset/stop

Used Audacity to do this.

## 3 Loading Data

- 2 I've used soundfile package to read the .wav. You may choose to use any other package like wavefile, librosa etc to do the same job.
- 2 As this is one of the slowest part, I've stored the loaded data as a numpy file for ease and speed of access. Now, I can load the data from npy file if repeating the experiment.

## 4 Split dataset

- 2 Do a stratified split of the dataset into train and test set with 20% as test samples.
- 2 Set a random seed for reproducing the split.

## 5 Augment data

- 4 Augment each audio sample by time shifting in 25000 length vectors filled with zeros.
- 4 Take steps of 500 to create 18 files per sample

## 6 Feature Extraction

MFCCs are most prominent features used in audio processing. Normalizing the MFCCs over the frequency axis is found to reduce effect of noise. Kapre is a python package that provides layers for audio processing that are compatible with keras and utilize GPU for faster processing. Kapre provides us with a layer basically

```
Melspectrogram (padding='same', sr=16000,
n_mels=39, n_dft = 1024, power_melgram=2.0,
return_decibel_melgram=True, trainable_fb=False,
trainable_kernel=False, name='mel_stft')
```

### Arguments to the layer

**padding:** Padding when convoluting

**sr:** Sampling rate of audio provided

**n\_mels:** number of coefficients to return

**n\_dft:** width

**power\_melgram:** exponent to raise log-mel-amplitudes before taking DCT. Using power 2 is shown to increase performance by reducing effect of noise

**return\_decibel\_melgram:** If to return log over values

**trainable\_fb:** If filter bank trainable

**trainable\_kernel:** If the kernel is trainable

## 7 Building Model

### 7.1 Concept

1. Using Convolutional layers ahead of LSTM is shown to improve performance in several research papers.
2. BatchNormalization layers are added to improve convergence rate.
3. Using Bidirectional LSTM is optimal when complete input is available. But this increases the runtime two-fold.
4. Final output sequence of LSTM layer is used to calculate importance of units in LSTM using a FC layer.
5. Then take the dot product of unit importance and output sequences of LSTM to get Attention scores of each time step.
6. Take the dot product of Attention scores and the output sequences of LSTM to get attention vector.
7. Add an additional FC Layer and then to output Layer with SoftMax Activation.

### 7.2 Hyper parameters

- **sparse\_categorical\_crossentropy** is used as **Loss** because only output which should be 1 is given instead of One Hot Encoding.
- **sparse\_categorical\_accuracy** is used as performance **Metric** for the above reason.
- **Adam** is used as **Optimizer**. Adam is adaptive learning rate optimization algorithm. This is shown to achieve a faster convergence because of having all the features of other optimization algorithms.

### 7.3 Notations

#### Operators:

- $\times$  indicate matrix multiplication
- $*$  denote convolution (0 padding to same size)
- $.$  denote dot product
- $+, -$  can expand dimensions of their arguments

#### Format:

Layer Name ( Layer Type ) (Output Size).

#### Parameters

#### Equations

#### Output

= equation

Layer name indicates output of the corresponding layer.

Let us understand the maths behind the model.

### 7.4 Math

You can have an overall look at the architecture of the model in Fig [5]. Lets observe the math in each layer below.

0. Input (InputLayer) (49, 39, 1)
1. Conv1 (Conv2D) (49, 39, 10)  
**Parameters:**  
Kernel = (5, 1, 1, 10), Bias = (10)  
**Conv1[:, :, i]**  
$$= \text{Kernel}[:, :, :, i] * \text{Input} + \text{Bias}[i]$$
2. BN1 (BatchNormalization) (49, 39, 10)  
**Parameters:**  
Trainable:  $\gamma = (10)$ ,  $\beta = (10)$ ,  
Non-Trainable: Mean = (10), Std = (10)  
**Equations:**  
$$\text{Mean}[i] = \text{mean}(\text{Conv1}[:, :, i])$$
$$\text{Std}[i] = \text{std}(\text{Conv1}[:, :, i])$$
**BN1[i]**  
$$= (\text{Conv1}[:, :, i] - \text{Mean}[i]) \frac{\gamma[i]}{\text{Std}[i]} + \beta[i]$$
3. Conv2 (Conv2D) (49, 39, 1)  
**Parameters:**  
Kernel = (5, 1, 10, 1), Bias = (1)  
**Conv2[:, :, 1]**  
$$= \text{Kernel}[:, :, :, 1] * \text{BN1} + \text{Bias}$$
4. BN2 (BatchNormalization) (49, 39, 1)  
**Parameters:**  
Trainable:  $\gamma = (1)$ ,  $\beta = (1)$ ,  
Non-Trainable: Mean = (1), Std = (1)  
**Equations:**  
$$\text{Mean}[i] = \text{mean}(\text{Conv2}[:, :, i])$$
$$\text{Std}[i] = \text{std}(\text{Conv2}[:, :, i])$$
**BN2[i]**  
$$= (\text{Conv2}[:, :, i] - \text{Mean}[i]) \frac{\gamma[i]}{\text{Std}[i]} + \beta[i]$$
5. Squeeze (Reshape) (49, 39)  
**Squeeze**  
$$= \text{BN2.reshape}(49, 39)$$
6. LSTM.Sequences (LSTM) (49, 64)  
**Parameters:**  
$$U^i = U^f = U^o = U^g = (39, 64),$$
$$W^i = W^f = W^o = W^g = (64, 64),$$
$$B^i = B^f = B^o = B^g = (64)$$
**Equations:**  
$$i_t = \sigma(\text{Squeeze}[:, t] \times U^i + h_{t-1} \times W^i + B^i)$$
$$f_t = \sigma(\text{Squeeze}[:, t] \times U^f + h_{t-1} \times W^f + B^f)$$
$$o_t = \sigma(\text{Squeeze}[:, t] \times U^o + h_{t-1} \times W^o + B^o)$$

$\tilde{C}_t = \tanh(\text{Squeeze}[:, t] \times U^g + h_{t-1} \times W^g + B^g)$   
 $C_t = \sigma(f_t * C_{t-1} + i_t * \tilde{C}_t)$   
 $h_t = \tanh(C_t) * o_t$   
**LSTM\_Sequences[t]**  
 $= h_t$

7. FinalSequence (Lambda) (64)

**FinalSequence**

$= \text{LSTM\_Sequences}[-1, :]$

8. UnitImportance (Dense) (64)

**Parameters:**

Weights = (64,64), Bias = (64)

**UnitImportance**

$= \text{Weights} \times \text{FinalSequence} + \text{Bias}$

9. AttentionScores (Dot) (49)

**AttentionScores[i]**

$= \text{UnitImportance.LSTM\_Sequences}[i, :]$

10. AttentionSoftmax (Softmax) (49)

**AttentionSoftmax[i]**

$= \frac{\exp(\text{AttentionScores}[i])}{\sum_j \exp(\text{AttentionScores}[j])}$

11. AttentionVector (Dot) (64)

**AttentionVector[i]**

$= \text{AttentionSoftmax.LSTM\_Sequences}[:, i]$

12. FC (Dense) (32)

**Parameters:**

Weights = (64,64), Bias = (64)

**FC**

$= \text{Weights} \times \text{AttentionVector} + \text{Bias}$

13. Output (Dense) (5)

**Parameters:**

Weights = (32,5), Bias = (5)

**Output**

$= \text{SoftMax}(\text{Weights} \times \text{FC} + \text{Bias})$

After an input passes through the layers, the training happens by principle of Back Propagating Loss or Gradients calculated by Sparse Categorical Cross-Entropy and updating weights using the Adam Optimizer update equations.

## 8 Training

- Batch size around 15 is found optimal.
- Often convergence is achieved in less than 5 epochs.

## 9 Testing

1. Augment the test set same as training set.
2. Extract MFCCs using same method as training set

3. Test set is passed as validation set to fit method of model.
4. The performance of model on test set is calculated after every epoch.

## 10 Visualize Attention

1. Now build a sub model from the trained model. Take same input layer but add 'AttentionSoftmax' layer as additional output layer.
2. Pass MFCCs of test samples to predict method.
3. Now plot log of Attention Scores and corresponding input vector before taking MFCCs on different axes.
4. By looking at Fig [1] and Fig [2], We observe that Attention Scores are high on informative part.




Figure 1: Attention Scores




Figure 2: Raw sample

## 11 Observations

- Smaller batch size is preferable

- Setting `power_melgram=2` of Melspectrogram gave faster convergence.

## 12 Files

- `Src/DataGenerator.py`: Augments the data
- `Src/FeatureExtractor.py`: Extracts MFCC coefficients
- `Src/TrainModel.py`: Trains model and saves it in h5 file
- `ColabNotebook.ipynb`: Use this for experimental purpose

## 13 Further

- Different augmentation techniques like adding noise, changing pitch, speed etc. [<https://medium.com/@makcedward/data-augmentation-for-audio-76912b01fdf6>]
- Given the low complexity of our dataset, We can replace LSTM with GRU which is little less complex but shown to outperform LSTM in many scenarios.
- We can change the arguments to Melspectrogram
- Changing the model architecture like layers and units in layers.
- Further the scope of project to check performance on Google's Speech Command Datasets (v1 and v2) and participate in Kaggle challenge by google [<https://www.kaggle.com/c/tensorflow-speech-recognition-challenge/>]

## References

- [1] Douglas Coimbra de Andrade, Sabato Leo, Martin Loesener Da Silva Viana, Christoph Bernkopf. *A neural attention model for speech command recognition.*




Figure 3: Data Flow Diagram




Figure 4: Model Diagram

Model: "Attention"

Layer (type)	Output Shape	Param #	Connected to
Input (InputLayer)	[(None, 49, 39, 1)]	0	
Conv1 (Conv2D)	(None, 49, 39, 10)	60	Input[0][0]
BN1 (BatchNormalization)	(None, 49, 39, 10)	40	Conv1[0][0]
Conv2 (Conv2D)	(None, 49, 39, 1)	51	BN1[0][0]
BN2 (BatchNormalization)	(None, 49, 39, 1)	4	Conv2[0][0]
Squeeze (Reshape)	(None, 49, 39)	0	BN2[0][0]
LSTM_Sequences (LSTM)	(None, 49, 64)	26624	Squeeze[0][0]
FinalSequence (Lambda)	(None, 64)	0	LSTM_Sequences[0][0]
UnitImportance (Dense)	(None, 64)	4160	FinalSequence[0][0]
AttentionScores (Dot)	(None, 49)	0	UnitImportance[0][0] LSTM_Sequences[0][0]
AttentionSoftmax (Softmax)	(None, 49)	0	AttentionScores[0][0]
AttentionVector (Dot)	(None, 64)	0	AttentionSoftmax[0][0] LSTM_Sequences[0][0]
FC (Dense)	(None, 32)	2080	AttentionVector[0][0]
Output (Dense)	(None, 5)	165	FC[0][0]
Total params: 33,184			
Trainable params: 33,162			
Non-trainable params: 22			

Figure 5: Model Architecture