



Started on	Thursday, 24 September 2026, 11:33 AM
State	Finished
Completed on	Thursday, 24 September 2026, 11:34 AM
Time taken	1 min 16 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int n, k, i, j;
5
6      scanf("%d", &n);
7
8      int a[n];
9
10     for (i = 0; i < n; i++)
11         scanf("%d", &a[i]);
12
13     scanf("%d", &k);
14
15     for (i = 0; i < n; i++) {
16         for (j = i + 1; j < n; j++) {
17             if (a[j] - a[i] == k) {
18                 printf("1");
19                 return 0;
20             }
21         }
22     }
23
24     printf("0");
25
26     return 0;
27 }
28

```

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Jayashna A H 251801112-2025-AIDS ▾

J2

Started on	Thursday, 24 September 2026, 11:11 AM
State	Finished
Completed on	Thursday, 24 September 2026, 11:20 AM
Time taken	8 mins 40 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[j] - A[i] = k$, $i \neq j$.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as $5 - 1 = 4$

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```

1  |
2  | #include <stdio.h>
3  |
4  | int main() {
5  |     int n, k, i, j;
6  |
7  |     scanf("%d", &n);
8  |
9  |     int a[n];
10 |
11 |     for (i = 0; i < n; i++)
12 |         scanf("%d", &a[i]);
13 |
14 |     scanf("%d", &k);
15 |
16 |     for (i = 0; i < n; i++) {
17 |         for (j = i + 1; j < n; j++) {
18 |             if (a[j] - a[i] == k) {
19 |                 printf("1");
20 |                 return 0;
21 |             }
22 |         }
23 |     }
24 |
25 |     printf("0");
26 |
27 |     return 0;
28 | }
```

	Input	Expected	Got	
✓	3 1 3 5 4	1	1	✓
✓	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✓
✓	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✓
✓	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Jayashna A H 251801112-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 11:10 AM**State** Finished**Completed on** Thursday, 24 September 2026, 11:11 AM**Time taken** 1 min 1 sec**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

```
1
3 10 17 57
6 2 7 10 15 57 246
```

Output:

```
10 57
```

Input:

```
1
6 1 2 3 4 5 6
2 1 6
```

Output:

```
1 6
```

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 int main() {
4     int T, n1, n2, i, j;
5
6     scanf("%d", &T);
7
8     while (T--) {
9         scanf("%d", &n1);
10
11         int a[n1];
12
13         for (i = 0; i < n1; i++)
14             scanf("%d", &a[i]);
15     }
```

```
15
16     scanf("%d", &n2);
17
18     int b[n2];
19
20     for (i = 0; i < n2; i++)
21         scanf("%d", &b[i]);
22
23     for (i = 0; i < n1; i++) {
24         for (j = 0; j < n2; j++) {
25             if (a[i] == b[j]) {
26                 printf("%d ", a[i]);
27                 break;
28             }
29         }
30     }
31
32     printf("\n");
33 }
34
35 return 0;
36 }
```

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Jayashna A H 251801112-2025-AIDS ▾

J2

Started on Thursday, 24 September 2026, 11:00 AM**State** Finished**Completed on** Thursday, 24 September 2026, 11:10 AM**Time taken** 10 mins 5 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

```
1
3 10 17 57
6 2 7 10 15 57 246
```

Output:

```
10 57
```

Input:

```
1
6 1 2 3 4 5 6
2 1 6
```

Output:

```
1 6
```

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 int main() {
4     int T, n1, n2, i, j;
5
6     scanf("%d", &T);
7
8     while (T--) {
9         scanf("%d", &n1);
10
11         int a[n1];
12
13         for (i = 0; i < n1; i++)
14             scanf("%d", &a[i]);
15     }
```

```
15
16     scanf("%d", &n2);
17
18     int b[n2];
19
20     for (i = 0; i < n2; i++)
21         scanf("%d", &b[i]);
22
23     for (i = 0; i < n1; i++) {
24         for (j = 0; j < n2; j++) {
25             if (a[i] == b[j]) {
26                 printf("%d ", a[i]);
27                 break;
28             }
29         }
30     }
31
32     printf("\n");
33 }
34
35 return 0;
36 }
```

	Input	Expected	Got	
✓	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✓
✓	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Started on	Thursday, 24 September 2026, 10:50 AM
State	Finished
Completed on	Thursday, 24 September 2026, 10:59 AM
Time taken	9 mins 21 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```

1  |
2  | #include <stdio.h>
3  |
4  | int main() {
5  |     int n, i, j;
6  |
7  |     scanf("%d", &n);
8  |
9  |     int a[n];
10 |
11 |     // Read array
12 |     for (i = 0; i < n; i++) {
13 |         scanf("%d", &a[i]);
14 |     }
15 |
16 |     // Find duplicate
17 |     for (i = 0; i < n; i++) {
18 |         for (j = i + 1; j < n; j++) {
19 |             if (a[i] == a[j]) {
20 |                 printf("%d", a[i]);
21 |                 return 0;
22 |             }
23 |         }
24 |     }
25 |
26 |     return 0;
27 | }
28 |
29 |

```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓

	Input	Expected	Got	
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



Started on	Thursday, 24 September 2026, 10:41 AM
State	Finished
Completed on	Thursday, 24 September 2026, 10:49 AM
Time taken	7 mins 39 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1

Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5	1
1 1 2 3 4	

Answer: (penalty regime: 0 %)

```
1  #include <stdio.h>
2
3  int main() {
4      int n, i, j;
5
6      scanf("%d", &n);
7
8      int a[n];
9
10     for (i = 0; i < n; i++)
11         scanf("%d", &a[i]);
12
13     for (i = 0; i < n; i++) {
14         for (j = i + 1; j < n; j++) {
15             if (a[i] == a[j]) {
16                 printf("%d", a[i]);
17                 return 0;
18             }
19         }
20     }
21
22     return 0;
23 }
```

	Input	Expected	Got	
✓	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✓
✓	5 1 2 3 4 4	4	4	✓
✓	5 1 1 2 3 4	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)