PRODUCT SPECIFICATION • VERSION 1.0

Make My Marriage

Product Requirements Document

A family-centered wedding planning workspace for organizing events, guests, expenses, vendors, invitations, and shared memories.

Document detail	Value
Product	Make My Marriage
Version	1.0 - V1 scope
Status	Implementation baseline / portfolio project
Date	20 October 2026
Primary platform	Responsive web application
Initial architecture	React + TypeScript, Java Spring Boot, PostgreSQL

Guiding idea: one shared wedding workspace, with the right people able to plan together and guests able to participate simply.

DOCUMENT GUIDE

Contents

Section	Topic
01	Product overview and goals
02	Personas, roles, and access
03	Scope and product principles
04	Functional requirements
05	Key user workflows
06	Screens and navigation
07	Data model
08	Technical architecture and API
09	Non-functional requirements
10	Acceptance criteria
11	Delivery milestones
12	Out of scope, assumptions, and risks
13	Definition of Done

Scope anchor V1 is a focused, responsive web app. It does not include AI features, automated WhatsApp Business messaging, vendor bookings, payment processing, or a custom livestream platform.

1. Product overview and goals

Make My Marriage helps a couple and their families coordinate wedding planning in one place instead of spreading tasks and information across messages, spreadsheets, and multiple apps.

1.1 Problem statement

Wedding planning involves many related activities: events and timelines, shared checklists, guest lists, invitation follow-ups, vendor research, spending, photo collection, and livestream information. Family organizers need a common source of truth, while guests need a simple way to RSVP and share photos without being given organizer-level access.

1.2 Product vision

Provide a practical, welcoming workspace for an Indian wedding, configurable for different traditions and ceremonies, while keeping the first release small enough to build, test, and demonstrate as a portfolio project.

1.3 V1 goals

- Let a couple create and manage one wedding workspace together.
- Let authorized family members help with planning through role-based access.
- Track events, tasks, guest responses, and expenses in a shared dashboard.
- Send email invitations and prepare WhatsApp messages for manual sending.
- Help users discover vendors by category and city without handling bookings.
- Collect guest photos through a QR-linked upload flow with moderation.
- Store a YouTube livestream link against an event and show an embed or safe external link.
- Provide three polished visual themes and a settings area.

1.4 Success measures for a demo

Measure	V1 target / evidence
Workspace setup	A couple can create a wedding and invite the other partner.
Planning utility	Events, tasks, expenses, and guest records can be created, edited, and viewed by authorized users.
Invitation journey	Email invitation can be sent; WhatsApp invitation opens a prefilled message for the user to send.
Guest participation	An invited guest can RSVP to an event and upload a photo using an approved link or QR code.
Governance	Unauthorized API calls are denied; photo uploads stay pending until moderated.
Responsive experience	Core flows work on desktop and common mobile viewport sizes.

2. Personas, roles, and access

Access is intentionally simple in V1. Authorization must be enforced by the backend for every protected resource, not only by hiding buttons in the UI.

Role	Typical user	Permissions in V1
Admin	Bride and groom	Full wedding-workspace control: workspace settings, members, events, tasks, expenses, guests, invitations, vendor saves, livestream links, and photo moderation.
Manager	Authorized family organizer	Help maintain planning information: events, tasks, guest list, invitations, expenses, and photo moderation when granted. Cannot change ownership or sensitive workspace-wide settings.
Guest	Invited guest with free account	View the event information shared with them, RSVP to their invited events, and upload photos through valid event/album upload access. No access to private expenses, organizer notes, or other guests' private details.

2.1 Account and membership rule

V1 rule One account belongs to one wedding workspace in V1. Bride and groom share the same workspace; family managers and guests join that wedding through an invitation or controlled onboarding flow. Multi-wedding memberships are out of scope for the first release.

2.2 Access-control rules

- A user must be authenticated to access private workspace information.
- Each wedding-owned record must be scoped to the correct wedding ID.
- The backend verifies both membership and role before read/write actions.
- Guest access is limited to invited events and allowed participation actions.
- Membership revocation takes effect on subsequent requests and active tokens/sessions must not preserve revoked access indefinitely.
- Public QR upload links must be random, hard to guess, revocable, and scoped to one event or album.

3. Scope and product principles

3.1 In-scope for V1

- Authentication and password recovery.
- Wedding workspace creation and membership.
- Dashboard and event/checklist planning.
- Expense tracking with total, paid, and outstanding amounts; no budget cap.
- Guest list, household grouping, invitations, and event-specific RSVP.
- Vendor directory searchable by category and city; favorites/saved vendors.
- Photo albums, QR/link uploads, and moderation.
- YouTube livestream link/eligible embed on an event.
- Three predefined themes: Traditional Gold, Pastel Floral, and Royal Elegance.
- Workspace settings, profile/settings area, and basic notifications.

3.2 Product principles

- One source of truth: planning records are shared inside the wedding workspace.

- Privacy first: guests see only what they need; expenses and organizer-only data remain private.
- Mobile-aware: guests often use a phone to RSVP or upload photos.
- Configurable traditions: ceremonies and events are user-created rather than hard-coded to one regional tradition.
- Modular monolith: keep the backend maintainable without the operational overhead of microservices.
- Use hosted services where sensible: email provider, object storage, and YouTube; do not recreate these systems in V1.

4. Functional requirements

“Must have” identifies a requirement needed for the V1 product journey. Optional items may be deferred if time is limited, provided the core journey remains coherent.

FR-01 Authentication and account *[Must have]*

Users can register, log in, log out, and recover access using a secure password-reset flow.

- Store passwords using a modern adaptive one-way password hash; never store plaintext passwords.
- Validate email and password inputs on both client and server.
- Protect APIs with Spring Security and use a consistent authentication/session strategy.
- Rate-limit or otherwise protect sensitive login and reset endpoints; avoid revealing whether an account exists.

FR-02 Wedding workspace setup *[Must have]*

An Admin can create a wedding workspace with its name, couple names, primary city, date or date range, and selected theme.

- The creating user becomes an Admin.
- The second partner can be invited to join as Admin.
- Workspace data is isolated from other weddings.
- The wedding date and event dates are configurable; V1 must not assume a single ceremony.

FR-03 Dashboard *[Must have]*

Display a helpful overview of the wedding plan and its current state.

- Show upcoming events, tasks due soon or overdue, RSVP summary, and expense totals.
- Provide clear navigation to the main planning areas.
- Show empty states and calls to action for a newly created workspace.

FR-04 Events and checklist *[Must have]*

Authorized organizers can create, edit, view, and archive events and tasks.

- Event fields include title, description, date/time, venue/location, event type, visibility, and optional livestream URL.
- Tasks include title, optional description, due date, status, assignee, and related event.
- Support custom ceremonies and event types instead of hard-coded regional assumptions.
- Allow filtering or grouping tasks by event and status.

FR-05 Expense tracking *[Must have]*

Authorized organizers can record expenses and payments without imposing a budget cap.

- Expense fields include title/category, vendor or payee, total amount, amount paid, due date, notes, and optional event association.
- Outstanding amount = total amount - amount paid; validate that amounts are not negative and paid does not exceed total unless an explicit refund model is added later.
- Use a decimal-safe numeric type for money; never use binary floating point for financial values.

- Dashboard reports total expenses, total paid, and outstanding amount. Currency is set or selected for the wedding.

FR-06 Guest management *[Must have]*

Organizers can manage guests and household/grouping information.

- Capture name, contact details as appropriate, household/group, and notes visible only to organizers.
- Support invitation status and event-level invite selection.
- Provide search and basic filters for guest list management.
- Collect only necessary personal information and keep organizer notes private.

FR-07 Invitations and RSVP *[Must have]*

Organizers can invite guests by email and generate a WhatsApp click-to-chat message. Guests can RSVP per event.

- Email invitations are sent through a configured email delivery service.
- WhatsApp opens a prefilled message; the sender manually reviews and sends it. No automated WhatsApp Business API is included.
- Invitation records track channel, recipient, sent/created status, timestamps, and a secure invitation token or link where required.
- RSVP is event-specific and supports a clear response state (for example: attending, not attending, maybe / pending).
- Repeated actions should be idempotent or safely update the existing response rather than creating duplicates.

FR-08 Vendor discovery *[Must have]*

Users can browse and search a curated or seeded vendor directory.

- Search/filter by vendor category and city.
- Vendor details include business name, category, city/service area, description, contact method, and available external link(s).
- Authorized members can save/favorite vendors for the wedding workspace.
- No vendor booking, contract workflow, lead marketplace, or payments are included.

FR-09 Photo gallery and QR upload *[Must have]*

Guests can upload wedding photos using a QR-linked web flow without receiving organizer permissions.

- Organizers can create an album or event-specific upload link and render a QR code for it.
- Upload tokens are scoped, revocable, and have optional expiry/limits.
- Uploaded media is stored in object storage; database stores metadata and object references, not the image bytes.
- New uploads are pending by default; an Admin or authorized Manager approves or rejects them.
- Validate file type and size; use generated object names; prevent executable content from being served as active content.
- Only approved photos appear in the shared gallery.

FR-10 YouTube livestream *[Must have]*

An Admin can associate a YouTube livestream URL with an event.

- Render an embedded player only when the URL is eligible and embedding is permitted.
- If the embed cannot be shown, display a safe external YouTube link.
- Do not store or distribute stream credentials; the product does not host video.

FR-11 Themes *[Must have]*

Users can choose among three preset visual themes.

- Traditional Gold: maroon and gold.
- Pastel Floral: blush and soft green.
- Royal Elegance: jewel tones.
- Theme choice changes visual tokens (color, selected decorative accents) without changing authorization or data behavior.

FR-12 Settings and privacy *[Must have]*

Users can manage personal settings and authorized Admins can manage wedding settings.

- Personal area: profile details and account/security actions.
- Wedding settings: wedding details, theme, currency, and membership controls for Admins.
- Allow authorized users to revoke members and upload links.
- Provide clear logout and account-access behavior.

FR-13 Notifications and auditability *[Should have]*

Provide basic useful notifications and record important sensitive actions.

- Notify relevant users of invitation/RSVP activity where appropriate.
- Record key actions such as role changes, member revocation, expense edits, photo moderation, and settings changes.
- Audit records should include actor, action, entity/reference, timestamp, and enough context for troubleshooting without logging secrets.

5. Key user workflows

5.1 Create a wedding workspace

1. User registers and verifies/validates their account as required by the chosen auth flow.
2. User creates a wedding workspace and becomes its Admin.
3. User enters basic wedding details and selects one of the three themes.
4. Admin invites the partner as Admin and family helpers as Managers.
5. Dashboard loads with clear empty states and next-step suggestions.

5.2 Plan events and track expenses

6. Admin or Manager adds events and ceremony details.
7. Organizer adds tasks, due dates, and optional assignments to events.
8. Organizer records expenses and payment amounts.
9. Dashboard totals update from persisted records and display paid/outstanding amounts.

5.3 Invite a guest and capture RSVP

10. Organizer creates/updates a guest record and selects the event(s) to which the guest is invited.
11. For email, the system sends an invitation with a secure event-specific link. For WhatsApp, the app opens a prefilled message for manual sending.
12. Guest signs in or creates a free account, then opens the invitation and responds to the relevant event.
13. Organizer sees updated RSVP status in the guest/event view.

5.4 Upload and moderate photos

14. Organizer creates an album/upload link and generates a QR code.
15. Guest scans the code on a phone and opens the upload page.
16. Guest selects and uploads allowed image files.
17. Photo metadata is saved; uploaded file is stored in object storage and marked pending review.
18. An Admin or authorized Manager approves/rejects it; only approved images appear in the gallery.

5.5 Add a livestream

19. Admin opens an event and adds a YouTube URL.
20. Application validates/normalizes the URL and stores it against the event.
21. Event page shows an allowed embed or a fallback external link to YouTube.

6. Screens and navigation

Navigation should remain consistent across desktop and mobile. Mobile can use a compact menu while preserving access to the same core sections.

Screen / area	Primary content and actions
Authentication	Register, login, logout, password recovery.
Wedding setup	Wedding name/details, date/city, theme selection, invite partner.
Dashboard	Upcoming events, task status, RSVP summary, expense summary, shortcuts.
Events & checklist	Event list/detail, create/edit event, related tasks, due dates, assignees.
Expenses	Expense list, create/edit expense, payment amount, paid and outstanding summaries.
Guests & invitations	Guest list, household grouping, event invite selection, email/WhatsApp actions, RSVP status.
Vendor discovery	Search/filter vendors, vendor detail, save/favorite list.
Photo gallery	Albums, approved photos, moderation queue, QR/link generation and revocation.
Livestream	Event livestream block, embedded player where allowed, fallback link.
Settings	Profile, wedding details, theme, currency, member/role management, logout.

6.1 Theme behavior

Theme	Visual direction
Traditional Gold	Maroon, warm gold, cream neutrals; festive but readable.
Pastel Floral	Blush, soft green, off-white; light and understated.
Royal Elegance	Jewel tones with restrained high-contrast accents; premium look.

All themes must preserve readable contrast, focus indicators, input states, error messages, and consistent component behavior.

7. Data model

The model below is a logical starting point. Exact columns, constraints, and indexes are to be finalized in Flyway migrations during implementation.

Entity / table	Purpose / key relationships
users	Account identity, email, password hash, account state, timestamps.

Entity / table	Purpose / key relationships
weddings	Workspace-level details, chosen theme, currency, city, date information, settings.
wedding_members	Join users to a wedding with role (ADMIN, MANAGER, GUEST), status, invited/accepted timestamps.
events	Wedding-scoped ceremonies or events, schedule, venue, visibility, livestream URL.
tasks	Wedding-scoped tasks; optionally linked to an event and assignee.
guest_households	Optional grouping for family/household records.
guests	Guest/contact records owned by a wedding; optional link to a registered user.
invitations	Guest/event invitation, channel, token/status, timestamps and delivery details.
rsvps	Event-specific response from a guest/account; constrain duplicates per invitee and event.
expenses	Expense and payment tracking with DECIMAL/NUMERIC amounts and optional event/vendor reference.
vendors	Directory profile, category, city/service area, contact details, external links.
saved_vendors	Link a wedding/member to a favorited vendor.
photo_albums	Wedding/event-scoped albums and visibility/moderation configuration.
photo_upload_links	Hashed/revocable upload token, album reference, expiry and usage limits.
photos	Album reference, object-storage key, uploader, metadata, moderation status and reviewer.
notifications	User-targeted notification records and read status.
audit_logs	Actor/action/entity/timestamp and structured context for sensitive changes.

7.1 Data integrity rules

- Use UUIDs or other non-sequential public identifiers for externally reachable tokens and resources as appropriate.
- Enforce foreign keys and useful uniqueness constraints (for example, one RSVP per guest/event where the model requires it).
- Include wedding_id on wedding-owned records or ensure an equivalent enforced parent path; validate workspace ownership on every request.
- Use DECIMAL/NUMERIC for money and explicit currency on workspace or expense records.
- Store upload token hashes rather than raw token values when feasible; never log raw invitation/upload secrets.
- Use created_at and updated_at timestamps consistently; define deletion/archive behavior for dependent records.

8. Technical architecture and API

8.1 Recommended V1 stack

Layer	Technology / decision
Frontend	React + TypeScript; responsive component system; React Testing Library for UI tests.
Backend	Java + Spring Boot; modular monolith organized by domain/feature.

Layer	Technology / decision
Security	Spring Security; secure password hashing; server-side role and workspace checks.
Database	PostgreSQL; schema migrations managed with Flyway.
Media	S3-compatible or equivalent object storage for photo bytes; database stores metadata and object keys.
Email	Configured transactional email provider; provider abstraction where practical.
Livestream	YouTube URL/embed integration; no video hosting.
Testing	JUnit, Spring integration tests, API/security tests, React Testing Library.
API versioning	REST endpoints under /api/v1; consistent request/response/error format.

8.2 Backend modules

- identity: registration, authentication, password recovery, profile.
- weddings: workspace lifecycle, membership, roles, settings.
- planning: events and tasks.
- finance: expenses and payment balances.
- guests: guest records, households, invitations, RSVP.
- vendors: directory search and favorites.
- media: upload links, photo metadata, moderation, gallery.
- notifications and audit: notifications and traceable sensitive actions.

8.3 API conventions

- Use resource-oriented REST endpoints under /api/v1.
- Use DTOs rather than exposing persistence entities directly.
- Validate inputs server-side and return consistent HTTP status codes and structured errors.
- Apply pagination/filtering to growing lists such as guests, expenses, vendors, and photos.
- Document endpoint contracts using OpenAPI/Swagger if available in the chosen setup.
- Derive the current user from authenticated server context; never trust a client-supplied role or wedding_id without authorization checks.

Area	Example endpoint shapes (illustrative)
Auth	POST /api/v1/auth/register; POST /api/v1/auth/login; POST /api/v1/auth/password/forgot
Wedding / members	POST /api/v1/weddings; GET /api/v1/weddings/current; POST /api/v1/weddings/current/members
Events / tasks	GET/POST /api/v1/events; GET/PATCH /api/v1/events/{eventId}; GET/POST /api/v1/tasks
Expenses	GET/POST /api/v1/expenses; PATCH /api/v1/expenses/{expenseId}
Guests / RSVP	GET/POST /api/v1/guests; POST /api/v1/invitations; PUT /api/v1/events/{eventId}/rsvp
Vendors	GET /api/v1/vendors?category=...&city=...; POST /api/v1/saved-vendors
Photos	POST /api/v1/photo-upload-links; POST /api/v1/photo-uploads; PATCH /api/v1/photos/{photoId}/moderation

Architecture guardrail Start as a modular monolith, not microservices. Keep domain boundaries clear so future extraction is possible only when justified by scale or operational need.

9. Non-functional requirements

Area	Requirement
Security	Enforce authorization on every protected backend operation; hash passwords; protect reset/invitation/upload tokens; validate uploaded files; use HTTPS in deployment.
Privacy	Minimize personal data; isolate wedding workspaces; restrict guest access; avoid exposing contact details or organizer notes publicly.
Reliability	Handle provider failures gracefully, especially email delivery, object storage, and YouTube embeds; show actionable errors and retry where safe.
Performance	Paginate lists; avoid loading full-resolution galleries by default; use thumbnails/optimized variants where practical.
Accessibility	Semantic controls, keyboard navigation, visible focus, labels, validation summaries, and sufficient color contrast.
Responsive design	Core organizer flows usable on desktop/tablet; RSVP and photo upload especially usable on mobile.
Maintainability	Feature-oriented packages, configuration through environment variables, migrations, automated tests, and documented setup.
Observability	Structured logs and useful error tracking; never log passwords, raw tokens, or sensitive payloads.
Data integrity	Validated currency/amounts, consistent timestamps, foreign keys, and transactions around multi-record operations.

9.1 Photo upload safeguards

- Allowlist file types and verify content rather than trusting only the extension.
- Set upload size limits and reject malformed or unsupported files.
- Use short-lived signed uploads or server-mediated upload with a strict authorization check.
- Keep pending images inaccessible from the public gallery until approved.
- Prevent token reuse where usage limits or expiry are configured; allow the organizer to revoke a link.

10. Acceptance criteria

ID	Area	Acceptance test
AC-01	Account and workspace	A new user can register, log in, create one wedding workspace, and reach the dashboard. A second partner can join as Admin.
AC-02	Roles	Admin, Manager, and Guest API access is differentiated; a Guest cannot read private expenses or perform organizer actions even by calling an API directly.

ID	Area	Acceptance test
AC-03	Planning	An authorized organizer can create/edit an event and its tasks; changes persist after refresh and are scoped to the correct wedding.
AC-04	Expenses	The app calculates paid and outstanding totals correctly; invalid negative values and inconsistent payments are rejected.
AC-05	Guest RSVP	A guest can access an invitation, respond for a specific event, and see their saved response; organizer view reflects it.
AC-06	Invitations	Email sends through the configured provider or returns a clear failure state. WhatsApp opens a prefilled message and does not claim to have sent it automatically.
AC-07	Vendor discovery	Category and city filters work; authorized users can save and remove a favorite vendor.
AC-08	Photo upload	A valid upload link/QR opens the upload flow; valid photo upload creates a pending record; invalid types/oversized files are rejected.
AC-09	Photo moderation	Only approved photos are visible in the shared gallery; review actions are permission-checked and auditable.
AC-10	Livestream	An event can store a YouTube URL and display an eligible embed or a functioning external fallback link.
AC-11	Themes and settings	All three themes are selectable and persist; theme choice does not bypass permissions or change underlying data.
AC-12	Responsive and tests	Core workflows pass on supported desktop/mobile widths and the automated test suite covers critical rules and security boundaries.

11. Delivery milestones

Milestones are capability-based rather than date-based; the schedule can be adjusted around available study and development time.

Milestone	Scope	Exit evidence
M1 - Foundation	Repository setup, frontend shell, Spring Boot skeleton, PostgreSQL, Flyway, environments, basic tests.	App runs locally; migration executes; health endpoint and first frontend route work.
M2 - Identity & workspace	Registration/login, security setup, roles, wedding creation, partner invitation/membership, workspace scoping.	Authenticated user can create a workspace; unauthorized access tests pass.
M3 - Core planning	Dashboard, events, tasks/checklists, expense CRUD and summary.	Core data persists; role checks and amount calculations tested.
M4 - Guests & invitations	Guest/household CRUD, event-specific invitations, RSVP, email delivery, WhatsApp click-to-chat.	End-to-end guest journey demonstrated; no automated WhatsApp sending implied.

Milestone	Scope	Exit evidence
M5 - Extend product	Vendor discovery/favorites, gallery and QR uploads, moderation, YouTube links, themes/settings.	Complete happy paths work; uploads remain private until approved.
M6 - Stabilize & demo	Responsive QA, validation, error states, accessibility pass, test automation, setup docs, demo data.	Acceptance criteria reviewed; clean local setup instructions; demo-ready walkthrough.

11.1 Suggested build order

- Make the database and backend authorization model reliable before implementing many screens.
- Complete one vertical slice at a time (UI → API → database → test).
- Use seed data for vendors and demo workspaces to avoid blocking on external vendor feeds.
- Integrate email and object storage behind small service interfaces so provider changes are contained.
- Defer polish to non-core screens until the create-workspace-to-RSVP journey works end to end.

12. Out of scope, assumptions, and risks

12.1 Explicitly out of scope for V1

- AI planning assistant, recommendations, or chat.
- Native iOS/Android applications.
- Multiple wedding workspaces per account.
- Automated WhatsApp Business API messages and delivery status.
- Payment gateway, money transfer, vendor deposits, or invoice settlement.
- Vendor booking/contract marketplace and booking management.
- Hotel, travel, transport, or seating-plan management.
- Custom theme editor; only three preset themes.
- Hosting livestream video or building streaming infrastructure.
- Advanced analytics, complex custom permission designer, and enterprise reporting.

12.2 Assumptions

- Email delivery requires configuration of a provider and verified sender/domain in the deployment environment.
- Photo uploads require an object-storage provider and a defined retention/storage policy.
- Vendor discovery may start with curated/seeded records; live integrations are not mandatory for V1.
- The app should support Indian wedding traditions by allowing custom events, not by enforcing one ceremony template.
- A guest needs an account for RSVP and uploads; public access is limited to scoped invitation/upload flows.

12.3 Risks and mitigations

Risk	Mitigation
Unauthorized cross-wedding access	Centralize workspace authorization; add negative integration tests for every sensitive resource family.
Photo abuse or unexpected files	File allowlist/size limits, pending moderation, revocable links, and secure object-storage permissions.
Invitation tokens leaked or reused	Use strong random tokens, store hashes where feasible, scope to event, support expiry/revocation, and avoid logging secrets.
Email provider configuration delays	Implement an email adapter, support local/dev mock mode, and show delivery status/failure clearly.

Risk	Mitigation
Scope becomes too large	Prioritize the core planning, guest RSVP, and secure workspace journey; defer nonessential integrations/polish.
Ambiguous guest visibility	Define private/public fields for each entity and write access rules before building the UI.

12.4 Decisions to revisit before production

- Whether one account should be allowed to attend multiple weddings in future; V1 restricts membership to one wedding workspace.
- Photo retention and deletion policy, consent wording, and handling of requests to remove images.
- Whether email verification is mandatory at registration or only before sending invitations.
- Final hosting provider, object-storage provider, email provider, monitoring, backups, and data residency requirements.
- Exact guest-facing visibility of event venue/details and whether a guest can update an RSVP until a cutoff time.

13. Definition of Done

A feature is considered complete when all applicable conditions below are met:

- The expected happy path works end to end in the UI, API, and database.
- Input validation and useful error states are implemented.
- Authorization is enforced server-side and negative access cases are tested.
- Database schema changes are versioned through Flyway migrations.
- Unit/integration tests cover core business rules and critical boundaries.
- UI tests cover important user interactions and empty/loading/error states where relevant.
- Responsive layout and keyboard/focus basics are checked.
- Logs do not contain passwords, secrets, raw tokens, or unnecessary personal data.
- Setup/configuration steps are documented and environment-specific secrets are externalized.
- Acceptance criteria are demonstrably met and the feature is included in the demo flow.

V1 release bar The most important demonstration is a secure end-to-end path: create a wedding workspace → invite collaborators → plan events and expenses → invite a guest → capture an event RSVP → collect and moderate a photo.

END OF DOCUMENT