

	CRANE INSPECTION & MAINTENANCE SERVICES A DIVISION OF AL-KHOBAR GATE INTERNATIONAL TRADING EST		
	INSPECTION CHECKLIST FOR BASE MOUNTED DRUM HOIST (WINCHES)		
	FRM.0601-1.16	Revision 01	Issue Date: 28/JAN/2021
	Prepared By Operations Manager	Reviewed & Approved By Managing Director	

REPORT NO	CIMS4609	DATE	2025-11-12
CLIENT	Sealand Maritime Group	INSPECTOR	Sonny De Guzman
LOCATION	DSV PICASSO, MARJAN FIELD	STICKER NO	31573
EQUIPMENT NO	Tooling Lars Winch-04757	EQUIP. SERIAL NO	11/04757
EQUIPMENT TYPE	TOOLING LARS WINCH	CAPACITY (SWL)	650 KG

S.N	ACCEPTANCE CRITERIA	PASS	FAIL	NA	REMARKS
1 RATINGS & MARKINGS					
1.1	Documentation is available	✓			
1.2	The winch rating is clearly marked	✓			
1.3	The following clearly marked: (a) drum size, consisting of barrel diameter, barrel length, and flange diameter; (b) rope diameter(s); (c) rope speed in meter per second at rated load on specified layer	✓			
1.4	Line pull ratings for each layer and a specified rope diameter are provided	✓			
2 CONSTRUCTION					
2.1	Cooling, power, and operational characteristics are provided to perform	✓			
2.2	The rope is anchored to the drum approved by manufacturer	✓			
2.3	Drum flanges extends a minimum of one-half rope diameter, but not less than 0.5 inches (13mm) above the top layer	✓			
2.4	Diameter of the drum provides first layer rope pitch diameter of not less than 15 times the nominal diameter of the rope	✓			
2.5	Mechanical holding device, other than brake, capable of holding the rated load	✓			
2.6	Each brake is equipped with at least one brake capable of holding not less than 125% of the rated load at the point where the brake is applied	✓			
2.7	Remote-operated winches is equipped with self-setting brake			✓	
2.8	Winch is allowed simultaneous underwind & overwind brake capable of holding 125% of the rated load in those directions	✓			
2.9	Means to control the drum speed when moving the load is provided	✓			

	CRANE INSPECTION & MAINTENANCE SERVICES A DIVISION OF AL-KHOBAR GATE INTERNATIONAL TRADING EST		
	INSPECTION CHECKLIST FOR BASE MOUNTED DRUM HOIST (WINCHES)		
	FRM.0601-1.16	Revision 01	Issue Date: 28/JAN/2021
	Prepared By Operations Manager	Reviewed & Approved By Managing Director	

S.N	ACCEPTANCE CRITERIA	PASS	FAIL	NA	REMARKS
2.10	Adjustments to compensate for wear in the braking system is provided	✓			
2.11	Guard(s) for exposed moving parts is provided	✓			
2.12	Guard(s) is capable of supporting the weight of a 200 lbs. (90 kg)	✓			
2.13	Rope size can withstand the minimum breaking force	✓			
2.14	Rope winch meets manufacturer or qualified person's recommendation	✓			
2.15	All controls are marked for identification of function and direction of the drum rotation	✓			
2.16	All winch controls are within reach of operator during the normal operating conditions	✓			
2.17	Electric motor-driven winches shall be provided with a device that will disconnect all motors from the power source in the event of a power failure			✓	
2.18	Remote operated winches shall function so that if the control signal becomes ineffective, winch motion shall stop			✓	
2.19	All prime mover controls shall return to neutral position when released	✓			
2.20	Engine-driven winches are provided with a clutch for disengaging power to winch			✓	
2.21	Lubrication points are accessible	✓			
3 INSPECTION CRITERIA					
3.1	Rope is properly spooled on drum	✓			
3.2	Control mechanisms are operating properly	✓			
3.3	Limit switches are properly working	✓			
3.4	No deterioration or leakage in air or hydraulic is found	✓			
3.5	No indication of loose, damaged, or missing structural components including supports and anchorages	✓			
3.6	Electrical apparatus properly functioning, without signs of excessive deterioration, and no dirt accumulation			✓	
3.7	Control & drive mechanisms are properly adjusted and without excessive wear	✓			
3.8	No damage tubing, piping, electrical cables, or hoses, and their fittings	✓			

	CRANE INSPECTION & MAINTENANCE SERVICES A DIVISION OF AL-KHOBAR GATE INTERNATIONAL TRADING EST		
	INSPECTION CHECKLIST FOR BASE MOUNTED DRUM HOIST (WINCHES)		
	FRM.0601-1.16	Revision 01	Issue Date: 28/JAN/2021
	Prepared By Operations Manager	Reviewed & Approved By Managing Director	

S.N	ACCEPTANCE CRITERIA	PASS	FAIL	NA	REMARKS
3.9	Pins, bearings, shafts, gears, rollers, and locking and clamping devices have no excessive wear, cracking, distortion, & corrosion	✓			
3.10	Brake & clutch system parts & linings have no excessive wear, sever distortion, & corrosion	✓			
3.11	Chain & chain drive sprockets have no excessive wear, & excessive chain stretch			✓	
3.12	Winch is operated by a qualified operator	✓			
REMARKS / RECOMMENDATIONS					
SATISFACTORY					

INSPECTOR	CLIENT REPRESENTATIVE
Sonny De Guzman 	FIELD ENGR. VISHNU SREEKUMAR (AMC) <i>Signature Not Available</i>