

git cheatsheet

git init

- running it in an empty folder creates .git directory in the folder

git status

- shows branch you are working on, commits, untracked/modified but tracked files

git add <location of untracked file> or git add .

- to track a file, we cannot commit it directly, we first need to add it to the staging area
- `git add .` will track all untracked files in current working directory
 - otherwise you can specify which untracked files you want to track by `git add <location of untracked file>`
- git add will create history but not create a restore point with a message(called a commit)

git commit -m "<commit message>"

- stage is now empty as we made a commit, `git status` says nothing to commit, working tree clean

git restore --staged

- if you committed by mistake you can undo the commit using this command, modified files will be back on the stage as if you had added them
 - you can only rollback one commit behind

git log

- prints the commit history with each commit having its commit id

git reset <commit id>

- if you want to roll back to older commit
- git log removes the commits above <commit id> including the <commit id>
 - these commits were unstaged so you need to add them to the stage before committing again so you have untracked changes

git stash

- when you want to reset, but could modify the files and still might want to undo the reset later
- before stashing, files should be staged using add
- status after stashing is nothing to commit, working tree clean
- allows you to try reimplementing something without having to commit incomplete work that you were implementing before
- rolls back to most recent commit

git stash pop

- if something was stashed it is moved to staging
- this may override the changes you have made between stashing and popping the stash

```
git stash clear
```

- suppose you successfully reimplemented something so you don't need the stashed incomplete work anymore

```
git remote add origin  
https://github.com/<username>/<reponame>.git
```

- binds a git repo on github to a local git folder
- origin means that `<username>` is the owner of the `<reponame>`

```
git push origin master
```

- uploads the local git folder/new commits to github.com

Branches

- the master branch reflects production ready code that is not work in progress
- to start working on a feature addition you should create a separate branch and merge it with master when the work is done
 - meanwhile it is possible that the same files you worked on were modified by someone else as they got their branch merged
 - lets suppose this did not happen, then your branch can be merged smoothly

1. `git branch <name of new branch>` creates the new branch
2. `git checkout <name of new branch>` like git add
3. `git merge <name of new branch>` merges the branch with master
 - commits made in the new branch will be visible from master branch