Restaurant Case Study UseCase (Using Hadoop and PySpark)

1. Global Cuisine Popularity Analysis

The Problem: The Cuisines column contains comma-separated values (e.g., "French, Japanese, Desserts").
Goal: Calculate the total count of each cuisine globally and per city to identify the most popular food types.

```
>>> df = spark.read.csv("/jaya/resturant",header=True,inferSchema=True)
>>> df.show()
```

```
>>> from pyspark.sql.functions import *
>>> cuisine_df = df.withColumn("Cuisine",
...     explode(split(col("Cuisines"),","))
... )
>>> cuisine_df = cuisine_df.withColumn(
...     "Cuisine",
...     trim(col("Cuisine"))
... )
```

The total count of each cuisine globally

```
>>> cuisine_df.groupBy("Cuisine") \
... .count() \
... .orderBy(desc("count")) \
... .show()
+------------+-----+
|     Cuisine|count|
+------------+-----+
|North Indian| 3958|
|     Chinese| 2733|
|   Fast Food| 1984|
|     Mughlai|  994|
|     Italian|  763|
|      Bakery|  745|
| Continental|  736|
|        Cafe|  703|
|    Desserts|  653|
|South Indian|  635|
| Street Food|  562|
|    American|  389|
|      Mithai|  380|
|       Pizza|  379|
|      Burger|  250|
|        Thai|  234|
|       Asian|  233|
|   Beverages|  229|
|   Ice Cream|  226|
|     Mexican|  180|
+------------+-----+
```

The total count of each cuisine per city

```
>>> cuisine_df.groupBy("City","Cuisine") \
... .count() \
... .orderBy(desc("count")) \
... .show()
+---------+------------+-----+
|     City|     Cuisine|count|
+---------+------------+-----+
|New Delhi|North Indian| 2425|
|New Delhi|     Chinese| 1638|
|New Delhi|   Fast Food| 1303|
|New Delhi|     Mughlai|  628|
|    Noida|North Indian|  530|
|  Gurgaon|North Indian|  508|
|New Delhi|      Bakery|  465|
|New Delhi|South Indian|  411|
|New Delhi| Street Food|  411|
|New Delhi|    Desserts|  383|
|    Noida|     Chinese|  382|
|New Delhi|     Italian|  376|
|         |            |     |
|New Delhi| Continental|  373|
|New Delhi|        Cafe|  325|
|  Gurgaon|     Chinese|  324|
|New Delhi|      Mithai|  282|
|    Noida|   Fast Food|  265|
|  Gurgaon|   Fast Food|  220|
|New Delhi|       Pizza|  196|
|    Noida|     Mughlai|  155|
```

2. Normalizing and Comparing Costs Across Currencies

The Problem: The Average Cost for two is in different local currencies (INR, Dollar, Botswana Pula, etc.).

Goal: Determine which city/country has the most expensive or affordable dining scenes on a global scale.

```
currency = [
("Botswana Pula(P)",0.075),
("Indian Rupees(Rs.)",0.012),
("Dollar($)",1.0)
]
cur_df = spark.createDataFrame(
    currency,
    ["Currency","rate"]
)
from pyspark.sql.functions import broadcast
join_df = df2.join(
    broadcast(cur_df),
    "Currency",
    "left"
)
cost_df = join_df.withColumn(
    "cost_usd",
    col("cost") * col("rate")
```

city the most expensive or affordable dining scenes on a global scale.

```
cost_df.groupBy("City") \
.avg("cost_usd") \
.orderBy(desc("avg(cost_usd)")) \
.show()
```

City	avg(cost_usd)
Pasay City	250.0
Singapore	158.94736842105263
Mandaluyong City	150.0
Taguig City	129.375
Paynesville	120.0
Tagaytay City	90.0
Makati City	86.25
Vineland Station	70.0
Princeton	70.0
Pasig City	70.0
San Juan City	63.75
Santa Rosa	61.875
Quezon City	60.0
Orlando	40.25
Ojo Caliente	40.0
Tampa Bay	34.75

Country the most expensive or affordable dining scenes on a global scale.

```
cost_df.groupBy("Country Code") \
.avg("cost_usd") \
.orderBy(desc("avg(cost_usd)")) \
.show()
-----------------+------------------+
     Country Code|     avg(cost_usd)|
-----------------+------------------+
              184|158.94736842105263|
              162|120.51136363636364|
               37|             36.25|
              216|26.152073732718893|
               14|24.083333333333332|
                1|7.4808510638297765|
```

3. Impact of Services on Customer Ratings

The Problem: Does having "Online Delivery" or "Table Booking" actually lead to better reviews?
Goal: Provide business insights into whether investing in delivery infrastructure correlates with higher customer satisfaction.

Has online delivery

```
df2.groupBy("Has Online delivery") \
.avg("rating") \
.show()
----------------+------------------+
 Online delivery|       avg(rating)|
----------------+------------------+
               0|              null|
            null|              null|
              No|2.4656236786469345|
             Yes|3.2486938775510255|
             3.2|              null|
----------------+------------------+
```

Has table booking

```
df2.groupBy("Has Table booking") \
.avg("rating") \
.show()
--------------+------------------+
 Table booking|       avg(rating)|
--------------+------------------+
          null|              null|
            No|  2.55956837963515|
           Yes|3.4419689119170966|
             1|              null|
             4|              null|
--------------+------------------+
```

```
df2.groupBy(
    "Has Online delivery",
    "Has Table booking"
).avg("rating") \
.show()
----------------+-----------------+------------------+
 Online delivery|Has Table booking|       avg(rating)|
----------------+-----------------+------------------+
             3.2|                4|              null|
               0|                1|              null|
             Yes|              Yes|3.5958620689655163|
            null|             null|              null|
              No|               No|2.3653483992467024|
             Yes|               No|3.1737468982630337|
              No|              Yes|3.3493775933609933|
----------------+-----------------+------------------+
```

4. Identifying "Hidden Gems" (Weighted Rating Analysis)

The Problem: Some restaurants have a 5.0 rating but only 2 votes, while others have 4.5 with 2,000 votes.

Goal: Find highly-rated restaurants that have significant customer trust.

Cast vote and create weighted

```
df2 = df.withColumn(
    "votes",
    col("Votes").cast("int")
)
score_df = df2.withColumn(
    "score",
    col("rating") * log(col("votes") + 1)
)
score_df.orderBy(
```

Top trusted restaurants

```
score_df.orderBy(
    desc("score")
).select(
    "Restaurant Name",
    "City",
    "rating",
    "votes",
    "score"
).show(10)
------------------+---------+------+-----+------------------+
   Restaurant Name|     City|rating|votes|             score|
------------------+---------+------+-----+------------------+
              Toit|Bangalore|   4.8|10934| 44.63867487893217|
          Truffles|Bangalore|   4.7| 9667| 43.12991068656986|
   Barbeque Nation|  Kolkata|   4.9| 5966| 42.60059788085821|
's - Absolute B...|Hyderabad|   4.9| 5434| 42.14301251782102|
's - Absolute B...|Bangalore|   4.6| 6907| 40.66600302062621|
   Mirchi And Mime|   Mumbai|   4.9| 3244| 39.61586608277714|
       Big Brewsky|Bangalore|   4.5| 5705|38.921730892980506|
```

cloudera@quickstart:~

5. Restaurant Clustering for Marketing (PySpark MLlib)

The Problem: Grouping restaurants for targeted advertisements.

Goal: Categorize restaurants into segments like "Luxury Dining," "Budget Eats," and "Popular Mid-range."

Group by price range

```
>>> df.groupBy("price_range").count().show()
+-----------+-----+
|price_range|count|
+-----------+-----+
|          3| 1406|
|         30|    1|
|          0|    2|
|          1| 4437|
|     Yellow|    2|
|          4|  585|
|          2| 3109|
+-----------+-----+
```

Restaurant name price range segment

```
df2.select(
    "Restaurant Name",
    "price_range",
    "segment"
).show(10)
------------------+-----------+---------+
   Restaurant Name|price_range|  segment|
------------------+-----------+---------+
  Le Petit Souffle|          3|Expensive|
  Izakaya Kikufuji|          3|Expensive|
at - Edsa Shang...|          4|   Luxury|
               Ooma|          4|   Luxury|
       Sambo Kojin|          4|   Luxury|
      Din Tai Fung|          3|Expensive|
        Buffet 101|          4|   Luxury|
           Vikings|          4|   Luxury|
iral - Sofitel ...|          4|   Luxury|
          Locavore|          3|Expensive|
------------------+-----------+---------+
```

Segment wise rating

```
>>> df2.groupBy("segment") \
... .avg("rating") \
... .show()
+---------+------------------+
|  segment|       avg(rating)|
+---------+------------------+
|     null|              null|
|Mid-range|2.9414924412994568|
|Expensive| 3.682633451957296|
|   Budget|1.9979265269326136|
|   Luxury|3.8189743589743625|
+---------+------------------+
```

6. Geolocation-based Food Hub Detection

The Problem: Identifying dense clusters of restaurants (Food Hubs) without relying on locality names.

Goal: Identify the exact geographic areas where restaurant competition is highest

Selecting latitude longitude

```
>>> df.select("Latitude","Longitude").show(5)
+---------+----------+
| Latitude| Longitude|
+---------+----------+
|14.565443|121.027535|
|14.553708|121.014101|
|14.581404|121.056831|
|14.585318|121.056475|
| 14.58445|121.057508|
+---------+----------+
```

```
>>> df.groupBy(
...     "City",
...     "Latitude",
...     "Longitude"
... ).count() \
... .orderBy(desc("count")) \
... .show(10)
+---------+----------+----------+-----+
|     City|  Latitude| Longitude|count|
+---------+----------+----------+-----+
|New Delhi|         0|         0|  233|
|    Noida|         0|         0|   93|
|  Gurgaon|         0|         0|   48|
|Faridabad|         0|         0|   22|
|    Noida|28.5743086|77.3536634|   16|
| Vadodara|         0|         0|   10|
|New Delhi| 28.551456|77.2514264|    9|
|Mangalore|         0|         0|    9|
|    Noida|28.5743001|77.3535737|    9|
|    Noida|28.5971027|77.3648332|    8|
+---------+----------+----------+-----+
```

7. Data Quality & Standardization Pipeline

The Problem: The dataset contains null values in Cuisines and potential encoding issues in city names.

Goal: Ensure the data is "Analytics Ready" for downstream business intelligence tools.

```
from pyspark.sql.functions import col, lower, trim
df_clean = df.dropna(subset=["Cuisines"]) \
    .withColumn("City", lower(trim(col("City")))) \
    .withColumn("Cuisines", lower(trim(col("Cuisines")))) \
    .dropDuplicates()
df_clean = df_clean.fillna({"Aggregate rating": 0})
```

8. Locality-wise Price Range Distribution

The Problem: Analyzing the economic profile of different neighborhoods.

Goal: Generate a report showing the percentage of "Cheap" vs "Expensive" restaurants in every locality to help new entrepreneurs find market gaps.

```
>>> df2.filter(
...     col("segment").isin("Cheap","Expensive")
... ).groupBy(
...     "Locality",
...     "segment"
... ).count().show()
+--------------------+---------+-----+
|            Locality|  segment|count|
+--------------------+---------+-----+
|         Cedar Falls|Expensive|    2|
|  CITY WALK, Al Safa|Expensive|    1|
|Koramangala 7th B...|Expensive|    1|
|         Gopalapuram|    Cheap|    1|
|Anil Plaza, Chris...|Expensive|    2|
|DLF Emporio Mall,...|Expensive|    2|
|Hotel Classic Dip...|Expensive|    1|
|The Royal Retreat...|Expensive|    1|
|         Green Point|Expensive|    2|
|           Inverloch|    Cheap|    1|
|             Al Khan|Expensive|    1|
|       Rajguru Nagar|Expensive|    1|
```

9. Price Range Prediction (Classification)

The Problem: Can we predict the Price range (1 to 4) of a new restaurant based on its location and cuisine?

Goal: Build a model that predicts the category of a restaurant based on its basic profile.

```
from pyspark.sql import SparkSession
from pyspark.sql.functions import col, when
spark = SparkSession.builder.appName("PricePrediction").getOrCreate()
df = spark.read.csv("/jaya/resturant", header=True, inferSchema=True)
result = df.withColumn(
    "Predicted_Price_Range",
    when(col("Average Cost for two") <= 500, 1)
    .when((col("Average Cost for two") > 500) & (col("Average Cost for two") <= 1500), 2)
    .when((col("Average Cost for two") > 1500) & (col("Average Cost for two") <= 3000), 3)
    .otherwise(4)
)
result.select("Restaurant Name", "City", "Average Cost for two", "Price range", "Predicted_Price_Range").show()
```

```
+--------------------+----------------+--------------------+-----------+---------------------+
|     Restaurant Name|            City|Average Cost for two|Price range|Predicted_Price_Range|
+--------------------+----------------+--------------------+-----------+---------------------+
|    Le Petit Souffle|     Makati City|                1100|          3|                    2|
|    Izakaya Kikufuji|     Makati City|                1200|          3|                    2|
|Heat - Edsa Shang...|Mandaluyong City|                4000|          4|                    4|
|                Ooma|Mandaluyong City|                1500|          4|                    2|
|         Sambo Kojin|Mandaluyong City|                1500|          4|                    2|
|        Din Tai Fung|Mandaluyong City|                1000|          3|                    2|
|          Buffet 101|      Pasay City|                2000|          4|                    3|
|             Vikings|      Pasay City|                2000|          4|                    3|
|Spiral - Sofitel ...|      Pasay City|                6000|          4|                    4|
|            Locavore|      Pasig City|                1100|          3|                    2|
|    Silantro Fil-Mex|      Pasig City|                 800|          3|                    2|
|Mad Mark's Creame...|      Pasig City|                 900|          3|                    2|
|    Silantro Fil-Mex|     Quezon City|                 800|          3|                    2|
|          Guevarra's|   San Juan City|                1000|          3|                    2|
|Sodam Korean Rest...|   San Juan City|                 700|          3|                    2|
|       Cafe Arabelle|      Santa Rosa|                 800|          3|                    2|
|Nonna's Pasta & P...|      Santa Rosa|                 850|          3|                    2|
|          Balay Dako|   Tagaytay City|                1200|          3|                    2|
```

10. Top-N Recommendation Engine (Content-Based)

The Problem: Recommending similar restaurants to a user.

Goal: Given a restaurant the user likes, recommend 5 other similar restaurants in the same city.

```
name = "Le Petit Souffle"
r = df.filter(col("Restaurant Name") == name).select(
    "City","Cuisines","Price range"
).collect()[0]
city = r[0]
cuisine = r[1]
price = r[2]
df.filter(
    (col("City") == city) &
    (col("Cuisines") == cuisine) &
    (col("Price range") == price)
).select(
    "Restaurant Name",
    "City",
    "Cuisines",
    "Price range",
    "Aggregate rating"
).orderBy(
    col("Aggregate rating").desc()
).show(5)
-------------+-----------+--------------------+----------
+----------------+-----------+--------------------+-----------+----------------+
| Restaurant Name|       City|            Cuisines|Price range|Aggregate rating|
+----------------+-----------+--------------------+-----------+----------------+
|Le Petit Souffle|Makati City|French, Japanese,...|          3|             4.8|
+----------------+-----------+--------------------+-----------+----------------+
```

11. Optimized Currency Conversion (Broadcast Join)

The Problem: Joining a massive restaurant dataset with a tiny 15-row currency exchange table triggers a standard shuffle join, moving millions of rows across the network unnecessarily

Goal: Implement a Broadcast Join to eliminate network shuffle and speed up the cost normalization process across different global currencies.

```
currency_data = [
("Botswana Pula(P)",0.075),
("Indian Rupees(Rs.)",0.012),
("Dollar($)",1.0)
]
cur_df = spark.createDataFrame(
    currency_data,
    ["Currency","rate"]
)
cost_df = df.join(
    broadcast(cur_df),
    "Currency",
    "left"
).withColumn(
    "cost_usd",
    col("Average Cost for two") * col("rate")
)
cost_df.select(
    "Restaurant Name",
    "City",
    "Currency",
```

```
>>> cost_df.select(
...     "Restaurant Name",
...     "City",
...     "Currency",
...     "Average Cost for two",
...     "cost_usd"
... ).show()
+--------------------+----------------+----------------+--------------------+--------+
|     Restaurant Name|            City|        Currency|Average Cost for two|cost_usd|
+--------------------+----------------+----------------+--------------------+--------+
|    Le Petit Souffle|     Makati City|Botswana Pula(P)|                1100|    82.5|
|    Izakaya Kikufuji|     Makati City|Botswana Pula(P)|                1200|    90.0|
|Heat - Edsa Shang...|Mandaluyong City|Botswana Pula(P)|                4000|   300.0|
|                Ooma|Mandaluyong City|Botswana Pula(P)|                1500|   112.5|
|         Sambo Kojin|Mandaluyong City|Botswana Pula(P)|                1500|   112.5|
|        Din Tai Fung|Mandaluyong City|Botswana Pula(P)|                1000|    75.0|
|          Buffet 101|      Pasay City|Botswana Pula(P)|                2000|   150.0|
|             Vikings|      Pasay City|Botswana Pula(P)|                2000|   150.0|
|Spiral - Sofitel ...|      Pasay City|Botswana Pula(P)|                6000|   450.0|
```

```
|                Ooma|Mandaluyong City|Botswana Pula(P)|                1500|   112.5|
|         Sambo Kojin|Mandaluyong City|Botswana Pula(P)|                1500|   112.5|
|        Din Tai Fung|Mandaluyong City|Botswana Pula(P)|                1000|    75.0|
|          Buffet 101|      Pasay City|Botswana Pula(P)|                2000|   150.0|
|             Vikings|      Pasay City|Botswana Pula(P)|                2000|   150.0|
|Spiral - Sofitel ...|      Pasay City|Botswana Pula(P)|                6000|   450.0|
|            Locavore|      Pasig City|Botswana Pula(P)|                1100|    82.5|
|    Silantro Fil-Mex|      Pasig City|Botswana Pula(P)|                 800|    60.0|
|Mad Mark's Creame...|      Pasig City|Botswana Pula(P)|                 900|    67.5|
|    Silantro Fil-Mex|     Quezon City|Botswana Pula(P)|                 800|    60.0|
|          Guevarra's|   San Juan City|Botswana Pula(P)|                1000|    75.0|
|Sodam Korean Rest...|   San Juan City|Botswana Pula(P)|                 700|    52.5|
|       Cafe Arabelle|      Santa Rosa|Botswana Pula(P)|                 800|    60.0|
|Nonna's Pasta & P...|      Santa Rosa|Botswana Pula(P)|                 850|   63.75|
|          Balay Dako|   Tagaytay City|Botswana Pula(P)|                1200|    90.0|
|Hobing Korean Des...|     Taguig City|Botswana Pula(P)|                 600|    45.0|
|Wildflour Cafe + ...|     Taguig City|Botswana Pula(P)|                1500|   112.5|
+--------------------+----------------+----------------+--------------------+--------+
```

12. Efficient Data Pipelines (Caching & Storage)

The Problem: The "Cuisine Popularity" analysis and "Price Range Prediction" both use the same cleaned dataset. Without optimization, Spark re-reads the raw CSV from HDFS and re-calculates the split() and explode() transformations for every single query.

Goal: Use .cache() to persist intermediate cleaned data in memory and save the final "Analytics Ready" dataset in Parquet format to leverage columnar storage and compression.

```
>>> from pyspark.sql import SparkSession
>>> from pyspark.sql.functions import col, lower, trim
>>> df_clean = df.dropna(subset=["Cuisines"]) \
..             .withColumn("City", lower(trim(col("City")))) \
..             .withColumn("Cuisines", lower(trim(col("Cuisines")))) \
..             .dropDuplicates()
>>> df_clean.cache()
DataFrame[Restaurant ID: string, Restaurant Name: string, Country Code: string, City: string, Address: string, Locality: string, Lo
cality Verbose: string, Longitude: string, Latitude: string, Cuisines: string, Average Cost for two: string, Currency: string, Has
Table booking: string, Has Online delivery: string, Is delivering now: string, Switch to order menu: string, Price range: string, A
ggregate rating: string, Rating color: string, Rating text: string, Votes: int]
>>> df_clean.groupBy("Cuisines").count().show()
--------------------+-----+
            Cuisines|count|
--------------------+-----+
north indian, chi...|  511|
north indian, mug...|  334|
cafe, kiwi, ice c...|    1|
cafe, north india...|    1|
bbq, caribbean, s...|    1|
```

```
>>> df_clean.groupBy("Price range").count().show()
+-----------+-----+
|Price range|count|
+-----------+-----+
|          3| 1406|
|         30|    1|
|          0|    2|
|          1| 4437|
|     Yellow|    2|
|          4|  585|
|          2| 3109|
+-----------+-----+

>>> df_clean.write.mode("overwrite").parquet("cleaned_restaurant_data.parquet")
```

13. Service Impact Comparative Visualization

The Problem: Simply listing the average rating for restaurants with "Online Delivery" vs. "Table Booking" doesn't show the full story of customer satisfaction or the volume of feedback.

Goal: Create a Side-by-Side Box Plot to compare rating distributions for each service, using Color Overlays to represent different price ranges and Point Density (Jitter) to show the total number of votes.

```
>>> df_vis = df.select(
...     "Has Online delivery",
...     "Has Table booking",
...     "Aggregate rating",
...     "Votes",
...     "Price range"
... )
>>> from pyspark.sql.functions import col
>>> df_vis = df_vis.withColumn(
...     "rating",
...     col("Aggregate rating").cast("double")
... ).withColumn(
...     "votes",
...     col("Votes").cast("int")
... )
>>> df_vis.groupBy(
...     "Has Online delivery",
...     "Has Table booking",
```

```
>>> df_vis.groupBy(
...     "Has Online delivery",
...     "Has Table booking",
...     "Price range"
... ).avg("rating","votes").show()
+------------------+----------------+-----------+------------------+-----------------+
|Has Online delivery|Has Table booking|Price range|       avg(rating)|        avg(votes)|
+------------------+----------------+-----------+------------------+-----------------+
|                 No|              No|          4| 4.015100671140939| 397.7953020134228|
|               null|            null|       null|              null|             null|
|                  0|               1|          0|              null|             null|
|                3.2|               4|         30|              null|             null|
|               Yes|             Yes|          1|               3.7|             61.0|
|               Yes|              No|          3| 3.622857142857143|498.32142857142856|
|                 No|             Yes|          3|   3.4112600536193| 346.9490616621984|
|                 No|              No|          1|1.8102618920363396|37.703367183324424|
|                 No|              No|          2|2.7392857142857134|132.69086651053865|
|               Yes|             Yes|          3|3.6302583025830266|494.23247232472323|
|                 No|              No|          3| 3.882692307692307| 467.6955128205128|
|                 No|              No|     Yellow|              null|             null|
|               Yes|             Yes|          2|3.4268292682926833| 317.6991869918699|
```

cloudera@quickstart:~

```
>>> df_vis.groupBy(
...     "Has Table booking",
...     "Price range"
... ).avg("rating").show()
+----------------+-----------+------------------+
|Has Table booking|Price range|       avg(rating)|
+----------------+-----------+------------------+
|               4|         30|              null|
|             Yes|          3|3.5034161490683204|
|            null|       null|              null|
|             Yes|          2|3.1020920502092033|
|              No|          1| 1.999954975236381|
|              No|          3| 3.835078534031416|
|              No|          2|2.9281184668989573|
|              No|          0|              null|
|             Yes|          4| 3.593065693430658|
|             Yes|          1|               3.7|
|               1|          0|              null|
|              No|          4| 4.018006430868167|
|              No|     Yellow|              null|
```