

# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING



Discover. Learn. Empower.

## Worksheet 7

### 1. Aim:

1. Design a PostgreSQL trigger that performs the following task:
  - a. Whenever a new record is inserted into the student table, the inserted row should be displayed on the output console.
  - b. Similarly, when a record is deleted from the student table, the deleted row should also be displayed on the console.
2. Create PostgreSQL triggers to maintain an audit log for employee actions.
  - a. Whenever a new employee is inserted into tbl\_employee, a record should be inserted into tbl\_employee\_audit with the message: "Employee name <emp\_name> has been added at <current\_time>"
  - b. Whenever an employee is deleted from tbl\_employee, a record should be inserted into tbl\_employee\_audit with the message: "Employee name <emp\_name> has been deleted at <current\_time>"

### 2. Objective:

- Maintain a complete and reliable record of all employee insertions and deletions for accountability and auditing purposes.
- Automatically insert descriptive audit messages into tbl\_employee\_audit whenever changes occur in tbl\_employee, without requiring manual input.
- Guarantee that every change in the employee table is consistently tracked in real-time, reducing the risk of unrecorded modifications.
- Store timestamps and employee names in the audit log to create a chronological history of employee activity for future reference and compliance checks.
- Increase visibility into employee-related database actions, supporting internal monitoring, troubleshooting, and security reviews.

### 3. Code:

#### 1.

```
-- Create the student table
CREATE TABLE student (
  id SERIAL PRIMARY KEY,
  name VARCHAR(100),
```

# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

```
age INT,    class
VARCHAR(50)
);

-- Create the trigger function
CREATE OR REPLACE FUNCTION fn_student_audit()
RETURNS TRIGGER
LANGUAGE plpgsql
AS
$$
BEGIN
    IF TG_OP = 'INSERT' THEN
        RAISE NOTICE 'Inserted Row -> ID: %, Name: %, Age: %, Class: %',
            NEW.id, NEW.name, NEW.age, NEW.class;
        RETURN NEW;

    ELSIF TG_OP = 'DELETE' THEN
        RAISE NOTICE 'Deleted Row -> ID: %, Name: %, Age: %, Class: %',
            OLD.id, OLD.name, OLD.age, OLD.class;
        RETURN OLD;
    END IF;

    RETURN NULL;
END;
$$;

-- Create the trigger
CREATE TRIGGER trg_student_audit
AFTER INSERT OR DELETE
ON student
FOR EACH ROW
EXECUTE FUNCTION fn_student_audit();

-- Test the trigger

-- Insert records
INSERT INTO student(name, age, class) VALUES ('Shivanshu', 20, 'B.Tech');
INSERT INTO student(name, age, class) VALUES ('Tanya', 21, 'B.Tech');
INSERT INTO student(name, age, class) VALUES ('Devanshu', 19, 'Non-CSE');

-- Delete a record
DELETE FROM student WHERE name = 'Devanshu';

SELECT * FROM student;
```

2.

```
-- Create employee and audit tables CREATE
TABLE tbl_employee (    emp_id SERIAL
PRIMARY KEY,    emp_name
VARCHAR(100) NOT NULL,
```

# DEPARTMENT OF

# COMPUTER SCIENCE & ENGINEERING

```
emp_salary NUMERIC
);

CREATE TABLE tbl_employee_audit (
sno SERIAL PRIMARY KEY,
message TEXT
);

-- Create the trigger function
CREATE OR REPLACE FUNCTION audit_employee_changes()
RETURNS TRIGGER
LANGUAGE plpgsql
AS
$$
BEGIN
    IF TG_OP = 'INSERT' THEN
        INSERT INTO tbl_employee_audit(message)
        VALUES ('Employee name ' || NEW.emp_name || ' has been added at ' || NOW());
        RETURN NEW;

    ELSIF TG_OP = 'DELETE' THEN
        INSERT INTO tbl_employee_audit(message)
        VALUES ('Employee name ' || OLD.emp_name || ' has been deleted at ' || NOW());
        RETURN OLD;
    END IF;

    RETURN NULL;
END;
$$;

-- Create the trigger
CREATE TRIGGER trg_employee_audit
AFTER INSERT OR DELETE
ON tbl_employee
FOR EACH ROW
EXECUTE FUNCTION audit_employee_changes();

-- Test the trigger

-- Insert employees
INSERT INTO tbl_employee(emp_name, emp_salary) VALUES ('Shivanshu', 90000);
INSERT INTO tbl_employee(emp_name, emp_salary) VALUES ('Tanya', 95000);
INSERT INTO tbl_employee(emp_name, emp_salary) VALUES ('Karan', 100000);

-- Delete one employee
DELETE FROM tbl_employee WHERE emp_name = 'Karan';

SELECT * FROM tbl_employee;
SELECT * FROM tbl_employee_audit;
```

# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING



Discover. Learn. Empower.

## 4. Output:

(1)

Output:

```
CREATE TABLE
CREATE FUNCTION
CREATE TRIGGER
INSERT 0 1
INSERT 0 1
INSERT 0 1
DELETE 1
```

| id | name      | age | class  |
|----|-----------|-----|--------|
| 1  | Shivanshu | 20  | B.Tech |
| 2  | Tanya     | 21  | B.Tech |

(2 rows)

```
psql:commands.sql:41: NOTICE:  Inserted Row -> ID: 1, Name: Shivanshu, Age: 20, Class: B.Tech
psql:commands.sql:42: NOTICE:  Inserted Row -> ID: 2, Name: Tanya, Age: 21, Class: B.Tech
psql:commands.sql:43: NOTICE:  Inserted Row -> ID: 3, Name: Devanshu, Age: 19, Class: Non-CSE
psql:commands.sql:46: NOTICE:  Deleted Row -> ID: 3, Name: Devanshu, Age: 19, Class: Non-CSE
```

(2)

# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Output:

```
CREATE TABLE
CREATE TABLE
CREATE FUNCTION
CREATE TRIGGER
INSERT 0 1
INSERT 0 1
INSERT 0 1
DELETE 1
```

| emp_id | emp_name  | emp_salary |
|--------|-----------|------------|
| 1      | Shivanshu | 90000      |
| 2      | Tanya     | 95000      |

(2 rows)

| sno | message   |
|-----|---|
| 1   | Employee name Shivanshu has been added at 2025-10-17 09:32:51.612426+00 |
| 2   | Employee name Tanya has been added at 2025-10-17 09:32:51.61611+00      |
| 3   | Employee name Karan has been added at 2025-10-17 09:32:51.618558+00     |
| 4   | Employee name Karan has been deleted at 2025-10-17 09:32:51.620008+00   |

(4 rows)



### 5. Learning Outcomes:

- Understanding Trigger Mechanisms
- Practical Use of Trigger Functions
- Implementing Auditing and Logging
- Event-driven Automation in Databases