


PIZZA SALES ANALYSIS ON SQL





Hello !



My Name is Jayesh Dabholkar and in this project I have utilize SQL queries to solve questions regarding sales of the pizza shop

Retrieve the total number of orders placed.

```
select count(order_id) as total_orders from orders
```

	total_orders
▶	21350

Calculate the total revenue generated from pizza sales.

```
SELECT
    ROUND(SUM(orders_details.quantity * pizzas.price),
          2) AS total_sales
FROM
    orders_details
    JOIN
    pizzas ON pizzas.pizza_id = orders_details.pizza_id
```

	total_sales
▶	817860.05

Identify the highest-priced pizza.

```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
        pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

	name	price
▶	The Greek Pizza	35.95

Identify the most common pizza size ordered.

```
SELECT
    pizzas.size,
    COUNT(orders_details.order_details_id) AS order_count
FROM
    pizzas
    JOIN
        orders_details ON pizzas.pizza_id = orders_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC
LIMIT 1;
```

	size	order_count
▶	L	18526

List the top 5 most ordered pizza types along with their quantities

```
SELECT
    pizza_types.name, SUM(orders_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    orders_details ON orders_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

	name	quantity
	The Classic Deluxe Pizza	2453
	The Barbecue Chicken Pizza	2432
	The Hawaiian Pizza	2422
	The Pepperoni Pizza	2418
	The Thai Chicken Pizza	2371

Join the necessary tables to find the total quantity of each pizza category ordered.

```
SELECT
    pizza_types.category,
    SUM(orders_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
    JOIN
    orders_details ON orders_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;
```

category	quantity
Classic	14888
Supreme	11987
Veggie	11649
Chicken	11050

Determine the distribution of orders by hour of the day.

```
SELECT
    HOUR(order_time) AS hour, COUNT(order_id) AS order_count
FROM
    orders
GROUP BY HOUR(order_time);
```

hour	order_count
11	1231
12	2520
13	2455
14	1472
15	1468
16	1920
17	2336
18	2399

Join relevant tables to find the category-wise distribution of pizzas.

```
SELECT
    category, COUNT(name)
FROM
    pizza_types
GROUP BY category;
```

category	count(name)
Chicken	6
Classic	8
Supreme	9
Veggie	9

Group the orders by date and calculate the average number of pizzas ordered per day.

```
SELECT
    ROUND(AVG(quantity), 0) as avg_pizza_per_day
FROM
    (SELECT
        orders.order_date, SUM(orders_details.quantity) AS quantity
    FROM
        orders
    JOIN orders_details ON orders.order_id = orders_details.order_id
    GROUP BY orders.order_date) AS order_quantity;
```

avg_pizza_per_day
138

Determine the top 3 most ordered pizza types based on revenue.

```
SELECT
    pizza_types.name,
    SUM(orders_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
    JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
    JOIN
    orders_details ON orders_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3;
```

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5

Calculate the percentage contribution of each pizza type to total revenue.

```
SELECT
    pizza_types.category,
    ROUND(SUM(orders_details.quantity * pizzas.price) / (SELECT
        ROUND(SUM(orders_details.quantity * pizzas.price),
            2) AS total_sales
    FROM
        orders_details
        JOIN
        pizzas ON pizzas.pizza_id = orders_details.pizza_id) * 100,
        2) AS revenue
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    orders_details ON orders_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY revenue DESC;
```

category	revenue
Classic	26.91
Supreme	25.46
Chicken	23.96
Veggie	23.68

Analyze the cumulative revenue generated over time.

```
select order_date, sum(revenue) over (order by order_date) as cum_revenue
from
(select orders.order_date,
sum(orders_details.quantity * pizzas.price) as revenue
from orders_details join pizzas
on orders_details.pizza_id = pizzas.pizza_id
join orders
on orders_details.order_id = orders.order_id
group by orders.order_date) as sales;
```

order_date	cum_revenue
2015-01-01	2713.8500000000004
2015-01-02	5445.75
2015-01-03	8108.15
2015-01-04	9863.6
2015-01-05	11929.55
2015-01-06	14358.5
2015-01-07	16560.7
2015-01-08	19399.05

Determine the top 3 most ordered pizza types based on revenue for each pizza category.

```
select name, revenue from
(select category, name, revenue,
rank() over (partition by category order by revenue desc) as rn
from
(select pizza_types.category, pizza_types.name,
sum((orders_details.quantity) * pizzas.price) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join orders_details on orders_details.pizza_id = pizzas.pizza_id
group by pizza_types.category, pizza_types.name) as a) b
where rn <= 3;
```

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5
The Classic Deluxe Pizza	38180.5
The Hawaiian Pizza	32273.25
The Pepperoni Pizza	30161.75
The Spicy Italian Pizza	34831.25
The Italian Supreme Pizza	33476.75
The Sicilian Pizza	30940.5
The Four Cheese Pizza	32265.700000000065