

# CS 245: Database System Principles

## Notes 09: Concurrency Control


Hector Garcia-Molina

CS 245

Notes 09

1

## Chapter 18 [18] Concurrency Control



CS 245

Notes 09

2

### Example:

T1: Read(A)	T2: Read(A)
A ← A+100	A ← A×2
Write(A)	Write(A)
Read(B)	Read(B)
B ← B+100	B ← B×2
Write(B)	Write(B)

Constraint: A=B

CS 245

Notes 09

3

### Schedule A

T1	T2
Read(A); A ← A+100	
Write(A);	
Read(B); B ← B+100;	
Write(B);	
	Read(A); A ← A×2;
	Write(A);
	Read(B); B ← B×2;
	Write(B);

CS 245

Notes 09

4

### Schedule A

T1	T2	A	B
Read(A); A ← A+100		25	25
Write(A);		125	
Read(B); B ← B+100;			125
Write(B);			
	Read(A); A ← A×2;		
	Write(A);	250	
	Read(B); B ← B×2;		250
	Write(B);	250	250

CS 245

Notes 09

5

### Schedule B

T1	T2
	Read(A); A ← A×2;
	Write(A);
	Read(B); B ← B×2;
	Write(B);
Read(A); A ← A+100	
Write(A);	
Read(B); B ← B+100;	
Write(B);	

CS 245

Notes 09

6

### Schedule B

T1	T2	A	B
		25	25
	Read(A); A $\leftarrow$ A $\times$ 2;		
	Write(A);	50	
	Read(B); B $\leftarrow$ B $\times$ 2;		
	Write(B);		50
Read(A); A $\leftarrow$ A+100			
Write(A);		150	
Read(B); B $\leftarrow$ B+100;			
Write(B);			150
		150	150

CS 245

Notes 09

7

### Schedule C

T1	T2
Read(A); A $\leftarrow$ A+100	
Write(A);	
	Read(A); A $\leftarrow$ A $\times$ 2;
	Write(A);
Read(B); B $\leftarrow$ B+100;	
Write(B);	
	Read(B); B $\leftarrow$ B $\times$ 2;
	Write(B);

CS 245

Notes 09

8

### Schedule C

T1	T2	A	B
		25	25
Read(A); A $\leftarrow$ A+100			
Write(A);		125	
	Read(A); A $\leftarrow$ A $\times$ 2;		
	Write(A);	250	
Read(B); B $\leftarrow$ B+100;			
Write(B);			125
	Read(B); B $\leftarrow$ B $\times$ 2;		
	Write(B);		250
		250	250

CS 245

Notes 09

9

### Schedule D

T1	T2
Read(A); A $\leftarrow$ A+100	
Write(A);	
	Read(A); A $\leftarrow$ A $\times$ 2;
	Write(A);
	Read(B); B $\leftarrow$ B $\times$ 2;
	Write(B);
Read(B); B $\leftarrow$ B+100;	
Write(B);	

CS 245

Notes 09

10

### Schedule D

T1	T2	A	B
		25	25
Read(A); A $\leftarrow$ A+100			
Write(A);		125	
	Read(A); A $\leftarrow$ A $\times$ 2;		
	Write(A);	250	
	Read(B); B $\leftarrow$ B $\times$ 2;		
	Write(B);		50
Read(B); B $\leftarrow$ B+100;			
Write(B);			150
		250	150

CS 245

Notes 09

11

### Schedule E

Same as Schedule D  
but with new T2'

T1	T2'
Read(A); A $\leftarrow$ A+100	
Write(A);	
	Read(A); A $\leftarrow$ A $\times$ 1;
	Write(A);
	Read(B); B $\leftarrow$ B $\times$ 1;
	Write(B);
Read(B); B $\leftarrow$ B+100;	
Write(B);	

CS 245

Notes 09

12

### Schedule E

Same as Schedule D but with new T2'

T1	T2'
Read(A); A ← A+100	
Write(A);	
	Read(A); A ← A×1;
	Write(A);
	Read(B); B ← B×1;
	Write(B);
Read(B); B ← B+100;	
Write(B);	

A	B
25	25
125	
125	
	25
	125
125	125

CS 245
Notes 09
13

- Want schedules that are “good”, regardless of
  - initial state and
  - transaction semantics
- Only look at order of read and writes

Example:

Sc=r<sub>1</sub>(A)w<sub>1</sub>(A)r<sub>2</sub>(A)w<sub>2</sub>(A)r<sub>1</sub>(B)w<sub>1</sub>(B)r<sub>2</sub>(B)w<sub>2</sub>(B)

CS 245
Notes 09
14

Example:

Sc=r<sub>1</sub>(A)w<sub>1</sub>(A)r<sub>2</sub>(A)w<sub>2</sub>(A)r<sub>1</sub>(B)w<sub>1</sub>(B)r<sub>2</sub>(B)w<sub>2</sub>(B)

Sc'=r<sub>1</sub>(A)w<sub>1</sub>(A) r<sub>1</sub>(B)w<sub>1</sub>(B)r<sub>2</sub>(A)w<sub>2</sub>(A)r<sub>2</sub>(B)w<sub>2</sub>(B)

T<sub>1</sub>
T<sub>2</sub>

CS 245
Notes 09
15

### The Transaction Game

A							
B							
T1							
T2							

CS 245
Notes 09
16

### The Transaction Game

A	r	w	r	w			
B					r	w	r
T1	r	w			r	w	
T2			r	w			r

CS 245
Notes 09
17

### The Transaction Game

A	r	w	r	w	r	w	
B					r	w	r
T1	r	w			r	w	
T2			r	w			r

until column

hits something

can move column

CS 245
Notes 09
18

A	r	w	r	w				
B					r	w	r	w
T1	r	w			r	w		
T2			r	w			r	w

move

A	r	w			r	w		
B			r	w			r	w
T1	r	w	r	w				
T2					r	w	r	w

CS 245 Notes 09 19

### Schedule D

A	r	w	r	w				
B					r	w	r	w
T1	r	w					r	w
T2			r	w	r	w		

CS 245 Notes 09 20

However, for  $S_d$ :

$$S_d = r_1(A)w_1(A)r_2(A)w_2(A)r_2(B)w_2(B)r_1(B)w_1(B)$$

as a matter of fact,  
 $T_2$  must precede  $T_1$   
 in any equivalent schedule,  
 i.e.,  $T_2 \rightarrow T_1$

CS 245 Notes 09 21

- $T_2 \rightarrow T_1$
- Also,  $T_1 \rightarrow T_2$

$T_1 \rightarrow T_2 \Rightarrow S_d$  cannot be rearranged into a serial schedule  
 $\Rightarrow S_d$  is not "equivalent" to any serial schedule  
 $\Rightarrow S_d$  is "bad"

CS 245 Notes 09 22

### Returning to $S_c$

$$S_c = r_1(A)w_1(A)r_2(A)w_2(A)r_1(B)w_1(B)r_2(B)w_2(B)$$

$T_1 \rightarrow T_2$        $T_1 \rightarrow T_2$

CS 245 Notes 09 23

### Returning to $S_c$

$$S_c = r_1(A)w_1(A)r_2(A)w_2(A)r_1(B)w_1(B)r_2(B)w_2(B)$$

$T_1 \rightarrow T_2$        $T_1 \rightarrow T_2$

no cycles  $\Rightarrow S_c$  is "equivalent" to a serial schedule  
 (in this case  $T_1, T_2$ )

CS 245 Notes 09 24

## Concepts

*Transaction*: sequence of  $r_i(x)$ ,  $w_i(x)$  actions

*Conflicting actions*:  $r_1(A) \begin{cases} w_2(A) \\ w_1(A) \end{cases}$   
 $w_2(A) \begin{cases} r_1(A) \\ w_2(A) \end{cases}$

*Schedule*: represents chronological order in which actions are executed

*Serial schedule*: no interleaving of actions or transactions

CS 245

Notes 09

25

Is it OK to model reads & writes as occurring at a single point in time in a schedule?


- $S = \dots r_1(x) \dots w_2(b) \dots$

CS 245

Notes 09

26

What about conflicting, concurrent actions on same object?




CS 245

Notes 09

27

What about conflicting, concurrent actions on same object?



- Assume equivalent to either  $r_1(A) w_2(A)$  or  $w_2(A) r_1(A)$
- $\Rightarrow$  low level synchronization mechanism
- Assumption called "atomic actions"

CS 245

Notes 09

28

## Definition

$S_1, S_2$  are conflict equivalent schedules if  $S_1$  can be transformed into  $S_2$  by a series of swaps on non-conflicting actions.

CS 245

Notes 09

29

## Definition

A schedule is conflict serializable if it is conflict equivalent to some serial schedule.

CS 245

Notes 09

30

### Precedence graph $P(S)$ ( $S$ is schedule)

Nodes: transactions in  $S$

Arcs:  $T_i \rightarrow T_j$  whenever

- $p_i(A), q_j(A)$  are actions in  $S$
- $p_i(A) <_S q_j(A)$
- at least one of  $p_i, q_j$  is a write

CS 245

Notes 09

31

### Exercise:

- What is  $P(S)$  for  
 $S = w_3(A) w_2(C) r_1(A) w_1(B) r_1(C) w_2(A) r_4(A) w_4(D)$
- Is  $S$  serializable?

CS 245

Notes 09

32

### Another Exercise:

- What is  $P(S)$  for  
 $S = w_1(A) r_2(A) r_3(A) w_4(A)$  ?

CS 245

Notes 09

33

### Lemma

$S_1, S_2$  conflict equivalent  $\Rightarrow P(S_1)=P(S_2)$

CS 245

Notes 09

34

### Lemma

$S_1, S_2$  conflict equivalent  $\Rightarrow P(S_1)=P(S_2)$

#### Proof:

Assume  $P(S_1) \neq P(S_2)$

$\Rightarrow \exists T_i: T_i \rightarrow T_j$  in  $S_1$  and not in  $S_2$

$\Rightarrow \begin{matrix} S_1 = \dots p_i(A) \dots q_j(A) \dots \\ S_2 = \dots q_j(A) \dots p_i(A) \dots \end{matrix} \quad \left\{ \begin{array}{l} p_i, q_j \\ \text{conflict} \end{array} \right.$

$\Rightarrow S_1, S_2$  not conflict equivalent

CS 245

Notes 09

35

Note:  $P(S_1)=P(S_2) \not\Rightarrow S_1, S_2$  conflict equivalent

CS 245

Notes 09

36

Note:  $P(S_1) = P(S_2) \not\Rightarrow S_1, S_2$  conflict equivalent

Counter example:

$S_1 = w_1(A) \ r_2(A) \quad w_2(B) \ r_1(B)$

$S_2 = r_2(A) \ w_1(A) \quad r_1(B) \ w_2(B)$

CS 245

Notes 09

37

### Theorem

$P(S_1)$  acyclic  $\iff S_1$  conflict serializable

CS 245

Notes 09

38

### Theorem

$P(S_1)$  acyclic  $\iff S_1$  conflict serializable

( $\Leftarrow$ ) Assume  $S_1$  is conflict serializable

$\Rightarrow \exists S_s: S_s, S_1$  conflict equivalent

$\Rightarrow P(S_s) = P(S_1)$

$\Rightarrow P(S_1)$  acyclic since  $P(S_s)$  is acyclic


CS 245

Notes 09

39

### Theorem

$P(S_1)$  acyclic  $\iff S_1$  conflict serializable



CS 245

Notes 09

40

### Theorem

$P(S_1)$  acyclic  $\iff S_1$  conflict serializable

( $\Rightarrow$ ) Assume  $P(S_1)$  is acyclic

Transform  $S_1$  as follows:

(1) Take  $T_1$  to be transaction with no incident arcs


(2) Move all  $T_1$  actions to the front

$S_1 = \dots q_j(A) \dots p_1(A) \dots$



(3) we now have  $S_1 = \langle T_1 \text{ actions} \rangle \dots \text{rest} \dots$

(4) repeat above steps to serialize rest!



CS 245

Notes 09

41

### How to enforce serializable schedules?

*Option 1:* run system, recording  $P(S)$ ;  
at end of day, check for  $P(S)$   
cycles and declare if execution  
was good


CS 245

Notes 09

42

## How to enforce serializable schedules?

*Option 2:* prevent P(S) cycles from occurring



CS 245

Notes 09


43

## A locking protocol

Two new actions:

lock (exclusive):  $li(A)$

unlock:  $ui(A)$



CS 245

Notes 09

44

## Rule #1: Well-formed transactions

$T_i: \dots li(A) \dots pi(A) \dots ui(A) \dots$

CS 245

Notes 09

45

## Rule #2 Legal scheduler

$S = \dots li(A) \dots ui(A) \dots$

$\longleftrightarrow$   
no  $lj(A)$

CS 245

Notes 09

46

## Exercise:

- What schedules are legal?  
What transactions are well-formed?

$S1 = l_1(A)l_1(B)r_1(A)w_1(B)l_2(B)u_1(A)u_1(B)$   
 $r_2(B)w_2(B)u_2(B)l_3(B)r_3(B)u_3(B)$

$S2 = l_1(A)r_1(A)w_1(B)u_1(A)u_1(B)$   
 $l_2(B)r_2(B)w_2(B)l_3(B)r_3(B)u_3(B)$

$S3 = l_1(A)r_1(A)u_1(A)l_1(B)w_1(B)u_1(B)$   
 $l_2(B)r_2(B)w_2(B)u_2(B)l_3(B)r_3(B)u_3(B)$

CS 245

Notes 09

47

## Exercise:

- What schedules are legal?  
What transactions are well-formed?

$S1 = l_1(A)l_1(B)r_1(A)w_1(B)l_2(B)u_1(A)u_1(B)$   
 $r_2(B)w_2(B)u_2(B)l_3(B)r_3(B)u_3(B)$

$S2 = l_1(A)r_1(A)w_1(B)u_1(A)u_1(B)$   
 $l_2(B)r_2(B)w_2(B)l_3(B)r_3(B)u_3(B)u_2(B)?$

$S3 = l_1(A)r_1(A)u_1(A)l_1(B)w_1(B)u_1(B)$   
 $l_2(B)r_2(B)w_2(B)u_2(B)l_3(B)r_3(B)u_3(B)$

CS 245

Notes 09

48



### Schedule F

T1	T2
$I_1(A); \text{Read}(A)$	
$A \leftarrow A + 100; \text{Write}(A); u_1(A)$	
	$I_2(A); \text{Read}(A)$
	$A \leftarrow A \times 2; \text{Write}(A); u_2(A)$
	$I_2(B); \text{Read}(B)$
	$B \leftarrow B \times 2; \text{Write}(B); u_2(B)$
$I_1(B); \text{Read}(B)$	
$B \leftarrow B + 100; \text{Write}(B); u_1(B)$	

CS 245

Notes 09

49

### Schedule F

T1	T2
$I_1(A); \text{Read}(A)$	
$A \leftarrow A + 100; \text{Write}(A); u_1(A)$	
	$I_2(A); \text{Read}(A)$
	$A \leftarrow A \times 2; \text{Write}(A); u_2(A)$
	$I_2(B); \text{Read}(B)$
	$B \leftarrow B \times 2; \text{Write}(B); u_2(B)$
$I_1(B); \text{Read}(B)$	
$B \leftarrow B + 100; \text{Write}(B); u_1(B)$	

A	B
25	25
125	
250	
	50
	150
250	150

CS 245

Notes 09

50

### Rule #3 Two phase locking (2PL) for transactions


$T_i = \dots \dots \dots I_i(A) \dots \dots \dots u_i(A) \dots \dots \dots$

no unlocks                      no locks

CS 245

Notes 09

51



CS 245

Notes 09

52

### Schedule G

T1	T2
$I_1(A); \text{Read}(A)$	
$A \leftarrow A + 100; \text{Write}(A)$	
$I_1(B); u_1(A)$	
	$I_2(A); \text{Read}(A)$
	$A \leftarrow A \times 2; \text{Write}(A);$

delayed

CS 245

Notes 09

53

### Schedule G

T1	T2
$I_1(A); \text{Read}(A)$	
$A \leftarrow A + 100; \text{Write}(A)$	
$I_1(B); u_1(A)$	
	$I_2(A); \text{Read}(A)$
	$A \leftarrow A \times 2; \text{Write}(A);$
$\text{Read}(B); B \leftarrow B + 100$	
$\text{Write}(B); u_1(B)$	

delayed

CS 245

Notes 09

54

### Schedule G

T1	T2
$I_1(A); \text{Read}(A)$	
$A \leftarrow A + 100; \text{Write}(A)$	
$I_1(B); u_1(A)$	
	$I_2(A); \text{Read}(A)$ <span style="border: 1px dashed black; border-radius: 50%; padding: 2px;">delayed</span>
	$A \leftarrow A \times 2; \text{Write}(A)$ <span style="border: 1px dashed black; border-radius: 50%; padding: 2px;">delayed</span>
$\text{Read}(B); B \leftarrow B + 100$	
$\text{Write}(B); u_1(B)$	
	$I_2(B); u_2(A); \text{Read}(B)$
	$B \leftarrow B \times 2; \text{Write}(B); u_2(B);$

CS 245

Notes 09

55

### Schedule H (T<sub>2</sub> reversed)

T1	T2
$I_1(A); \text{Read}(A)$	$I_2(B); \text{Read}(B)$
$A \leftarrow A + 100; \text{Write}(A)$	$B \leftarrow B \times 2; \text{Write}(B)$
<span style="border: 1px dashed black; border-radius: 50%; padding: 2px;">delayed</span>	<span style="border: 1px dashed black; border-radius: 50%; padding: 2px;">delayed</span>

CS 245

Notes 09

56

- Assume deadlocked transactions are rolled back
  - They have no effect
  - They do not appear in schedule

E.g., Schedule H = This space intentionally left blank!

CS 245

Notes 09

57

### Next step:

Show that rules #1,2,3  $\Rightarrow$  conflict-serializable schedules

CS 245

Notes 09

58

### Conflict rules for $I_i(A), u_i(A)$ :

- $I_i(A), I_j(A)$  conflict
- $I_i(A), u_j(A)$  conflict

Note: no conflict  $\langle u_i(A), u_j(A) \rangle, \langle I_i(A), r_j(A) \rangle, \dots$

CS 245

Notes 09

59

Theorem Rules #1,2,3  $\Rightarrow$  conflict-serializable schedule (2PL)

CS 245

Notes 09

60

Theorem Rules #1,2,3  $\Rightarrow$  conflict  
(2PL) serializable  
schedule

To help in proof:

Definition  $\text{Shrink}(Ti) = \text{SH}(Ti) =$   
first unlock action of  $Ti$

CS 245

Notes 09

61

Lemma

$Ti \rightarrow Tj \text{ in } S \Rightarrow \text{SH}(Ti) <_S \text{SH}(Tj)$

CS 245

Notes 09

62

Lemma

$Ti \rightarrow Tj \text{ in } S \Rightarrow \text{SH}(Ti) <_S \text{SH}(Tj)$

Proof of lemma:

$Ti \rightarrow Tj$  means that

$S = \dots p_i(A) \dots q_j(A) \dots; \quad p, q \text{ conflict}$

By rules 1,2:

$S = \dots p_i(A) \dots u_i(A) \dots l_j(A) \dots q_j(A) \dots$

CS 245

Notes 09

63

Lemma

$Ti \rightarrow Tj \text{ in } S \Rightarrow \text{SH}(Ti) <_S \text{SH}(Tj)$

Proof of lemma:

$Ti \rightarrow Tj$  means that

$S = \dots p_i(A) \dots q_j(A) \dots; \quad p, q \text{ conflict}$

By rules 1,2:

$S = \dots p_i(A) \dots u_i(A) \dots l_j(A) \dots q_j(A) \dots$

By rule 3:  $\text{SH}(Ti) \quad \text{SH}(Tj)$

So,  $\text{SH}(Ti) <_S \text{SH}(Tj)$

CS 245

Notes 09

64

Theorem Rules #1,2,3  $\Rightarrow$  conflict  
(2PL) serializable  
schedule

Proof:

(1) Assume  $P(S)$  has cycle

$T_1 \rightarrow T_2 \rightarrow \dots T_n \rightarrow T_1$

(2) By lemma:  $\text{SH}(T_1) < \text{SH}(T_2) < \dots < \text{SH}(T_1)$

(3) Impossible, so  $P(S)$  acyclic


(4)  $\Rightarrow S$  is conflict serializable

CS 245

Notes 09

65


2PL subset of Serializable



CS 245

Notes 09

66



S1: w1(x) w3(x) w2(y) w1(y)

S1: w1(x) w3(x) w2(y) w1(y)

- S1 cannot be achieved via 2PL:  
The lock by T1 for y must occur after w2(y), so the unlock by T1 for x must occur after this point (and before w1(x)). Thus, w3(x) cannot occur under 2PL where shown in S1 because T1 holds the x lock at that point.
- However, S1 is serializable (equivalent to T2, T1, T3).

If you need a bit more practice:  
Are our schedules  $S_C$  and  $S_D$  2PL schedules?

$S_C$ : w1(A) w2(A) w1(B) w2(B)


$S_D$ : w1(A) w2(A) w2(B) w1(B)

- Beyond this simple 2PL protocol, it is all a matter of improving performance and allowing more concurrency....
  - Shared locks
  - Multiple granularity
  - Inserts, deletes and phantoms
  - Other types of C.C. mechanisms

### Shared locks

So far:


$S = \dots l_1(A) \ r_1(A) \ u_1(A) \ \dots \ l_2(A) \ r_2(A) \ u_2(A) \ \dots$



### Shared locks

So far:

$S = \dots l_1(A) \ r_1(A) \ u_1(A) \ \dots \ l_2(A) \ r_2(A) \ u_2(A) \ \dots$



### Instead:

$S = \dots ls_1(A) \ r_1(A) \ ls_2(A) \ r_2(A) \ \dots \ us_1(A) \ us_2(A)$

### Lock actions

$l-t_i(A)$ : lock A in t mode (t is S or X)

$u-t_i(A)$ : unlock t mode (t is S or X)

### Shorthand:

$u_i(A)$ : unlock whatever modes

$T_i$  has locked A

CS 245

Notes 09

73

### Rule #1 Well formed transactions

$T_i = \dots l-S_1(A) \dots r_1(A) \dots u_1(A) \dots$

$T_i = \dots l-X_1(A) \dots w_1(A) \dots u_1(A) \dots$

CS 245

Notes 09

74

- What about transactions that read and write same object?

### Option 1: Request exclusive lock

$T_i = \dots l-X_1(A) \dots r_1(A) \dots w_1(A) \dots u(A) \dots$

CS 245

Notes 09

75

- What about transactions that read and write same object?

### Option 2: Upgrade

(E.g., need to read, but don't know if will write...)

$T_i = \dots l-S_1(A) \dots r_1(A) \dots l-X_1(A) \dots w_1(A) \dots u(A) \dots$

Think of  
- Get 2nd lock on A, or  
- Drop S, get X lock

CS 245

Notes 09

76

### Rule #2 Legal scheduler

$S = \dots l-S_i(A) \dots \dots u_i(A) \dots$

$\longleftrightarrow$   
no  $l-X_j(A)$

$S = \dots l-X_i(A) \dots \dots u_i(A) \dots$

$\longleftrightarrow$   
no  $l-X_j(A)$   
no  $l-S_j(A)$

CS 245

Notes 09

77

### A way to summarize Rule #2

Compatibility matrix

Comp

	S	X
S	true	false
X	false	false

CS 245

Notes 09

78

### Rule # 3 2PL transactions

No change except for upgrades:

- (I) If upgrade gets more locks  
(e.g.,  $S \rightarrow \{S, X\}$ ) then no change!
- (II) If upgrade releases read (shared)  
lock (e.g.,  $S \rightarrow X$ )  
- can be allowed in growing phase

CS 245

Notes 09

79

Theorem Rules 1,2,3  $\Rightarrow$  Conf.serializable  
for S/X locks schedules

Proof: similar to X locks case

Detail:

$I-t_i(A), I-r_j(A)$  do not conflict if  $\text{comp}(t,r)$

$I-t_i(A), u-r_j(A)$  do not conflict if  $\text{comp}(t,r)$

CS 245

Notes 09

80

### Lock types beyond S/X

Examples:

- (1) increment lock
- (2) update lock


CS 245

Notes 09

81

### Example (1): increment lock

- Atomic increment action:  $IN_i(A)$   
 $\{ \text{Read}(A); A \leftarrow A+k; \text{Write}(A) \}$
- $IN_i(A), IN_j(A)$  do not conflict!



CS 245

Notes 09

82

Comp

	S	X	I
S			
X			
I			

CS 245

Notes 09

83

Comp

	S	X	I
S	T	F	F
X	F	F	F
I	F	F	T


CS 245

Notes 09

84

## Update locks

A common deadlock problem with upgrades:



--- Deadlock ---

CS 245

Notes 09

85


## Solution

If T<sub>i</sub> wants to read A and knows it may later want to write A, it requests update lock (not shared)

CS 245

Notes 09


86



CS 245

Notes 09

87



-> symmetric table?

CS 245

Notes 09

88

Note: object A may be locked in different modes at the same time...

$S_1 = \dots I-S_1(A) \dots I-S_2(A) \dots I-U_3(A) \dots \left\{ \begin{array}{l} I-S_4(A) \dots ? \\ I-U_4(A) \dots ? \end{array} \right.$

CS 245

Notes 09

89

Note: object A may be locked in different modes at the same time...

$S_1 = \dots I-S_1(A) \dots I-S_2(A) \dots I-U_3(A) \dots \left\{ \begin{array}{l} I-S_4(A) \dots ? \\ I-U_4(A) \dots ? \end{array} \right.$

- To grant a lock in mode t, mode t must be compatible with all currently held locks on object

CS 245

Notes 09

90

## How does locking work in practice?

- Every system is different  
(E.g., may not even provide  
CONFLICT-SERIALIZABLE schedules)
- But here is one (simplified) way ...


CS 245

Notes 09

91

## Sample Locking System:


- (1) Don't trust transactions to request/release locks
- (2) Hold all locks until transaction commits



CS 245

Notes 09


92



CS 245

Notes 09

93




CS 245

Notes 09

94

## Lock table Conceptually




CS 245

Notes 09

95

## But use hash table:



If object not found in hash table, it is unlocked


CS 245

Notes 09

96



### Lock info for A - example




CS 245

Notes 09

97

### What are the objects we lock?



CS 245

Notes 09

98

- Locking works in any case, but should we choose small or large objects?

CS 245

Notes 09

99

- Locking works in any case, but should we choose small or large objects?
- If we lock large objects (e.g., Relations)
  - Need few locks
  - Low concurrency
- If we lock small objects (e.g., tuples, fields)
  - Need more locks
  - More concurrency


CS 245

Notes 09

100

We can have it both ways!!

Ask any janitor to give you the solution...




CS 245

Notes 09

101

### Example




CS 245

Notes 09

102

### Example




CS 245

Notes 09

103

### Example




CS 245

Notes 09

104

### Example (b)




CS 245

Notes 09

105

### Example



CS 245

Notes 09

106

### Multiple granularity

Comp	Holder	Requestor					
		IS	IX	S	SIX	X	
	IS						
	IX						
	S						
	SIX						
	X						

CS 245

Notes 09

107

### Multiple granularity

Comp	Holder	Requestor					
		IS	IX	S	SIX	X	
	IS	T	T	T	T	F	
	IX	T	T	F	F	F	
	S	T	F	T	F	F	
	SIX	T	F	F	F	F	
	X	F	F	F	F	F	

CS 245

Notes 09

108




Parent locked in	Child can be locked in
IS	
IX	
S	
SIX	
X	

CS 245 Notes 09 109

Parent locked in	Child can be locked by same transaction in
IS	IS, S
IX	IS, S, IX, X, SIX
S	none
SIX	X, IX, [SIX]
X	none


CS 245 Notes 09 110

- ### Rules
- (1) Follow multiple granularity comp function
  - (2) Lock root of tree first, any mode
  - (3) Node Q can be locked by Ti in S or IS only if parent(Q) locked by Ti in IX or IS
  - (4) Node Q can be locked by Ti in X, SIX, IX only if parent(Q) locked by Ti in IX, SIX
  - (5) Ti is two-phase
  - (6) Ti can unlock node Q only if none of Q's children are locked by Ti
- CS 245 Notes 09 111



### Exercise:

- Can T<sub>2</sub> access object f<sub>2.2</sub> in S mode?  
What locks will T<sub>2</sub> get?




CS 245

Notes 09

115

### Exercise:

- Can T<sub>2</sub> access object f<sub>2.2</sub> in X mode?  
What locks will T<sub>2</sub> get?




CS 245

Notes 09

116

### Insert + delete operations



CS 245

Notes 09

117

### Modifications to locking rules:

- (1) Get exclusive lock on A before deleting A
- (2) At insert A operation by T<sub>i</sub>, T<sub>i</sub> is given exclusive lock on A

CS 245

Notes 09

118

### Still have a problem: **Phantoms**

Example: relation R (E#,name,...)  
constraint: E# is key  
use tuple locking

R	E#	Name	...
o1	55	Smith	
o2	75	Jones	

CS 245

Notes 09

119

T<sub>1</sub>: Insert <12,Obama,...> into R  
T<sub>2</sub>: Insert <12,Romney,...> into R

T <sub>1</sub>	T <sub>2</sub>
S <sub>1</sub> (o1)	S <sub>2</sub> (o1)
S <sub>1</sub> (o2)	S <sub>2</sub> (o2)
Check Constraint	Check Constraint
⋮	⋮
Insert o3[12,Obama,...]	Insert o4[12,Romney,...]


CS 245

Notes 09

120

### Solution

- Use multiple granularity tree
- Before insert of node Q, lock parent(Q) in X mode



CS 245

Notes 09

121

### Back to example

T1: Insert<12,Obama>

T2: Insert<12,Romney>

T1

T2

X<sub>1</sub>(R)



Check constraint

Insert<12,Obama>

U<sub>1</sub>(R)

X<sub>2</sub>(R)

Check constraint

Oops! e# = 12 already in R!


CS 245

Notes 09

122

Instead of using R, can use index on R:

Example:



CS 245

Notes 09

123

- This approach can be generalized to multiple indexes...

CS 245

Notes 09

124

### Next:

- Tree-based concurrency control
- Validation concurrency control


CS 245

Notes 09

125

### Example

- all objects accessed through root, following pointers




CS 245

Notes 09

126

### Example

- all objects accessed through root, following pointers




CS 245

Notes 09

127

### Example

- all objects accessed through root, following pointers




- can we release A lock if we no longer need A??

CS 245

Notes 09

128

### Idea: traverse like "Monkey Bars"




CS 245

Notes 09

129

### Idea: traverse like "Monkey Bars"




CS 245

Notes 09

130

### Idea: traverse like "Monkey Bars"




CS 245

Notes 09

131

### Why does this work?

- Assume all  $T_i$  start at root; exclusive lock
- $T_i \rightarrow T_j \Rightarrow T_i$  locks root before  $T_j$



- Actually works if we don't always start at root

CS 245

Notes 09

132

### Rules: tree protocol (exclusive locks)


- (1) First lock by  $T_i$  may be on any item
- (2) After that, item Q can be locked by  $T_i$  only if parent(Q) locked by  $T_i$
- (3) Items may be unlocked at any time
- (4) After  $T_i$  unlocks Q, it cannot relock Q

CS 245

Notes 09

133

- Tree-like protocols are used typically for B-tree concurrency control



E.g., during insert, do not release parent lock, until you are certain child does not have to split


CS 245

Notes 09

134

### Tree Protocol with Shared Locks

- Rules for shared & exclusive locks?




CS 245

Notes 09

135

### Tree Protocol with Shared Locks

- Rules for shared & exclusive locks?



CS 245

Notes 09

136

### Tree Protocol with Shared Locks

- Need more restrictive protocol
- Will this work??
  - Once  $T_1$  locks one object in X mode, all further locks down the tree must be in X mode

CS 245

Notes 09

137

### Validation

Transactions have 3 phases:

- (1) Read
  - all DB values read
  - writes to temporary storage
  - no locking
- (2) Validate
  - check if schedule so far is serializable
- (3) Write
  - if validate ok, write to DB

CS 245

Notes 09

138

### Key idea

- Make validation atomic
- If  $T_1, T_2, T_3, \dots$  is validation order, then resulting schedule will be conflict equivalent to  $S_s = T_1 T_2 T_3 \dots$

CS 245

Notes 09

139

To implement validation, system keeps two sets:

- FIN = transactions that have finished phase 3 (and are all done)
- VAL = transactions that have successfully finished phase 2 (validation)


CS 245

Notes 09

140

### Example of what validation must prevent:

$RS(T_2) = \{B\}$        $RS(T_3) = \{A, B\} \neq \phi$   
 $WS(T_2) = \{B, D\}$        $WS(T_3) = \{C\}$




CS 245

Notes 09

141

### Example of what validation must prevent:

$RS(T_2) = \{B\}$        $RS(T_3) = \{A, B\} \neq \phi$   
 $WS(T_2) = \{B, D\}$        $WS(T_3) = \{C\}$




CS 245

Notes 09

142

### Another thing validation must prevent:

$RS(T_2) = \{A\}$        $RS(T_3) = \{A, B\}$   
 $WS(T_2) = \{D, E\}$        $WS(T_3) = \{C, D\}$




CS 245

Notes 09

143

### Another thing validation must prevent:

$RS(T_2) = \{A\}$        $RS(T_3) = \{A, B\}$   
 $WS(T_2) = \{D, E\}$        $WS(T_3) = \{C, D\}$



CS 245


Notes 09

144



allow  
Another thing validation must prevent:

$RS(T_2) = \{A\}$        $RS(T_3) = \{A, B\}$   
 $WS(T_2) = \{D, E\}$        $WS(T_3) = \{C, D\}$



CS 245

Notes 09

145

Validation rules for  $T_j$ :

- (1) When  $T_j$  starts phase 1:  
 $ignore(T_j) \leftarrow FIN$
- (2) at  $T_j$  Validation:  
 if check ( $T_j$ ) then  
     [  $VAL \leftarrow VAL \cup \{T_j\}$ ;  
     do write phase;  
      $FIN \leftarrow FIN \cup \{T_j\}$  ]

CS 245

Notes 09

146

Check ( $T_j$ ):

For  $T_i \in VAL - IGNORE(T_j)$  DO  
 IF [  $WS(T_i) \cap RS(T_j) \neq \emptyset$  OR  
 $T_i \notin FIN$  ] THEN RETURN false;  
 RETURN true;

CS 245

Notes 09

147

Check ( $T_j$ ):

For  $T_i \in VAL - IGNORE(T_j)$  DO  
 IF [  $WS(T_i) \cap RS(T_j) \neq \emptyset$  OR  
 $T_i \notin FIN$  ] THEN RETURN false;  
 RETURN true;

Is this check too restrictive ?

CS 245

Notes 09

148

Improving Check( $T_i$ )


For  $T_i \in VAL - IGNORE(T_j)$  DO  
 IF [  $WS(T_i) \cap RS(T_j) \neq \emptyset$  OR  
 $(T_i \notin FIN \text{ AND } WS(T_i) \cap WS(T_j) \neq \emptyset)$  ]  
 THEN RETURN false;  
 RETURN true;

CS 245

Notes 09

149

Exercise:




CS 245

Notes 09

150

## Is Validation = 2PL?



CS 245

Notes 09

151

## S2: w2(y) w1(x) w2(x)

- Achievable with 2PL?
- Achievable with validation?

CS 245

Notes 09

152

## S2: w2(y) w1(x) w2(x)

- S2 can be achieved with 2PL:  
l2(y) w2(y) l1(x) w1(x) u1(x) l2(x) w2(x) u2(y) u2(x)
- S2 cannot be achieved by validation:  
The validation point of T2, val2 must occur before w2(y) since transactions do not write to the database until after validation. Because of the conflict on x, val1 < val2, so we must have something like  
S2: val1 val2 w2(y) w1(x) w2(x)  
With the validation protocol, the writes of T2 should not start until T1 is all done with its writes, which is not the case.

CS 245

Notes 09

153

## Validation subset of 2PL?

- Possible proof (Check!):
  - Let S be validation schedule
  - For each T in S insert lock/unlocks, get S':
    - At T start: request read locks for all of RS(T)
    - At T validation: request write locks for WS(T); release read locks for read-only objects
    - At T end: release all write locks
  - Clearly transactions well-formed and 2PL
  - Must show S' is legal (next page)

CS 245

Notes 09

154


- Say S' not legal (due to w-r conflict):  
S': ... l1(x) w2(x) r1(x) val1 u1(x) ...  
 – At val1: T2 not in Ignore(T1); T2 in VAL  
 – T1 does not validate:  $WS(T2) \cap RS(T1) \neq \emptyset$   
 – contradiction!
- Say S' not legal (due to w-w conflict):  
S': ... val1 l1(x) w2(x) w1(x) u1(x) ...  
 – Say T2 validates first (proof similar if T1 validates first)  
 – At val1: T2 not in Ignore(T1); T2 in VAL  
 – T1 does not validate:  
 $T2 \notin \text{FIN} \text{ AND } WS(T1) \cap WS(T2) \neq \emptyset$   
 – contradiction!

CS 245

Notes 09

155

## Conclusion: Validation subset 2PL



CS 245

Notes 09

156

Validation (also called optimistic concurrency control) is useful in some cases:

- Conflicts rare
- System resources plentiful
- Have real time constraints

## Summary

Have studied C.C. mechanisms used in practice

- 2 PL
- Multiple granularity
- Tree (index) protocols
- Validation